

# ISO/IEC 17821:2015-04 (E)

## Information technology - Specification of low power wireless mesh network over channel-hopped TDMA links

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Abbreviations .....	2
5	General description .....	3
5.1	General .....	3
5.2	Components of the LPWMN .....	3
5.3	Architecture of the LPWMN .....	4
5.4	Functional overview .....	5
5.4.1	Link network formation .....	5
5.4.2	Link connection .....	6
5.4.3	Unbalanced cluster-tree addressing .....	7
5.4.4	Routing .....	8
6	Functional description .....	9
6.1	Starting the LPWMN .....	9
6.1.1	Starting a link network .....	9
6.1.2	Starting a router .....	10
6.1.3	Starting a device .....	11
6.2	Joining a link network .....	12
6.2.1	Device procedure .....	12
6.2.2	Router procedure .....	12
6.3	Leaving a link network .....	13
6.4	Address assignment with an unbalanced cluster-tree structure .....	14
6.5	DSME MAC link and link-path .....	15
6.5.1	Establishing a link-path .....	15
6.5.2	Maintaining a link-path .....	16
6.5.3	Routing a link-path .....	17
6.6	Data services .....	19
6.6.1	General .....	19
6.6.2	DLN sublayer data service .....	19
6.6.3	DLC sublayer data service .....	20
6.6.4	Data reception .....	20
7	LPWMN services .....	21
7.1	LPWMN management services .....	21
7.1.1	Primitives for link network formation .....	22
7.1.2	Primitives for link network joining as a router .....	24
7.1.3	Primitives for link network joining as a device .....	25
7.1.4	Primitives for the DLIB management .....	26
7.1.5	Primitives for link network resources management .....	29
7.2	LPWMN link management services .....	30
7.2.1	Primitives for link establishment .....	30

7.2.2	Primitives for link release .....	32
7.2.3	Primitives for link management .....	34
7.3	LPWMN data services .....	35
7.3.1	Primitives for data service on a CAP link .....	35
7.3.2	Primitives for data service on a shared GTS link .....	37
7.3.3	Primitives for data service on a dedicated link path .....	39
7.3.4	Primitives for data service through DLN sublayer .....	41
8	LPWMN frame formats .....	43
8.1	General link network frame format .....	43
8.1.1	Frame Control field .....	44
8.1.2	Destination Address field .....	44
8.1.3	Source Address field .....	45
8.1.4	Destination IEEE Address field .....	45
8.1.5	Source IEEE Address field .....	45
8.1.6	Link Management subframe field .....	45
8.1.7	Link Network Management subframe field .....	45
8.1.8	Frame Payload field .....	45
8.2	Data frames .....	45
8.3	Link management command frames .....	46
8.3.1	Link Management Command Frame Identifier field .....	46
8.3.2	Sequence Number field .....	46
8.3.3	Length of Link Management Command field .....	47
8.3.4	Link Management Command Payload field .....	47
8.4	Link network management command frames .....	48
8.4.1	Link Network Management Command Frame Identifier field .....	49
8.4.2	Sequence Number field .....	49
8.4.3	Length of Link Network Management Command Frame field .....	50
8.4.4	Link Network Management Command Payload field .....	50
9	Link network constants, information bases, and status values .....	52
9.1	Link network constants .....	52
9.2	DSME MAC link Information base .....	52
9.3	Link network status values .....	57
Annex A (informative) Enhanced MAC for reliable services .....		58
Annex B (informative) Authentication and Key Establishment Protocols (AKEP) .....		60
Bibliography .....		65