

# ISO/IEC/IEEE 8802-22:2015-05 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 22: Cognitive Wireless RAN Medium Access Control (MCA) and Physical Layer (PHY) Specifications: Policies and Procedures for Operation in the TV Bands

---

## Contents

Page

# Contents

|      |   |     |
|------|---|-----|
| 1    | Overview.....                               | 1   |
| 1.1  | Scope.....                                  | 1   |
| 1.2  | Purpose.....                                | 2   |
| 1.3  | Reference application.....                  | 2   |
| 2    | Normative references.....                   | 3   |
| 3    | Definitions.....                            | 5   |
| 4    | Abbreviations and acronyms.....             | 10  |
| 5    | System architecture.....                    | 13  |
| 5.1  | Reference architecture.....                 | 13  |
| 5.2  | Management reference architecture.....      | 17  |
| 6    | Packet Convergence sublayer.....            | 20  |
| 6.1  | MAC SDU format.....                         | 20  |
| 6.2  | Classification.....                         | 20  |
| 6.3  | IEEE 802.3/Ethernet-specific part.....      | 22  |
| 6.4  | IP specific part.....                       | 22  |
| 7    | MAC Common Part sublayer.....               | 24  |
| 7.1  | General.....                                | 24  |
| 7.2  | Addressing and connections.....             | 24  |
| 7.3  | General superframe structure.....           | 26  |
| 7.4  | General frame structure.....                | 27  |
| 7.5  | Control headers.....                        | 31  |
| 7.6  | MAC PDU formats.....                        | 35  |
| 7.7  | Management messages.....                    | 45  |
| 7.8  | Management of MAC PDUs.....                 | 110 |
| 7.9  | ARQ mechanism.....                          | 115 |
| 7.10 | Scheduling services.....                    | 125 |
| 7.11 | Bandwidth management.....                   | 128 |
| 7.12 | PHY support.....                            | 132 |
| 7.13 | Contention resolution.....                  | 134 |
| 7.14 | Initialization and network association..... | 135 |
| 7.15 | Ranging.....                                | 159 |
| 7.16 | Channel descriptor management.....          | 164 |
| 7.17 | Multicast support.....                      | 166 |
| 7.18 | QoS.....                                    | 169 |
| 7.19 | Incumbent protection.....                   | 212 |
| 7.20 | Self-coexistence.....                       | 221 |
| 7.21 | Quiet periods and sensing.....              | 237 |
| 7.22 | Channel management.....                     | 246 |

|                     |   |     |
|---------------------|---|-----|
| 7.23                | Synchronization of the IEEE 802.22 base stations .....                    | 249 |
| 8                   | Security mechanism in IEEE 802.22 .....                                   | 250 |
| 8.1                 | Security Architecture for the Data/Control and Management Planes.....     | 250 |
| 8.2                 | SCM protocol .....  | 253 |
| 8.3                 | Key usage .....   | 275 |
| 8.4                 | Cryptographic methods .....   | 281 |
| 8.5                 | Certificate profile .....   | 286 |
| 8.6                 | Security sublayer 2—Security mechanisms for the cognitive functions ..... | 293 |
| 8.7                 | CPE privacy.....  | 306 |
| 9                   | PHY .....   | 307 |
| 9.1                 | Symbol description.....   | 307 |
| 9.2                 | Data rates.....   | 310 |
| 9.3                 | Functional block diagram applicable to the PHY layer .....                | 311 |
| 9.4                 | Superframe and frame structures.....                                      | 312 |
| 9.5                 | CBP packet format .....   | 320 |
| 9.6                 | OFDM subcarrier allocation.....   | 322 |
| 9.7                 | Channel coding.....   | 329 |
| 9.8                 | Constellation mapping and modulation.....                                 | 348 |
| 9.9                 | Control mechanisms .....  | 351 |
| 9.10                | Network synchronization.....  | 357 |
| 9.11                | Frequency Control requirements .....                                      | 358 |
| 9.12                | Antenna .....   | 358 |
| 9.13                | RF mask.....  | 362 |
| 9.14                | Receiver requirements.....  | 363 |
| 10                  | Cognitive radio capability.....   | 365 |
| 10.1                | General .....   | 365 |
| 10.2                | Spectrum Manager operation .....  | 366 |
| 10.3                | Spectrum Sensing Automaton (SSA) .....                                    | 392 |
| 10.4                | Spectrum sensing.....   | 406 |
| 10.5                | Geolocation .....   | 416 |
| 10.6                | Database service .....  | 421 |
| 10.7                | Primitives for cognitive radio capabilities.....                          | 423 |
| 11                  | Configuration.....  | 440 |
| 12                  | Parameters and connection management .....                                | 441 |
| 12.1                | Parameters, timers, message IEs.....                                      | 441 |
| 12.2                | Well-known CIDs.....  | 450 |
| 12.3                | ARQ parameters .....  | 452 |
| 13                  | MIB structure.....  | 453 |
| 13.1                | MIB description.....  | 453 |
| Annex A (normative) | IEEE 802.22 regulatory domains and regulatory classes requirements.....   | 557 |

|  |     |
|--|-----|
| A.1 Regulatory domains, regulatory classes, and professional installation .....  | 557 |
| A.2 Radio performance requirements .....   | 558 |
| A.3 Channel availability and sensing requirements .....  | 560 |
| A.4 Device identification requirements .....   | 563 |
| A.5 Channelization based on the regulatory domain .....  | 564 |
| Annex B (informative) Multicarrier fine ranging method .....   | 568 |
| B.1 General description .....  | 568 |
| B.2 Practical embodiment of the proposed multicarrier fine ranging method .....  | 573 |
| B.3 References .....   | 575 |
| Annex C (informative) Sensing .....  | 576 |
| C.1 Blind sensing techniques .....   | 576 |
| C.2 Signal specific sensing techniques .....   | 585 |
| C.3 References .....   | 627 |
| Annex D (informative) Summary of the characteristics of the IEEE 802.22.1 beacon signal<br>and protocols .....             | 629 |
| D.1 General .....  | 629 |
| D.2 Superframe structure .....   | 629 |
| D.3 Beacon frame structure .....   | 630 |
| D.4 Synchronization burst .....  | 631 |
| D.5 Inter-device communication period (ICP) .....  | 632 |
| D.6 PHY specifications .....   | 632 |
| D.7 Reference architecture for the WRAN receiver .....   | 633 |
| D.8 Sensing and detection at the WRAN receiver .....   | 634 |
| D.9 Options for detecting the IEEE 802.22.1 beacon signal .....  | 644 |
| D.10 Operation scenarios for the coexistence of IEEE 802.22.1 and IEEE 802.22 .....  | 646 |
| D.11 References .....  | 647 |
| Annex E (informative) Distributed spectrum sensing and authentication to provide protection against<br>thermal noise ..... | 648 |
| Annex F (informative) Network security aspects .....   | 653 |
| F.1 Availability .....   | 653 |
| F.2 Authentication .....   | 653 |
| F.3 Authorization .....  | 654 |
| F.4 Identification .....   | 654 |
| F.5 Integrity .....  | 654 |
| F.6 Confidentiality/Privacy .....  | 655 |
| Annex G (informative) Bibliography .....   | 656 |