

ISO/IEC/IEEE 8802-22:2015-05 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 22: Cognitive Wireless RAN Medium Access Control (MCA) and Physical Layer (PHY) Specifications: Policies and Procedures for Operation in the TV Bands

Contents

Page

Contents

1	Overview.....	1
1.1	Scope.....	1
1.2	Purpose.....	2
1.3	Reference application.....	2
2	Normative references.....	3
3	Definitions.....	5
4	Abbreviations and acronyms.....	10
5	System architecture.....	13
5.1	Reference architecture.....	13
5.2	Management reference architecture.....	17
6	Packet Convergence sublayer.....	20
6.1	MAC SDU format.....	20
6.2	Classification.....	20
6.3	IEEE 802.3/Ethernet-specific part.....	22
6.4	IP specific part.....	22
7	MAC Common Part sublayer.....	24
7.1	General.....	24
7.2	Addressing and connections.....	24
7.3	General superframe structure.....	26
7.4	General frame structure.....	27
7.5	Control headers.....	31
7.6	MAC PDU formats.....	35
7.7	Management messages.....	45
7.8	Management of MAC PDUs.....	110
7.9	ARQ mechanism.....	115
7.10	Scheduling services.....	125
7.11	Bandwidth management.....	128
7.12	PHY support.....	132
7.13	Contention resolution.....	134
7.14	Initialization and network association.....	135
7.15	Ranging.....	159
7.16	Channel descriptor management.....	164
7.17	Multicast support.....	166
7.18	QoS.....	169
7.19	Incumbent protection.....	212
7.20	Self-coexistence.....	221
7.21	Quiet periods and sensing.....	237
7.22	Channel management.....	246

7.23	Synchronization of the IEEE 802.22 base stations	249
8	Security mechanism in IEEE 802.22	250
8.1	Security Architecture for the Data/Control and Management Planes.....	250
8.2	SCM protocol	253
8.3	Key usage	275
8.4	Cryptographic methods	281
8.5	Certificate profile	286
8.6	Security sublayer 2—Security mechanisms for the cognitive functions	293
8.7	CPE privacy.....	306
9	PHY	307
9.1	Symbol description.....	307
9.2	Data rates.....	310
9.3	Functional block diagram applicable to the PHY layer	311
9.4	Superframe and frame structures.....	312
9.5	CBP packet format	320
9.6	OFDM subcarrier allocation.....	322
9.7	Channel coding.....	329
9.8	Constellation mapping and modulation.....	348
9.9	Control mechanisms	351
9.10	Network synchronization.....	357
9.11	Frequency Control requirements	358
9.12	Antenna	358
9.13	RF mask.....	362
9.14	Receiver requirements.....	363
10	Cognitive radio capability.....	365
10.1	General	365
10.2	Spectrum Manager operation	366
10.3	Spectrum Sensing Automaton (SSA)	392
10.4	Spectrum sensing.....	406
10.5	Geolocation	416
10.6	Database service	421
10.7	Primitives for cognitive radio capabilities.....	423
11	Configuration.....	440
12	Parameters and connection management	441
12.1	Parameters, timers, message IEs.....	441
12.2	Well-known CIDs.....	450
12.3	ARQ parameters	452
13	MIB structure.....	453
13.1	MIB description.....	453
Annex A (normative) IEEE 802.22 regulatory domains and regulatory classes requirements.....		557

A.1 Regulatory domains, regulatory classes, and professional installation	557
A.2 Radio performance requirements	558
A.3 Channel availability and sensing requirements	560
A.4 Device identification requirements	563
A.5 Channelization based on the regulatory domain	564
Annex B (informative) Multicarrier fine ranging method	568
B.1 General description	568
B.2 Practical embodiment of the proposed multicarrier fine ranging method	573
B.3 References	575
Annex C (informative) Sensing	576
C.1 Blind sensing techniques	576
C.2 Signal specific sensing techniques	585
C.3 References	627
Annex D (informative) Summary of the characteristics of the IEEE 802.22.1 beacon signal and protocols	629
D.1 General	629
D.2 Superframe structure	629
D.3 Beacon frame structure	630
D.4 Synchronization burst	631
D.5 Inter-device communication period (ICP)	632
D.6 PHY specifications	632
D.7 Reference architecture for the WRAN receiver	633
D.8 Sensing and detection at the WRAN receiver	634
D.9 Options for detecting the IEEE 802.22.1 beacon signal	644
D.10 Operation scenarios for the coexistence of IEEE 802.22.1 and IEEE 802.22	646
D.11 References	647
Annex E (informative) Distributed spectrum sensing and authentication to provide protection against thermal noise	648
Annex F (informative) Network security aspects	653
F.1 Availability	653
F.2 Authentication	653
F.3 Authorization	654
F.4 Identification	654
F.5 Integrity	654
F.6 Confidentiality/Privacy	655
Annex G (informative) Bibliography	656