ISO/IEC 18000-63:2015-10 (E)

Information technology - Radio frequency identification for item manageme nt - Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Conformance 1
2.1 Claiming conformance 1
2.2 General conformance requirements 2
2.2.1 Interrogators 2
2.2.2 Tags 2
2.3 Command structure and extensibility 3
2.3.1 Mandatory commands 3
2.3.2 Optional commands 3
2.3.3 Proprietary commands 3
2.3.4 Custom commands 3
2.4 Reserved for Future Use (RFU) 3
2.5 Cryptographic Suite Indicators 3

3 Normative references 4

4 Terms and definitions 4

5 Symbols, abbreviated terms and notation 11
5.1 Symbols 12
5.2 Abbreviated terms 13
5.3 Notation 16

6 Protocol requirements - Type C 16
6.1 Protocol overview 16
6.1.1 Physical layer 16
6.1.2 Tag-identification layer 17
6.2 Protocol parameters 17
6.2.1 Signaling - Physical and media access control parameters 17
6.2.2 Logical - Operating procedure parameters 20
6.3 Description of operating procedure 21
6.3.1 Physical interface 21
6.3.2 Logical interface 43

7 Battery Assisted Passive (BAP) Interrogator Talks First Type C systems (optional) 117
7.1 Applicability 117
7.2 General overview, definitions, and requirements of BAP 117
7.3 Battery Assisted Passive inventoried flag and state machine behaviour modifications 119
7.3.1 Modification to ready state and power-down support for BAP Tags 119
7.3.2 Signal loss tolerance via timer (mandatory) 119
7.3.3 Modified persistence of BAP PIE inventory flags (optional) 122
7.4 Battery Assisted Passive PIE (optional) 124
7.4.1 Flex_Query command (optional) 124
7.4.2 BAP PIE detailed operation including optional Battery Saver Mode 126
7.5 Manchester mode Battery Assisted operation protocol extensions 132
7.5.1 Introduction 132

7.5.2 Physical layer 133
7.5.3 Manchester Activation 138
7.5.4 Commands summary 153
7.6 Extended Protocol Control 167

8 Sensor support 168
8.1 Applicability 168
8.2 Overview 168
8.3 Real Time Clock (RTC) 169

8.3.1 General 169
8.3.2 Setting the RTC 169
8.3.3 BroadcastSync command (optional) 170
8.3.4 Time synchronisation 170
8.4 HandleSensor command (optional) 171
8.5 Simple Sensor 172
8.5.1 Type C and Simple Sensor 173
8.6 Sensor Directory System and Full Function Sensors 175
8.6.1 Sensor Access - General Approach 175

Annex A (normative) Extensible bit vectors (EBV) 181

Annex B (normative) State-transition tables 182

Annex C (normative) Command-Response Tables 233

Annex D (informative) Example slot-count (Q) selection algorithm 261

Annex E (informative) Example Tag inventory and access 262

Annex F (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks 263

Annex G (normative) Multiple- and dense-Interrogator channelized signaling 265

Annex H (informative) Interrogator-to-Tag link modulation 268

Annex I (normative) Error codes 270

Annex J (normative) Slot counter 272

Annex K (informative) Example data-flow exchange 273

Annex L (informative) Optional Tag Features 276

Annex M (informative) Cryptographic-Suite Checklist 279

Annex N (informative) Battery Assisted Tag to Interrogator synchronization 280

Annex O (normative) Simple Sensors Data Block 283

Annex P (normative) Record structures and commands for Ported Simple Sensors 295

Annex Q (informative) BAP PIE and Manchester mode tutorial guide 310

Annex R (informative) Manchester mode RF power control 320

Bibliography 325