

ISO/IEC 18000-63:2015-10 (E)

Information technology - Radio frequency identification for item management - Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Conformance	1
2.1	Claiming conformance	1
2.2	General conformance requirements	2
2.2.1	Interrogators	2
2.2.2	Tags	2
2.3	Command structure and extensibility	3
2.3.1	Mandatory commands	3
2.3.2	Optional commands	3
2.3.3	Proprietary commands	3
2.3.4	Custom commands	3
2.4	Reserved for Future Use (RFU)	3
2.5	Cryptographic Suite Indicators	3
3	Normative references	4
4	Terms and definitions	4
5	Symbols, abbreviated terms and notation	11
5.1	Symbols	12
5.2	Abbreviated terms	13
5.3	Notation	16
6	Protocol requirements - Type C	16
6.1	Protocol overview	16
6.1.1	Physical layer	16
6.1.2	Tag-identification layer	17
6.2	Protocol parameters	17
6.2.1	Signaling - Physical and media access control parameters	17
6.2.2	Logical - Operating procedure parameters	20
6.3	Description of operating procedure	21
6.3.1	Physical interface	21
6.3.2	Logical interface	43
7	Battery Assisted Passive (BAP) Interrogator Talks First Type C systems (optional)	117
7.1	Applicability	117
7.2	General overview, definitions, and requirements of BAP	117
7.3	Battery Assisted Passive inventoried flag and state machine behaviour modifications ...	119
7.3.1	Modification to ready state and power-down support for BAP Tags	119
7.3.2	Signal loss tolerance via timer (mandatory)	119
7.3.3	Modified persistence of BAP PIE inventory flags (optional)	122
7.4	Battery Assisted Passive PIE (optional)	124
7.4.1	Flex_Query command (optional)	124
7.4.2	BAP PIE detailed operation including optional Battery Saver Mode	126
7.5	Manchester mode Battery Assisted operation protocol extensions	132
7.5.1	Introduction	132

7.5.2	Physical layer	133
7.5.3	Manchester Activation	138
7.5.4	Commands summary	153
7.6	Extended Protocol Control	167
8	Sensor support	168
8.1	Applicability	168
8.2	Overview	168
8.3	Real Time Clock (RTC)	169
8.3.1	General	169
8.3.2	Setting the RTC	169
8.3.3	BroadcastSync command (optional)	170
8.3.4	Time synchronisation	170
8.4	HandleSensor command (optional)	171
8.5	Simple Sensor	172
8.5.1	Type C and Simple Sensor	173
8.6	Sensor Directory System and Full Function Sensors	175
8.6.1	Sensor Access - General Approach	175
Annex A (normative) Extensible bit vectors (EBV)		181
Annex B (normative) State-transition tables		182
Annex C (normative) Command-Response Tables		233
Annex D (informative) Example slot-count (Q) selection algorithm		261
Annex E (informative) Example Tag inventory and access		262
Annex F (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks		263
Annex G (normative) Multiple- and dense-Interrogator channelized signaling		265
Annex H (informative) Interrogator-to-Tag link modulation		268
Annex I (normative) Error codes		270
Annex J (normative) Slot counter		272
Annex K (informative) Example data-flow exchange		273
Annex L (informative) Optional Tag Features		276
Annex M (informative) Cryptographic-Suite Checklist		279
Annex N (informative) Battery Assisted Tag to Interrogator synchronization		280
Annex O (normative) Simple Sensors Data Block		283
Annex P (normative) Record structures and commands for Ported Simple Sensors		295
Annex Q (informative) BAP PIE and Manchester mode tutorial guide		310
Annex R (informative) Manchester mode RF power control		320
Bibliography		325