

ISO/IEC 14443-3:2016-06 (E)

Identification cards - Contactless integrated circuit cards - Proximity cards - Part 3: Initialization and anticollision

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols and abbreviated terms | 3 |
| 5 | Initial dialogs | 4 |
| 5.1 | Alternating PICC and PCD support (PXD) | 4 |
| 5.2 | Alternating between Type A and Type B commands | 5 |
| 5.2.1 | Polling | 5 |
| 5.2.2 | Influence of Type A commands on PICC Type B operation | 5 |
| 5.2.3 | Influence of Type B commands on PICC Type A operation | 6 |
| 5.2.4 | Transition to POWER-OFF state | 6 |
| 6 | Type A -- Initialization and anticollision | 6 |
| 6.1 | etu | 6 |
| 6.2 | Frame format and timing | 6 |
| 6.2.1 | Frame delay time | 7 |
| 6.2.2 | Request Guard Time | 8 |
| 6.2.3 | Frame formats | 8 |
| 6.2.4 | CRC_A | 11 |
| 6.3 | PICC states | 12 |
| 6.3.1 | POWER-OFF state | 13 |
| 6.3.2 | IDLE state | 14 |
| 6.3.3 | READY state | 14 |
| 6.3.4 | ACTIVE state | 14 |
| 6.3.5 | HALT state | 14 |
| 6.3.6 | READY* state | 14 |
| 6.3.7 | ACTIVE* state | 14 |
| 6.3.8 | PROTOCOL state | 15 |
| 6.4 | Command set | 15 |
| 6.4.1 | REQA and WUPA commands | 15 |
| 6.4.2 | ANTICOLLISION and SELECT commands | 16 |
| 6.4.3 | HLTA command | 16 |
| 6.5 | Select sequence | 16 |
| 6.5.1 | Select sequence flowchart | 16 |
| 6.5.2 | ATQA -- Answer to Request | 17 |
| 6.5.3 | Anticollision and Select | 18 |
| 6.5.4 | UID contents and cascade levels | 22 |
| 7 | Type B -- Initialization and anticollision | 24 |
| 7.1 | Character, frame format and timing | 24 |
| 7.1.1 | Character transmission format | 24 |
| 7.1.2 | Character separation | 24 |
| 7.1.3 | Frame format | 25 |

| | | |
|--|---|----|
| 7.1.4 | SOF | 25 |
| 7.1.5 | EOF | 26 |
| 7.1.6 | Timing before the PICC SOF | 27 |
| 7.1.7 | Timing before the PCD SOF | 27 |
| 7.2 | CRC_B | 28 |
| 7.3 | Anticollision sequence | 28 |
| 7.4 | PICC states description | 29 |
| 7.4.1 | Initialization and anticollision flowchart | 31 |
| 7.4.2 | General statement for state description and transitions | 31 |
| 7.4.3 | POWER-OFF state | 32 |
| 7.4.4 | IDLE state | 32 |
| 7.4.5 | READY-REQUESTED sub-state | 32 |
| 7.4.6 | READY-DECLARED sub-state | 32 |
| 7.4.7 | PROTOCOL state | 33 |
| 7.4.8 | HALT state | 33 |
| 7.5 | Command set | 33 |
| 7.6 | Anticollision response rules | 34 |
| 7.6.1 | PICC with initialization only | 34 |
| 7.7 | REQB/WUPB command | 34 |
| 7.7.1 | REQB/WUPB command format | 34 |
| 7.7.2 | Coding of anticollision prefix byte APf | 34 |
| 7.7.3 | Coding of AFI | 35 |
| 7.7.4 | Coding of PARAM | 35 |
| 7.8 | Slot-MARKER command | 36 |
| 7.8.1 | Slot-MARKER command format | 36 |
| 7.8.2 | Coding of anticollision prefix byte APn | 37 |
| 7.9 | ATQB Response | 37 |
| 7.9.1 | ATQB response format | 37 |
| 7.9.2 | PUPI (Pseudo-Unique PICC Identifier) | 38 |
| 7.9.3 | Application data | 38 |
| 7.9.4 | Protocol Info | 38 |
| 7.10 | ATTRIB command | 42 |
| 7.10.1 | ATTRIB command format | 42 |
| 7.10.2 | Identifier | 42 |
| 7.10.3 | Coding of Param 1 | 42 |
| 7.10.4 | Coding of Param 2 | 44 |
| 7.10.5 | Coding of Param 3 | 44 |
| 7.10.6 | Coding of Param 4 | 45 |
| 7.10.7 | Higher layer INF | 45 |
| 7.11 | Answer to ATTRIB command | 45 |
| 7.12 | HLTB command and Answer | 46 |
| 8 | Electromagnetic disturbance handling | 47 |
| 8.1 | General | 47 |
| 8.2 | EMD handling timing constraints | 47 |
| 8.3 | Recommendations for a PCD EMD handling algorithm | 48 |
| Annex A (informative) Communication example Type A | | 49 |
| Annex B (informative) CRC_A and CRC_B encoding | | 51 |
| Annex C (informative) Type A timeslot -- Initialization and anticollision | | 54 |
| Annex D (informative) Example of Type B Anticollision Sequence | | 58 |
| Annex E (normative) Bit rates of 3fc/4, fc, 3fc/2 and 2fc from PCD to PICC | | 61 |
| Bibliography | | 63 |