

ISO/IEC 30190:2016-06 (E)

Information technology - Digitally recorded media for information interchange and storage - 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disk

Contents		Page
1	Scope	1
2	Conformance	2
2.1	Optical disk	2
2.2	Generating system	2
2.3	Receiving system	2
2.4	Compatibility statement	2
3	Normative references	2
4	Terms and definitions	3
5	Conventions and notations	7
5.1	Terminology:	7
5.1.1	Meaning of words	7
5.1.2	Levels of grouping	7
5.2	Representation of numbers	7
5.3	Integer calculus	8
5.4	Names	8
6	List of acronyms	9
7	General description of disk	11
8	General requirements	14
8.1	Environments	14
8.1.1	Test environment	14
8.1.2	Operating environment	14
8.1.3	Storage environment	15
8.1.4	Transportation	16
8.2	Safety requirements	16
8.3	Flammability	16
9	Reference drive	16
9.1	General	16
9.2	Measurement conditions	16
9.3	Optical system	17
9.4	Optical beam	18
9.5	HF read channel	18
9.6	Radial PP read channel	18
9.7	Disk Clamping	19
9.8	Rotation of disk and Measurement Velocity	19
9.9	Normalized servo transfer function	20
9.10	Measurement Velocities and Reference servos for axial tracking	20
9.10.1	General	20
9.10.2	Reference servo for axial tracking for 1x Measurement Velocity	21
9.10.3	Reference servo for axial tracking for 2x Measurement Velocity and 3x Measurement Velocity	22
9.11	Measurement Velocities and Reference servos for radial tracking	23

9.11.1	General	23
9.11.2	Reference servo for radial tracking for 1x Measurement Velocity	23
9.11.3	Reference servo for radial tracking for 2x Measurement Velocity and 3x Measurement Velocity	24
10	Dimensional characteristics	25
10.1	General	25
10.2	Disk reference planes and reference axis	25
10.3	Overall dimensions	27
10.4	First transition Area	27
10.5	Protection ring	28
10.6	Clamping Zone	28
10.7	Second transition Area	28
10.8	Information Area	28
10.8.1	General	28
10.8.2	Subdivision of Information Zone on SL disks	29
10.8.3	Subdivision of Information Zone on DL disks	29
10.9	Rim Area	30
11	Mechanical characteristics	31
11.1	Mass	31
11.2	Moment of inertia	31
11.3	Dynamic imbalance	31
11.4	Axial runout	31
11.4.1	General	31
11.4.2	Residual axial tracking error for 1x Measurement Velocity	31
11.4.3	Residual axial tracking error for 2x Measurement Velocity	32
11.4.4	Residual axial tracking error for 3x Measurement Velocity	32
11.5	Radial runout	33
11.5.1	General	33
11.5.2	Residual radial tracking error for 1x Measurement Velocity on SL disks	33
11.5.3	Residual radial tracking error for 1x Measurement Velocity on DL disks	33
11.5.4	Residual radial tracking error for 2x Measurement Velocity on SL and DL disks	34
11.5.5	Residual radial tracking error for 3x Measurement Velocity on SL and DL disks	34
11.6	Durability of Cover Layer	34
11.6.1	Impact resistance of Cover Layer	34
11.6.2	Scratch resistance of Cover Layer	34
11.6.3	Repulsion of fingerprints by Cover Layer	35
12	Optical characteristics in Information Area	35
12.1	General	35
12.2	Refractive index of Transmission Stacks (TS)	35
12.3	Thickness of Transmission Stacks (TS)	35
12.3.1	Thickness of Transmission Stack of SL disks	35
12.3.2	Thickness of Transmission Stacks of DL disks	35
12.4	Reflectivity	37
12.4.1	Reflectivity of Recording Layer of SL disks	37
12.4.2	Reflectivity of Recording Layers of DL disks	37
12.5	Birefringence	37
12.6	Angular deviation	38
13	Data Format	39
13.1	General	39
13.2	Data Frame	41
13.3	Error-Detection Code (EDC)	41
13.4	Scrambled Data Frame	42
13.5	Data Block	43
13.6	LDC Block	44
13.7	LDC code-words	44
13.8	LDC Cluster	45
13.8.1	General	45
13.8.2	First interleaving step	45

13.8.3	Second interleaving step	45
13.9	Addressing and Control Data	47
13.9.1	General	47
13.9.2	Address Units	47
13.9.3	User-Control Data	50
13.9.4	Byte/Bit assignment for User-Control Data	50
13.10	Access Block	52
13.11	BIS Block	52
13.12	BIS code-words	53
13.13	BIS Cluster	53
13.14	ECC Cluster	58
13.15	Recording Frames	59
13.16	Physical Cluster	59
13.17	17PP modulation for Recordable data	60
13.17.1	General	60
13.17.2	Bit conversion rules	60
13.17.3	dc-control procedure	61
13.17.4	Frame Sync	61
13.18	Modulation and NRZI conversion	62
14	Physical Data Allocating and Linking	63
14.1	General	63
14.2	Recording-Unit Block (RUB)	63
14.2.1	General	63
14.2.2	Data Run-in	64
14.2.3	Data Run-out	65
14.2.4	Guard_3 field	66
14.3	Locating data relative to wobble addresses	66
15	Track format	67
15.1	General	67
15.2	Track shape	67
15.3	Track path	68
15.4	Track Pitch	69
15.4.1	Track Pitch in BCA Zone	69
15.4.2	Track Pitch in Embossed HFM Area	69
15.4.3	Track Pitch in Recordable Area(s)	69
15.4.4	Track Pitch between Embossed HFM Area and Recordable Area	69
15.5	Track layout of HFM Groove	69
15.5.1	General	69
15.5.2	Data Format	70
15.5.3	Addressing and Control Data	71
15.5.4	Recording Frames	75
15.6	Track layout of Wobbled Groove(s)	77
15.6.1	General	77
15.6.2	Modulation of wobbles	77
15.6.3	Wobble polarity	79
15.7	ADIP information	79
15.7.1	General	79
15.7.2	ADIP-Unit Types	79
15.7.3	ADIP word structure	80
15.7.4	ADIP data structure	82
15.7.5	ADIP error correction	84
15.8	Disk Information in ADIP Aux Frame	86
15.8.1	General	86
15.8.2	Error protection for Disk-Information Aux Frames	86
15.8.3	Disk-Information data structure	87
16	General description of Information Zone	127
16.1	General	127
16.2	Format of Information Zone on Single-Layer disk	127
16.3	Format of Information Zone on Dual-Layer disk	127

17	Layout of Recordable Area of Information Zone	127
18	Inner Zone	131
18.1	General	131
18.2	Permanent Information & Control data (PIC) Zone	133
18.2.1	General	133
18.2.2	Content of PIC Zone	133
18.2.3	Emergency Brake	135
18.3	Recordable Area of Inner Zone 0	136
18.3.1	Protection-Zone 2	136
18.3.2	INFO 2 / Reserved 8	137
18.3.3	INFO 2 / Reserved 7	137
18.3.4	INFO 2 / Reserved 6	137
18.3.5	INFO 2 / Reserved 5	137
18.3.6	INFO 2 / PAC 2	137
18.3.7	INFO 2 / DMA 2	137
18.3.8	INFO 2 / Control Data 2	137
18.3.9	INFO 2 / Buffer 2	137
18.3.10	OPC 0 / Test Zone	137
18.3.11	Usage of OPC Areas	138
18.3.12	OPC 0 / OPC 0 Buffer	139
18.3.13	TDMA 0	139
18.3.14	INFO 1 / Pre-write Area	139
18.3.15	INFO 1 / Drive Area	139
18.3.16	INFO 1 / DMA 1	141
18.3.17	INFO 1 / Control Data 1	141
18.3.18	INFO 1 / PAC 1	141
18.4	Recordable Area of Inner Zone 1	142
18.4.1	Buffer	142
18.4.2	OPC 1	142
18.4.3	Buffer	142
18.4.4	INFO 2 / Reserved 8	142
18.4.5	INFO 2 / Reserved 7	142
18.4.6	INFO 2 / Reserved 6	142
18.4.7	INFO 2 / Reserved 5	142
18.4.8	INFO 2 / PAC 2	142
18.4.9	INFO 2 / DMA 2	142
18.4.10	INFO 2 / Control Data 2	142
18.4.11	INFO 2 / Buffer 2	143
18.4.12	TDMA 1	143
18.4.13	Reserved	143
18.4.14	INFO 1 / Pre-write Area	143
18.4.15	INFO 1 / Drive Area	143
18.4.16	INFO 1 / DMA 1	143
18.4.17	INFO 1 / Control Data 1	143
18.4.18	INFO 1 / PAC 1	143
19	Data Zone	143
20	Outer Zone(s)	144
20.1	General	144
20.2	Recordable Area of Outer Zone(s)	144
20.2.1	INFO 3 / Buffer 4	144
20.2.2	INFO 3 / DMA 3	144
20.2.3	INFO 3 / Control Data 3	145
20.2.4	Angular buffer	145
20.2.5	INFO 4 / DMA 4	145
20.2.6	INFO 4 / Control Data 4	145
20.2.7	INFO 4 / Buffer 6	145
20.2.8	DCZ 0 / Test Zone and DCZ 1 / Test Zone	145
20.2.9	Usage of DCZ Area	145

20.2.10	Protection-Zone 3	147
21	Physical-Access Control Clusters	148
21.1	General	148
21.2	Layout of PAC Zones	148
21.3	General structure of PAC Clusters	149
21.4	IS1 and IS2 PAC Clusters	152
22	Disk Management	153
22.1	General	153
22.2	Recording Management	153
22.2.1	Sequential-Recording Mode (SRM)	153
22.2.2	Recording User Data in SRR	153
22.2.3	SRR status	154
22.2.4	Closing SRR	154
22.3	Temporary Disk-Management Areas (TDMA)	154
22.3.1	General	154
22.3.2	TDMA Access indicators	154
22.4	Disk-Management Structure (DMS)	155
22.4.1	General	155
22.4.2	Temporary Disk-Management Structure (TDMS)	155
22.4.3	TDMS in Sequential-Recording Mode	156
22.4.4	Temporary Disk-Definition Structure (TDDS)	156
22.4.5	Temporary Defect List (TDFL)	160
22.4.6	Sequential-Recording Range Information (SRRI)	162
22.5	Unrecorded (blank) disk structure	164
22.5.1	General	164
22.5.2	Pre-recorded Areas on Unrecorded disk	164
22.5.3	Pre-recorded BCA	165
22.5.4	Pre-recorded INFO 2 / Reserved 5, Reserved 8 and Pre-recorded INFO 1 / Pre-write Area	165
22.5.5	Pre-recorded INFO 1 / PAC 1 and Pre-recorded INFO 2 / PAC 2	165
22.5.6	OPC 0 / Test Zone and OPC 1 / Test Zone	165
22.5.7	TDMA 0	166
22.5.8	Initialization of disk	166
22.6	Recorded (Closed) disk structure	166
22.6.1	General	166
22.6.2	DMA Zones	166
22.6.3	Disk-Management Structures (DMS)	167
23	Assignment of Logical-Sector Numbers (LSNs)	169
24	Characteristics of Grooved Areas	170
25	Method of testing for Grooved Area	171
25.1	General	171
25.2	Environment	171
25.3	Reference drive	171
25.3.1	General	171
25.3.2	Read power	171
25.3.3	Read channels	171
25.3.4	Tracking requirements	171
25.3.5	Scanning velocities	171
25.4	Definition of signals	172
26	Signals from HFM Groove	174
26.1	Push-Pull polarity	174
26.2	Push-Pull signal	174
26.3	Wobble signal	174
26.4	Jitter of HFM signal	174
27	Signals from Wobbled Groove(s)	175
27.1	Phase depth	175

27.2	Push-Pull signal	175
27.3	Wobble signal	175
27.3.1	General	175
27.3.2	Measurement of NWS	176
27.3.3	Measurement of wobble CNR	176
27.3.4	Measurement of harmonic distortion of wobble	176
27.4	HFM and Wobbled Groove transition requirements	176
28	Characteristics of Recording Layer	177
29	Method of testing for Recording Layer	178
29.1	General	178
29.2	Environment	178
29.3	Reference drive	178
29.3.1	General	178
29.3.2	Read power	178
29.3.3	Read channels	178
29.3.4	Tracking requirements	178
29.3.5	Scanning velocities	178
29.4	Write conditions	179
29.4.1	Write-pulse waveform	179
29.4.2	Write powers	180
29.4.3	Write conditions for jitter measurement	180
29.5	Definition of signals	180
30	Signals from Recorded Areas	182
30.1	HF signals	182
30.2	Modulated amplitude	182
30.3	Reflectivity-Modulation product	183
30.4	Asymmetry	183
30.5	Jitter	183
30.6	Read stability	184
31	Local defects	185
32	Characteristics of User Data	185
33	Method of testing for User Data	186
33.1	General	186
33.2	Environment	186
33.3	Reference drive	186
33.3.1	General	186
33.3.2	Read power	186
33.3.3	Read channels	186
33.3.4	Error correction	186
33.3.5	Tracking requirements	186
33.3.6	Scanning velocities	186
33.4	Definition of signals	187
34	Minimum quality of recorded information	188
34.1	Symbol Error Rate	188
34.2	Maximum burst errors	188
34.3	User-written Data	188
35	BCA	189
Annex A (normative) Thickness of Transmission Stacks in case of multiple layers		190
A.1	General	190
A.2	Refractive Index n_i of all layers in Cover and Spacer Layers	190
A.3	Thickness variation of Transmission Stack	190
A.4	Example of thickness calculation for SL	190

Annex B (normative) Measurement of reflectivity	191
B.1 General	191
B.2 Calibration method	191
B.3 Measuring method	192
Annex C (normative) Measurement of scratch resistance of Cover Layer	194
C.1 General	194
C.2 Taber Abrasion test	194
Annex D (normative) Measurement of repulsion of grime by Cover Layer	196
D.1 General	196
D.2 Specifications of stamp	196
D.3 Preparation of ink	197
D.4 Preparation of ink pad	197
D.5 Using ink pad and stamp	198
Annex E (normative) Measurement of wobble amplitude	199
E.1 Measurement methods	199
E.2 Calibration of filters	203
Annex F (normative) Write-pulse waveform for testing	204
F.1 General write-pulse waveform	204
F.2 N-1 write strategy	205
F.3 N/2 write strategy	208
F.4 Castle write strategy	211
F.5 Definition of pulse widths and rise and fall times	215
Annex G (normative) Optimum Power Control(OPC) procedure for disk	216
G.1 General	216
G.2 Mathematical model for modulation versus power function	216
G.3 Procedure for determination of OPC parameters for disk	218
G.4 Procedure to determine Beta value	218
Annex H (normative) HF signal pre-processing for jitter measurements	220
H.1 General	220
H.2 General implementation of equalizer	220
H.3 Conventional Equalizer circuit	221
H.4 Limit Equalizer circuit	222
H.5 Specifications of supporting circuits	223
H.5.1 Amplifiers and filters	223
H.5.2 Open-loop transfer function for PLL	224
H.5.3 Slicer	225
H.6 Condition for measurement	225
H.7 Jitter measurement	226
Annex I (normative) Measurement procedure	227
I.1 General	227
I.2 Initial adjustments of Reference drive	227
I.3 Jitter measurement	227
I.4 Modulated amplitude measurements	228
I.5 Measurements of Resolution I2pp / I8pp and I3pp / I8pp	228
I.5.1 Method for measuring I2pp and I8pp	228
I.5.2 I3pp / I8pp, I8pp / I8H and asymmetry measurement procedure	229

I.6	Tracking-error signal measurements (PPnorm measurement procedure)	230
I.7	Residual error of axial tracking measurement procedure	231
I.8	Residual error of radial tracking measurement procedure	232
I.9	Random SER measurement	233
Annex J (informative) Measurement of birefringence		234
J.1	Principle of measurement	234
J.2	Measurements conditions	234
J.3	Example of measurement procedure	235
J.4	Interchangeability of measuring results	235
Annex K (informative) Measurement of thickness of Cover Layer and Spacer Layer		236
K.1	Focusing method	236
K.2	Interferometer method	237
Annex L (informative) Measurement of impact resistance of Cover Layer		239
L.1	General	239
L.2	Recommendation for drives	239
L.3	Measurements of impact resistance of Cover Layer	239
Annex M (informative) Groove deviation and wobble amplitude		241
M.1	Relation between normalized wobble signal and wobble amplitude	241
M.2	Tolerance of normalized wobble signal	241