

ISO/IEC 14443-2:2016-07 (E)

Identification cards - Contactless integrated circuit cards - Proximity cards - Part 2: Radio frequency power and signal interface

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
5	General considerations	4
5.1	Initial dialogue	4
5.2	Compliance	4
5.2.1	PICC compliance	4
5.2.2	PCD compliance	4
6	Power transfer	5
6.1	Frequency	5
6.2	Operating field strength	5
7	Signal interface	7
8	Communication signal interface Type A	8
8.1	Communication PCD to PICC	8
8.1.1	Bit rate	8
8.1.2	Modulation	9
8.1.3	Bit representation and coding	16
8.2	Communication PICC to PCD	17
8.2.1	Bit rate	17
8.2.2	Load modulation	17
8.2.3	Subcarrier	21
8.2.4	Subcarrier modulation	21
8.2.5	Bit representation and coding	22
9	Communication signal interface Type B	22
9.1	Communication PCD to PICC	22
9.1.1	Bit rate	22
9.1.2	Modulation	23
9.1.3	Bit representation and coding	31
9.2	Communication PICC to PCD	31
9.2.1	Bit rate	31
9.2.2	Load modulation	31
9.2.3	Subcarrier	31
9.2.4	Subcarrier modulation	31
9.2.5	Bit representation and coding	31
10	Electromagnetic disturbance levels	32
10.1	PCD limits	32
10.2	PICC limits	32

Annex A (normative) Bit rates of $3f_c/4$, f_c, $3f_c/2$ and $2f_c$ from PCD to PICC	34
Annex B (informative) Complex envelope and constellation diagram	42
Annex C (informative) Inter Symbol Interference	43