

# DIN ISO/IEC 28360:2017-01 (E)

## Information technology - Office equipment - Determination of chemical emission rates from electronic equipment (ISO/IEC 28360:2015)

---

<b>Contents</b>		<b>Page</b>
National foreword.....		4
National Annex NA (informative) Bibliography.....		5
Introduction.....		6
1 Scope.....		7
2 Conformance .....		7
3 Normative references.....		8
4 Terms and definitions .....		8
5 Symbols and abbreviated terms .....		11
5.1 Abbreviated terms .....		11
5.2 Symbols.....		12
6 Method overview .....		13
7 ETC requirements.....		15
7.1 Construction materials .....		15
7.2 Air tightness.....		15
7.3 Air mixing efficiency .....		15
8 Determination method .....		15
8.1 Test conditions .....		15
8.1.1 General .....		15
8.1.2 Operating temperature and relative humidity (rH) .....		15
8.1.3 Air exchange rate (n).....		15
8.1.4 Air velocity .....		15
8.1.5 Sampled air flow .....		15
8.2 Handling of EUT and ETC .....		15
8.2.1 Selection and storage of EUT .....		15
8.2.2 Loading Factor.....		15
8.2.3 ETC purging .....		16
8.2.4 Background concentrations (C <sub>bg</sub> ) .....		16
8.2.5 EUT unpacking .....		16
8.2.6 Preparation of the EUT before testing.....		16
8.2.7 EUT installation .....		17
8.2.8 EUT operation during test .....		18
8.3 VOC, carbonyl compounds .....		19
8.3.1 Sorbents .....		19
8.3.2 Sample collection .....		19
8.3.3 Emission rate calculation .....		20
8.4 Ozone.....		21
8.4.1 Analyser and sampling line requirements .....		22
8.4.2 Monitoring .....		22
8.4.3 Emission rate calculation .....		23
8.5 Particulate matter .....		23
8.5.1 Weighing and Filter conditioning .....		24
8.5.2 Sampling.....		24
8.5.3 Emission rate calculation .....		24
8.6 Fine and Ultrafine Particles (FP and UFP) .....		25
8.6.1 General Requirements for Aerosol Measuring Systems (AMS) .....		26
8.6.2 Measurement .....		28
8.6.3 Calculation .....		28

<b>9</b>	<b>Test report</b> .....	<b>31</b>
<b>Annex A (normative)</b>	<b>Print Patterns</b> .....	<b>34</b>
<b>A.1</b>	<b>Monochrome print pattern 5% coverage</b> .....	<b>34</b>
<b>A.2</b>	<b>Colour print pattern, 20% coverage</b> .....	<b>36</b>
<b>Annex B (normative)</b>	<b>Preparatory AMS Test Procedures</b> .....	<b>37</b>
<b>B.1</b>	<b>Procedures for operational readiness of AMS</b> .....	<b>37</b>
<b>B.1.1</b>	<b>Particle size concentration range measurements</b> .....	<b>37</b>
<b>B.1.2</b>	<b>Particle number concentration range measurements</b> .....	<b>37</b>
<b>B.2</b>	<b>Procedures for Operational readiness test of Fast AMS</b> .....	<b>38</b>
<b>B.2.1</b>	<b>Set up of instrument</b> .....	<b>38</b>
<b>B.2.2</b>	<b>Zero Check</b> .....	<b>39</b>
<b>B.2.3</b>	<b>Preparation for measurement</b> .....	<b>39</b>
<b>B.3</b>	<b>Procedures for Operational readiness test of CPC</b> .....	<b>40</b>
<b>B.3.1</b>	<b>Preparation</b> .....	<b>40</b>
<b>Annex C (informative)</b>	<b>Emission rate model for EUT using consumables</b> .....	<b>42</b>
<b>C.1</b>	<b>Objective</b> .....	<b>42</b>
<b>C.2</b>	<b>Approach</b> .....	<b>42</b>
<b>C.3</b>	<b>General mass balance and concentration equations</b> .....	<b>42</b>
<b>C.4</b>	<b>Background SER</b> .....	<b>42</b>
<b>C.5</b>	<b>Emission during pre-operating phase</b> .....	<b>43</b>
<b>C.6</b>	<b>Emission during operating phase</b> .....	<b>43</b>
<b>C.7</b>	<b>Emission during post-operating phase</b> .....	<b>46</b>
<b>C.8</b>	<b>Special cases</b> .....	<b>47</b>
<b>C.9</b>	<b>Model for RAL-UZ 171 Option</b> .....	<b>48</b>
	<b>Bibliography</b> .....	<b>51</b>