

ISO/IEC 23008-1:2017-08 (E)

Information technology - High efficiency coding and media delivery in heterogeneous environments - Part 1: MPEG media transport (MMT)

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | vi |
| Introduction | | vii |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions and abbreviated terms | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Abbreviated terms | 4 |
| 4 | Conventions | 6 |
| 5 | Overview | 6 |
| 6 | MMT data model | 9 |
| 6.1 | General | 9 |
| 6.2 | Package | 10 |
| 6.3 | Asset | 10 |
| 6.4 | Media processing unit (MPU) | 11 |
| 6.5 | Asset delivery characteristics | 12 |
| 6.5.1 | General | 12 |
| 6.5.2 | ADC descriptors | 12 |
| 6.5.3 | Syntax | 13 |
| 6.5.4 | Semantics | 14 |
| 6.6 | Bundle delivery characteristics | 15 |
| 6.6.1 | General | 15 |
| 6.6.2 | BDC descriptors | 15 |
| 6.6.3 | Syntax | 15 |
| 6.6.4 | Semantics | 16 |
| 7 | ISOBMFF-based MPU | 17 |
| 7.1 | General | 17 |
| 7.2 | MPU brand definition | 18 |
| 7.3 | MPU box | 19 |
| 7.3.1 | Definition | 19 |
| 7.3.2 | Syntax | 20 |
| 7.3.3 | Semantics | 20 |
| 8 | MMT hint track | 21 |
| 8.1 | General | 21 |
| 8.2 | Sample description format | 21 |
| 8.2.1 | Definition | 21 |
| 8.2.2 | Syntax | 21 |
| 8.2.3 | Semantics | 21 |
| 8.3 | Sample format | 22 |
| 8.3.1 | Definition | 22 |
| 8.3.2 | Syntax | 22 |
| 8.3.3 | Semantics | 22 |

| | | |
|---------|---|----|
| 9 | Packetized delivery of Package | 23 |
| 9.1 | General | 23 |
| 9.2 | MMT protocol | 24 |
| 9.2.1 | General | 24 |
| 9.2.2 | Structure of an MMTP packet | 25 |
| 9.2.3 | Semantics | 26 |
| 9.2.4 | MMTP session description information | 29 |
| 9.3 | MMTP payload | 29 |
| 9.3.1 | General | 29 |
| 9.3.2 | MPU mode | 30 |
| 9.3.3 | Generic file delivery mode | 32 |
| 9.3.4 | Signalling message mode | 37 |
| 9.4 | MMTP operation | 38 |
| 9.4.1 | General | 38 |
| 9.4.2 | Delivering MPUs | 38 |
| 9.4.3 | Delivering generic objects | 40 |
| 9.4.4 | Header compression for MMTP packet | 43 |
| 10 | Signalling | 45 |
| 10.1 | General | 45 |
| 10.2 | Signalling message format | 46 |
| 10.2.1 | General | 46 |
| 10.2.2 | Syntax | 47 |
| 10.2.3 | Semantics | 47 |
| 10.3 | Signalling messages for Package consumption | 47 |
| 10.3.1 | General | 47 |
| 10.3.2 | PA message | 48 |
| 10.3.3 | MPI message | 49 |
| 10.3.4 | MPT message | 51 |
| 10.3.5 | CRI message | 51 |
| 10.3.6 | DCI message | 52 |
| 10.3.7 | PA table | 53 |
| 10.3.8 | MPI table | 54 |
| 10.3.9 | MP table | 57 |
| 10.3.10 | CRI table | 60 |
| 10.3.11 | DCI table | 61 |
| 10.3.12 | SSWR message | 63 |
| 10.3.13 | LS message | 64 |
| 10.3.14 | LR message | 65 |
| 10.3.15 | SI table | 66 |
| 10.4 | Signalling messages for Package delivery | 70 |
| 10.4.1 | General | 70 |
| 10.4.2 | Hypothetical receiver buffer model (HRBM) message | 71 |
| 10.4.3 | Measurement configuration (MC) message | 72 |
| 10.4.4 | ARQ configuration (AC) message | 74 |
| 10.4.5 | ARQ feedback (AF) message | 75 |
| 10.4.6 | Reception quality feedback (RQF) message | 78 |
| 10.4.7 | NAM feedback (NAMF) message | 80 |
| 10.4.8 | Low delay consumption (LDC) message | 82 |
| 10.4.9 | HRBM removal message | 83 |
| 10.4.10 | ADC message | 84 |
| 10.5 | Descriptors | 87 |
| 10.5.1 | CRI descriptor | 87 |
| 10.5.2 | MPU timestamp descriptor | 88 |
| 10.5.3 | Dependency descriptor | 89 |
| 10.5.4 | GFDT descriptor | 90 |
| 10.5.5 | SI descriptor | 92 |
| 10.6 | Syntax element groups | 93 |
| 10.6.1 | MMT_general_location_info | 93 |
| 10.6.2 | asset_id | 96 |
| 10.6.3 | Identifier mapping | 96 |

| | | |
|--------|---|-----|
| 10.6.4 | mime_type | 98 |
| 10.7 | ID and tags values | 98 |
| 11 | Hypothetical receiver buffer model (HRBM) | 100 |
| 11.1 | General | 100 |
| 11.2 | FEC decoding buffer | 101 |
| 11.3 | De-jitter buffer | 101 |
| 11.4 | MMTP packet decapsulation buffer | 102 |
| 11.5 | Usage of HRBM | 102 |
| 11.6 | Estimation of end-to-end delay and buffer requirement | 102 |
| 11.7 | HRBM signalling | 103 |
| 12 | Cross layer interface (CLI) | 103 |
| 12.1 | General | 103 |
| 12.2 | Cross layer information | 103 |
| 12.2.1 | General | 103 |
| 12.2.2 | Top-down QoS information | 103 |
| 12.2.3 | Bottom-up QoS information | 103 |
| 12.2.4 | Network abstraction for media (NAM) | 104 |
| 12.2.5 | Syntax | 104 |
| 12.2.6 | Semantics | 105 |
| | Annex A (informative) Jitter calculation in MMTP | 106 |
| | Annex B (normative) XML syntax and MIME type for signalling message | 107 |
| | Annex C (normative) AL-FEC framework for MMT | 114 |
| | Annex D (informative) QoS management model for MMT | 139 |
| | Annex E (informative) Operation of downloadable DRM and CAS | 141 |
| | Annex F (informative) DASH segment over MMTP | 142 |
| | Annex G (normative) Scheme of MMT URI | 145 |
| | Bibliography | 146 |