ISO/IEC TR 23008-13:2017-08 (E)

Information technology - High efficiency coding and media delivery in heterogeneous environments - Part 13: MPEG media transport implementation guidelines

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviated terms 1

4 Overview 1
4.1 System overview 1
4.2 Normative parts 2

5 MMT function deployments 3
5.1 General 3
5.2 Object reconstruction 3
5.2.1 General 3
5.2.2 Recovery in MPU mode 4
5.2.3 Recovery in GFD mode 5
5.3 Default assets 6
5.4 Low-delay live streaming 6
5.5 Parallel processing in MMT sending and receiving entities 9
5.5.1 Processing in MMT sending entity 9
5.5.2 Processing in MMT receiving entity 11
5.6 MPU streaming for live services 13
5.6.1 MPU packetization 13
5.6.2 Sending of MPU and signalling message 16
5.7 Fast MMT session acquisition 17
5.8 Referencing and processing non-timed data 18
5.8.1 General 18
5.8.2 Resource grouping and referencing 19
5.8.3 Receiver handling 19
5.9 Media adaptation for quality control in MMTP 19
5.9.1 General 19
5.9.2 Parameters for media adaptation 19
5.9.3 Adaptation operation of MMT entity 20
5.10 Hybrid delivery in MMT 20
5.10.1 General 20
5.10.2 Classification of hybrid delivery 20
5.10.3 Technical elements for hybrid delivery 21
5.11 Example of detailed implementation of MMT 22
5.11.1 Use case: Combination of MMT and MPEG-2 TS for synchronized presentation .22 5.11.2 Use case: True real-time video streaming over lossy channel 22
5.12 HRBM signalling for hybrid delivery 23
5.12.1 Hybrid delivery from the single MMT sending entity 23
5.12.2 Hybrid delivery from the multiple MMT sending entities 25
5.13 Error resilience in MMT protocol 27
5.14 Delay-constrained ARQ 28
5.14.1 General 28
5.14.2 Delivery-time constrained ARQ 28

5.14.3 Arrival-deadline constrained ARQ 29
5.15 Application layer forward error correction (AL-FEC) 31
5.15.1 FEC decoding method for ssbg_mode2 31
5.15.2 Usage of two-stage FEC coding structure 35
5.15.3 MPU mapping to source packet block 37
5.15.4 FEC for hybrid service 38
5.16 Delivery of encrypted MPUs 40

5.17 HRBM message updating 41
5.17.1 General 41
5.17.2 HRBM message sending schedule 41
5.17.3 Use case 42
5.18 MMTP packet with padded data 42

6 Use cases for MMT deployment 44
6.1 General 44
6.2 Delivery of DASH Presentations using MMT 44
6.2.1 General 44
6.2.2 Delivery of the MPD 44
6.2.3 Delivery of the data segments 44
6.3 Client operation for DASH service delivered through MMT Protocol 45
6.3.1 Delivery of MPD with MMTP 45
6.3.2 Delivery and consumption of DASH Segments with MMTP 45
6.4 Hybrid of MMT and DASH over heterogeneous network 47
6.5 MMT caching for effective bandwidth utilization 49
6.5.1 Overview of MMT caching middlebox architecture 49
6.5.2 Content-based caching of MMT media 49
6.5.3 MPU sync protocol between server and caching middlebox 52
6.5.4 MMT cache manifest 56
6.6 Usage of ADC signalling message 58
6.6.1 General 58
6.6.2 Operation in MMT sending entity 58
6.6.3 Operation in MANE router 58
6.6.4 Example operation in MMT receiving entities 58
6.6.5 QoE multiplexing gain and bottleneck coordination 58
6.7 MMT deployment in Japanese broadcasting systems 62
6.7.1 General 62
6.7.2 Broadcasting systems using MMT 62
6.7.3 Media transport protocol 64
6.7.4 Signalling information 69
6.7.5 Start-up procedure of broadcasting service 78
6.8 Conversion of MMTP stream to MPEG-2 TS 80
6.8.1 Overview of conversion operation 80
6.8.2 Restrictions to MMTP packets 80
6.8.3 Calculation of PTS, DTS 80
6.8.4 Restriction related to MPEG-2 T-STD 81
6.8.5 Packet field conversion rule 81
6.8.6 PSI conversion rules 82
6.9 MMT service provisioning at conventional broadcast environment 84
6.10 Usage of multimedia configuration for interface switching management 86

Bibliography 87