ISO/IEC/IEEE 8802-15-3:2017-10 (E)

Information technology - Telecommunications and inform ation exchange between systems - Local and metropolitan area networks - Specific requirements - Part 15-3: High data rate wireless multi-media networks

Contents

1. Overview 26

1.1 Scope 26
1.2 Purpose 26

2. Normative references 27

3. Definitions, acronyms, and abbreviations 28

3.1 Definitions 28
3.2 Acronyms and abbreviations 29

4. General description 33

4.1 What is a piconet? 33
4.2 Components of an IEEE 802.15.3 piconet 33
4.3 Overview of medium access control (MAC) functionality 33
4.3.1 Coordination 34
4.3.1.1 Starting a piconet 34
4.3.1.2 Handing over control of the piconet 34
4.3.1.3 Creating a child piconet 34
4.3.1.4 Creating a neighbor piconet 35
4.3.2 Ending a piconet 35
4.3.3 Ending a piconet with a dependent piconet involved 35
4.3.4 Association and disassociation 36
4.3.5 Security overview 36
4.3.6 The IEEE 802.15.3 superframe 36
4.3.7 Channel time management 37
4.3.8 Data communications between DEVs 38
4.3.9 Information discovery in the piconet 38
4.3.10 Dynamic channel selection 39
4.3.11 Power management 39
4.3.12 Controlling transmit power in the piconet 40
4.3.13 Superfame structure using quasi-omni mode 40
4.3.14 Frame aggregation 41
4.3.15 Beam forming 41
4.3.16 Channel probing 41
4.3.17 Unequal error protection (UEP) 41
4.4 Characteristics of the 2.4 GHz PHY 41
4.4.1 General characteristics 41
4.4.2 Coexistence and interoperability 42
4.5 Characteristics of the mmWave PHY 42
4.5.1 mmWave PHY characteristics 42
4.5.2 Piconets using mmWave PHY modes 43
4.6 Conventions 44
4.7 Concept of primitives 44

5. Layer management 46

5.1 Overview of management model 46
5.2 Generic management primitives 47
5.2.1 MLME-GET.request 48

5.2.2 MLME-GET.confirm 48
5.2.3 MLME-SET.request 48
5.2.4 MLME-SET.confirm 48
5.3 MLME SAP interface 49
5.3.1 Resetting the MAC/MLME 50
5.3.1.1 MLME-RESET.request 50
5.3.1.2 MLME-RESET.confirm 50
5.3.2 Scanning for piconets 51
5.3.2.1 MLME-SCAN.request 53
5.3.2.2 MLME-SCAN.confirm 53
5.3.2.3 MLME-SCAN.indication 54
5.3.3 Starting a piconet 54
5.3.3.1 MLME-START.request 55
5.3.3.2 MLME-START.confirm 55
5.3.4 Stopping a piconet 55
5.3.4.1 MLME-STOP.request 56
5.3.4.2 MLME-STOP.confirm 56
5.3.5 Associating with a piconet 57
5.3.5.1 MLME-ASSOCIATE.request 58
5.3.5.2 MLME-ASSOCIATE.confirm 58
5.3.5.3 MLME-ASSOCIATE.indication 58
5.3.6 Disassociation from a piconet 58
5.3.6.1 MLME-DISASSOCIATE.request 59
5.3.6.2 MLME-DISASSOCIATE.confirm 59
5.3.6.3 MLME-DISASSOCIATE.indication 60
5.3.7 Security management 60
5.3.7.1 MLME-MEMBERSHIP-UPDATE.request 62
5.3.7.2 MLME-MEMBERSHIP-UPDATE.confirm 62
5.3.7.3 MLME-SECURITY-ERROR.indication 62
5.3.7.4 MLME-SECURITY-MESSAGE.request 62
5.3.7.5 MLME-SECURITY-MESSAGE.confirm 63
5.3.7.6 MLME-SECURITY-MESSAGE.indication 63
5.3.8 PNC handover 63
5.3.8.1 MLME-PNC-HANDOVER.indication 63
5.3.8.2 MLME-PNC-HANDOVER.response 64
5.3.8.3 MLME-NEW-PNC.indication 64
5.3.9 Requesting DEV information from the PNC 64
5.3.9.1 MLME-DEV-INFO.request 65
5.3.9.2 MLME-DEV-INFO.confirm 65
5.3.9.3 MLME-DEV-INFO.indication 65
5.3.10 Security information retrieval 65
5.3.10.1 MLME-SECURITY-INFO.request 65
5.3.10.2 MLME-SECURITY-INFO.confirm 66
5.3.10.3 MLME-SECURITY-INFO.indication 67
5.3.10.4 MLME-SECURITY-INFO.response 67
5.3.11 Application specific data management 67
5.3.11.1 MLME-APPLICATION-SPECIFIC.request 68
5.3.11.2 MLME-APPLICATION-SPECIFIC.confirm 69
5.3.11.3 MLME-APPLICATION-SPECIFIC.indication 69
5.3.12 Piconet services management 69
5.3.12.1 MLME-ANNOUNCE-SERVICE.request 70
5.3.12.2 MLME-ANNOUNCE-SERVICE.confirm 70
5.3.12.3 MLME-PICONET-SERVICES.request 71
5.3.12.4 MLME-PICONET-SERVICES.confirm 71

5.3.12.5 MLME-PICONET-SERVICES.indication ... 71
5.3.13 Stream management ... 71
5.3.13.1 MLME-CREATE-STREAM.request ... 73
5.3.13.2 MLME-CREATE-STREAM.confirm ... 74
5.3.13.3 MLME-CREATE-STREAM.indication ... 74
5.3.13.4 MLME-MODIFY-STREAM.request ... 74
5.3.13.5 MLME-MODIFY-STREAM.confirm ... 75
5.3.13.6 MLME-TERMINATE-STREAM.request ... 75
5.3.13.7 MLME-TERMINATE-STREAM.confirm ... 75
5.3.13.8 MLME-TERMINATE-STREAM.indication ... 75
5.3.14 Piconet parameter management ... 76
5.3.14.1 MLME-BSID-CHANGE.request ... 76
5.3.14.2 MLME-BSID-CHANGE.confirm ... 76
5.3.14.3 MLME-PICONET-PARM-CHANGE.indication ... 77
5.3.15 Power management ... 77
5.3.15.1 MLME-PS-SET-INFORMATION.request ... 79
5.3.15.2 MLME-PS-SET-INFORMATION.confirm ... 79
5.3.15.3 MLME-SPS-CONFIGURE.request ... 79
5.3.15.4 MLME-SPS-CONFIGURE.confirm ... 80
5.3.15.5 MLME-PM-MODE-CHANGE.request ... 80
5.3.15.6 MLME-PM-MODE-CHANGE.confirm ... 80
5.3.15.7 MLME-PM-MODE-CHANGE.indication ... 80
5.3.15.8 MLME-MONITOR-PM-MODE.request ... 81
5.3.15.9 MLME-MONITOR-PM-MODE.confirm ... 81
5.3.15.10 MLME-MONITOR-PM-MODE.indication ... 81
5.3.16 Multicast operations ... 82
5.3.16.1 MLME-MULTICAST-CONFIGURATION.request ... 83
5.3.16.2 MLME-MULTICAST-CONFIGURATION.confirm ... 83
5.3.16.3 MLME-MULTICAST-RX-SETUP.request ... 83
5.3.16.4 MLME-MULTICAST-RX-SETUP.confirm ... 84
5.3.17 Timing synchronization ... 84
5.3.17.1 MLME-BEACON-EVENT.request ... 84
5.3.17.2 MLME-BEACON-EVENT.confirm ... 84
5.3.17.3 MLME-BEACON-EVENT.indication ... 85
5.3.18 Transmit switched diversity (TSD) ... 85
5.3.18.1 MLME-TXDIV.request ... 85
5.3.18.2 MLME-TXDIV.confirm ... 86
5.4 MAC management ... 86
5.4.1 MAC PIB PNC group ... 86
5.4.2 MAC PIB characteristic group ... 87
5.5 MAC SAP ... 88
5.5.1 MAC-ASYNC-DATA.request ... 91
5.5.2 MAC-ASYNC-DATA.confirm ... 91
5.5.3 MAC-ASYNC-DATA.indication ... 91
5.5.4 MAC-ISOCH-DATA.request ... 92
5.5.5 MAC-ISOCH-DATA.confirm ... 92
5.5.6 MAC-ISOCH-DATA.indication ... 93

6. MAC frame formats ... 94

6.1 Frame format conventions ... 94
6.2 General frame format ... 95
6.2.1 Frame Control field ... 96
6.2.1.1 Protocol Version field ... 96

6.2.1.2 Frame Type field ... 97
6.2.1.3 SEC field ... 97
6.2.1.4 ACK Policy field, Imp-ACK Request field, and Blk-ACK field ... 97
6.2.1.5 Retry field ... 97
6.2.1.6 More Data field ... 98
6.2.1.7 Imp-ACK Negative Acknowledgment (NAK) field ... 98
6.2.1.8 CTA Relinquish field ... 98
6.2.2 Piconet ID (PNID) field ... 99
6.2.3 SrcID and DestID fields ... 99
6.2.4 Fragmentation Control field ... 99
6.2.4.1 MSDU Number field ... 99
6.2.4.2 Fragment Number field ... 100
6.2.4.3 Last Fragment Number field ... 100
6.2.5 Stream Index field ... 100
6.2.6 MAC header validation ... 100
6.2.7 MAC Frame Body field ... 101
6.2.7.1 Frame Payload field ... 101
6.2.7.2 Secure session ID (SECID) field ... 101
6.2.7.3 Secure Frame Counter (SFC) field ... 101
6.2.7.4 Secure Payload field ... 101
6.2.7.5 Integrity Code field ... 101
6.2.7.6 Frame Check Sequence (FCS) field ... 101
6.2.8 SC and HSI aggregated frame format ... 102
6.2.8.1 Standard aggregation format ... 102
6.2.8.1.1 Non-secure standard aggregation format ... 102
6.2.8.1.2 Secure standard aggregation format ... 105
6.2.8.2 Low-latency aggregation formats ... 105
6.2.8.2.1 Non-secure low-latency aggregation format ... 105
6.2.8.2.2 Secure low-latency aggregation format ... 108
6.2.9 AV aggregated frame format ... 109
6.2.9.1 Extended MAC header format ... 109
6.2.9.1.1 Extended Control Header field ... 110
6.2.9.1.2 MAC Extension Header field ... 111
6.2.9.1.3 Security Header field ... 112
6.2.9.1.4 Video Header field ... 112
6.2.9.2 Subframe format ... 113
6.2.9.3 AV aggregated ... 115
6.2.9.4 Regular ... 115
6.2.9.5 Directional ACK ... 116
6.3 Format of individual frame types ... 116
6.3.1 Beacon frame ... 116
6.3.1.1 Non-secure Beacon frame ... 116
6.3.1.2 Secure Beacon frame ... 118
6.3.2 Acknowledgment frames ... 119
6.3.2.1 Imm-ACK frame ... 119
6.3.2.2 Delayed ACK (Dly-ACK) frame ... 120
6.3.3 Command frame ... 121
6.3.3.1 Non-secure Command frame ... 121
6.3.3.2 Secure Command frame ... 122
6.3.4 Data frame ... 123
6.3.4.1 Non-secure Data frame ... 123
6.3.4.2 Secure Data frame ... 123
6.3.5 Multi-protocol Data frame ... 124
6.3.5.1 Non-secure Multi-protocol Data frame ... 124

6.3.5.2 Secure Multi-protocol Data frame 125
6.3.6 Sync frame 125
6.4 Information elements (IEs) 126
6.4.1 CTA IE 128
6.4.2 BSID IE 129
6.4.3 Parent Piconet IE 129
6.4.4 DEV Association IE 129
6.4.5 PNC shutdown IE 130
6.4.6 Piconet Parameter Change IE 131
6.4.7 AS IE 132
6.4.8 Pending channel time map (PCTM) IE 132
6.4.9 PNC Handover IE 133
6.4.10 CTA Status IE 133
6.4.11 Capability IE 134
6.4.12 Transmit Power Parameters IE 140
6.4.13 PS Status IE 141
6.4.14 CWB IE 141
6.4.15 Overlapping PNID IE 142
6.4.16 Piconet Services IE 142
6.4.17 Vendor Defined IE 143
6.4.18 Group ID IE 143
6.4.19 Stream Renew IE 144
6.4.20 Next PNC IE 144
6.4.21 Piconet Channel Status IE 144
6.4.22 Synchronization IE 145
6.4.23 TSD IE 147
6.4.24 UEP Specific IE 148
6.4.25 IFS IE 148
6.4.26 CTA Relinquish Duration IE 149
6.4.27 Feedback IE 149
6.4.28 Mapping IE 151
6.4.29 BST Clustering IE 152
6.4.30 PET Clustering IE 152
6.4.31 Beam PET IE 153
6.4.32 HRS Beam PET IE 154
6.4.33 PET Amplitude IE 155
6.4.34 PET Phase IE 155
6.4.35 Sync Frame Frequency IE 156
6.4.36 Directional Peer IE 156
6.5 MAC commands 157
6.5.1 Association and disassociation commands 159
6.5.1.1 Association Request command 159
6.5.1.2 Association Response command 160
6.5.1.3 Disassociation Request command 161
6.5.2 Security commands 161
6.5.2.1 Request Key command 161
6.5.2.2 Request Key Response command 161
6.5.2.3 Distribute Key Request command 162
6.5.2.4 Distribute Key Response command 162
6.5.3 PNC handover commands 162
6.5.3.1 PNC Handover Request commnad 163
6.5.3.2 PNC Handover Response command 163
6.5.3.3 PNC Handover Information command 164
6.5.4 Information request commands 164

6.5.4.1 PNC Information Request command 164
6.5.4.2 PNC Information command 164
6.5.4.3 Security Information Request command 166
6.5.4.4 Security Information command 166
6.5.4.5 Probe Request command 167
6.5.4.6 Probe Response command 169
6.5.5 Information announcement commands 171
6.5.5.1 Piconet Services command 171
6.5.5.2 Announce command 171
6.5.5.3 Announce Response command 173
6.5.6 Channel time allocation request, modification, and termination commands 173
6.5.6.1 Channel Time Request command 173
6.5.6.2 Channel Time Response command 176
6.5.7 Channel status commands 177
6.5.7.1 Channel Status Request command 177
6.5.7.2 Channel status response 177
6.5.7.3 Remote Scan Request command 178
6.5.7.4 Remote Scan Response command 178
6.5.7.5 Transmit Power Change command 180
6.5.8 Power management commands 180
6.5.8.1 PS Set Information Request command 180
6.5.8.2 PS Set Information Response command 180
6.5.8.3 SPS Configuration Request command 181
6.5.8.4 SPS Configuration Response command 182
6.5.8.5 PM Mode Change command 183
6.5.8.6 PM Mode Change Response command 183
6.5.9 Special commands 184
6.5.9.1 Security Message command 184
6.5.9.2 Vendor Defined command 184
6.5.9.3 AS IE Request command 185
6.5.9.4 AS IE Response command 185
6.5.10 Multicast configuration commands 186
6.5.10.1 Multicast Configuration Request command 186
6.5.10.2 Multicast Configuration Response command 186

7. MAC functional description 187

7.1 Introduction 187
7.2 Starting, maintaining, and stopping piconets 188
7.2.1 Scanning through channels 188
7.2.2 Starting a piconet 189
7.2.3 PNC handover 190
7.2.4 Preliminary handover 193
7.2.5 Next PNC 194
7.2.6 Dependent PNC handover 195
7.2.7 Child piconet 198
7.2.8 Neighbor piconet 200
7.2.9 Stopping piconet operations 202
7.2.9.1 Stopping an independent or parent piconet 203
7.2.9.2 Parent PNC stopping a dependent piconet 203
7.2.9.3 Dependent PNC termination of a dependent piconet 204
7.2.10 Non-PNC-capable DEVs 204
7.3 Association and disassociation with a piconet 204
7.3.1 Association 204

7.3.2 Piconet services 206
7.3.3 Broadcasting piconet information 208
7.3.4 Disassociation 209
7.4 Channel access 210
7.4.1 Interframe space (IFS) 211
7.4.2 Carrier sense multiple access with collision avoidance (CSMA/CA) 211
7.4.3 Channel time allocation period channel access 213
7.4.3.1 Channel time allocations (CTAs) 213
7.4.3.2 Channel time allocation (CTA) and channel time usage 215
7.4.3.3 Management CTAs 216
7.4.3.4 Slotted aloha access 216
7.4.3.5 Allocation of MCTAs 217
7.4.3.6 Guard time 217
7.4.3.7 Calculating channel time requests 219
7.4.3.8 Relinquishing CTA time to another DEV 220
7.5 Channel time management 222
7.5.1 Isochronous stream management 222
7.5.1.1 Isochronous stream creation 223
7.5.1.2 Isochronous stream modification 226
7.5.1.3 Isochronous stream termination 229
7.5.2 Asynchronous channel time reservation and termination 231
7.5.2.1 Asynchronous channel time reservation 231
7.5.2.2 Asynchronous channel time termination 233
7.5.3 Multicast group configuration 234
7.6 Synchronization 235
7.6.1 Time accuracy 236
7.6.2 Beacon generation 236
7.6.3 Beacon reception 237
7.6.4 Beacon information announcement 237
7.6.5 Superframe support for directional PHYs 238
7.6.5.1 Quasi-omni beacon 239
7.6.5.2 Directional CAP 240
7.6.5.3 Directional association 241
7.6.5.4 DEV quasi-omni transmit direction training and tracking 242
7.7 Fragmentation and defragmentation 243
7.8 Aggregation 244
7.8.1 Standard aggregation 244
7.8.2 Low-latency aggregation 245
7.9 Acknowledgment and retransmission 246
7.9.1 No acknowledgment (no-ACK) 246
7.9.2 Immediate acknowledgment (Imm-ACK) 246
7.9.3 Delayed acknowledgment (Dly-ACK) 247
7.9.4 Implied acknowledgment (Imp-ACK) 248
7.9.5 Block acknowledgment (Blk-ACK) 250
7.9.5.1 Blk-ACK for standard aggregation 250
7.9.5.2 Blk-ACK for low-latency aggregation 251
7.9.6 Retransmissions 252
7.9.7 Duplicate detection 252
7.10 Peer discovery 252
7.10.1 PNC information request 252
7.10.2 Probe request and response 253
7.10.3 Announce 254
7.10.4 Channel status request 254
7.10.5 Remote scan 254

7.10.6 PNC channel scanning 255
7.10.7 Channel probing 255
7.11 Changing piconet parameters 256
7.11.1 Moving beacon 256
7.11.2 Changing superframe duration 256
7.11.3 Setting the PNID or BSID 257
7.11.4 Maintaining synchronization in dependent piconets 258
7.12 Interference mitigation 258
7.12.1 Dynamic channel selection 259
7.12.2 Transmit power control 260
7.12.2.1 Maximum transmitter power for the CAP, beacon, and directed MCTAs 260
7.12.2.2 Adjustable transmitter power in a CTA 261
7.13 Multi-rate support 261
7.14 Power management 262
7.14.1 Piconet synchronized power save (PSPS) mode 263
7.14.2 Device synchronized power save (DSPS) mode 264
7.14.2.1 Creation, use, and management of DSPS sets 264
7.14.2.2 Changing DSPS mode and operation 265
7.14.2.3 CTA timing in DSPS mode 266
7.14.3 Asynchronous power save (APS) mode 268
7.14.4 MSCs for power save modes 269
7.15 AS IE operation 272
7.16 MAC sublayer parameters 275
7.17 Unequal error protection (UEP) 278
7.18 Sync frame transmission and virtually dependent piconet 278

8. Security 280

8.1 Security mechanisms 280
8.1.1 Security membership and key establishment 280
8.1.2 Key transport 280
8.1.3 Data encryption 280
8.1.4 Data integrity 280
8.1.5 Beacon integrity protection 280
8.1.6 Command integrity protection 281
8.1.7 Freshness protection 281
8.2 Security modes 281
8.2.1 Security mode 0 281
8.2.2 Security mode 1 281
8.3 Security support 281
8.3.1 PNC handover 281
8.3.2 Changes in the piconet group data key 282
8.3.3 Joining a secure piconet 282
8.3.4 Membership update 282
8.3.5 Secure frame generation 283
8.3.6 Updating CurrentTimeToken 284
8.3.7 Secure frame reception 284
8.3.8 Selecting the SECID for a new key 285
8.3.9 Key selection 285
8.4 Protocol details 289
8.4.1 Security information request and distribution 289
8.4.2 Key distribution protocol 291
8.4.3 Key request protocol 291

9. Security specifications 292

9.1 Modes for security 292
9.2 Symmetric cryptography building blocks 292
9.2.1 Notational conventions 292
9.2.2 CCM combined encryption and data authentication 292
9.2.3 CCM parameters 292
9.2.4 Nonce value 292
9.2.5 AES encryption 293
9.3 Symmetric cryptography implementation 293
9.3.1 Symmetric cryptography data formats 293
9.3.2 Symmetric cryptographic operations 293
9.4 CCM mode 295
9.4.1 Inputs 295
9.4.2 Data authentication 296
9.4.3 Encryption 298
9.4.4 Output 298
9.4.5 Decryption 299
9.4.6 Restrictions 299
9.4.7 List of symbols 299

10. PHY specification for the 2.4 GHz band 301

10.1 Overview of the 2.4 GHz PHY 301
10.2 General requirements 302
10.2.1 Operating frequency range 302
10.2.2 Radio frequency (RF) power measurements 302
10.2.3 Channel assignments 302
10.2.4 Scanning channels 302
10.2.5 Unwanted emissions 303
10.2.6 Operating temperature range 303
10.2.7 PHY layer timing 303
10.2.7.1 Interframe space 303
10.2.7.2 Receive-to-transmit turnaround time 303
10.2.7.3 Transmit-to-receive turnaround time 304
10.2.7.4 Time between successive transmissions 304
10.2.7.5 Channel switch time 304
10.2.8 Data size restrictions 304
10.2.8.1 Maximum frame length 304
10.2.8.2 Maximum transfer unit size 304
10.2.8.3 Minimum fragment size 304
10.2.9 Header check sequence 304
10.2.10 Channel access methods 306
10.3 Modulation and coding 306
10.3.1 Base data rate 307
10.3.2 Signal constellations 307
10.3.3 DQPSK modulation 308
10.3.4 QPSK and 16/32/64-QAM with trellis coding 309
10.4 PHY frame format 316
10.4.1 Frame format 316
10.4.2 PHY preamble 317
10.4.3 Header modulation 319
10.4.4 Scrambling 319
10.4.5 PHY header 321

10.4.6 Stuff bits 322
10.4.7 Tail symbols 322
10.5 Transmitter specifications 325
10.5.1 Error vector magnitude definition 325
10.5.2 EVM calculated values 326
10.5.3 Transmit power spectral density (PSD) mask 326
10.5.4 Transmit center frequency tolerance 326
10.5.5 Symbol rate 326
10.5.6 Clock synchronization 327
10.5.7 Transmit power-on and power-down ramp 327
10.5.8 RF carrier suppression 327
10.5.9 Transmit power 327
10.6 Receiver specifications 328
10.6.1 Error rate criterion 328
10.6.2 Receiver sensitivity 328
10.6.3 Receiver maximum input level 329
10.6.4 Receiver jamming resistance 329
10.6.5 Receiver CCA performance 330
10.6.6 Receiver RSSI 330
10.6.7 Link quality indication 330
10.7 PHY management 330

11. PHY specification for millimeter wave 333

11.1 General requirements 333
11.1.1 Regulatory information 333
11.1.2 RF power measurements 334
11.1.3 Unwanted emissions 334
11.1.4 Operating temperature range 334
11.1.5 RF channelization 334
11.1.6 Transmit PSD mask 334
11.1.7 Error vector magnitude calculation 334
11.1.7.1 SC PHY 334
11.1.7.2 AV and HSI PHYs 335
11.1.8 Common PHY management for mmWave PHY modes 336
11.1.8.1 Supported MCSs 336
11.1.8.2 Preferred fragment size 336
11.1.8.3 Receive Status field 337
11.1.9 Requirements for mmWave PNCs 338
11.1.10 CP operation 338
11.1.11 mmWave PHY mode usage in CTA 339
11.1.12 Common mode signaling (CMS) 339
11.1.12.1 Forward error correction for CMS 340
11.1.12.2 Code spreading for CMS 340
11.1.12.3 Scrambling for CMS 340
11.1.12.4 PHY preamble for CMS 341
11.1.12.5 Frame header for CMS 341
11.1.12.6 PHY header for CMS 342
11.1.12.7 PHY Payload field for CMS 343
11.1.12.8 Receiver clear channel assessment performance for CMS 343
11.1.13 mmWave PHY PIB 343
11.2 Single Carrier Mode of mmWave PHY 344
11.2.1 PHY operating specifications of SC PHY 345
11.2.1.1 Channelization 345

11.2.1.2 Scanning channels ... 345
11.2.2 Modulation, forward error correction, and spreading ... 345
11.2.2.1 MCS-dependent parameters ... 345
11.2.2.2 Header rate-dependent parameters ... 347
11.2.2.3 Timing-related parameters ... 348
11.2.2.4 Frame-related parameters ... 348
11.2.2.5 Modulation ... 349
11.2.2.5.1 p/2 BPSK ... 349
11.2.2.5.2 p/2 QPSK ... 349
11.2.2.5.3 p/2 8-PSK ... 350
11.2.2.5.4 p/2 16-QAM ... 351
11.2.2.6 FEC ... 351
11.2.2.6.1 Reed-Solomon block codes in GF(28) ... 351
11.2.2.6.2 Irregular LDPC codes ... 352
11.2.2.6.3 Rate 14/15 LDPC code ... 353
11.2.2.7 Stuff bits ... 353
11.2.2.8 Code spreading ... 356
11.2.2.8.1 Golay sequences ... 356
11.2.2.8.2 PRBS generation with LFSR ... 356
11.2.2.9 Unequal error protection ... 357
11.2.2.10 Scrambling ... 358
11.2.3 SC PHY frame format ... 359
11.2.3.1 PHY preamble ... 360
11.2.3.1.1 Sync field ... 360
11.2.3.1.2 SFD field ... 360
11.2.3.1.3 Channel estimation sequence (CES) ... 360
11.2.3.2 Frame header ... 360
11.2.3.2.1 SC PHY header ... 362
11.2.3.2.2 Base header HCS ... 363
11.2.3.2.3 Base header FEC ... 363
11.2.3.2.4 MAC subheader HCS ... 363
11.2.3.2.5 MAC subheader FEC ... 364
11.2.3.3 SC PHY Payload field ... 364
11.2.3.3.1 SC PHY Payload scrambling ... 364
11.2.3.3.2 Modulation ... 364
11.2.3.3.3 FEC ... 364
11.2.3.3.4 Code spreading ... 364
11.2.3.4 Pilot word and PCES ... 365
11.2.3.4.1 Subblocks and pilot word ... 365
11.2.3.4.2 Pilot channel estimation sequence (PCES) ... 365
11.2.4 Transmitter specifications ... 366
11.2.4.1 Error vector magnitude ... 366
11.2.4.2 Transmit center frequency tolerance ... 366
11.2.4.3 Symbol rate ... 366
11.2.4.4 Transmit power-on and power-down ramp ... 366
11.2.5 Receiver specifications ... 366
11.2.5.1 Error rate criterion ... 366
11.2.5.2 Receiver sensitivity ... 367
11.2.5.3 Receiver maximum input level ... 367
11.2.5.4 Receiver clear channel assessment performance ... 367
11.2.6 PHY layer timing ... 368
11.2.6.1 Interframe space ... 368
11.2.6.2 Receive-to-transmit turnaround time ... 368
11.2.6.3 Transmit-to-receive turnaround-time ... 368

11.2.6.4 Time between successive transmissions 368
11.2.6.5 Channel switch 369
11.2.7 PHY management for SC PHY 369
11.2.7.1 Maximum frame size 369
11.2.7.2 Maximum transfer unit size 369
11.2.7.3 Minimum fragment size 369
11.2.8 Optional OOK/DAMI modes 369
11.2.8.1 OOK 369
11.2.8.2 DAMI 370
11.2.8.3 FEC 370
11.2.8.4 OOK/DAMI spreading 370
11.3 High Speed Interface mode of mmWave PHY 370
11.3.1 General operating specifications 370
11.3.1.1 Operating frequency bands 370
11.3.2 HSI PHY modulation, forward error correction, and spreading 370
11.3.2.1 MCS-dependent parameters 370
11.3.2.2 HSI PHY timing-related parameters 372
11.3.2.3 HSI PHY frame-related parameters 373
11.3.2.4 HSI PHY FEC 373
11.3.2.4.1 LDPC block code 374
11.3.2.4.2 EEP data multiplexer 374
11.3.2.4.3 UEP data multiplexer 374
11.3.2.4.4 Bit interleaver 375
11.3.2.5 Stuff bits 376
11.3.2.6 Constellation mapping 376
11.3.2.7 HSI spreader 378
11.3.2.7.1 Spreader for spreading factor of 1 379
11.3.2.7.2 Spreader for spreading factor of 48 379
11.3.2.8 Tone interleaver 379
11.3.2.9 HSI PHY OFDM modulator 380
11.3.2.9.1 Pilot subcarriers 381
11.3.2.9.2 Guard subcarriers 382
11.3.2.10 PCES insertion 382
11.3.2.11 HSI PHY scrambling 382
11.3.3 HSI PHY frame format 383
11.3.3.1 PHY preamble 383
11.3.3.2 Frame header 384
11.3.3.3 HSI PHY header 386
11.3.3.4 Header check sequences 387
11.3.3.4.1 Main Header HCS 387
11.3.3.4.2 MAC Subheader HCS 387
11.3.3.5 PHY Payload field 388
11.3.4 Transmitter specifications 388
11.3.4.1 EVM requirement 388
11.3.4.2 Chip rate and clock alignment 389
11.3.5 Receiver specifications 389
11.3.5.1 Receiver sensitivity 389
11.3.5.2 Receiver CCA performance 389
11.3.5.3 Receiver maximum input level 389
11.3.5.4 PHY layer timing 389
11.3.5.5 Interframe spacing 389
11.3.5.6 Receive-to-transmit turnaround time 390
11.3.5.7 Transmit-to-receive turnaround time 390
11.3.5.8 Time between successive transmissions 390

11.3.5.9 Channel switch time 390
11.3.6 HSI PHY management 390
11.3.6.1 PHY supported data rate encoding 390
11.3.6.2 HSI PHY fragment size encoding 390
11.3.6.3 Maximum frame length 391
11.3.6.4 Maximum transfer unit size 391
11.3.6.5 Minimum fragment size 391
11.4 Audio/Visual mode of mmWave PHY 391
11.4.1 General requirements 392
11.4.1.1 AV PHY channelization 392
11.4.1.2 PHY layer timing 393
11.4.1.2.1 Interframe space 393
11.4.1.2.2 Receive-to-transmit turnaround time 394
11.4.1.2.3 Transmit-to-receive turnaround time 394
11.4.1.2.4 Time between successive transmissions 394
11.4.1.2.5 Channel switch time 394
11.4.1.2.6 CCA detect time 394
11.4.1.3 Data size restrictions 394
11.4.1.3.1 Maximum frame length 394
11.4.1.3.2 Maximum transfer unit size 395
11.4.1.3.3 Minimum fragment size 395
11.4.1.4 Header check sequence 395
11.4.2 AV PHY modulation and forward error correction 395
11.4.2.1 AV PHY base rate 396
11.4.2.2 Repetition coding and spatial diversity 397
11.4.2.3 Stuff bits 397
11.4.2.4 HRP splitter and scrambler 398
11.4.2.5 LRP scrambler 398
11.4.2.6 HRP outer code 399
11.4.2.7 HRP outer interleaver 399
11.4.2.8 Convolutional encoder 400
11.4.2.9 Puncturing 400
11.4.2.10 HRP data multiplexer and bit interleaver 400
11.4.2.10.1 EEP data multiplexer 401
11.4.2.10.2 UEP coding data multiplexer 402
11.4.2.10.3 UEP mapping data multiplexer 404
11.4.2.10.4 HRP header data multiplexer 405
11.4.2.11 Bit reversal tone interleaver 406
11.4.2.12 Signal constellations 406
11.4.2.13 AV PHY non-data subcarriers 407
11.4.2.14 AV PHY OFDM modulation 408
11.4.3 AV PHY frame formats 409
11.4.3.1 HRP preamble 410
11.4.3.2 HRP header 411
11.4.3.3 LRP preamble sequences 411
11.4.3.4 Long omni LRP preamble 412
11.4.3.5 Short omni LRP preamble 413
11.4.3.6 Omni LRP header 414
11.4.3.7 Directional LRP preamble 414
11.4.3.8 Directional LRP header and payload 415
11.4.4 AV PHY transmitter requirements 416
11.4.4.1 TX mask 416
11.4.4.2 EVM requirement 417
11.4.4.3 Symbol timing 417

11.4.4.4 TX frequency accuracy 418
11.4.4.5 TX power ramp on and off 418
11.4.5 AV PHY Receiver characteristics 418
11.4.5.1 Error rate criterion 418
11.4.5.2 Sensitivity 418
11.4.5.3 Maximum input level 418
11.4.6 Preambles and training symbols 418

12. Beam forming 423

12.1 Introduction 423
12.2 Beam forming terminology 423
12.2.1 Quasi-omni patterns 424
12.2.2 Sectors 424
12.2.3 Beams 425
12.2.4 Clusters 426
12.3 Beam forming codebooks 427
12.3.1 Beam forming codebooks 428
12.4 Beam forming reference model 429
12.5 Beam forming protocol 431
12.5.1 Two-level training mechanism 431
12.5.1.1 Sector-level training 431
12.5.1.1.1 AAS sector-level training 431
12.5.1.1.2 SAS sector-level training 434
12.5.1.1.3 Sector-level training failure remedy 437
12.5.1.2 Beam-level training 437
12.5.1.2.1 AAS beam-level training 437
12.5.1.2.2 SAS beam-level training 440
12.5.2 Beam tracking 443
12.6 On-demand beam forming 445
12.7 Proactive beam forming 445
12.8 TSD 445

Annex A (informative) Bibliography 447

Annex B (normative) Frame convergence sublayer 448

B.1 Generic convergence sublayer 448
B.2 EPD FCSL PDU classification 449
B.3 EPD FCSL 449
B.3.1 EPD FCSL QoS support 450
B.3.2 Data entity inter-relationships 450
B.4 EPD FCSL SAP 451
B.4.1 MA-UNITDATA.request 452
B.4.2 MA-UNITDATA.indication 452
B.4.3 MA-UNITDATA-STATUS.indication 453
B.5 Stream SAP 454
B.5.1 Stream creation, modification, and deletion 454
B.5.1.1 STREAM_INITIATE.request 456
B.5.1.2 STREAM_INITIATE.confirm 456
B.5.1.3 STREAM_INITIATE.indication 456
B.5.1.4 STREAM_MODIFY.request 457
B.5.1.5 STREAM_MODIFY.confirm 457
B.5.1.6 STREAM_END.request 457

B.5.1.7 STREAM_END.confirm ... 458
B.5.1.8 STREAM_END.indication ... 458
B.5.2 Stream data interface ... 458
B.5.2.1 STREAM_DATA.request ... 459
B.5.2.2 STREAM_DATA.confirm ... 460
B.5.2.3 STREAM_DATA.indication ... 460

Annex C (informative) Security considerations ... 461

C.1 Background assumptions ... 461
C.1.1 Physical assumptions ... 461
C.1.2 Network assumptions ... 461
C.1.3 Attack model assumptions ... 462
C.1.4 Security key lifecycle issues ... 462
C.1.4.1 Key lifecycle ... 462
C.1.4.2 Membership lifecycle ... 462
C.1.4.3 Group membership change rekey ... 462
C.2 Claimed security services ... 462
C.2.1 Beacon protection protocol ... 462
C.2.2 Distribute key protocol ... 463
C.2.3 Key request protocol ... 463
C.2.4 Data protection protocol ... 464
C.3 Properties of the IEEE 802.15.3 security suite ... 464
C.3.1 Key usage ... 464
C.3.2 Replay prevention ... 464

Annex D (informative) Coexistence, interoperability, and interference ... 466

D.1 Interoperability ... 466
D.1.1 Interoperability with IEEE 802.11 DSSS and IEEE 802.11b ... 466
D.1.2 IEEE 802.11 FHSS and IEEE 802.15.1 ... 467
D.2 Coexistence ... 467
D.2.1 Coexistence with IEEE Std 802.11b ... 467
D.2.1.1 Passive scanning ... 468
D.2.1.2 Dynamic channel selection ... 468
D.2.1.3 The ability to request channel quality information ... 468
D.2.1.4 Link quality and RSSI ... 468
D.2.1.5 Channel plan that minimizes channel overlap ... 468
D.2.1.6 Lower transmit power ... 469
D.2.1.7 Transmit power control ... 469
D.2.1.8 Neighbor piconet capability ... 469
D.2.2 Coexistence with IEEE 802.15.1 and IEEE 802.11 FHSS ... 470
D.2.2.1 PHY collaborative coexistence enhancements ... 470
D.2.2.2 MAC coexistence via collaboration ... 470
D.2.2.3 Other techniques ... 471
D.3 Coexistence performance ... 471
D.3.1 Allowed operation ... 471
D.3.2 Assumptions for coexistence calculations ... 471
D.3.3 Performance impact on IEEE 802.15.3 piconets ... 473
D.3.3.1 IEEE 802.11b overlapping with IEEE 802.15.3 ... 473
D.3.3.2 IEEE 802.15.1 and IEEE 802.11 FHSS overlapping with IEEE 802.15.3 ... 476
D.4 Notes on the calculations ... 477

Annex E (normative) Protocol implementation conformance statement (PICS) proforma 478

E.1 Introduction 478
E.1.1 Scope 478
E.1.2 Purpose 478
E.2 Abbreviations and special symbols 478
E.3 Instructions for completing the PICS proforma 479
E.4 Identification of the implementation 479
E.5 Identification of the protocol 480
E.6 Global statement of conformance 481
E.7 PICS proforma—IEEE Std 802.15.3-2016 481
E.7.1 Major roles for IEEE 802.15.3 DEVs 481
E.7.2 PHY functions 482
E.7.3 Major capabilities for the MAC sublayer 483
E.7.3.1 MAC frames 483
E.7.3.2 MAC sublayer functions 486
E.7.4 Security support 490

Annex F (informative) Implementation considerations 491

F.1 Channel time requests 491
F.1.1 Types of CTAs 491
F.1.2 Interpretation of channel time requests 492
F.1.3 Determining CTA Rate Factor from stream requirements 493
F.1.3.1 Example 1 494
F.1.3.2 Example 2 495
F.1.4 PNC interpretation of CTA rate factor 495
F.1.5 Creating channel time requests from MLME requests 496
F.1.6 Interpreting channel time requests 498
F.2 Sample frames 500
F.3 Use of multiple mmWave PHYs in a single piconet 502

Annex G (normative) Optional OOK/DAMI modes 504

G.1 Introduction 504
G.2 Child piconet operation 504
G.3 DAMI 504
G.4 PHY preamble 506
G.5 PHY frame format 507
G.6 Interframe space 507
G.7 Eye opening for OOK 508
G.8 EVM for DAMI 508