

ISO/IEC/IEEE 8802-15-3:2017-10 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 15-3: High data rate wireless multi-media networks

Contents

| | | |
|---------|--|----|
| 1. | Overview..... | 26 |
| 1.1 | Scope..... | 26 |
| 1.2 | Purpose..... | 26 |
| 2. | Normative references..... | 27 |
| 3. | Definitions, acronyms, and abbreviations..... | 28 |
| 3.1 | Definitions..... | 28 |
| 3.2 | Acronyms and abbreviations..... | 29 |
| 4. | General description..... | 33 |
| 4.1 | What is a piconet?..... | 33 |
| 4.2 | Components of an IEEE 802.15.3 piconet..... | 33 |
| 4.3 | Overview of medium access control (MAC) functionality..... | 33 |
| 4.3.1 | Coordination..... | 34 |
| 4.3.1.1 | Starting a piconet..... | 34 |
| 4.3.1.2 | Handing over control of the piconet..... | 34 |
| 4.3.1.3 | Creating a child piconet..... | 34 |
| 4.3.1.4 | Creating a neighbor piconet..... | 35 |
| 4.3.2 | Ending a piconet..... | 35 |
| 4.3.3 | Ending a piconet with a dependent piconet involved..... | 35 |
| 4.3.4 | Association and disassociation..... | 36 |
| 4.3.5 | Security overview..... | 36 |
| 4.3.6 | The IEEE 802.15.3 superframe..... | 36 |
| 4.3.7 | Channel time management..... | 37 |
| 4.3.8 | Data communications between DEVS..... | 38 |
| 4.3.9 | Information discovery in the piconet..... | 38 |
| 4.3.10 | Dynamic channel selection..... | 39 |
| 4.3.11 | Power management..... | 39 |
| 4.3.12 | Controlling transmit power in the piconet..... | 40 |
| 4.3.13 | Superframe structure using quasi-omni mode..... | 40 |
| 4.3.14 | Frame aggregation..... | 41 |
| 4.3.15 | Beam forming..... | 41 |
| 4.3.16 | Channel probing..... | 41 |
| 4.3.17 | Unequal error protection (UEP)..... | 41 |
| 4.4 | Characteristics of the 2.4 GHz PHY..... | 41 |
| 4.4.1 | General characteristics..... | 41 |
| 4.4.2 | Coexistence and interoperability..... | 42 |
| 4.5 | Characteristics of the mmWave PHY..... | 42 |
| 4.5.1 | mmWave PHY characteristics..... | 42 |
| 4.5.2 | Piconets using mmWave PHY modes..... | 43 |
| 4.6 | Conventions..... | 44 |
| 4.7 | Concept of primitives..... | 44 |
| 5. | Layer management..... | 46 |
| 5.1 | Overview of management model..... | 46 |
| 5.2 | Generic management primitives..... | 47 |
| 5.2.1 | MLME-GET.request..... | 48 |

| | | |
|----------|---|----|
| 5.2.2 | MLME-GET.confirm | 48 |
| 5.2.3 | MLME-SET.request | 48 |
| 5.2.4 | MLME-SET.confirm | 48 |
| 5.3 | MLME SAP interface | 49 |
| 5.3.1 | Resetting the MAC/MLME | 50 |
| 5.3.1.1 | MLME-RESET.request | 50 |
| 5.3.1.2 | MLME-RESET.confirm | 50 |
| 5.3.2 | Scanning for piconets | 51 |
| 5.3.2.1 | MLME-SCAN.request | 53 |
| 5.3.2.2 | MLME-SCAN.confirm | 53 |
| 5.3.2.3 | MLME-SCAN.indication | 54 |
| 5.3.3 | Starting a piconet | 54 |
| 5.3.3.1 | MLME-START.request | 55 |
| 5.3.3.2 | MLME-START.confirm | 55 |
| 5.3.4 | Stopping a piconet | 55 |
| 5.3.4.1 | MLME-STOP.request | 56 |
| 5.3.4.2 | MLME-STOP.confirm | 56 |
| 5.3.5 | Associating with a piconet | 57 |
| 5.3.5.1 | MLME-ASSOCIATE.request | 58 |
| 5.3.5.2 | MLME-ASSOCIATE.confirm | 58 |
| 5.3.5.3 | MLME-ASSOCIATE.indication | 58 |
| 5.3.6 | Disassociation from a piconet | 58 |
| 5.3.6.1 | MLME-DISASSOCIATE.request | 59 |
| 5.3.6.2 | MLME-DISASSOCIATE.confirm | 59 |
| 5.3.6.3 | MLME-DISASSOCIATE.indication | 60 |
| 5.3.7 | Security management | 60 |
| 5.3.7.1 | MLME-MEMBERSHIP-UPDATE.request | 62 |
| 5.3.7.2 | MLME-MEMBERSHIP-UPDATE.confirm | 62 |
| 5.3.7.3 | MLME-SECURITY-ERROR.indication | 62 |
| 5.3.7.4 | MLME-SECURITY-MESSAGE.request | 62 |
| 5.3.7.5 | MLME-SECURITY-MESSAGE.confirm | 63 |
| 5.3.7.6 | MLME-SECURITY-MESSAGE.indication | 63 |
| 5.3.8 | PNC handover | 63 |
| 5.3.8.1 | MLME-PNC-HANDOVER.indication | 63 |
| 5.3.8.2 | MLME-PNC-HANDOVER.response | 64 |
| 5.3.8.3 | MLME-NEW-PNC.indication | 64 |
| 5.3.9 | Requesting DEV information from the PNC | 64 |
| 5.3.9.1 | MLME-DEV-INFO.request | 65 |
| 5.3.9.2 | MLME-DEV-INFO.confirm | 65 |
| 5.3.9.3 | MLME-DEV-INFO.indication | 65 |
| 5.3.10 | Security information retrieval | 65 |
| 5.3.10.1 | MLME-SECURITY-INFO.request | 65 |
| 5.3.10.2 | MLME-SECURITY-INFO.confirm | 66 |
| 5.3.10.3 | MLME-SECURITY-INFO.indication | 67 |
| 5.3.10.4 | MLME-SECURITY-INFO.response | 67 |
| 5.3.11 | Application specific data management | 67 |
| 5.3.11.1 | MLME-APPLICATION-SPECIFIC.request | 68 |
| 5.3.11.2 | MLME-APPLICATION-SPECIFIC.confirm | 69 |
| 5.3.11.3 | MLME-APPLICATION-SPECIFIC.indication | 69 |
| 5.3.12 | Piconet services management | 69 |
| 5.3.12.1 | MLME-ANNOUNCE-SERVICE.request | 70 |
| 5.3.12.2 | MLME-ANNOUNCE-SERVICE.confirm | 70 |
| 5.3.12.3 | MLME-PICONET-SERVICES.request | 71 |
| 5.3.12.4 | MLME-PICONET-SERVICES.confirm | 71 |

| | | |
|-----------|--|----|
| 5.3.12.5 | MLME-PICONET-SERVICES.indication | 71 |
| 5.3.13 | Stream management | 71 |
| 5.3.13.1 | MLME-CREATE-STREAM.request | 73 |
| 5.3.13.2 | MLME-CREATE-STREAM.confirm | 74 |
| 5.3.13.3 | MLME-CREATE-STREAM.indication | 74 |
| 5.3.13.4 | MLME-MODIFY-STREAM.request | 74 |
| 5.3.13.5 | MLME-MODIFY-STREAM.confirm | 75 |
| 5.3.13.6 | MLME-TERMINATE-STREAM.request | 75 |
| 5.3.13.7 | MLME-TERMINATE-STREAM.confirm | 75 |
| 5.3.13.8 | MLME-TERMINATE-STREAM.indication | 75 |
| 5.3.14 | Piconet parameter management | 76 |
| 5.3.14.1 | MLME-BSID-CHANGE.request | 76 |
| 5.3.14.2 | MLME-BSID-CHANGE.confirm | 76 |
| 5.3.14.3 | MLME-PICONET-PARM-CHANGE.indication | 77 |
| 5.3.15 | Power management | 77 |
| 5.3.15.1 | MLME-PS-SET-INFORMATION.request | 79 |
| 5.3.15.2 | MLME-PS-SET-INFORMATION.confirm | 79 |
| 5.3.15.3 | MLME-SPS-CONFIGURE.request | 79 |
| 5.3.15.4 | MLME-SPS-CONFIGURE.confirm | 80 |
| 5.3.15.5 | MLME-PM-MODE-CHANGE.request | 80 |
| 5.3.15.6 | MLME-PM-MODE-CHANGE.confirm | 80 |
| 5.3.15.7 | MLME-PM-MODE-CHANGE.indication | 80 |
| 5.3.15.8 | MLME-MONITOR-PM-MODE.request | 81 |
| 5.3.15.9 | MLME-MONITOR-PM-MODE.confirm | 81 |
| 5.3.15.10 | MLME-MONITOR-PM-MODE.indication | 81 |
| 5.3.16 | Multicast operations | 82 |
| 5.3.16.1 | MLME-MULTICAST-CONFIGURATION.request | 83 |
| 5.3.16.2 | MLME-MULTICAST-CONFIGURATION.confirm | 83 |
| 5.3.16.3 | MLME-MULTICAST-RX-SETUP.request | 83 |
| 5.3.16.4 | MLME-MULTICAST-RX-SETUP.confirm | 84 |
| 5.3.17 | Timing synchronization | 84 |
| 5.3.17.1 | MLME-BEACON-EVENT.request | 84 |
| 5.3.17.2 | MLME-BEACON-EVENT.confirm | 84 |
| 5.3.17.3 | MLME-BEACON-EVENT.indication | 85 |
| 5.3.18 | Transmit switched diversity (TSD) | 85 |
| 5.3.18.1 | MLME-TXDIV.request | 85 |
| 5.3.18.2 | MLME-TXDIV.confirm | 86 |
| 5.4 | MAC management | 86 |
| 5.4.1 | MAC PIB PNC group | 86 |
| 5.4.2 | MAC PIB characteristic group | 87 |
| 5.5 | MAC SAP | 88 |
| 5.5.1 | MAC-ASYNC-DATA.request | 91 |
| 5.5.2 | MAC-ASYNC-DATA.confirm | 91 |
| 5.5.3 | MAC-ASYNC-DATA.indication | 91 |
| 5.5.4 | MAC-ISOCH-DATA.request | 92 |
| 5.5.5 | MAC-ISOCH-DATA.confirm | 92 |
| 5.5.6 | MAC-ISOCH-DATA.indication | 93 |
| 6. | MAC frame formats | 94 |
| 6.1 | Frame format conventions | 94 |
| 6.2 | General frame format | 95 |
| 6.2.1 | Frame Control field | 96 |
| 6.2.1.1 | Protocol Version field | 96 |

| | | |
|-----------|--|-----|
| 6.2.1.2 | Frame Type field..... | 97 |
| 6.2.1.3 | SEC field..... | 97 |
| 6.2.1.4 | ACK Policy field, Imp-ACK Request field, and Blk-ACK field | 97 |
| 6.2.1.5 | Retry field | 97 |
| 6.2.1.6 | More Data field..... | 98 |
| 6.2.1.7 | Imp-ACK Negative Acknowledgment (NAK) field..... | 98 |
| 6.2.1.8 | CTA Relinquish field..... | 98 |
| 6.2.2 | Piconet ID (PNID) field | 99 |
| 6.2.3 | SrcID and DestID fields | 99 |
| 6.2.4 | Fragmentation Control field | 99 |
| 6.2.4.1 | MSDU Number field | 99 |
| 6.2.4.2 | Fragment Number field..... | 100 |
| 6.2.4.3 | Last Fragment Number field..... | 100 |
| 6.2.5 | Stream Index field | 100 |
| 6.2.6 | MAC header validation | 100 |
| 6.2.7 | MAC Frame Body field | 101 |
| 6.2.7.1 | Frame Payload field..... | 101 |
| 6.2.7.2 | Secure session ID (SECID) field | 101 |
| 6.2.7.3 | Secure Frame Counter (SFC) field | 101 |
| 6.2.7.4 | Secure Payload field | 101 |
| 6.2.7.5 | Integrity Code field..... | 101 |
| 6.2.7.6 | Frame Check Sequence (FCS) field..... | 101 |
| 6.2.8 | SC and HSI aggregated frame format | 102 |
| 6.2.8.1 | Standard aggregation format..... | 102 |
| 6.2.8.1.1 | Non-secure standard aggregation format | 102 |
| 6.2.8.1.2 | Secure standard aggregation format | 105 |
| 6.2.8.2 | Low-latency aggregation formats | 105 |
| 6.2.8.2.1 | Non-secure low-latency aggregation format..... | 105 |
| 6.2.8.2.2 | Secure low-latency aggregation format | 108 |
| 6.2.9 | AV aggregated frame format | 109 |
| 6.2.9.1 | Extended MAC header format | 109 |
| 6.2.9.1.1 | Extended Control Header field | 110 |
| 6.2.9.1.2 | MAC Extension Header field | 111 |
| 6.2.9.1.3 | Security Header field | 112 |
| 6.2.9.1.4 | Video Header field..... | 112 |
| 6.2.9.2 | Subframe format | 113 |
| 6.2.9.3 | AV aggregated | 115 |
| 6.2.9.4 | Regular..... | 115 |
| 6.2.9.5 | Directional ACK | 116 |
| 6.3 | Format of individual frame types..... | 116 |
| 6.3.1 | Beacon frame | 116 |
| 6.3.1.1 | Non-secure Beacon frame..... | 116 |
| 6.3.1.2 | Secure Beacon frame | 118 |
| 6.3.2 | Acknowledgment frames | 119 |
| 6.3.2.1 | Imm-ACK frame..... | 119 |
| 6.3.2.2 | Delayed ACK (Dly-ACK) frame..... | 120 |
| 6.3.3 | Command frame | 121 |
| 6.3.3.1 | Non-secure Command frame | 121 |
| 6.3.3.2 | Secure Command frame..... | 122 |
| 6.3.4 | Data frame | 123 |
| 6.3.4.1 | Non-secure Data frame | 123 |
| 6.3.4.2 | Secure Data frame..... | 123 |
| 6.3.5 | Multi-protocol Data frame | 124 |
| 6.3.5.1 | Non-secure Multi-protocol Data frame..... | 124 |

| | | |
|---------|---|-----|
| 6.3.5.2 | Secure Multi-protocol Data frame | 125 |
| 6.3.6 | Sync frame | 125 |
| 6.4 | Information elements (IEs) | 126 |
| 6.4.1 | CTA IE | 128 |
| 6.4.2 | BSID IE | 129 |
| 6.4.3 | Parent Piconet IE | 129 |
| 6.4.4 | DEV Association IE | 129 |
| 6.4.5 | PNC shutdown IE | 130 |
| 6.4.6 | Piconet Parameter Change IE | 131 |
| 6.4.7 | AS IE | 132 |
| 6.4.8 | Pending channel time map (PCTM) IE | 132 |
| 6.4.9 | PNC Handover IE | 133 |
| 6.4.10 | CTA Status IE | 133 |
| 6.4.11 | Capability IE | 134 |
| 6.4.12 | Transmit Power Parameters IE | 140 |
| 6.4.13 | PS Status IE | 141 |
| 6.4.14 | CWB IE | 141 |
| 6.4.15 | Overlapping PNID IE | 142 |
| 6.4.16 | Piconet Services IE | 142 |
| 6.4.17 | Vendor Defined IE | 143 |
| 6.4.18 | Group ID IE | 143 |
| 6.4.19 | Stream Renew IE | 144 |
| 6.4.20 | Next PNC IE | 144 |
| 6.4.21 | Piconet Channel Status IE | 144 |
| 6.4.22 | Synchronization IE | 145 |
| 6.4.23 | TSD IE | 147 |
| 6.4.24 | UEP Specific IE | 148 |
| 6.4.25 | IFS IE | 148 |
| 6.4.26 | CTA Relinquish Duration IE | 149 |
| 6.4.27 | Feedback IE | 149 |
| 6.4.28 | Mapping IE | 151 |
| 6.4.29 | BST Clustering IE | 152 |
| 6.4.30 | PET Clustering IE | 152 |
| 6.4.31 | Beam PET IE | 153 |
| 6.4.32 | HRS Beam PET IE | 154 |
| 6.4.33 | PET Amplitude IE | 155 |
| 6.4.34 | PET Phase IE | 155 |
| 6.4.35 | Sync Frame Frequency IE | 156 |
| 6.4.36 | Directional Peer IE | 156 |
| 6.5 | MAC commands | 157 |
| 6.5.1 | Association and disassociation commands | 159 |
| 6.5.1.1 | Association Request command | 159 |
| 6.5.1.2 | Association Response command | 160 |
| 6.5.1.3 | Disassociation Request command | 161 |
| 6.5.2 | Security commands | 161 |
| 6.5.2.1 | Request Key command | 161 |
| 6.5.2.2 | Request Key Response command | 161 |
| 6.5.2.3 | Distribute Key Request command | 162 |
| 6.5.2.4 | Distribute Key Response command | 162 |
| 6.5.3 | PNC handover commands | 162 |
| 6.5.3.1 | PNC Handover Request commnad | 163 |
| 6.5.3.2 | PNC Handover Response command | 163 |
| 6.5.3.3 | PNC Handover Information command | 164 |
| 6.5.4 | Information request commands | 164 |

| | | |
|----------|---|-----|
| 6.5.4.1 | PNC Information Request command | 164 |
| 6.5.4.2 | PNC Information command | 164 |
| 6.5.4.3 | Security Information Request command | 166 |
| 6.5.4.4 | Security Information command | 166 |
| 6.5.4.5 | Probe Request command | 167 |
| 6.5.4.6 | Probe Response command | 169 |
| 6.5.5 | Information announcement commands | 171 |
| 6.5.5.1 | Piconet Services command | 171 |
| 6.5.5.2 | Announce command | 171 |
| 6.5.5.3 | Announce Response command | 173 |
| 6.5.6 | Channel time allocation request, modification, and termination commands | 173 |
| 6.5.6.1 | Channel Time Request command | 173 |
| 6.5.6.2 | Channel Time Response command | 176 |
| 6.5.7 | Channel status commands | 177 |
| 6.5.7.1 | Channel Status Request command | 177 |
| 6.5.7.2 | Channel status response | 177 |
| 6.5.7.3 | Remote Scan Request command | 178 |
| 6.5.7.4 | Remote Scan Response command | 178 |
| 6.5.7.5 | Transmit Power Change command | 180 |
| 6.5.8 | Power management commands | 180 |
| 6.5.8.1 | PS Set Information Request command | 180 |
| 6.5.8.2 | PS Set Information Response command | 180 |
| 6.5.8.3 | SPS Configuration Request command | 181 |
| 6.5.8.4 | SPS Configuration Response command | 182 |
| 6.5.8.5 | PM Mode Change command | 183 |
| 6.5.8.6 | PM Mode Change Response command | 183 |
| 6.5.9 | Special commands | 184 |
| 6.5.9.1 | Security Message command | 184 |
| 6.5.9.2 | Vendor Defined command | 184 |
| 6.5.9.3 | AS IE Request command | 185 |
| 6.5.9.4 | AS IE Response command | 185 |
| 6.5.10 | Multicast configuration commands | 186 |
| 6.5.10.1 | Multicast Configuration Request command | 186 |
| 6.5.10.2 | Multicast Configuration Response command | 186 |
| 7. | MAC functional description | 187 |
| 7.1 | Introduction | 187 |
| 7.2 | Starting, maintaining, and stopping piconets | 188 |
| 7.2.1 | Scanning through channels | 188 |
| 7.2.2 | Starting a piconet | 189 |
| 7.2.3 | PNC handover | 190 |
| 7.2.4 | Preliminary handover | 193 |
| 7.2.5 | Next PNC | 194 |
| 7.2.6 | Dependent PNC handover | 195 |
| 7.2.7 | Child piconet | 198 |
| 7.2.8 | Neighbor piconet | 200 |
| 7.2.9 | Stopping piconet operations | 202 |
| 7.2.9.1 | Stopping an independent or parent piconet | 203 |
| 7.2.9.2 | Parent PNC stopping a dependent piconet | 203 |
| 7.2.9.3 | Dependent PNC termination of a dependent piconet | 204 |
| 7.2.10 | Non-PNC-capable DEVs | 204 |
| 7.3 | Association and disassociation with a piconet | 204 |
| 7.3.1 | Association | 204 |

| | | |
|---------|--|-----|
| 7.3.2 | Piconet services | 206 |
| 7.3.3 | Broadcasting piconet information | 208 |
| 7.3.4 | Disassociation | 209 |
| 7.4 | Channel access | 210 |
| 7.4.1 | Interframe space (IFS) | 211 |
| 7.4.2 | Carrier sense multiple access with collision avoidance (CSMA/CA) | 211 |
| 7.4.3 | Channel time allocation period channel access | 213 |
| 7.4.3.1 | Channel time allocations (CTAs) | 213 |
| 7.4.3.2 | Channel time allocation (CTA) and channel time usage | 215 |
| 7.4.3.3 | Management CTAs | 216 |
| 7.4.3.4 | Slotted aloha access | 216 |
| 7.4.3.5 | Allocation of MCTAs | 217 |
| 7.4.3.6 | Guard time | 217 |
| 7.4.3.7 | Calculating channel time requests | 219 |
| 7.4.3.8 | Relinquishing CTA time to another DEV | 220 |
| 7.5 | Channel time management | 222 |
| 7.5.1 | Isochronous stream management | 222 |
| 7.5.1.1 | Isochronous stream creation | 223 |
| 7.5.1.2 | Isochronous stream modification | 226 |
| 7.5.1.3 | Isochronous stream termination | 229 |
| 7.5.2 | Asynchronous channel time reservation and termination | 231 |
| 7.5.2.1 | Asynchronous channel time reservation | 231 |
| 7.5.2.2 | Asynchronous channel time termination | 233 |
| 7.5.3 | Multicast group configuration | 234 |
| 7.6 | Synchronization | 235 |
| 7.6.1 | Time accuracy | 236 |
| 7.6.2 | Beacon generation | 236 |
| 7.6.3 | Beacon reception | 237 |
| 7.6.4 | Beacon information announcement | 237 |
| 7.6.5 | Superframe support for directional PHYs | 238 |
| 7.6.5.1 | Quasi-omni beacon | 239 |
| 7.6.5.2 | Directional CAP | 240 |
| 7.6.5.3 | Directional association | 241 |
| 7.6.5.4 | DEV quasi-omni transmit direction training and tracking | 242 |
| 7.7 | Fragmentation and defragmentation | 243 |
| 7.8 | Aggregation | 244 |
| 7.8.1 | Standard aggregation | 244 |
| 7.8.2 | Low-latency aggregation | 245 |
| 7.9 | Acknowledgment and retransmission | 246 |
| 7.9.1 | No acknowledgment (no-ACK) | 246 |
| 7.9.2 | Immediate acknowledgment (Imm-ACK) | 246 |
| 7.9.3 | Delayed acknowledgment (Dly-ACK) | 247 |
| 7.9.4 | Implied acknowledgment (Imp-ACK) | 248 |
| 7.9.5 | Block acknowledgment (Blk-ACK) | 250 |
| 7.9.5.1 | Blk-ACK for standard aggregation | 250 |
| 7.9.5.2 | Blk-ACK for low-latency aggregation | 251 |
| 7.9.6 | Retransmissions | 252 |
| 7.9.7 | Duplicate detection | 252 |
| 7.10 | Peer discovery | 252 |
| 7.10.1 | PNC information request | 252 |
| 7.10.2 | Probe request and response | 253 |
| 7.10.3 | Announce | 254 |
| 7.10.4 | Channel status request | 254 |
| 7.10.5 | Remote scan | 254 |

| | | |
|----------|---|-----|
| 7.10.6 | PNC channel scanning | 255 |
| 7.10.7 | Channel probing | 255 |
| 7.11 | Changing piconet parameters..... | 256 |
| 7.11.1 | Moving beacon | 256 |
| 7.11.2 | Changing superframe duration | 256 |
| 7.11.3 | Setting the PNID or BSID | 257 |
| 7.11.4 | Maintaining synchronization in dependent piconets | 258 |
| 7.12 | Interference mitigation..... | 258 |
| 7.12.1 | Dynamic channel selection | 259 |
| 7.12.2 | Transmit power control | 260 |
| 7.12.2.1 | Maximum transmitter power for the CAP, beacon, and directed MCTAs.. | 260 |
| 7.12.2.2 | Adjustable transmitter power in a CTA..... | 261 |
| 7.13 | Multi-rate support | 261 |
| 7.14 | Power management..... | 262 |
| 7.14.1 | Piconet synchronized power save (PSPS) mode | 263 |
| 7.14.2 | Device synchronized power save (DSPS) mode | 264 |
| 7.14.2.1 | Creation, use, and management of DSPS sets | 264 |
| 7.14.2.2 | Changing DSPS mode and operation..... | 265 |
| 7.14.2.3 | CTA timing in DSPS mode | 266 |
| 7.14.3 | Asynchronous power save (APS) mode | 268 |
| 7.14.4 | MSCs for power save modes | 269 |
| 7.15 | AS IE operation | 272 |
| 7.16 | MAC sublayer parameters | 275 |
| 7.17 | Unequal error protection (UEP)..... | 278 |
| 7.18 | Sync frame transmission and virtually dependent piconet | 278 |
| 8. | Security | 280 |
| 8.1 | Security mechanisms | 280 |
| 8.1.1 | Security membership and key establishment | 280 |
| 8.1.2 | Key transport | 280 |
| 8.1.3 | Data encryption | 280 |
| 8.1.4 | Data integrity | 280 |
| 8.1.5 | Beacon integrity protection | 280 |
| 8.1.6 | Command integrity protection | 281 |
| 8.1.7 | Freshness protection | 281 |
| 8.2 | Security modes..... | 281 |
| 8.2.1 | Security mode 0 | 281 |
| 8.2.2 | Security mode 1 | 281 |
| 8.3 | Security support | 281 |
| 8.3.1 | PNC handover | 281 |
| 8.3.2 | Changes in the piconet group data key | 282 |
| 8.3.3 | Joining a secure piconet | 282 |
| 8.3.4 | Membership update | 282 |
| 8.3.5 | Secure frame generation | 283 |
| 8.3.6 | Updating CurrentTimeToken | 284 |
| 8.3.7 | Secure frame reception | 284 |
| 8.3.8 | Selecting the SECID for a new key | 285 |
| 8.3.9 | Key selection | 285 |
| 8.4 | Protocol details | 289 |
| 8.4.1 | Security information request and distribution | 289 |
| 8.4.2 | Key distribution protocol | 291 |
| 8.4.3 | Key request protocol | 291 |

| | | |
|----------|---|-----|
| 9. | Security specifications | 292 |
| 9.1 | Modes for security | 292 |
| 9.2 | Symmetric cryptography building blocks..... | 292 |
| 9.2.1 | Notational conventions | 292 |
| 9.2.2 | CCM combined encryption and data authentication | 292 |
| 9.2.3 | CCM parameters | 292 |
| 9.2.4 | Nonce value | 292 |
| 9.2.5 | AES encryption | 293 |
| 9.3 | Symmetric cryptography implementation | 293 |
| 9.3.1 | Symmetric cryptography data formats | 293 |
| 9.3.2 | Symmetric cryptographic operations | 293 |
| 9.4 | CCM mode..... | 295 |
| 9.4.1 | Inputs | 295 |
| 9.4.2 | Data authentication | 296 |
| 9.4.3 | Encryption | 298 |
| 9.4.4 | Output | 298 |
| 9.4.5 | Decryption | 299 |
| 9.4.6 | Restrictions | 299 |
| 9.4.7 | List of symbols | 299 |
| 10. | PHY specification for the 2.4 GHz band | 301 |
| 10.1 | Overview of the 2.4 GHz PHY | 301 |
| 10.2 | General requirements..... | 302 |
| 10.2.1 | Operating frequency range | 302 |
| 10.2.2 | Radio frequency (RF) power measurements | 302 |
| 10.2.3 | Channel assignments | 302 |
| 10.2.4 | Scanning channels | 302 |
| 10.2.5 | Unwanted emissions | 303 |
| 10.2.6 | Operating temperature range | 303 |
| 10.2.7 | PHY layer timing | 303 |
| 10.2.7.1 | Interframe space..... | 303 |
| 10.2.7.2 | Receive-to-transmit turnaround time | 303 |
| 10.2.7.3 | Transmit-to-receive turnaround time | 304 |
| 10.2.7.4 | Time between successive transmissions | 304 |
| 10.2.7.5 | Channel switch time..... | 304 |
| 10.2.8 | Data size restrictions | 304 |
| 10.2.8.1 | Maximum frame length | 304 |
| 10.2.8.2 | Maximum transfer unit size | 304 |
| 10.2.8.3 | Minimum fragment size..... | 304 |
| 10.2.9 | Header check sequence | 304 |
| 10.2.10 | Channel access methods | 306 |
| 10.3 | Modulation and coding | 306 |
| 10.3.1 | Base data rate | 307 |
| 10.3.2 | Signal constellations | 307 |
| 10.3.3 | DQPSK modulation | 308 |
| 10.3.4 | QPSK and 16/32/64-QAM with trellis coding | 309 |
| 10.4 | PHY frame format | 316 |
| 10.4.1 | Frame format | 316 |
| 10.4.2 | PHY preamble | 317 |
| 10.4.3 | Header modulation | 319 |
| 10.4.4 | Scrambling | 319 |
| 10.4.5 | PHY header | 321 |

| | | |
|-----------|--|-----|
| 10.4.6 | Stuff bits | 322 |
| 10.4.7 | Tail symbols | 322 |
| 10.5 | Transmitter specifications..... | 325 |
| 10.5.1 | Error vector magnitude definition | 325 |
| 10.5.2 | EVM calculated values | 326 |
| 10.5.3 | Transmit power spectral density (PSD) mask | 326 |
| 10.5.4 | Transmit center frequency tolerance | 326 |
| 10.5.5 | Symbol rate | 326 |
| 10.5.6 | Clock synchronization | 327 |
| 10.5.7 | Transmit power-on and power-down ramp | 327 |
| 10.5.8 | RF carrier suppression | 327 |
| 10.5.9 | Transmit power | 327 |
| 10.6 | Receiver specifications | 328 |
| 10.6.1 | Error rate criterion | 328 |
| 10.6.2 | Receiver sensitivity | 328 |
| 10.6.3 | Receiver maximum input level | 329 |
| 10.6.4 | Receiver jamming resistance | 329 |
| 10.6.5 | Receiver CCA performance | 330 |
| 10.6.6 | Receiver RSSI | 330 |
| 10.6.7 | Link quality indication | 330 |
| 10.7 | PHY management..... | 330 |
| 11. | PHY specification for millimeter wave | 333 |
| 11.1 | General requirements..... | 333 |
| 11.1.1 | Regulatory information | 333 |
| 11.1.2 | RF power measurements | 334 |
| 11.1.3 | Unwanted emissions | 334 |
| 11.1.4 | Operating temperature range | 334 |
| 11.1.5 | RF channelization | 334 |
| 11.1.6 | Transmit PSD mask | 334 |
| 11.1.7 | Error vector magnitude calculation | 334 |
| 11.1.7.1 | SC PHY..... | 334 |
| 11.1.7.2 | AV and HSI PHYs..... | 335 |
| 11.1.8 | Common PHY management for mmWave PHY modes | 336 |
| 11.1.8.1 | Supported MCSs..... | 336 |
| 11.1.8.2 | Preferred fragment size..... | 336 |
| 11.1.8.3 | Receive Status field | 337 |
| 11.1.9 | Requirements for mmWave PNCs | 338 |
| 11.1.10 | CP operation | 338 |
| 11.1.11 | mmWave PHY mode usage in CTA | 339 |
| 11.1.12 | Common mode signaling (CMS) | 339 |
| 11.1.12.1 | Forward error correction for CMS..... | 340 |
| 11.1.12.2 | Code spreading for CMS | 340 |
| 11.1.12.3 | Scrambling for CMS..... | 340 |
| 11.1.12.4 | PHY preamble for CMS | 341 |
| 11.1.12.5 | Frame header for CMS | 341 |
| 11.1.12.6 | PHY header for CMS..... | 342 |
| 11.1.12.7 | PHY Payload field for CMS | 343 |
| 11.1.12.8 | Receiver clear channel assessment performance for CMS..... | 343 |
| 11.1.13 | mmWave PHY PIB | 343 |
| 11.2 | Single Carrier Mode of mmWave PHY..... | 344 |
| 11.2.1 | PHY operating specifications of SC PHY | 345 |
| 11.2.1.1 | Channelization | 345 |

| | | |
|------------|---|-----|
| 11.2.1.2 | Scanning channels..... | 345 |
| 11.2.2 | Modulation, forward error correction, and spreading | 345 |
| 11.2.2.1 | MCS-dependent parameters..... | 345 |
| 11.2.2.2 | Header rate-dependent parameters..... | 347 |
| 11.2.2.3 | Timing-related parameters | 348 |
| 11.2.2.4 | Frame-related parameters | 348 |
| 11.2.2.5 | Modulation..... | 349 |
| 11.2.2.5.1 | p/2 BPSK | 349 |
| 11.2.2.5.2 | p/2 QPSK | 349 |
| 11.2.2.5.3 | p/2 8-PSK..... | 350 |
| 11.2.2.5.4 | p/2 16-QAM..... | 351 |
| 11.2.2.6 | FEC | 351 |
| 11.2.2.6.1 | Reed-Solomon block codes in GF(28)..... | 351 |
| 11.2.2.6.2 | Irregular LDPC codes | 352 |
| 11.2.2.6.3 | Rate 14/15 LDPC code | 353 |
| 11.2.2.7 | Stuff bits..... | 353 |
| 11.2.2.8 | Code spreading | 356 |
| 11.2.2.8.1 | Golay sequences | 356 |
| 11.2.2.8.2 | PRBS generation with LFSR | 356 |
| 11.2.2.9 | Unequal error protection..... | 357 |
| 11.2.2.10 | Scrambling | 358 |
| 11.2.3 | SC PHY frame format | 359 |
| 11.2.3.1 | PHY preamble..... | 360 |
| 11.2.3.1.1 | Sync field | 360 |
| 11.2.3.1.2 | SFD field..... | 360 |
| 11.2.3.1.3 | Channel estimation sequence (CES)..... | 360 |
| 11.2.3.2 | Frame header..... | 360 |
| 11.2.3.2.1 | SC PHY header | 362 |
| 11.2.3.2.2 | Base header HCS | 363 |
| 11.2.3.2.3 | Base header FEC..... | 363 |
| 11.2.3.2.4 | MAC subheader HCS | 363 |
| 11.2.3.2.5 | MAC subheader FEC..... | 364 |
| 11.2.3.3 | SC PHY Payload field | 364 |
| 11.2.3.3.1 | SC PHY Payload scrambling..... | 364 |
| 11.2.3.3.2 | Modulation..... | 364 |
| 11.2.3.3.3 | FEC | 364 |
| 11.2.3.3.4 | Code spreading | 364 |
| 11.2.3.4 | Pilot word and PCES | 365 |
| 11.2.3.4.1 | Subblocks and pilot word | 365 |
| 11.2.3.4.2 | Pilot channel estimation sequence (PCES)..... | 365 |
| 11.2.4 | Transmitter specifications | 366 |
| 11.2.4.1 | Error vector magnitude | 366 |
| 11.2.4.2 | Transmit center frequency tolerance..... | 366 |
| 11.2.4.3 | Symbol rate..... | 366 |
| 11.2.4.4 | Transmit power-on and power-down ramp | 366 |
| 11.2.5 | Receiver specifications | 366 |
| 11.2.5.1 | Error rate criterion | 366 |
| 11.2.5.2 | Receiver sensitivity..... | 367 |
| 11.2.5.3 | Receiver maximum input level..... | 367 |
| 11.2.5.4 | Receiver clear channel assessment performance | 367 |
| 11.2.6 | PHY layer timing | 368 |
| 11.2.6.1 | Interframe space..... | 368 |
| 11.2.6.2 | Receive-to-transmit turnaround time | 368 |
| 11.2.6.3 | Transmit-to-receive turnaround-time..... | 368 |

| | | |
|------------|---|-----|
| 11.2.6.4 | Time between successive transmissions | 368 |
| 11.2.6.5 | Channel switch..... | 369 |
| 11.2.7 | PHY management for SC PHY | 369 |
| 11.2.7.1 | Maximum frame size | 369 |
| 11.2.7.2 | Maximum transfer unit size | 369 |
| 11.2.7.3 | Minimum fragment size..... | 369 |
| 11.2.8 | Optional OOK/DAMI modes | 369 |
| 11.2.8.1 | OOK..... | 369 |
| 11.2.8.2 | DAMI..... | 370 |
| 11.2.8.3 | FEC | 370 |
| 11.2.8.4 | OOK/DAMI spreading | 370 |
| 11.3 | High Speed Interface mode of mmWave PHY | 370 |
| 11.3.1 | General operating specifications | 370 |
| 11.3.1.1 | Operating frequency bands | 370 |
| 11.3.2 | HSI PHY modulation, forward error correction, and spreading | 370 |
| 11.3.2.1 | MCS-dependent parameters..... | 370 |
| 11.3.2.2 | HSI PHY timing-related parameters..... | 372 |
| 11.3.2.3 | HSI PHY frame-related parameters | 373 |
| 11.3.2.4 | HSI PHY FEC..... | 373 |
| 11.3.2.4.1 | LDPC block code..... | 374 |
| 11.3.2.4.2 | EEP data multiplexer | 374 |
| 11.3.2.4.3 | UEP data multiplexer..... | 374 |
| 11.3.2.4.4 | Bit interleaver | 375 |
| 11.3.2.5 | Stuff bits..... | 376 |
| 11.3.2.6 | Constellation mapping | 376 |
| 11.3.2.7 | HSI spreader | 378 |
| 11.3.2.7.1 | Spreader for spreading factor of 1 | 379 |
| 11.3.2.7.2 | Spreader for spreading factor of 48 | 379 |
| 11.3.2.8 | Tone interleaver | 379 |
| 11.3.2.9 | HSI PHY OFDM modulator | 380 |
| 11.3.2.9.1 | Pilot subcarriers | 381 |
| 11.3.2.9.2 | Guard subcarriers..... | 382 |
| 11.3.2.10 | PCES insertion..... | 382 |
| 11.3.2.11 | HSI PHY scrambling | 382 |
| 11.3.3 | HSI PHY frame format | 383 |
| 11.3.3.1 | PHY preamble..... | 383 |
| 11.3.3.2 | Frame header..... | 384 |
| 11.3.3.3 | HSI PHY header | 386 |
| 11.3.3.4 | Header check sequences | 387 |
| 11.3.3.4.1 | Main Header HCS..... | 387 |
| 11.3.3.4.2 | MAC Subheader HCS..... | 387 |
| 11.3.3.5 | PHY Payload field | 388 |
| 11.3.4 | Transmitter specifications | 388 |
| 11.3.4.1 | EVM requirement | 388 |
| 11.3.4.2 | Chip rate and clock alignment | 389 |
| 11.3.5 | Receiver specifications | 389 |
| 11.3.5.1 | Receiver sensitivity..... | 389 |
| 11.3.5.2 | Receiver CCA performance..... | 389 |
| 11.3.5.3 | Receiver maximum input level..... | 389 |
| 11.3.5.4 | PHY layer timing | 389 |
| 11.3.5.5 | Interframe spacing | 389 |
| 11.3.5.6 | Receive-to-transmit turnaround time | 390 |
| 11.3.5.7 | Transmit-to-receive turnaround time | 390 |
| 11.3.5.8 | Time between successive transmissions | 390 |

| | | |
|-------------|--|-----|
| 11.3.5.9 | Channel switch time..... | 390 |
| 11.3.6 | HSI PHY management | 390 |
| 11.3.6.1 | PHY supported data rate encoding | 390 |
| 11.3.6.2 | HSI PHY fragment size encoding..... | 390 |
| 11.3.6.3 | Maximum frame length | 391 |
| 11.3.6.4 | Maximum transfer unit size | 391 |
| 11.3.6.5 | Minimum fragment size..... | 391 |
| 11.4 | Audio/Visual mode of mmWave PHY | 391 |
| 11.4.1 | General requirements | 392 |
| 11.4.1.1 | AV PHY channelization | 392 |
| 11.4.1.2 | PHY layer timing..... | 393 |
| 11.4.1.2.1 | Interframe space..... | 393 |
| 11.4.1.2.2 | Receive-to-transmit turnaround time..... | 394 |
| 11.4.1.2.3 | Transmit-to-receive turnaround time..... | 394 |
| 11.4.1.2.4 | Time between successive transmissions | 394 |
| 11.4.1.2.5 | Channel switch time..... | 394 |
| 11.4.1.2.6 | CCA detect time..... | 394 |
| 11.4.1.3 | Data size restrictions | 394 |
| 11.4.1.3.1 | Maximum frame length | 394 |
| 11.4.1.3.2 | Maximum transfer unit size | 395 |
| 11.4.1.3.3 | Minimum fragment size..... | 395 |
| 11.4.1.4 | Header check sequence..... | 395 |
| 11.4.2 | AV PHY modulation and forward error correction | 395 |
| 11.4.2.1 | AV PHY base rate..... | 396 |
| 11.4.2.2 | Repetition coding and spatial diversity..... | 397 |
| 11.4.2.3 | Stuff bits..... | 397 |
| 11.4.2.4 | HRP splitter and scrambler | 398 |
| 11.4.2.5 | LRP scrambler | 398 |
| 11.4.2.6 | HRP outer code | 399 |
| 11.4.2.7 | HRP outer interleaver | 399 |
| 11.4.2.8 | Convolutional encoder | 400 |
| 11.4.2.9 | Puncturing..... | 400 |
| 11.4.2.10 | HRP data multiplexer and bit interleaver | 400 |
| 11.4.2.10.1 | EEP data multiplexer | 401 |
| 11.4.2.10.2 | UEP coding data multiplexer | 402 |
| 11.4.2.10.3 | UEP mapping data multiplexer | 404 |
| 11.4.2.10.4 | HRP header data multiplexer | 405 |
| 11.4.2.11 | Bit reversal tone interleaver | 406 |
| 11.4.2.12 | Signal constellations | 406 |
| 11.4.2.13 | AV PHY non-data subcarriers | 407 |
| 11.4.2.14 | AV PHY OFDM modulation | 408 |
| 11.4.3 | AV PHY frame formats | 409 |
| 11.4.3.1 | HRP preamble..... | 410 |
| 11.4.3.2 | HRP header | 411 |
| 11.4.3.3 | LRP preamble sequences | 411 |
| 11.4.3.4 | Long omni LRP preamble..... | 412 |
| 11.4.3.5 | Short omni LRP preamble | 413 |
| 11.4.3.6 | Omni LRP header | 414 |
| 11.4.3.7 | Directional LRP preamble | 414 |
| 11.4.3.8 | Directional LRP header and payload | 415 |
| 11.4.4 | AV PHY transmitter requirements | 416 |
| 11.4.4.1 | TX mask..... | 416 |
| 11.4.4.2 | EVM requirement | 417 |
| 11.4.4.3 | Symbol timing..... | 417 |

| | | |
|------------|--|-----|
| 11.4.4.4 | TX frequency accuracy | 418 |
| 11.4.4.5 | TX power ramp on and off | 418 |
| 11.4.5 | AV PHY Receiver characteristics | 418 |
| 11.4.5.1 | Error rate criterion | 418 |
| 11.4.5.2 | Sensitivity | 418 |
| 11.4.5.3 | Maximum input level | 418 |
| 11.4.6 | Preambles and training symbols | 418 |
| 12. | Beam forming | 423 |
| 12.1 | Introduction | 423 |
| 12.2 | Beam forming terminology | 423 |
| 12.2.1 | Quasi-omni patterns | 424 |
| 12.2.2 | Sectors | 424 |
| 12.2.3 | Beams | 425 |
| 12.2.4 | Clusters | 426 |
| 12.3 | Beam forming codebooks | 427 |
| 12.3.1 | Beam forming codebooks | 428 |
| 12.4 | Beam forming reference model | 429 |
| 12.5 | Beam forming protocol | 431 |
| 12.5.1 | Two-level training mechanism | 431 |
| 12.5.1.1 | Sector-level training | 431 |
| 12.5.1.1.1 | AAS sector-level training | 431 |
| 12.5.1.1.2 | SAS sector-level training | 434 |
| 12.5.1.1.3 | Sector-level training failure remedy | 437 |
| 12.5.1.2 | Beam-level training | 437 |
| 12.5.1.2.1 | AAS beam-level training | 437 |
| 12.5.1.2.2 | SAS beam-level training | 440 |
| 12.5.2 | Beam tracking | 443 |
| 12.6 | On-demand beam forming | 445 |
| 12.7 | Proactive beam forming | 445 |
| 12.8 | TSD | 445 |
| | Annex A (informative) Bibliography | 447 |
| | Annex B (normative) Frame convergence sublayer | 448 |
| B.1 | Generic convergence sublayer | 448 |
| B.2 | EPD FCSL PDU classification | 449 |
| B.3 | EPD FCSL | 449 |
| B.3.1 | EPD FCSL QoS support | 450 |
| B.3.2 | Data entity inter-relationships | 450 |
| B.4 | EPD FCSL SAP | 451 |
| B.4.1 | MA-UNITDATA.request | 452 |
| B.4.2 | MA-UNITDATA.indication | 452 |
| B.4.3 | MA-UNITDATA-STATUS.indication | 453 |
| B.5 | Stream SAP | 454 |
| B.5.1 | Stream creation, modification, and deletion | 454 |
| B.5.1.1 | STREAM_INITIATE.request | 456 |
| B.5.1.2 | STREAM_INITIATE.confirm | 456 |
| B.5.1.3 | STREAM_INITIATE.indication | 456 |
| B.5.1.4 | STREAM_MODIFY.request | 457 |
| B.5.1.5 | STREAM_MODIFY.confirm | 457 |
| B.5.1.6 | STREAM_END.request | 457 |

| | | |
|-----------------------|---|-----|
| B.5.1.7 | STREAM_END.confirm..... | 458 |
| B.5.1.8 | STREAM_END.indication..... | 458 |
| B.5.2 | Stream data interface..... | 458 |
| B.5.2.1 | STREAM_DATA.request..... | 459 |
| B.5.2.2 | STREAM_DATA.confirm..... | 460 |
| B.5.2.3 | STREAM_DATA.indication..... | 460 |
| Annex C (informative) | Security considerations..... | 461 |
| C.1 | Background assumptions..... | 461 |
| C.1.1 | Physical assumptions..... | 461 |
| C.1.2 | Network assumptions..... | 461 |
| C.1.3 | Attack model assumptions..... | 462 |
| C.1.4 | Security key lifecycle issues..... | 462 |
| C.1.4.1 | Key lifecycle..... | 462 |
| C.1.4.2 | Membership lifecycle..... | 462 |
| C.1.4.3 | Group membership change rekey..... | 462 |
| C.2 | Claimed security services..... | 462 |
| C.2.1 | Beacon protection protocol..... | 462 |
| C.2.2 | Distribute key protocol..... | 463 |
| C.2.3 | Key request protocol..... | 463 |
| C.2.4 | Data protection protocol..... | 464 |
| C.3 | Properties of the IEEE 802.15.3 security suite..... | 464 |
| C.3.1 | Key usage..... | 464 |
| C.3.2 | Replay prevention..... | 464 |
| Annex D (informative) | Coexistence, interoperability, and interference..... | 466 |
| D.1 | Interoperability..... | 466 |
| D.1.1 | Interoperability with IEEE 802.11 DSSS and IEEE 802.11b..... | 466 |
| D.1.2 | IEEE 802.11 FHSS and IEEE 802.15.1..... | 467 |
| D.2 | Coexistence..... | 467 |
| D.2.1 | Coexistence with IEEE Std 802.11b..... | 467 |
| D.2.1.1 | Passive scanning..... | 468 |
| D.2.1.2 | Dynamic channel selection..... | 468 |
| D.2.1.3 | The ability to request channel quality information..... | 468 |
| D.2.1.4 | Link quality and RSSI..... | 468 |
| D.2.1.5 | Channel plan that minimizes channel overlap..... | 468 |
| D.2.1.6 | Lower transmit power..... | 469 |
| D.2.1.7 | Transmit power control..... | 469 |
| D.2.1.8 | Neighbor piconet capability..... | 469 |
| D.2.2 | Coexistence with IEEE 802.15.1 and IEEE 802.11 FHSS..... | 470 |
| D.2.2.1 | PHY collaborative coexistence enhancements..... | 470 |
| D.2.2.2 | MAC coexistence via collaboration..... | 470 |
| D.2.2.3 | Other techniques..... | 471 |
| D.3 | Coexistence performance..... | 471 |
| D.3.1 | Allowed operation..... | 471 |
| D.3.2 | Assumptions for coexistence calculations..... | 471 |
| D.3.3 | Performance impact on IEEE 802.15.3 piconets..... | 473 |
| D.3.3.1 | IEEE 802.11b overlapping with IEEE 802.15.3..... | 473 |
| D.3.3.2 | IEEE 802.15.1 and IEEE 802.11 FHSS overlapping with IEEE 802.15.3..... | 476 |
| D.4 | Notes on the calculations..... | 477 |

| | |
|--|-----|
| Annex E (normative) Protocol implementation conformance statement (PICS) proforma..... | 478 |
| E.1 Introduction..... | 478 |
| E.1.1 Scope..... | 478 |
| E.1.2 Purpose..... | 478 |
| E.2 Abbreviations and special symbols..... | 478 |
| E.3 Instructions for completing the PICS proforma..... | 479 |
| E.4 Identification of the implementation..... | 479 |
| E.5 Identification of the protocol | 480 |
| E.6 Global statement of conformance | 481 |
| E.7 PICS proforma—IEEE Std 802.15.3-2016..... | 481 |
| E.7.1 Major roles for IEEE 802.15.3 DEVs..... | 481 |
| E.7.2 PHY functions..... | 482 |
| E.7.3 Major capabilities for the MAC sublayer | 483 |
| E.7.3.1 MAC frames | 483 |
| E.7.3.2 MAC sublayer functions | 486 |
| E.7.4 Security support | 490 |
| Annex F (informative) Implementation considerations..... | 491 |
| F.1 Channel time requests..... | 491 |
| F.1.1 Types of CTAs..... | 491 |
| F.1.2 Interpretation of channel time requests..... | 492 |
| F.1.3 Determining CTA Rate Factor from stream requirements | 493 |
| F.1.3.1 Example 1..... | 494 |
| F.1.3.2 Example 2..... | 495 |
| F.1.4 PNC interpretation of CTA rate factor | 495 |
| F.1.5 Creating channel time requests from MLME requests | 496 |
| F.1.6 Interpreting channel time requests..... | 498 |
| F.2 Sample frames..... | 500 |
| F.3 Use of multiple mmWave PHYs in a single piconet | 502 |
| Annex G (normative) Optional OOK/DAMI modes | 504 |
| G.1 Introduction..... | 504 |
| G.2 Child piconet operation..... | 504 |
| G.3 DAMI..... | 504 |
| G.4 PHY preamble..... | 506 |
| G.5 PHY frame format | 507 |
| G.6 Interframe space..... | 507 |
| G.7 Eye opening for OOK | 508 |
| G.8 EVM for DAMI | 508 |