

# ISO/IEC/IEEE 8802-15-3:2017-10 (E)

## Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 15-3: High data rate wireless multi-media networks

---

### Contents

1.	Overview.....	26
1.1	Scope.....	26
1.2	Purpose.....	26
2.	Normative references.....	27
3.	Definitions, acronyms, and abbreviations.....	28
3.1	Definitions.....	28
3.2	Acronyms and abbreviations.....	29
4.	General description.....	33
4.1	What is a piconet?.....	33
4.2	Components of an IEEE 802.15.3 piconet.....	33
4.3	Overview of medium access control (MAC) functionality.....	33
4.3.1	Coordination.....	34
4.3.1.1	Starting a piconet.....	34
4.3.1.2	Handing over control of the piconet.....	34
4.3.1.3	Creating a child piconet.....	34
4.3.1.4	Creating a neighbor piconet.....	35
4.3.2	Ending a piconet.....	35
4.3.3	Ending a piconet with a dependent piconet involved.....	35
4.3.4	Association and disassociation.....	36
4.3.5	Security overview.....	36
4.3.6	The IEEE 802.15.3 superframe.....	36
4.3.7	Channel time management.....	37
4.3.8	Data communications between DEVS.....	38
4.3.9	Information discovery in the piconet.....	38
4.3.10	Dynamic channel selection.....	39
4.3.11	Power management.....	39
4.3.12	Controlling transmit power in the piconet.....	40
4.3.13	Superframe structure using quasi-omni mode.....	40
4.3.14	Frame aggregation.....	41
4.3.15	Beam forming.....	41
4.3.16	Channel probing.....	41
4.3.17	Unequal error protection (UEP).....	41
4.4	Characteristics of the 2.4 GHz PHY.....	41
4.4.1	General characteristics.....	41
4.4.2	Coexistence and interoperability.....	42
4.5	Characteristics of the mmWave PHY.....	42
4.5.1	mmWave PHY characteristics.....	42
4.5.2	Piconets using mmWave PHY modes.....	43
4.6	Conventions.....	44
4.7	Concept of primitives.....	44
5.	Layer management.....	46
5.1	Overview of management model.....	46
5.2	Generic management primitives.....	47
5.2.1	MLME-GET.request.....	48

5.2.2	MLME-GET.confirm	48
5.2.3	MLME-SET.request	48
5.2.4	MLME-SET.confirm	48
5.3	MLME SAP interface	49
5.3.1	Resetting the MAC/MLME	50
5.3.1.1	MLME-RESET.request	50
5.3.1.2	MLME-RESET.confirm	50
5.3.2	Scanning for piconets	51
5.3.2.1	MLME-SCAN.request	53
5.3.2.2	MLME-SCAN.confirm	53
5.3.2.3	MLME-SCAN.indication	54
5.3.3	Starting a piconet	54
5.3.3.1	MLME-START.request	55
5.3.3.2	MLME-START.confirm	55
5.3.4	Stopping a piconet	55
5.3.4.1	MLME-STOP.request	56
5.3.4.2	MLME-STOP.confirm	56
5.3.5	Associating with a piconet	57
5.3.5.1	MLME-ASSOCIATE.request	58
5.3.5.2	MLME-ASSOCIATE.confirm	58
5.3.5.3	MLME-ASSOCIATE.indication	58
5.3.6	Disassociation from a piconet	58
5.3.6.1	MLME-DISASSOCIATE.request	59
5.3.6.2	MLME-DISASSOCIATE.confirm	59
5.3.6.3	MLME-DISASSOCIATE.indication	60
5.3.7	Security management	60
5.3.7.1	MLME-MEMBERSHIP-UPDATE.request	62
5.3.7.2	MLME-MEMBERSHIP-UPDATE.confirm	62
5.3.7.3	MLME-SECURITY-ERROR.indication	62
5.3.7.4	MLME-SECURITY-MESSAGE.request	62
5.3.7.5	MLME-SECURITY-MESSAGE.confirm	63
5.3.7.6	MLME-SECURITY-MESSAGE.indication	63
5.3.8	PNC handover	63
5.3.8.1	MLME-PNC-HANDOVER.indication	63
5.3.8.2	MLME-PNC-HANDOVER.response	64
5.3.8.3	MLME-NEW-PNC.indication	64
5.3.9	Requesting DEV information from the PNC	64
5.3.9.1	MLME-DEV-INFO.request	65
5.3.9.2	MLME-DEV-INFO.confirm	65
5.3.9.3	MLME-DEV-INFO.indication	65
5.3.10	Security information retrieval	65
5.3.10.1	MLME-SECURITY-INFO.request	65
5.3.10.2	MLME-SECURITY-INFO.confirm	66
5.3.10.3	MLME-SECURITY-INFO.indication	67
5.3.10.4	MLME-SECURITY-INFO.response	67
5.3.11	Application specific data management	67
5.3.11.1	MLME-APPLICATION-SPECIFIC.request	68
5.3.11.2	MLME-APPLICATION-SPECIFIC.confirm	69
5.3.11.3	MLME-APPLICATION-SPECIFIC.indication	69
5.3.12	Piconet services management	69
5.3.12.1	MLME-ANNOUNCE-SERVICE.request	70
5.3.12.2	MLME-ANNOUNCE-SERVICE.confirm	70
5.3.12.3	MLME-PICONET-SERVICES.request	71
5.3.12.4	MLME-PICONET-SERVICES.confirm	71

5.3.12.5	MLME-PICONET-SERVICES.indication .....	71
5.3.13	Stream management .....	71
5.3.13.1	MLME-CREATE-STREAM.request .....	73
5.3.13.2	MLME-CREATE-STREAM.confirm .....	74
5.3.13.3	MLME-CREATE-STREAM.indication .....	74
5.3.13.4	MLME-MODIFY-STREAM.request .....	74
5.3.13.5	MLME-MODIFY-STREAM.confirm .....	75
5.3.13.6	MLME-TERMINATE-STREAM.request .....	75
5.3.13.7	MLME-TERMINATE-STREAM.confirm .....	75
5.3.13.8	MLME-TERMINATE-STREAM.indication .....	75
5.3.14	Piconet parameter management .....	76
5.3.14.1	MLME-BSID-CHANGE.request .....	76
5.3.14.2	MLME-BSID-CHANGE.confirm .....	76
5.3.14.3	MLME-PICONET-PARM-CHANGE.indication .....	77
5.3.15	Power management .....	77
5.3.15.1	MLME-PS-SET-INFORMATION.request .....	79
5.3.15.2	MLME-PS-SET-INFORMATION.confirm .....	79
5.3.15.3	MLME-SPS-CONFIGURE.request .....	79
5.3.15.4	MLME-SPS-CONFIGURE.confirm .....	80
5.3.15.5	MLME-PM-MODE-CHANGE.request .....	80
5.3.15.6	MLME-PM-MODE-CHANGE.confirm .....	80
5.3.15.7	MLME-PM-MODE-CHANGE.indication .....	80
5.3.15.8	MLME-MONITOR-PM-MODE.request .....	81
5.3.15.9	MLME-MONITOR-PM-MODE.confirm .....	81
5.3.15.10	MLME-MONITOR-PM-MODE.indication .....	81
5.3.16	Multicast operations .....	82
5.3.16.1	MLME-MULTICAST-CONFIGURATION.request .....	83
5.3.16.2	MLME-MULTICAST-CONFIGURATION.confirm .....	83
5.3.16.3	MLME-MULTICAST-RX-SETUP.request .....	83
5.3.16.4	MLME-MULTICAST-RX-SETUP.confirm .....	84
5.3.17	Timing synchronization .....	84
5.3.17.1	MLME-BEACON-EVENT.request .....	84
5.3.17.2	MLME-BEACON-EVENT.confirm .....	84
5.3.17.3	MLME-BEACON-EVENT.indication .....	85
5.3.18	Transmit switched diversity (TSD) .....	85
5.3.18.1	MLME-TXDIV.request .....	85
5.3.18.2	MLME-TXDIV.confirm .....	86
5.4	MAC management .....	86
5.4.1	MAC PIB PNC group .....	86
5.4.2	MAC PIB characteristic group .....	87
5.5	MAC SAP .....	88
5.5.1	MAC-ASYNC-DATA.request .....	91
5.5.2	MAC-ASYNC-DATA.confirm .....	91
5.5.3	MAC-ASYNC-DATA.indication .....	91
5.5.4	MAC-ISOCH-DATA.request .....	92
5.5.5	MAC-ISOCH-DATA.confirm .....	92
5.5.6	MAC-ISOCH-DATA.indication .....	93
6.	MAC frame formats .....	94
6.1	Frame format conventions .....	94
6.2	General frame format .....	95
6.2.1	Frame Control field .....	96
6.2.1.1	Protocol Version field .....	96

6.2.1.2	Frame Type field.....	97
6.2.1.3	SEC field.....	97
6.2.1.4	ACK Policy field, Imp-ACK Request field, and Blk-ACK field .....	97
6.2.1.5	Retry field .....	97
6.2.1.6	More Data field.....	98
6.2.1.7	Imp-ACK Negative Acknowledgment (NAK) field.....	98
6.2.1.8	CTA Relinquish field.....	98
6.2.2	Piconet ID (PNID) field .....	99
6.2.3	SrcID and DestID fields .....	99
6.2.4	Fragmentation Control field .....	99
6.2.4.1	MSDU Number field .....	99
6.2.4.2	Fragment Number field.....	100
6.2.4.3	Last Fragment Number field.....	100
6.2.5	Stream Index field .....	100
6.2.6	MAC header validation .....	100
6.2.7	MAC Frame Body field .....	101
6.2.7.1	Frame Payload field.....	101
6.2.7.2	Secure session ID (SECID) field .....	101
6.2.7.3	Secure Frame Counter (SFC) field .....	101
6.2.7.4	Secure Payload field .....	101
6.2.7.5	Integrity Code field.....	101
6.2.7.6	Frame Check Sequence (FCS) field.....	101
6.2.8	SC and HSI aggregated frame format .....	102
6.2.8.1	Standard aggregation format.....	102
6.2.8.1.1	Non-secure standard aggregation format.....	102
6.2.8.1.2	Secure standard aggregation format .....	105
6.2.8.2	Low-latency aggregation formats .....	105
6.2.8.2.1	Non-secure low-latency aggregation format.....	105
6.2.8.2.2	Secure low-latency aggregation format .....	108
6.2.9	AV aggregated frame format .....	109
6.2.9.1	Extended MAC header format.....	109
6.2.9.1.1	Extended Control Header field .....	110
6.2.9.1.2	MAC Extension Header field .....	111
6.2.9.1.3	Security Header field .....	112
6.2.9.1.4	Video Header field.....	112
6.2.9.2	Subframe format .....	113
6.2.9.3	AV aggregated .....	115
6.2.9.4	Regular.....	115
6.2.9.5	Directional ACK .....	116
6.3	Format of individual frame types.....	116
6.3.1	Beacon frame .....	116
6.3.1.1	Non-secure Beacon frame.....	116
6.3.1.2	Secure Beacon frame .....	118
6.3.2	Acknowledgment frames .....	119
6.3.2.1	Imm-ACK frame.....	119
6.3.2.2	Delayed ACK (Dly-ACK) frame.....	120
6.3.3	Command frame .....	121
6.3.3.1	Non-secure Command frame.....	121
6.3.3.2	Secure Command frame.....	122
6.3.4	Data frame .....	123
6.3.4.1	Non-secure Data frame .....	123
6.3.4.2	Secure Data frame.....	123
6.3.5	Multi-protocol Data frame .....	124
6.3.5.1	Non-secure Multi-protocol Data frame.....	124

6.3.5.2	Secure Multi-protocol Data frame .....	125
6.3.6	Sync frame .....	125
6.4	Information elements (IEs) .....	126
6.4.1	CTA IE .....	128
6.4.2	BSID IE .....	129
6.4.3	Parent Piconet IE .....	129
6.4.4	DEV Association IE .....	129
6.4.5	PNC shutdown IE .....	130
6.4.6	Piconet Parameter Change IE .....	131
6.4.7	AS IE .....	132
6.4.8	Pending channel time map (PCTM) IE .....	132
6.4.9	PNC Handover IE .....	133
6.4.10	CTA Status IE .....	133
6.4.11	Capability IE .....	134
6.4.12	Transmit Power Parameters IE .....	140
6.4.13	PS Status IE .....	141
6.4.14	CWB IE .....	141
6.4.15	Overlapping PNID IE .....	142
6.4.16	Piconet Services IE .....	142
6.4.17	Vendor Defined IE .....	143
6.4.18	Group ID IE .....	143
6.4.19	Stream Renew IE .....	144
6.4.20	Next PNC IE .....	144
6.4.21	Piconet Channel Status IE .....	144
6.4.22	Synchronization IE .....	145
6.4.23	TSD IE .....	147
6.4.24	UEP Specific IE .....	148
6.4.25	IFS IE .....	148
6.4.26	CTA Relinquish Duration IE .....	149
6.4.27	Feedback IE .....	149
6.4.28	Mapping IE .....	151
6.4.29	BST Clustering IE .....	152
6.4.30	PET Clustering IE .....	152
6.4.31	Beam PET IE .....	153
6.4.32	HRS Beam PET IE .....	154
6.4.33	PET Amplitude IE .....	155
6.4.34	PET Phase IE .....	155
6.4.35	Sync Frame Frequency IE .....	156
6.4.36	Directional Peer IE .....	156
6.5	MAC commands .....	157
6.5.1	Association and disassociation commands .....	159
6.5.1.1	Association Request command .....	159
6.5.1.2	Association Response command .....	160
6.5.1.3	Disassociation Request command .....	161
6.5.2	Security commands .....	161
6.5.2.1	Request Key command .....	161
6.5.2.2	Request Key Response command .....	161
6.5.2.3	Distribute Key Request command .....	162
6.5.2.4	Distribute Key Response command .....	162
6.5.3	PNC handover commands .....	162
6.5.3.1	PNC Handover Request commnad .....	163
6.5.3.2	PNC Handover Response command .....	163
6.5.3.3	PNC Handover Information command .....	164
6.5.4	Information request commands .....	164

6.5.4.1	PNC Information Request command .....	164
6.5.4.2	PNC Information command .....	164
6.5.4.3	Security Information Request command .....	166
6.5.4.4	Security Information command .....	166
6.5.4.5	Probe Request command .....	167
6.5.4.6	Probe Response command .....	169
6.5.5	Information announcement commands .....	171
6.5.5.1	Piconet Services command .....	171
6.5.5.2	Announce command .....	171
6.5.5.3	Announce Response command .....	173
6.5.6	Channel time allocation request, modification, and termination commands .....	173
6.5.6.1	Channel Time Request command .....	173
6.5.6.2	Channel Time Response command .....	176
6.5.7	Channel status commands .....	177
6.5.7.1	Channel Status Request command .....	177
6.5.7.2	Channel status response .....	177
6.5.7.3	Remote Scan Request command .....	178
6.5.7.4	Remote Scan Response command .....	178
6.5.7.5	Transmit Power Change command .....	180
6.5.8	Power management commands .....	180
6.5.8.1	PS Set Information Request command .....	180
6.5.8.2	PS Set Information Response command .....	180
6.5.8.3	SPS Configuration Request command .....	181
6.5.8.4	SPS Configuration Response command .....	182
6.5.8.5	PM Mode Change command .....	183
6.5.8.6	PM Mode Change Response command .....	183
6.5.9	Special commands .....	184
6.5.9.1	Security Message command .....	184
6.5.9.2	Vendor Defined command .....	184
6.5.9.3	AS IE Request command .....	185
6.5.9.4	AS IE Response command .....	185
6.5.10	Multicast configuration commands .....	186
6.5.10.1	Multicast Configuration Request command .....	186
6.5.10.2	Multicast Configuration Response command .....	186
7.	MAC functional description .....	187
7.1	Introduction .....	187
7.2	Starting, maintaining, and stopping piconets .....	188
7.2.1	Scanning through channels .....	188
7.2.2	Starting a piconet .....	189
7.2.3	PNC handover .....	190
7.2.4	Preliminary handover .....	193
7.2.5	Next PNC .....	194
7.2.6	Dependent PNC handover .....	195
7.2.7	Child piconet .....	198
7.2.8	Neighbor piconet .....	200
7.2.9	Stopping piconet operations .....	202
7.2.9.1	Stopping an independent or parent piconet .....	203
7.2.9.2	Parent PNC stopping a dependent piconet .....	203
7.2.9.3	Dependent PNC termination of a dependent piconet .....	204
7.2.10	Non-PNC-capable DEVs .....	204
7.3	Association and disassociation with a piconet .....	204
7.3.1	Association .....	204

7.3.2	Piconet services .....	206
7.3.3	Broadcasting piconet information .....	208
7.3.4	Disassociation .....	209
7.4	Channel access .....	210
7.4.1	Interframe space (IFS) .....	211
7.4.2	Carrier sense multiple access with collision avoidance (CSMA/CA) .....	211
7.4.3	Channel time allocation period channel access .....	213
7.4.3.1	Channel time allocations (CTAs) .....	213
7.4.3.2	Channel time allocation (CTA) and channel time usage .....	215
7.4.3.3	Management CTAs .....	216
7.4.3.4	Slotted aloha access .....	216
7.4.3.5	Allocation of MCTAs .....	217
7.4.3.6	Guard time .....	217
7.4.3.7	Calculating channel time requests .....	219
7.4.3.8	Relinquishing CTA time to another DEV .....	220
7.5	Channel time management .....	222
7.5.1	Isochronous stream management .....	222
7.5.1.1	Isochronous stream creation .....	223
7.5.1.2	Isochronous stream modification .....	226
7.5.1.3	Isochronous stream termination .....	229
7.5.2	Asynchronous channel time reservation and termination .....	231
7.5.2.1	Asynchronous channel time reservation .....	231
7.5.2.2	Asynchronous channel time termination .....	233
7.5.3	Multicast group configuration .....	234
7.6	Synchronization .....	235
7.6.1	Time accuracy .....	236
7.6.2	Beacon generation .....	236
7.6.3	Beacon reception .....	237
7.6.4	Beacon information announcement .....	237
7.6.5	Superframe support for directional PHYs .....	238
7.6.5.1	Quasi-omni beacon .....	239
7.6.5.2	Directional CAP .....	240
7.6.5.3	Directional association .....	241
7.6.5.4	DEV quasi-omni transmit direction training and tracking .....	242
7.7	Fragmentation and defragmentation .....	243
7.8	Aggregation .....	244
7.8.1	Standard aggregation .....	244
7.8.2	Low-latency aggregation .....	245
7.9	Acknowledgment and retransmission .....	246
7.9.1	No acknowledgment (no-ACK) .....	246
7.9.2	Immediate acknowledgment (Imm-ACK) .....	246
7.9.3	Delayed acknowledgment (Dly-ACK) .....	247
7.9.4	Implied acknowledgment (Imp-ACK) .....	248
7.9.5	Block acknowledgment (Blk-ACK) .....	250
7.9.5.1	Blk-ACK for standard aggregation .....	250
7.9.5.2	Blk-ACK for low-latency aggregation .....	251
7.9.6	Retransmissions .....	252
7.9.7	Duplicate detection .....	252
7.10	Peer discovery .....	252
7.10.1	PNC information request .....	252
7.10.2	Probe request and response .....	253
7.10.3	Announce .....	254
7.10.4	Channel status request .....	254
7.10.5	Remote scan .....	254

7.10.6	PNC channel scanning .....	255
7.10.7	Channel probing .....	255
7.11	Changing piconet parameters.....	256
7.11.1	Moving beacon .....	256
7.11.2	Changing superframe duration .....	256
7.11.3	Setting the PNID or BSID .....	257
7.11.4	Maintaining synchronization in dependent piconets .....	258
7.12	Interference mitigation.....	258
7.12.1	Dynamic channel selection .....	259
7.12.2	Transmit power control .....	260
7.12.2.1	Maximum transmitter power for the CAP, beacon, and directed MCTAs..	260
7.12.2.2	Adjustable transmitter power in a CTA.....	261
7.13	Multi-rate support .....	261
7.14	Power management.....	262
7.14.1	Piconet synchronized power save (PSPS) mode .....	263
7.14.2	Device synchronized power save (DSPS) mode .....	264
7.14.2.1	Creation, use, and management of DSPS sets .....	264
7.14.2.2	Changing DSPS mode and operation.....	265
7.14.2.3	CTA timing in DSPS mode .....	266
7.14.3	Asynchronous power save (APS) mode .....	268
7.14.4	MSCs for power save modes .....	269
7.15	AS IE operation .....	272
7.16	MAC sublayer parameters .....	275
7.17	Unequal error protection (UEP).....	278
7.18	Sync frame transmission and virtually dependent piconet .....	278
8.	Security .....	280
8.1	Security mechanisms .....	280
8.1.1	Security membership and key establishment .....	280
8.1.2	Key transport .....	280
8.1.3	Data encryption .....	280
8.1.4	Data integrity .....	280
8.1.5	Beacon integrity protection .....	280
8.1.6	Command integrity protection .....	281
8.1.7	Freshness protection .....	281
8.2	Security modes.....	281
8.2.1	Security mode 0 .....	281
8.2.2	Security mode 1 .....	281
8.3	Security support .....	281
8.3.1	PNC handover .....	281
8.3.2	Changes in the piconet group data key .....	282
8.3.3	Joining a secure piconet .....	282
8.3.4	Membership update .....	282
8.3.5	Secure frame generation .....	283
8.3.6	Updating CurrentTimeToken .....	284
8.3.7	Secure frame reception .....	284
8.3.8	Selecting the SECID for a new key .....	285
8.3.9	Key selection .....	285
8.4	Protocol details .....	289
8.4.1	Security information request and distribution .....	289
8.4.2	Key distribution protocol .....	291
8.4.3	Key request protocol .....	291

9.	Security specifications .....	292
9.1	Modes for security .....	292
9.2	Symmetric cryptography building blocks .....	292
9.2.1	Notational conventions .....	292
9.2.2	CCM combined encryption and data authentication .....	292
9.2.3	CCM parameters .....	292
9.2.4	Nonce value .....	292
9.2.5	AES encryption .....	293
9.3	Symmetric cryptography implementation .....	293
9.3.1	Symmetric cryptography data formats .....	293
9.3.2	Symmetric cryptographic operations .....	293
9.4	CCM mode.....	295
9.4.1	Inputs .....	295
9.4.2	Data authentication .....	296
9.4.3	Encryption .....	298
9.4.4	Output .....	298
9.4.5	Decryption .....	299
9.4.6	Restrictions .....	299
9.4.7	List of symbols .....	299
10.	PHY specification for the 2.4 GHz band .....	301
10.1	Overview of the 2.4 GHz PHY .....	301
10.2	General requirements.....	302
10.2.1	Operating frequency range .....	302
10.2.2	Radio frequency (RF) power measurements .....	302
10.2.3	Channel assignments .....	302
10.2.4	Scanning channels .....	302
10.2.5	Unwanted emissions .....	303
10.2.6	Operating temperature range .....	303
10.2.7	PHY layer timing .....	303
10.2.7.1	Interframe space.....	303
10.2.7.2	Receive-to-transmit turnaround time .....	303
10.2.7.3	Transmit-to-receive turnaround time .....	304
10.2.7.4	Time between successive transmissions .....	304
10.2.7.5	Channel switch time.....	304
10.2.8	Data size restrictions .....	304
10.2.8.1	Maximum frame length .....	304
10.2.8.2	Maximum transfer unit size .....	304
10.2.8.3	Minimum fragment size.....	304
10.2.9	Header check sequence .....	304
10.2.10	Channel access methods .....	306
10.3	Modulation and coding .....	306
10.3.1	Base data rate .....	307
10.3.2	Signal constellations .....	307
10.3.3	DQPSK modulation .....	308
10.3.4	QPSK and 16/32/64-QAM with trellis coding .....	309
10.4	PHY frame format .....	316
10.4.1	Frame format .....	316
10.4.2	PHY preamble .....	317
10.4.3	Header modulation .....	319
10.4.4	Scrambling .....	319
10.4.5	PHY header .....	321

10.4.6	Stuff bits .....	322
10.4.7	Tail symbols .....	322
10.5	Transmitter specifications.....	325
10.5.1	Error vector magnitude definition .....	325
10.5.2	EVM calculated values .....	326
10.5.3	Transmit power spectral density (PSD) mask .....	326
10.5.4	Transmit center frequency tolerance .....	326
10.5.5	Symbol rate .....	326
10.5.6	Clock synchronization .....	327
10.5.7	Transmit power-on and power-down ramp .....	327
10.5.8	RF carrier suppression .....	327
10.5.9	Transmit power .....	327
10.6	Receiver specifications .....	328
10.6.1	Error rate criterion .....	328
10.6.2	Receiver sensitivity .....	328
10.6.3	Receiver maximum input level .....	329
10.6.4	Receiver jamming resistance .....	329
10.6.5	Receiver CCA performance .....	330
10.6.6	Receiver RSSI .....	330
10.6.7	Link quality indication .....	330
10.7	PHY management.....	330
11.	PHY specification for millimeter wave .....	333
11.1	General requirements.....	333
11.1.1	Regulatory information .....	333
11.1.2	RF power measurements .....	334
11.1.3	Unwanted emissions .....	334
11.1.4	Operating temperature range .....	334
11.1.5	RF channelization .....	334
11.1.6	Transmit PSD mask .....	334
11.1.7	Error vector magnitude calculation .....	334
11.1.7.1	SC PHY.....	334
11.1.7.2	AV and HSI PHYs.....	335
11.1.8	Common PHY management for mmWave PHY modes .....	336
11.1.8.1	Supported MCSs.....	336
11.1.8.2	Preferred fragment size.....	336
11.1.8.3	Receive Status field .....	337
11.1.9	Requirements for mmWave PNCs .....	338
11.1.10	CP operation .....	338
11.1.11	mmWave PHY mode usage in CTA .....	339
11.1.12	Common mode signaling (CMS) .....	339
11.1.12.1	Forward error correction for CMS.....	340
11.1.12.2	Code spreading for CMS .....	340
11.1.12.3	Scrambling for CMS.....	340
11.1.12.4	PHY preamble for CMS .....	341
11.1.12.5	Frame header for CMS .....	341
11.1.12.6	PHY header for CMS.....	342
11.1.12.7	PHY Payload field for CMS.....	343
11.1.12.8	Receiver clear channel assessment performance for CMS.....	343
11.1.13	mmWave PHY PIB .....	343
11.2	Single Carrier Mode of mmWave PHY.....	344
11.2.1	PHY operating specifications of SC PHY .....	345
11.2.1.1	Channelization .....	345

11.2.1.2	Scanning channels.....	345
11.2.2	Modulation, forward error correction, and spreading .....	345
11.2.2.1	MCS-dependent parameters.....	345
11.2.2.2	Header rate-dependent parameters.....	347
11.2.2.3	Timing-related parameters .....	348
11.2.2.4	Frame-related parameters .....	348
11.2.2.5	Modulation.....	349
11.2.2.5.1	p/2 BPSK .....	349
11.2.2.5.2	p/2 QPSK .....	349
11.2.2.5.3	p/2 8-PSK.....	350
11.2.2.5.4	p/2 16-QAM.....	351
11.2.2.6	FEC .....	351
11.2.2.6.1	Reed-Solomon block codes in GF(28).....	351
11.2.2.6.2	Irregular LDPC codes .....	352
11.2.2.6.3	Rate 14/15 LDPC code .....	353
11.2.2.7	Stuff bits.....	353
11.2.2.8	Code spreading .....	356
11.2.2.8.1	Golay sequences .....	356
11.2.2.8.2	PRBS generation with LFSR .....	356
11.2.2.9	Unequal error protection.....	357
11.2.2.10	Scrambling .....	358
11.2.3	SC PHY frame format .....	359
11.2.3.1	PHY preamble.....	360
11.2.3.1.1	Sync field .....	360
11.2.3.1.2	SFD field.....	360
11.2.3.1.3	Channel estimation sequence (CES).....	360
11.2.3.2	Frame header.....	360
11.2.3.2.1	SC PHY header .....	362
11.2.3.2.2	Base header HCS .....	363
11.2.3.2.3	Base header FEC.....	363
11.2.3.2.4	MAC subheader HCS .....	363
11.2.3.2.5	MAC subheader FEC.....	364
11.2.3.3	SC PHY Payload field .....	364
11.2.3.3.1	SC PHY Payload scrambling.....	364
11.2.3.3.2	Modulation.....	364
11.2.3.3.3	FEC .....	364
11.2.3.3.4	Code spreading .....	364
11.2.3.4	Pilot word and PCES .....	365
11.2.3.4.1	Subblocks and pilot word .....	365
11.2.3.4.2	Pilot channel estimation sequence (PCES).....	365
11.2.4	Transmitter specifications .....	366
11.2.4.1	Error vector magnitude .....	366
11.2.4.2	Transmit center frequency tolerance.....	366
11.2.4.3	Symbol rate.....	366
11.2.4.4	Transmit power-on and power-down ramp .....	366
11.2.5	Receiver specifications .....	366
11.2.5.1	Error rate criterion .....	366
11.2.5.2	Receiver sensitivity.....	367
11.2.5.3	Receiver maximum input level.....	367
11.2.5.4	Receiver clear channel assessment performance .....	367
11.2.6	PHY layer timing .....	368
11.2.6.1	Interframe space.....	368
11.2.6.2	Receive-to-transmit turnaround time .....	368
11.2.6.3	Transmit-to-receive turnaround-time.....	368

11.2.6.4	Time between successive transmissions .....	368
11.2.6.5	Channel switch.....	369
11.2.7	PHY management for SC PHY .....	369
11.2.7.1	Maximum frame size .....	369
11.2.7.2	Maximum transfer unit size .....	369
11.2.7.3	Minimum fragment size.....	369
11.2.8	Optional OOK/DAMI modes .....	369
11.2.8.1	OOK.....	369
11.2.8.2	DAMI.....	370
11.2.8.3	FEC .....	370
11.2.8.4	OOK/DAMI spreading .....	370
11.3	High Speed Interface mode of mmWave PHY .....	370
11.3.1	General operating specifications .....	370
11.3.1.1	Operating frequency bands .....	370
11.3.2	HSI PHY modulation, forward error correction, and spreading .....	370
11.3.2.1	MCS-dependent parameters.....	370
11.3.2.2	HSI PHY timing-related parameters.....	372
11.3.2.3	HSI PHY frame-related parameters .....	373
11.3.2.4	HSI PHY FEC.....	373
11.3.2.4.1	LDPC block code.....	374
11.3.2.4.2	EEP data multiplexer .....	374
11.3.2.4.3	UEP data multiplexer.....	374
11.3.2.4.4	Bit interleaver .....	375
11.3.2.5	Stuff bits.....	376
11.3.2.6	Constellation mapping .....	376
11.3.2.7	HSI spreader .....	378
11.3.2.7.1	Spreader for spreading factor of 1 .....	379
11.3.2.7.2	Spreader for spreading factor of 48 .....	379
11.3.2.8	Tone interleaver .....	379
11.3.2.9	HSI PHY OFDM modulator .....	380
11.3.2.9.1	Pilot subcarriers .....	381
11.3.2.9.2	Guard subcarriers.....	382
11.3.2.10	PCES insertion.....	382
11.3.2.11	HSI PHY scrambling .....	382
11.3.3	HSI PHY frame format .....	383
11.3.3.1	PHY preamble.....	383
11.3.3.2	Frame header.....	384
11.3.3.3	HSI PHY header .....	386
11.3.3.4	Header check sequences .....	387
11.3.3.4.1	Main Header HCS.....	387
11.3.3.4.2	MAC Subheader HCS.....	387
11.3.3.5	PHY Payload field .....	388
11.3.4	Transmitter specifications .....	388
11.3.4.1	EVM requirement .....	388
11.3.4.2	Chip rate and clock alignment .....	389
11.3.5	Receiver specifications .....	389
11.3.5.1	Receiver sensitivity.....	389
11.3.5.2	Receiver CCA performance.....	389
11.3.5.3	Receiver maximum input level.....	389
11.3.5.4	PHY layer timing .....	389
11.3.5.5	Interframe spacing .....	389
11.3.5.6	Receive-to-transmit turnaround time .....	390
11.3.5.7	Transmit-to-receive turnaround time .....	390
11.3.5.8	Time between successive transmissions .....	390

11.3.5.9	Channel switch time.....	390
11.3.6	HSI PHY management .....	390
11.3.6.1	PHY supported data rate encoding .....	390
11.3.6.2	HSI PHY fragment size encoding.....	390
11.3.6.3	Maximum frame length .....	391
11.3.6.4	Maximum transfer unit size .....	391
11.3.6.5	Minimum fragment size.....	391
11.4	Audio/Visual mode of mmWave PHY .....	391
11.4.1	General requirements .....	392
11.4.1.1	AV PHY channelization .....	392
11.4.1.2	PHY layer timing.....	393
11.4.1.2.1	Interframe space.....	393
11.4.1.2.2	Receive-to-transmit turnaround time.....	394
11.4.1.2.3	Transmit-to-receive turnaround time.....	394
11.4.1.2.4	Time between successive transmissions .....	394
11.4.1.2.5	Channel switch time.....	394
11.4.1.2.6	CCA detect time.....	394
11.4.1.3	Data size restrictions .....	394
11.4.1.3.1	Maximum frame length .....	394
11.4.1.3.2	Maximum transfer unit size .....	395
11.4.1.3.3	Minimum fragment size.....	395
11.4.1.4	Header check sequence.....	395
11.4.2	AV PHY modulation and forward error correction .....	395
11.4.2.1	AV PHY base rate.....	396
11.4.2.2	Repetition coding and spatial diversity.....	397
11.4.2.3	Stuff bits.....	397
11.4.2.4	HRP splitter and scrambler .....	398
11.4.2.5	LRP scrambler .....	398
11.4.2.6	HRP outer code .....	399
11.4.2.7	HRP outer interleaver .....	399
11.4.2.8	Convolutional encoder .....	400
11.4.2.9	Puncturing.....	400
11.4.2.10	HRP data multiplexer and bit interleaver .....	400
11.4.2.10.1	EEP data multiplexer .....	401
11.4.2.10.2	UEP coding data multiplexer .....	402
11.4.2.10.3	UEP mapping data multiplexer .....	404
11.4.2.10.4	HRP header data multiplexer .....	405
11.4.2.11	Bit reversal tone interleaver .....	406
11.4.2.12	Signal constellations .....	406
11.4.2.13	AV PHY non-data subcarriers .....	407
11.4.2.14	AV PHY OFDM modulation .....	408
11.4.3	AV PHY frame formats .....	409
11.4.3.1	HRP preamble.....	410
11.4.3.2	HRP header .....	411
11.4.3.3	LRP preamble sequences .....	411
11.4.3.4	Long omni LRP preamble.....	412
11.4.3.5	Short omni LRP preamble .....	413
11.4.3.6	Omni LRP header .....	414
11.4.3.7	Directional LRP preamble .....	414
11.4.3.8	Directional LRP header and payload .....	415
11.4.4	AV PHY transmitter requirements .....	416
11.4.4.1	TX mask.....	416
11.4.4.2	EVM requirement .....	417
11.4.4.3	Symbol timing.....	417

11.4.4.4	TX frequency accuracy .....	418
11.4.4.5	TX power ramp on and off .....	418
11.4.5	AV PHY Receiver characteristics .....	418
11.4.5.1	Error rate criterion .....	418
11.4.5.2	Sensitivity .....	418
11.4.5.3	Maximum input level .....	418
11.4.6	Preambles and training symbols .....	418
12.	Beam forming .....	423
12.1	Introduction .....	423
12.2	Beam forming terminology .....	423
12.2.1	Quasi-omni patterns .....	424
12.2.2	Sectors .....	424
12.2.3	Beams .....	425
12.2.4	Clusters .....	426
12.3	Beam forming codebooks .....	427
12.3.1	Beam forming codebooks .....	428
12.4	Beam forming reference model .....	429
12.5	Beam forming protocol .....	431
12.5.1	Two-level training mechanism .....	431
12.5.1.1	Sector-level training .....	431
12.5.1.1.1	AAS sector-level training .....	431
12.5.1.1.2	SAS sector-level training .....	434
12.5.1.1.3	Sector-level training failure remedy .....	437
12.5.1.2	Beam-level training .....	437
12.5.1.2.1	AAS beam-level training .....	437
12.5.1.2.2	SAS beam-level training .....	440
12.5.2	Beam tracking .....	443
12.6	On-demand beam forming .....	445
12.7	Proactive beam forming .....	445
12.8	TSD .....	445
Annex A	(informative) Bibliography .....	447
Annex B	(normative) Frame convergence sublayer .....	448
B.1	Generic convergence sublayer .....	448
B.2	EPD FCSL PDU classification .....	449
B.3	EPD FCSL .....	449
B.3.1	EPD FCSL QoS support .....	450
B.3.2	Data entity inter-relationships .....	450
B.4	EPD FCSL SAP .....	451
B.4.1	MA-UNITDATA.request .....	452
B.4.2	MA-UNITDATA.indication .....	452
B.4.3	MA-UNITDATA-STATUS.indication .....	453
B.5	Stream SAP .....	454
B.5.1	Stream creation, modification, and deletion .....	454
B.5.1.1	STREAM_INITIATE.request .....	456
B.5.1.2	STREAM_INITIATE.confirm .....	456
B.5.1.3	STREAM_INITIATE.indication .....	456
B.5.1.4	STREAM_MODIFY.request .....	457
B.5.1.5	STREAM_MODIFY.confirm .....	457
B.5.1.6	STREAM_END.request .....	457

B.5.1.7	STREAM_END.confirm.....	458
B.5.1.8	STREAM_END.indication.....	458
B.5.2	Stream data interface.....	458
B.5.2.1	STREAM_DATA.request.....	459
B.5.2.2	STREAM_DATA.confirm.....	460
B.5.2.3	STREAM_DATA.indication.....	460
Annex C (informative)	Security considerations.....	461
C.1	Background assumptions.....	461
C.1.1	Physical assumptions.....	461
C.1.2	Network assumptions.....	461
C.1.3	Attack model assumptions.....	462
C.1.4	Security key lifecycle issues.....	462
C.1.4.1	Key lifecycle.....	462
C.1.4.2	Membership lifecycle.....	462
C.1.4.3	Group membership change rekey.....	462
C.2	Claimed security services.....	462
C.2.1	Beacon protection protocol.....	462
C.2.2	Distribute key protocol.....	463
C.2.3	Key request protocol.....	463
C.2.4	Data protection protocol.....	464
C.3	Properties of the IEEE 802.15.3 security suite.....	464
C.3.1	Key usage.....	464
C.3.2	Replay prevention.....	464
Annex D (informative)	Coexistence, interoperability, and interference.....	466
D.1	Interoperability.....	466
D.1.1	Interoperability with IEEE 802.11 DSSS and IEEE 802.11b.....	466
D.1.2	IEEE 802.11 FHSS and IEEE 802.15.1.....	467
D.2	Coexistence.....	467
D.2.1	Coexistence with IEEE Std 802.11b.....	467
D.2.1.1	Passive scanning.....	468
D.2.1.2	Dynamic channel selection.....	468
D.2.1.3	The ability to request channel quality information.....	468
D.2.1.4	Link quality and RSSI.....	468
D.2.1.5	Channel plan that minimizes channel overlap.....	468
D.2.1.6	Lower transmit power.....	469
D.2.1.7	Transmit power control.....	469
D.2.1.8	Neighbor piconet capability.....	469
D.2.2	Coexistence with IEEE 802.15.1 and IEEE 802.11 FHSS.....	470
D.2.2.1	PHY collaborative coexistence enhancements.....	470
D.2.2.2	MAC coexistence via collaboration.....	470
D.2.2.3	Other techniques.....	471
D.3	Coexistence performance.....	471
D.3.1	Allowed operation.....	471
D.3.2	Assumptions for coexistence calculations.....	471
D.3.3	Performance impact on IEEE 802.15.3 piconets.....	473
D.3.3.1	IEEE 802.11b overlapping with IEEE 802.15.3.....	473
D.3.3.2	IEEE 802.15.1 and IEEE 802.11 FHSS overlapping with IEEE 802.15.3.....	476
D.4	Notes on the calculations.....	477

Annex E (normative) Protocol implementation conformance statement (PICS) proforma.....	478
E.1 Introduction.....	478
E.1.1 Scope.....	478
E.1.2 Purpose.....	478
E.2 Abbreviations and special symbols.....	478
E.3 Instructions for completing the PICS proforma.....	479
E.4 Identification of the implementation.....	479
E.5 Identification of the protocol .....	480
E.6 Global statement of conformance .....	481
E.7 PICS proforma—IEEE Std 802.15.3-2016.....	481
E.7.1 Major roles for IEEE 802.15.3 DEVs.....	481
E.7.2 PHY functions.....	482
E.7.3 Major capabilities for the MAC sublayer .....	483
E.7.3.1 MAC frames .....	483
E.7.3.2 MAC sublayer functions .....	486
E.7.4 Security support .....	490
Annex F (informative) Implementation considerations.....	491
F.1 Channel time requests.....	491
F.1.1 Types of CTAs.....	491
F.1.2 Interpretation of channel time requests.....	492
F.1.3 Determining CTA Rate Factor from stream requirements .....	493
F.1.3.1 Example 1.....	494
F.1.3.2 Example 2.....	495
F.1.4 PNC interpretation of CTA rate factor .....	495
F.1.5 Creating channel time requests from MLME requests .....	496
F.1.6 Interpreting channel time requests.....	498
F.2 Sample frames.....	500
F.3 Use of multiple mmWave PHYs in a single piconet .....	502
Annex G (normative) Optional OOK/DAMI modes .....	504
G.1 Introduction.....	504
G.2 Child piconet operation.....	504
G.3 DAMI.....	504
G.4 PHY preamble.....	506
G.5 PHY frame format .....	507
G.6 Interframe space.....	507
G.7 Eye opening for OOK .....	508
G.8 EVM for DAMI .....	508