

ISO/IEC/IEEE 8802-15-3:2017-10 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 15-3: High data rate wireless multi-media networks

Contents

1.	Overview.....	26
1.1	Scope.....	26
1.2	Purpose.....	26
2.	Normative references.....	27
3.	Definitions, acronyms, and abbreviations.....	28
3.1	Definitions.....	28
3.2	Acronyms and abbreviations.....	29
4.	General description.....	33
4.1	What is a piconet?.....	33
4.2	Components of an IEEE 802.15.3 piconet.....	33
4.3	Overview of medium access control (MAC) functionality.....	33
4.3.1	Coordination.....	34
4.3.1.1	Starting a piconet.....	34
4.3.1.2	Handing over control of the piconet.....	34
4.3.1.3	Creating a child piconet.....	34
4.3.1.4	Creating a neighbor piconet.....	35
4.3.2	Ending a piconet.....	35
4.3.3	Ending a piconet with a dependent piconet involved.....	35
4.3.4	Association and disassociation.....	36
4.3.5	Security overview.....	36
4.3.6	The IEEE 802.15.3 superframe.....	36
4.3.7	Channel time management.....	37
4.3.8	Data communications between DEVS.....	38
4.3.9	Information discovery in the piconet.....	38
4.3.10	Dynamic channel selection.....	39
4.3.11	Power management.....	39
4.3.12	Controlling transmit power in the piconet.....	40
4.3.13	Superframe structure using quasi-omni mode.....	40
4.3.14	Frame aggregation.....	41
4.3.15	Beam forming.....	41
4.3.16	Channel probing.....	41
4.3.17	Unequal error protection (UEP).....	41
4.4	Characteristics of the 2.4 GHz PHY.....	41
4.4.1	General characteristics.....	41
4.4.2	Coexistence and interoperability.....	42
4.5	Characteristics of the mmWave PHY.....	42
4.5.1	mmWave PHY characteristics.....	42
4.5.2	Piconets using mmWave PHY modes.....	43
4.6	Conventions.....	44
4.7	Concept of primitives.....	44
5.	Layer management.....	46
5.1	Overview of management model.....	46
5.2	Generic management primitives.....	47
5.2.1	MLME-GET.request.....	48

5.2.2	MLME-GET.confirm	48
5.2.3	MLME-SET.request	48
5.2.4	MLME-SET.confirm	48
5.3	MLME SAP interface	49
5.3.1	Resetting the MAC/MLME	50
5.3.1.1	MLME-RESET.request	50
5.3.1.2	MLME-RESET.confirm	50
5.3.2	Scanning for piconets	51
5.3.2.1	MLME-SCAN.request	53
5.3.2.2	MLME-SCAN.confirm	53
5.3.2.3	MLME-SCAN.indication	54
5.3.3	Starting a piconet	54
5.3.3.1	MLME-START.request	55
5.3.3.2	MLME-START.confirm	55
5.3.4	Stopping a piconet	55
5.3.4.1	MLME-STOP.request	56
5.3.4.2	MLME-STOP.confirm	56
5.3.5	Associating with a piconet	57
5.3.5.1	MLME-ASSOCIATE.request	58
5.3.5.2	MLME-ASSOCIATE.confirm	58
5.3.5.3	MLME-ASSOCIATE.indication	58
5.3.6	Disassociation from a piconet	58
5.3.6.1	MLME-DISASSOCIATE.request	59
5.3.6.2	MLME-DISASSOCIATE.confirm	59
5.3.6.3	MLME-DISASSOCIATE.indication	60
5.3.7	Security management	60
5.3.7.1	MLME-MEMBERSHIP-UPDATE.request	62
5.3.7.2	MLME-MEMBERSHIP-UPDATE.confirm	62
5.3.7.3	MLME-SECURITY-ERROR.indication	62
5.3.7.4	MLME-SECURITY-MESSAGE.request	62
5.3.7.5	MLME-SECURITY-MESSAGE.confirm	63
5.3.7.6	MLME-SECURITY-MESSAGE.indication	63
5.3.8	PNC handover	63
5.3.8.1	MLME-PNC-HANDOVER.indication	63
5.3.8.2	MLME-PNC-HANDOVER.response	64
5.3.8.3	MLME-NEW-PNC.indication	64
5.3.9	Requesting DEV information from the PNC	64
5.3.9.1	MLME-DEV-INFO.request	65
5.3.9.2	MLME-DEV-INFO.confirm	65
5.3.9.3	MLME-DEV-INFO.indication	65
5.3.10	Security information retrieval	65
5.3.10.1	MLME-SECURITY-INFO.request	65
5.3.10.2	MLME-SECURITY-INFO.confirm	66
5.3.10.3	MLME-SECURITY-INFO.indication	67
5.3.10.4	MLME-SECURITY-INFO.response	67
5.3.11	Application specific data management	67
5.3.11.1	MLME-APPLICATION-SPECIFIC.request	68
5.3.11.2	MLME-APPLICATION-SPECIFIC.confirm	69
5.3.11.3	MLME-APPLICATION-SPECIFIC.indication	69
5.3.12	Piconet services management	69
5.3.12.1	MLME-ANNOUNCE-SERVICE.request	70
5.3.12.2	MLME-ANNOUNCE-SERVICE.confirm	70
5.3.12.3	MLME-PICONET-SERVICES.request	71
5.3.12.4	MLME-PICONET-SERVICES.confirm	71

5.3.12.5	MLME-PICONET-SERVICES.indication	71
5.3.13	Stream management	71
5.3.13.1	MLME-CREATE-STREAM.request	73
5.3.13.2	MLME-CREATE-STREAM.confirm	74
5.3.13.3	MLME-CREATE-STREAM.indication	74
5.3.13.4	MLME-MODIFY-STREAM.request	74
5.3.13.5	MLME-MODIFY-STREAM.confirm	75
5.3.13.6	MLME-TERMINATE-STREAM.request	75
5.3.13.7	MLME-TERMINATE-STREAM.confirm	75
5.3.13.8	MLME-TERMINATE-STREAM.indication	75
5.3.14	Piconet parameter management	76
5.3.14.1	MLME-BSID-CHANGE.request	76
5.3.14.2	MLME-BSID-CHANGE.confirm	76
5.3.14.3	MLME-PICONET-PARM-CHANGE.indication	77
5.3.15	Power management	77
5.3.15.1	MLME-PS-SET-INFORMATION.request	79
5.3.15.2	MLME-PS-SET-INFORMATION.confirm	79
5.3.15.3	MLME-SPS-CONFIGURE.request	79
5.3.15.4	MLME-SPS-CONFIGURE.confirm	80
5.3.15.5	MLME-PM-MODE-CHANGE.request	80
5.3.15.6	MLME-PM-MODE-CHANGE.confirm	80
5.3.15.7	MLME-PM-MODE-CHANGE.indication	80
5.3.15.8	MLME-MONITOR-PM-MODE.request	81
5.3.15.9	MLME-MONITOR-PM-MODE.confirm	81
5.3.15.10	MLME-MONITOR-PM-MODE.indication	81
5.3.16	Multicast operations	82
5.3.16.1	MLME-MULTICAST-CONFIGURATION.request	83
5.3.16.2	MLME-MULTICAST-CONFIGURATION.confirm	83
5.3.16.3	MLME-MULTICAST-RX-SETUP.request	83
5.3.16.4	MLME-MULTICAST-RX-SETUP.confirm	84
5.3.17	Timing synchronization	84
5.3.17.1	MLME-BEACON-EVENT.request	84
5.3.17.2	MLME-BEACON-EVENT.confirm	84
5.3.17.3	MLME-BEACON-EVENT.indication	85
5.3.18	Transmit switched diversity (TSD)	85
5.3.18.1	MLME-TXDIV.request	85
5.3.18.2	MLME-TXDIV.confirm	86
5.4	MAC management	86
5.4.1	MAC PIB PNC group	86
5.4.2	MAC PIB characteristic group	87
5.5	MAC SAP	88
5.5.1	MAC-ASYNC-DATA.request	91
5.5.2	MAC-ASYNC-DATA.confirm	91
5.5.3	MAC-ASYNC-DATA.indication	91
5.5.4	MAC-ISOCH-DATA.request	92
5.5.5	MAC-ISOCH-DATA.confirm	92
5.5.6	MAC-ISOCH-DATA.indication	93
6.	MAC frame formats	94
6.1	Frame format conventions	94
6.2	General frame format	95
6.2.1	Frame Control field	96
6.2.1.1	Protocol Version field	96

6.2.1.2	Frame Type field.....	97
6.2.1.3	SEC field.....	97
6.2.1.4	ACK Policy field, Imp-ACK Request field, and Blk-ACK field	97
6.2.1.5	Retry field	97
6.2.1.6	More Data field.....	98
6.2.1.7	Imp-ACK Negative Acknowledgment (NAK) field.....	98
6.2.1.8	CTA Relinquish field.....	98
6.2.2	Piconet ID (PNID) field	99
6.2.3	SrcID and DestID fields	99
6.2.4	Fragmentation Control field	99
6.2.4.1	MSDU Number field	99
6.2.4.2	Fragment Number field.....	100
6.2.4.3	Last Fragment Number field.....	100
6.2.5	Stream Index field	100
6.2.6	MAC header validation	100
6.2.7	MAC Frame Body field	101
6.2.7.1	Frame Payload field.....	101
6.2.7.2	Secure session ID (SECID) field	101
6.2.7.3	Secure Frame Counter (SFC) field	101
6.2.7.4	Secure Payload field	101
6.2.7.5	Integrity Code field.....	101
6.2.7.6	Frame Check Sequence (FCS) field.....	101
6.2.8	SC and HSI aggregated frame format	102
6.2.8.1	Standard aggregation format.....	102
6.2.8.1.1	Non-secure standard aggregation format.....	102
6.2.8.1.2	Secure standard aggregation format	105
6.2.8.2	Low-latency aggregation formats	105
6.2.8.2.1	Non-secure low-latency aggregation format.....	105
6.2.8.2.2	Secure low-latency aggregation format	108
6.2.9	AV aggregated frame format	109
6.2.9.1	Extended MAC header format	109
6.2.9.1.1	Extended Control Header field	110
6.2.9.1.2	MAC Extension Header field	111
6.2.9.1.3	Security Header field	112
6.2.9.1.4	Video Header field.....	112
6.2.9.2	Subframe format	113
6.2.9.3	AV aggregated	115
6.2.9.4	Regular.....	115
6.2.9.5	Directional ACK	116
6.3	Format of individual frame types.....	116
6.3.1	Beacon frame	116
6.3.1.1	Non-secure Beacon frame.....	116
6.3.1.2	Secure Beacon frame	118
6.3.2	Acknowledgment frames	119
6.3.2.1	Imm-ACK frame.....	119
6.3.2.2	Delayed ACK (Dly-ACK) frame.....	120
6.3.3	Command frame	121
6.3.3.1	Non-secure Command frame	121
6.3.3.2	Secure Command frame.....	122
6.3.4	Data frame	123
6.3.4.1	Non-secure Data frame	123
6.3.4.2	Secure Data frame.....	123
6.3.5	Multi-protocol Data frame	124
6.3.5.1	Non-secure Multi-protocol Data frame.....	124

6.3.5.2	Secure Multi-protocol Data frame	125
6.3.6	Sync frame	125
6.4	Information elements (IEs)	126
6.4.1	CTA IE	128
6.4.2	BSID IE	129
6.4.3	Parent Piconet IE	129
6.4.4	DEV Association IE	129
6.4.5	PNC shutdown IE	130
6.4.6	Piconet Parameter Change IE	131
6.4.7	AS IE	132
6.4.8	Pending channel time map (PCTM) IE	132
6.4.9	PNC Handover IE	133
6.4.10	CTA Status IE	133
6.4.11	Capability IE	134
6.4.12	Transmit Power Parameters IE	140
6.4.13	PS Status IE	141
6.4.14	CWB IE	141
6.4.15	Overlapping PNID IE	142
6.4.16	Piconet Services IE	142
6.4.17	Vendor Defined IE	143
6.4.18	Group ID IE	143
6.4.19	Stream Renew IE	144
6.4.20	Next PNC IE	144
6.4.21	Piconet Channel Status IE	144
6.4.22	Synchronization IE	145
6.4.23	TSD IE	147
6.4.24	UEP Specific IE	148
6.4.25	IFS IE	148
6.4.26	CTA Relinquish Duration IE	149
6.4.27	Feedback IE	149
6.4.28	Mapping IE	151
6.4.29	BST Clustering IE	152
6.4.30	PET Clustering IE	152
6.4.31	Beam PET IE	153
6.4.32	HRS Beam PET IE	154
6.4.33	PET Amplitude IE	155
6.4.34	PET Phase IE	155
6.4.35	Sync Frame Frequency IE	156
6.4.36	Directional Peer IE	156
6.5	MAC commands	157
6.5.1	Association and disassociation commands	159
6.5.1.1	Association Request command	159
6.5.1.2	Association Response command	160
6.5.1.3	Disassociation Request command	161
6.5.2	Security commands	161
6.5.2.1	Request Key command	161
6.5.2.2	Request Key Response command	161
6.5.2.3	Distribute Key Request command	162
6.5.2.4	Distribute Key Response command	162
6.5.3	PNC handover commands	162
6.5.3.1	PNC Handover Request commnad	163
6.5.3.2	PNC Handover Response command	163
6.5.3.3	PNC Handover Information command	164
6.5.4	Information request commands	164

6.5.4.1	PNC Information Request command	164
6.5.4.2	PNC Information command	164
6.5.4.3	Security Information Request command	166
6.5.4.4	Security Information command	166
6.5.4.5	Probe Request command	167
6.5.4.6	Probe Response command	169
6.5.5	Information announcement commands	171
6.5.5.1	Piconet Services command	171
6.5.5.2	Announce command	171
6.5.5.3	Announce Response command	173
6.5.6	Channel time allocation request, modification, and termination commands	173
6.5.6.1	Channel Time Request command	173
6.5.6.2	Channel Time Response command	176
6.5.7	Channel status commands	177
6.5.7.1	Channel Status Request command	177
6.5.7.2	Channel status response	177
6.5.7.3	Remote Scan Request command	178
6.5.7.4	Remote Scan Response command	178
6.5.7.5	Transmit Power Change command	180
6.5.8	Power management commands	180
6.5.8.1	PS Set Information Request command	180
6.5.8.2	PS Set Information Response command	180
6.5.8.3	SPS Configuration Request command	181
6.5.8.4	SPS Configuration Response command	182
6.5.8.5	PM Mode Change command	183
6.5.8.6	PM Mode Change Response command	183
6.5.9	Special commands	184
6.5.9.1	Security Message command	184
6.5.9.2	Vendor Defined command	184
6.5.9.3	AS IE Request command	185
6.5.9.4	AS IE Response command	185
6.5.10	Multicast configuration commands	186
6.5.10.1	Multicast Configuration Request command	186
6.5.10.2	Multicast Configuration Response command	186
7.	MAC functional description	187
7.1	Introduction	187
7.2	Starting, maintaining, and stopping piconets	188
7.2.1	Scanning through channels	188
7.2.2	Starting a piconet	189
7.2.3	PNC handover	190
7.2.4	Preliminary handover	193
7.2.5	Next PNC	194
7.2.6	Dependent PNC handover	195
7.2.7	Child piconet	198
7.2.8	Neighbor piconet	200
7.2.9	Stopping piconet operations	202
7.2.9.1	Stopping an independent or parent piconet	203
7.2.9.2	Parent PNC stopping a dependent piconet	203
7.2.9.3	Dependent PNC termination of a dependent piconet	204
7.2.10	Non-PNC-capable DEVs	204
7.3	Association and disassociation with a piconet	204
7.3.1	Association	204

7.3.2	Piconet services	206
7.3.3	Broadcasting piconet information	208
7.3.4	Disassociation	209
7.4	Channel access	210
7.4.1	Interframe space (IFS)	211
7.4.2	Carrier sense multiple access with collision avoidance (CSMA/CA)	211
7.4.3	Channel time allocation period channel access	213
7.4.3.1	Channel time allocations (CTAs)	213
7.4.3.2	Channel time allocation (CTA) and channel time usage	215
7.4.3.3	Management CTAs	216
7.4.3.4	Slotted aloha access	216
7.4.3.5	Allocation of MCTAs	217
7.4.3.6	Guard time	217
7.4.3.7	Calculating channel time requests	219
7.4.3.8	Relinquishing CTA time to another DEV	220
7.5	Channel time management	222
7.5.1	Isochronous stream management	222
7.5.1.1	Isochronous stream creation	223
7.5.1.2	Isochronous stream modification	226
7.5.1.3	Isochronous stream termination	229
7.5.2	Asynchronous channel time reservation and termination	231
7.5.2.1	Asynchronous channel time reservation	231
7.5.2.2	Asynchronous channel time termination	233
7.5.3	Multicast group configuration	234
7.6	Synchronization	235
7.6.1	Time accuracy	236
7.6.2	Beacon generation	236
7.6.3	Beacon reception	237
7.6.4	Beacon information announcement	237
7.6.5	Superframe support for directional PHYs	238
7.6.5.1	Quasi-omni beacon	239
7.6.5.2	Directional CAP	240
7.6.5.3	Directional association	241
7.6.5.4	DEV quasi-omni transmit direction training and tracking	242
7.7	Fragmentation and defragmentation	243
7.8	Aggregation	244
7.8.1	Standard aggregation	244
7.8.2	Low-latency aggregation	245
7.9	Acknowledgment and retransmission	246
7.9.1	No acknowledgment (no-ACK)	246
7.9.2	Immediate acknowledgment (Imm-ACK)	246
7.9.3	Delayed acknowledgment (Dly-ACK)	247
7.9.4	Implied acknowledgment (Imp-ACK)	248
7.9.5	Block acknowledgment (Blk-ACK)	250
7.9.5.1	Blk-ACK for standard aggregation	250
7.9.5.2	Blk-ACK for low-latency aggregation	251
7.9.6	Retransmissions	252
7.9.7	Duplicate detection	252
7.10	Peer discovery	252
7.10.1	PNC information request	252
7.10.2	Probe request and response	253
7.10.3	Announce	254
7.10.4	Channel status request	254
7.10.5	Remote scan	254

7.10.6	PNC channel scanning	255
7.10.7	Channel probing	255
7.11	Changing piconet parameters.....	256
7.11.1	Moving beacon	256
7.11.2	Changing superframe duration	256
7.11.3	Setting the PNID or BSID	257
7.11.4	Maintaining synchronization in dependent piconets	258
7.12	Interference mitigation.....	258
7.12.1	Dynamic channel selection	259
7.12.2	Transmit power control	260
7.12.2.1	Maximum transmitter power for the CAP, beacon, and directed MCTAs..	260
7.12.2.2	Adjustable transmitter power in a CTA.....	261
7.13	Multi-rate support	261
7.14	Power management.....	262
7.14.1	Piconet synchronized power save (PSPS) mode	263
7.14.2	Device synchronized power save (DSPS) mode	264
7.14.2.1	Creation, use, and management of DSPS sets	264
7.14.2.2	Changing DSPS mode and operation.....	265
7.14.2.3	CTA timing in DSPS mode	266
7.14.3	Asynchronous power save (APS) mode	268
7.14.4	MSCs for power save modes	269
7.15	AS IE operation	272
7.16	MAC sublayer parameters	275
7.17	Unequal error protection (UEP).....	278
7.18	Sync frame transmission and virtually dependent piconet	278
8.	Security	280
8.1	Security mechanisms	280
8.1.1	Security membership and key establishment	280
8.1.2	Key transport	280
8.1.3	Data encryption	280
8.1.4	Data integrity	280
8.1.5	Beacon integrity protection	280
8.1.6	Command integrity protection	281
8.1.7	Freshness protection	281
8.2	Security modes.....	281
8.2.1	Security mode 0	281
8.2.2	Security mode 1	281
8.3	Security support	281
8.3.1	PNC handover	281
8.3.2	Changes in the piconet group data key	282
8.3.3	Joining a secure piconet	282
8.3.4	Membership update	282
8.3.5	Secure frame generation	283
8.3.6	Updating CurrentTimeToken	284
8.3.7	Secure frame reception	284
8.3.8	Selecting the SECID for a new key	285
8.3.9	Key selection	285
8.4	Protocol details	289
8.4.1	Security information request and distribution	289
8.4.2	Key distribution protocol	291
8.4.3	Key request protocol	291

9.	Security specifications	292
9.1	Modes for security	292
9.2	Symmetric cryptography building blocks	292
9.2.1	Notational conventions	292
9.2.2	CCM combined encryption and data authentication	292
9.2.3	CCM parameters	292
9.2.4	Nonce value	292
9.2.5	AES encryption	293
9.3	Symmetric cryptography implementation	293
9.3.1	Symmetric cryptography data formats	293
9.3.2	Symmetric cryptographic operations	293
9.4	CCM mode.....	295
9.4.1	Inputs	295
9.4.2	Data authentication	296
9.4.3	Encryption	298
9.4.4	Output	298
9.4.5	Decryption	299
9.4.6	Restrictions	299
9.4.7	List of symbols	299
10.	PHY specification for the 2.4 GHz band	301
10.1	Overview of the 2.4 GHz PHY	301
10.2	General requirements.....	302
10.2.1	Operating frequency range	302
10.2.2	Radio frequency (RF) power measurements	302
10.2.3	Channel assignments	302
10.2.4	Scanning channels	302
10.2.5	Unwanted emissions	303
10.2.6	Operating temperature range	303
10.2.7	PHY layer timing	303
10.2.7.1	Interframe space.....	303
10.2.7.2	Receive-to-transmit turnaround time	303
10.2.7.3	Transmit-to-receive turnaround time	304
10.2.7.4	Time between successive transmissions	304
10.2.7.5	Channel switch time.....	304
10.2.8	Data size restrictions	304
10.2.8.1	Maximum frame length	304
10.2.8.2	Maximum transfer unit size	304
10.2.8.3	Minimum fragment size.....	304
10.2.9	Header check sequence	304
10.2.10	Channel access methods	306
10.3	Modulation and coding	306
10.3.1	Base data rate	307
10.3.2	Signal constellations	307
10.3.3	DQPSK modulation	308
10.3.4	QPSK and 16/32/64-QAM with trellis coding	309
10.4	PHY frame format	316
10.4.1	Frame format	316
10.4.2	PHY preamble	317
10.4.3	Header modulation	319
10.4.4	Scrambling	319
10.4.5	PHY header	321

10.4.6	Stuff bits	322
10.4.7	Tail symbols	322
10.5	Transmitter specifications.....	325
10.5.1	Error vector magnitude definition	325
10.5.2	EVM calculated values	326
10.5.3	Transmit power spectral density (PSD) mask	326
10.5.4	Transmit center frequency tolerance	326
10.5.5	Symbol rate	326
10.5.6	Clock synchronization	327
10.5.7	Transmit power-on and power-down ramp	327
10.5.8	RF carrier suppression	327
10.5.9	Transmit power	327
10.6	Receiver specifications	328
10.6.1	Error rate criterion	328
10.6.2	Receiver sensitivity	328
10.6.3	Receiver maximum input level	329
10.6.4	Receiver jamming resistance	329
10.6.5	Receiver CCA performance	330
10.6.6	Receiver RSSI	330
10.6.7	Link quality indication	330
10.7	PHY management.....	330
11.	PHY specification for millimeter wave	333
11.1	General requirements.....	333
11.1.1	Regulatory information	333
11.1.2	RF power measurements	334
11.1.3	Unwanted emissions	334
11.1.4	Operating temperature range	334
11.1.5	RF channelization	334
11.1.6	Transmit PSD mask	334
11.1.7	Error vector magnitude calculation	334
11.1.7.1	SC PHY.....	334
11.1.7.2	AV and HSI PHYs.....	335
11.1.8	Common PHY management for mmWave PHY modes	336
11.1.8.1	Supported MCSs.....	336
11.1.8.2	Preferred fragment size.....	336
11.1.8.3	Receive Status field	337
11.1.9	Requirements for mmWave PNCs	338
11.1.10	CP operation	338
11.1.11	mmWave PHY mode usage in CTA	339
11.1.12	Common mode signaling (CMS)	339
11.1.12.1	Forward error correction for CMS.....	340
11.1.12.2	Code spreading for CMS	340
11.1.12.3	Scrambling for CMS.....	340
11.1.12.4	PHY preamble for CMS	341
11.1.12.5	Frame header for CMS	341
11.1.12.6	PHY header for CMS.....	342
11.1.12.7	PHY Payload field for CMS.....	343
11.1.12.8	Receiver clear channel assessment performance for CMS.....	343
11.1.13	mmWave PHY PIB	343
11.2	Single Carrier Mode of mmWave PHY.....	344
11.2.1	PHY operating specifications of SC PHY	345
11.2.1.1	Channelization	345

11.2.1.2	Scanning channels.....	345
11.2.2	Modulation, forward error correction, and spreading	345
11.2.2.1	MCS-dependent parameters.....	345
11.2.2.2	Header rate-dependent parameters.....	347
11.2.2.3	Timing-related parameters	348
11.2.2.4	Frame-related parameters	348
11.2.2.5	Modulation.....	349
11.2.2.5.1	p/2 BPSK	349
11.2.2.5.2	p/2 QPSK	349
11.2.2.5.3	p/2 8-PSK.....	350
11.2.2.5.4	p/2 16-QAM.....	351
11.2.2.6	FEC	351
11.2.2.6.1	Reed-Solomon block codes in GF(28).....	351
11.2.2.6.2	Irregular LDPC codes	352
11.2.2.6.3	Rate 14/15 LDPC code	353
11.2.2.7	Stuff bits.....	353
11.2.2.8	Code spreading	356
11.2.2.8.1	Golay sequences	356
11.2.2.8.2	PRBS generation with LFSR	356
11.2.2.9	Unequal error protection.....	357
11.2.2.10	Scrambling	358
11.2.3	SC PHY frame format	359
11.2.3.1	PHY preamble.....	360
11.2.3.1.1	Sync field	360
11.2.3.1.2	SFD field.....	360
11.2.3.1.3	Channel estimation sequence (CES).....	360
11.2.3.2	Frame header.....	360
11.2.3.2.1	SC PHY header	362
11.2.3.2.2	Base header HCS	363
11.2.3.2.3	Base header FEC.....	363
11.2.3.2.4	MAC subheader HCS	363
11.2.3.2.5	MAC subheader FEC.....	364
11.2.3.3	SC PHY Payload field	364
11.2.3.3.1	SC PHY Payload scrambling.....	364
11.2.3.3.2	Modulation.....	364
11.2.3.3.3	FEC	364
11.2.3.3.4	Code spreading	364
11.2.3.4	Pilot word and PCES	365
11.2.3.4.1	Subblocks and pilot word	365
11.2.3.4.2	Pilot channel estimation sequence (PCES).....	365
11.2.4	Transmitter specifications	366
11.2.4.1	Error vector magnitude	366
11.2.4.2	Transmit center frequency tolerance.....	366
11.2.4.3	Symbol rate.....	366
11.2.4.4	Transmit power-on and power-down ramp	366
11.2.5	Receiver specifications	366
11.2.5.1	Error rate criterion	366
11.2.5.2	Receiver sensitivity.....	367
11.2.5.3	Receiver maximum input level.....	367
11.2.5.4	Receiver clear channel assessment performance	367
11.2.6	PHY layer timing	368
11.2.6.1	Interframe space.....	368
11.2.6.2	Receive-to-transmit turnaround time	368
11.2.6.3	Transmit-to-receive turnaround-time.....	368

11.2.6.4	Time between successive transmissions	368
11.2.6.5	Channel switch.....	369
11.2.7	PHY management for SC PHY	369
11.2.7.1	Maximum frame size	369
11.2.7.2	Maximum transfer unit size	369
11.2.7.3	Minimum fragment size.....	369
11.2.8	Optional OOK/DAMI modes	369
11.2.8.1	OOK.....	369
11.2.8.2	DAMI.....	370
11.2.8.3	FEC	370
11.2.8.4	OOK/DAMI spreading	370
11.3	High Speed Interface mode of mmWave PHY	370
11.3.1	General operating specifications	370
11.3.1.1	Operating frequency bands	370
11.3.2	HSI PHY modulation, forward error correction, and spreading	370
11.3.2.1	MCS-dependent parameters.....	370
11.3.2.2	HSI PHY timing-related parameters.....	372
11.3.2.3	HSI PHY frame-related parameters	373
11.3.2.4	HSI PHY FEC.....	373
11.3.2.4.1	LDPC block code.....	374
11.3.2.4.2	EEP data multiplexer	374
11.3.2.4.3	UEP data multiplexer.....	374
11.3.2.4.4	Bit interleaver	375
11.3.2.5	Stuff bits.....	376
11.3.2.6	Constellation mapping	376
11.3.2.7	HSI spreader	378
11.3.2.7.1	Spreader for spreading factor of 1	379
11.3.2.7.2	Spreader for spreading factor of 48	379
11.3.2.8	Tone interleaver	379
11.3.2.9	HSI PHY OFDM modulator	380
11.3.2.9.1	Pilot subcarriers	381
11.3.2.9.2	Guard subcarriers.....	382
11.3.2.10	PCES insertion.....	382
11.3.2.11	HSI PHY scrambling	382
11.3.3	HSI PHY frame format	383
11.3.3.1	PHY preamble.....	383
11.3.3.2	Frame header.....	384
11.3.3.3	HSI PHY header	386
11.3.3.4	Header check sequences	387
11.3.3.4.1	Main Header HCS.....	387
11.3.3.4.2	MAC Subheader HCS.....	387
11.3.3.5	PHY Payload field	388
11.3.4	Transmitter specifications	388
11.3.4.1	EVM requirement	388
11.3.4.2	Chip rate and clock alignment	389
11.3.5	Receiver specifications	389
11.3.5.1	Receiver sensitivity.....	389
11.3.5.2	Receiver CCA performance.....	389
11.3.5.3	Receiver maximum input level.....	389
11.3.5.4	PHY layer timing	389
11.3.5.5	Interframe spacing	389
11.3.5.6	Receive-to-transmit turnaround time	390
11.3.5.7	Transmit-to-receive turnaround time	390
11.3.5.8	Time between successive transmissions	390

11.3.5.9	Channel switch time.....	390
11.3.6	HSI PHY management	390
11.3.6.1	PHY supported data rate encoding	390
11.3.6.2	HSI PHY fragment size encoding.....	390
11.3.6.3	Maximum frame length	391
11.3.6.4	Maximum transfer unit size	391
11.3.6.5	Minimum fragment size.....	391
11.4	Audio/Visual mode of mmWave PHY	391
11.4.1	General requirements	392
11.4.1.1	AV PHY channelization	392
11.4.1.2	PHY layer timing	393
11.4.1.2.1	Interframe space.....	393
11.4.1.2.2	Receive-to-transmit turnaround time.....	394
11.4.1.2.3	Transmit-to-receive turnaround time.....	394
11.4.1.2.4	Time between successive transmissions	394
11.4.1.2.5	Channel switch time.....	394
11.4.1.2.6	CCA detect time.....	394
11.4.1.3	Data size restrictions	394
11.4.1.3.1	Maximum frame length	394
11.4.1.3.2	Maximum transfer unit size	395
11.4.1.3.3	Minimum fragment size.....	395
11.4.1.4	Header check sequence	395
11.4.2	AV PHY modulation and forward error correction	395
11.4.2.1	AV PHY base rate.....	396
11.4.2.2	Repetition coding and spatial diversity.....	397
11.4.2.3	Stuff bits.....	397
11.4.2.4	HRP splitter and scrambler	398
11.4.2.5	LRP scrambler	398
11.4.2.6	HRP outer code	399
11.4.2.7	HRP outer interleaver	399
11.4.2.8	Convolutional encoder	400
11.4.2.9	Puncturing.....	400
11.4.2.10	HRP data multiplexer and bit interleaver	400
11.4.2.10.1	EEP data multiplexer	401
11.4.2.10.2	UEP coding data multiplexer	402
11.4.2.10.3	UEP mapping data multiplexer	404
11.4.2.10.4	HRP header data multiplexer	405
11.4.2.11	Bit reversal tone interleaver	406
11.4.2.12	Signal constellations	406
11.4.2.13	AV PHY non-data subcarriers	407
11.4.2.14	AV PHY OFDM modulation	408
11.4.3	AV PHY frame formats	409
11.4.3.1	HRP preamble.....	410
11.4.3.2	HRP header	411
11.4.3.3	LRP preamble sequences	411
11.4.3.4	Long omni LRP preamble.....	412
11.4.3.5	Short omni LRP preamble	413
11.4.3.6	Omni LRP header	414
11.4.3.7	Directional LRP preamble	414
11.4.3.8	Directional LRP header and payload	415
11.4.4	AV PHY transmitter requirements	416
11.4.4.1	TX mask.....	416
11.4.4.2	EVM requirement	417
11.4.4.3	Symbol timing.....	417

11.4.4.4	TX frequency accuracy	418
11.4.4.5	TX power ramp on and off	418
11.4.5	AV PHY Receiver characteristics	418
11.4.5.1	Error rate criterion	418
11.4.5.2	Sensitivity	418
11.4.5.3	Maximum input level	418
11.4.6	Preambles and training symbols	418
12.	Beam forming	423
12.1	Introduction	423
12.2	Beam forming terminology	423
12.2.1	Quasi-omni patterns	424
12.2.2	Sectors	424
12.2.3	Beams	425
12.2.4	Clusters	426
12.3	Beam forming codebooks	427
12.3.1	Beam forming codebooks	428
12.4	Beam forming reference model	429
12.5	Beam forming protocol	431
12.5.1	Two-level training mechanism	431
12.5.1.1	Sector-level training	431
12.5.1.1.1	AAS sector-level training	431
12.5.1.1.2	SAS sector-level training	434
12.5.1.1.3	Sector-level training failure remedy	437
12.5.1.2	Beam-level training	437
12.5.1.2.1	AAS beam-level training	437
12.5.1.2.2	SAS beam-level training	440
12.5.2	Beam tracking	443
12.6	On-demand beam forming	445
12.7	Proactive beam forming	445
12.8	TSD	445
Annex A	(informative) Bibliography	447
Annex B	(normative) Frame convergence sublayer	448
B.1	Generic convergence sublayer	448
B.2	EPD FCSL PDU classification	449
B.3	EPD FCSL	449
B.3.1	EPD FCSL QoS support	450
B.3.2	Data entity inter-relationships	450
B.4	EPD FCSL SAP	451
B.4.1	MA-UNITDATA.request	452
B.4.2	MA-UNITDATA.indication	452
B.4.3	MA-UNITDATA-STATUS.indication	453
B.5	Stream SAP	454
B.5.1	Stream creation, modification, and deletion	454
B.5.1.1	STREAM_INITIATE.request	456
B.5.1.2	STREAM_INITIATE.confirm	456
B.5.1.3	STREAM_INITIATE.indication	456
B.5.1.4	STREAM_MODIFY.request	457
B.5.1.5	STREAM_MODIFY.confirm	457
B.5.1.6	STREAM_END.request	457

B.5.1.7	STREAM_END.confirm.....	458
B.5.1.8	STREAM_END.indication.....	458
B.5.2	Stream data interface.....	458
B.5.2.1	STREAM_DATA.request.....	459
B.5.2.2	STREAM_DATA.confirm.....	460
B.5.2.3	STREAM_DATA.indication.....	460
Annex C (informative) Security considerations.....		461
C.1	Background assumptions.....	461
C.1.1	Physical assumptions.....	461
C.1.2	Network assumptions.....	461
C.1.3	Attack model assumptions.....	462
C.1.4	Security key lifecycle issues.....	462
C.1.4.1	Key lifecycle.....	462
C.1.4.2	Membership lifecycle.....	462
C.1.4.3	Group membership change rekey.....	462
C.2	Claimed security services.....	462
C.2.1	Beacon protection protocol.....	462
C.2.2	Distribute key protocol.....	463
C.2.3	Key request protocol.....	463
C.2.4	Data protection protocol.....	464
C.3	Properties of the IEEE 802.15.3 security suite.....	464
C.3.1	Key usage.....	464
C.3.2	Replay prevention.....	464
Annex D (informative) Coexistence, interoperability, and interference.....		466
D.1	Interoperability.....	466
D.1.1	Interoperability with IEEE 802.11 DSSS and IEEE 802.11b.....	466
D.1.2	IEEE 802.11 FHSS and IEEE 802.15.1.....	467
D.2	Coexistence.....	467
D.2.1	Coexistence with IEEE Std 802.11b.....	467
D.2.1.1	Passive scanning.....	468
D.2.1.2	Dynamic channel selection.....	468
D.2.1.3	The ability to request channel quality information.....	468
D.2.1.4	Link quality and RSSI.....	468
D.2.1.5	Channel plan that minimizes channel overlap.....	468
D.2.1.6	Lower transmit power.....	469
D.2.1.7	Transmit power control.....	469
D.2.1.8	Neighbor piconet capability.....	469
D.2.2	Coexistence with IEEE 802.15.1 and IEEE 802.11 FHSS.....	470
D.2.2.1	PHY collaborative coexistence enhancements.....	470
D.2.2.2	MAC coexistence via collaboration.....	470
D.2.2.3	Other techniques.....	471
D.3	Coexistence performance.....	471
D.3.1	Allowed operation.....	471
D.3.2	Assumptions for coexistence calculations.....	471
D.3.3	Performance impact on IEEE 802.15.3 piconets.....	473
D.3.3.1	IEEE 802.11b overlapping with IEEE 802.15.3.....	473
D.3.3.2	IEEE 802.15.1 and IEEE 802.11 FHSS overlapping with IEEE 802.15.3.....	476
D.4	Notes on the calculations.....	477

Annex E (normative) Protocol implementation conformance statement (PICS) proforma.....	478
E.1 Introduction.....	478
E.1.1 Scope.....	478
E.1.2 Purpose.....	478
E.2 Abbreviations and special symbols.....	478
E.3 Instructions for completing the PICS proforma.....	479
E.4 Identification of the implementation.....	479
E.5 Identification of the protocol	480
E.6 Global statement of conformance	481
E.7 PICS proforma—IEEE Std 802.15.3-2016.....	481
E.7.1 Major roles for IEEE 802.15.3 DEVs.....	481
E.7.2 PHY functions.....	482
E.7.3 Major capabilities for the MAC sublayer	483
E.7.3.1 MAC frames	483
E.7.3.2 MAC sublayer functions	486
E.7.4 Security support	490
Annex F (informative) Implementation considerations.....	491
F.1 Channel time requests.....	491
F.1.1 Types of CTAs.....	491
F.1.2 Interpretation of channel time requests.....	492
F.1.3 Determining CTA Rate Factor from stream requirements	493
F.1.3.1 Example 1.....	494
F.1.3.2 Example 2.....	495
F.1.4 PNC interpretation of CTA rate factor	495
F.1.5 Creating channel time requests from MLME requests	496
F.1.6 Interpreting channel time requests.....	498
F.2 Sample frames.....	500
F.3 Use of multiple mmWave PHYs in a single piconet	502
Annex G (normative) Optional OOK/DAMI modes	504
G.1 Introduction.....	504
G.2 Child piconet operation.....	504
G.3 DAMI.....	504
G.4 PHY preamble.....	506
G.5 PHY frame format	507
G.6 Interframe space.....	507
G.7 Eye opening for OOK	508
G.8 EVM for DAMI	508