

ISO/IEC 14443-4:2018 (E)

Cards and security devices for personal identification — Contactless proximity objects — Part 4: Transmission protocol

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols, abbreviated terms and notation |
| 4.1 | Symbols and abbreviated terms |
| 4.2 | Notations |
| 5 | Protocol activation of PICC Type A |
| 5.1 | Activation sequences |
| 5.2 | Request for answer to select |
| 5.3 | Answer to select |
| 5.3.1 | Structure of the bytes |
| 5.3.2 | Length byte |
| 5.3.3 | Format byte |
| 5.3.4 | Interface byte TA(1) |
| 5.3.5 | Interface byte TB(1) |
| 5.3.6 | Interface byte TC(1) |
| 5.3.7 | Historical bytes |
| 5.4 | Protocol and parameter selection request |
| 5.4.1 | Start byte |
| 5.4.2 | Parameter 0 |
| 5.4.3 | Parameter 1 |
| 5.5 | Protocol and parameter selection response |
| 5.6 | Activation frame waiting time |
| 5.7 | Error detection and recovery |
| 5.7.1 | Handling of RATS and ATS |
| 5.7.1.1 | PCD rules |
| 5.7.1.2 | PICC rules |
| 5.7.2 | Handling of PPS request and PPS response |
| 5.7.2.1 | PCD rules |
| 5.7.2.2 | PICC rules |
| 5.7.3 | Handling of the CID during activation |
| 6 | Protocol activation of PICC Type B |
| 7 | Half-duplex block transmission protocol |
| 7.1 | Elements and mechanisms |
| 7.2 | Block format |
| 7.2.1 | Length field |
| 7.2.2 | Prologue field |
| 7.2.2.1 | Protocol control byte field |
| 7.2.2.2 | Card identifier field |
| 7.2.2.3 | Node address field |
| 7.2.3 | Information field |
| 7.2.4 | Epilogue field |
| 7.3 | Frame waiting time |

| | |
|---------|--|
| 7.4 | Frame waiting time extension |
| 7.5 | Power level indication |
| 7.6 | Protocol operation |
| 7.6.1 | S(PARAMETERS) blocks |
| 7.6.2 | Multi-Activation |
| 7.6.3 | Chaining |
| 7.6.4 | Block numbering rules |
| 7.6.4.1 | PCD rules |
| 7.6.4.2 | PICC rules |
| 7.6.5 | Block handling rules |
| 7.6.5.1 | General rules |
| 7.6.5.2 | PCD rules |
| 7.6.5.3 | PICC rules |
| 7.6.6 | PICC presence check |
| 7.6.6.1 | Method 1 |
| 7.6.6.2 | Method 2 |
| 7.6.7 | Error detection and recovery |
| 7.6.7.1 | Errors detected by the PCD |
| 7.6.7.2 | Errors detected by the PICC |
| 8 | Protocol deactivation of PICC Type A and Type B |
| 8.1 | Deactivation frame waiting time |
| 8.2 | Error detection and recovery |
| 9 | Activation of bit rates and framing options in PROTOCOL state |
| 10 | Frame with error correction |
| 10.1 | General |
| 10.2 | Type A PCD frame format for bit rates up to $fc/16$ and higher than $fc/2$ and Type A PICC frame format for all bit rates |
| 10.3 | Type A PCD frame format for bit rates of $fc/8$, $fc/4$ and $fc/2$ and Type B PCD and PICC frame format for all bit rates |
| 10.4 | Enhanced block with error correction |
| 10.4.1 | General |
| 10.4.2 | Modified Hamming sub-block format |
| 10.4.3 | Hamming control byte |
| 10.4.4 | Hamming control generation matrix A |
| 10.4.5 | Hamming control bits calculation |
| 10.4.6 | Hamming control check matrix H |
| 10.4.7 | Error correction |
| 10.5 | Activation of frame with error correction in PROTOCOL state |
| Annex A | (informative) Multi-Activation example |
| Annex B | (informative) Protocol scenarios |
| B.1 | General |
| B.2 | Notation |
| B.3 | Error-free operation |
| B.3.1 | Exchange of I-blocks |
| B.3.2 | Request for waiting time extension |
| B.3.3 | DESELECT |
| B.3.4 | Chaining |
| B.3.5 | PICC Presence check |
| B.3.6 | Exchange of additional parameters |
| B.4 | Error handling |
| B.4.1 | Exchange of I-blocks |
| B.4.2 | Request for waiting time extension |
| B.4.3 | DESELECT |
| B.4.4 | Chaining |
| Annex C | (informative) Block and frame coding overview |
| Annex D | (deliberately left blank) |

Annex E (informative) CRC_32 encoding

E.1 CRC_32 encoding

E.2 Code sample written in ANSI C language for CRC_32 calculation

Annex F (informative) Frame with error correction

F.1 Example

F.2 Code sample written in ANSI C language for Hamming control byte calculation

Annex G (informative) Framing options

Page count: 55