

# ISO/IEC TR 23008-15:2018-08 (E)

## Information technology - High efficiency coding and media delivery in heterogeneous environments - Part 15: Signalling, backward compatibility and display adaptation for HDR/WCG video

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Abbreviated terms .....</b>	<b>3</b>
<b>5</b>	<b>Conventions .....</b>	<b>4</b>
5.1	General .....	4
5.2	Arithmetic operators .....	5
5.3	Bit-wise operators .....	5
5.4	Assignment operators .....	6
5.5	Relational, logical and other operators .....	6
5.6	Mathematical functions .....	6
5.7	Order of operations .....	7
<b>6</b>	<b>Overview .....</b>	<b>8</b>
<b>7</b>	<b>HEVC signalling mechanisms applicable to HDR/WCG video .....</b>	<b>9</b>
7.1	General .....	9
7.2	VUI syntax elements .....	9
7.3	SEI messages applicable for HDR/WCG video .....	10
7.3.1	General .....	10
7.3.2	Mastering display colour volume SEI message .....	10
7.3.3	Content light level information SEI message .....	11
7.3.4	Ambient viewing environment SEI message .....	11
7.3.5	Alternative transfer characteristics SEI message .....	11
7.3.6	Tone mapping information SEI message .....	11
7.3.7	Colour remapping information SEI message .....	12
7.4	Overview of PQ and HLG transfer functions .....	13
7.4.1	General .....	13
7.4.2	Reference PQ EOTF .....	14
7.4.3	Reference HLG OETF .....	15
7.5	ICTCP colour representation .....	16
7.5.1	General .....	16
7.5.2	Pre-encoding process .....	17
7.5.3	Encoding process .....	20
7.5.4	Decoding process .....	22
7.5.5	Post-decoding process .....	22
<b>8</b>	<b>Bitstream SDR backward compatibility with single-layer coding .....</b>	<b>24</b>
8.1	General .....	24
8.2	Approach 1: usage of HLG for "static" bitstream SDR backward compatibility .....	24
8.2.1	General .....	24

8.2.2	HLG pre-encoding conversion process .....	25
8.2.3	Encoding process .....	27
8.2.4	Decoding process .....	29
8.2.5	HLG post-decoding conversion .....	29
8.2.6	Colour representation conversion: YCbCr to RGB .....	30
8.3	Approach 2: usage of SEI messages for "dynamic" bitstream SDR backward compatibility .....	30
8.3.1	General .....	30
8.3.2	CRI applied in YCbCr 4:2:0 domain .....	31
8.3.3	CRI applied in YCbCr 4:4:4 domain .....	32
8.3.4	TMI applied in RGB 4:4:4 domain .....	33
8.3.5	Derivation of DRA functions .....	34
8.3.6	Settings with colour remapping information SEI message .....	35
8.3.7	Settings with tone mapping information SEI message .....	36
9	Bitstream SDR backward compatibility with dual-layer SHVC coding .....	37
9.1	General .....	37
9.2	Encoding and decoding stages .....	37
10	Display adaptation .....	39
10.1	General .....	39
10.2	Display SDR backward compatibility .....	39
10.2.1	Conversion and coding process example .....	39
10.2.2	Using colour remapping information SEI message .....	41
	Bibliography .....	43