

ISO/IEC 7811-7:2018 (E)

Identification cards — Recording technique — Part 7: Magnetic stripe: High coercivity, high density

Contents

	Foreword
1	Scope
2	Normative references
3	Terms, definitions, symbols and abbreviated terms
3.1	Terms and definitions
3.2	Symbols and abbreviated terms
4	Conformance
5	Physical characteristics of the identification card
5.1	General
5.2	Magnetic stripe area warpage
5.3	Surface distortions
6	Physical characteristics of the magnetic stripe
6.1	Height and surface profile of the magnetic stripe area
6.1.1	Surface profile of the magnetic stripe area
6.1.2	Height of the magnetic stripe area
6.2	Surface roughness
6.3	Adhesion of stripe to card
6.4	Wear of magnetic stripe from read/write head
6.5	Resistance to chemicals
7	Performance characteristics for the magnetic material
7.1	General
7.2	Testing and operating environment
7.3	Signal amplitude requirements for magnetic media
8	Data structure
9	Encoding specification
9.1	Angle of recording
9.2	Nominal bit density
9.3	Flux transition spacing variation
9.4	Signal amplitude requirements
9.5	Bit configuration
9.6	Direction of recording
9.7	Leading and trailing clock bits
10	Data structure
10.1	Track format
10.1.1	Track layout
10.1.2	FSC
10.1.3	Data frame
10.1.3.1	Frame identifier
10.1.3.2	Data
10.1.3.3	Frame CRC character
10.2	Coding for error detection and correction
10.2.1	Track CRC
10.2.2	Column parity

10.2.3 Frame CRC

11 Decoding

12 Location of encoded tracks

Annex A (informative) Compatibility of magnetic stripes (ISO/IEC 7811-6, ISO/IEC 7811-7)

Annex B (informative) Magnetic stripe abrasivity

Annex C (informative) Static magnetic characteristics

C.1 Introduction

C.2 Terms and definitions

C.3 Recommended characteristics

Annex D (informative) Reed-Solomon code references

Page count: 24