

ISO/IEC 28360-2:2018 (E)

Information technology — Office equipment — Determination of chemical emission rates from electronic equipment — Part 2: Not using-consumables

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols and abbreviated terms |
| 4.1 | Abbreviated terms |
| 4.2 | Symbols |
| 5 | Conformance |
| 6 | Method overview |
| 7 | ETC requirements |
| 7.1 | Construction materials |
| 7.2 | Air tightness |
| 7.3 | Air mixing efficiency |
| 8 | Determination method |
| 8.1 | Test conditions |
| 8.1.1 | General |
| 8.1.2 | Operating temperature and relative humidity (RH) |
| 8.1.3 | Air exchange rate (n) |
| 8.1.4 | Air velocity |
| 8.1.5 | Sampled air flow |
| 8.2 | Handling of EUT and ETC |
| 8.2.1 | Selection and storage of EUT |
| 8.2.2 | Loading Factor |
| 8.2.3 | ETC purging |
| 8.2.4 | Background concentrations (C _{bg}) |
| 8.2.5 | EUT unpacking |
| 8.2.6 | Preparation of the EUT before testing |
| 8.2.7 | EUT installation |
| 8.2.8 | EUT operation during test |
| 8.2.8.1 | General |
| 8.2.8.2 | Recording of EUT operation |
| 8.3 | VOC, carbonyl compounds |
| 8.3.1 | Sorbents |
| 8.3.2 | Sample collection |
| 8.3.3 | Emission rate calculation |
| 8.4 | Ozone |
| 8.4.1 | Analyser and sampling line requirements |
| 8.4.2 | Monitoring |
| 8.4.3 | Emission rate calculation |
| 9 | Test report |