

ISO/IEC 24770-5:2019 (E)

Information technology — Real-time locating system (RTLS) device performance test methods — Part 5: Test methods for chirp spread spectrum (CSS) air interface

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms, definitions, and abbreviated terms
3.1	Terms and definitions
3.2	Abbreviated terms
4	General
4.1	Performance requirements
4.1.1	Overview
4.1.2	Location accuracy
4.1.3	Tag capacity
4.1.4	Location latency
4.1.5	Tag orientation
4.1.6	System range and packet error rates
4.2	Default conditions applicable to the test methods
4.2.1	Overview
4.2.2	Test environment
4.2.3	Default tolerance
4.2.4	System logging
5	Performance tests for ISO/IEC 24730-5
5.1	System locate performance
5.1.1	Test overview
5.1.2	Test objective
5.1.3	Test setup
5.1.4	Test procedure
5.1.5	Test measurements and requirements
5.1.5.1	Location accuracy
5.1.5.2	Location reporting latency
5.1.5.3	Tag capacity
5.1.5.4	Tag orientation
5.1.6	Test report
5.2	Tests for CSS tag to reader air interface using default blink mode
5.2.1	Test objective
5.2.2	Test setup
5.2.3	Test procedure
5.2.4	Test measurements and requirements
5.2.4.1	Packet error rate
5.2.4.2	Tag range
5.2.4.3	Tag orientation
5.2.5	Test report
5.3	Tests for CSS tag to reader air interface using two-way-ranging
5.3.1	Overview
5.3.2	Test objective
5.3.3	Test setup
5.3.4	Test procedure

- 5.3.5 Test measurements and requirements**
- 5.3.5.1 Ranging success rate**
- 5.3.5.2 Ranging range**
- 5.3.5.3 Ranging accuracy**
- 5.3.5.4 Orientation**

Page count: 9