

ISO/IEC 30193:2020-03 (E)

Information technology - Digitally recorded media for information interchange and storage - 120 mm Triple Layer (100,0 Gbytes per disk) BD Rewritable disk

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | ix |
| Introduction | | x |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and abbreviated terms | 6 |
| 5 | Conformance | 9 |
| 5.1 | Optical disk | 9 |
| 5.2 | Generating system | 9 |
| 5.3 | Receiving system | 9 |
| 5.4 | Compatibility statement | 9 |
| 6 | Conventions and notations | 9 |
| 6.1 | Levels of grouping | 9 |
| 6.2 | Representation of numbers | 10 |
| 6.3 | Integer calculus | 11 |
| 7 | General description of disk | 11 |
| 8 | General requirements | 12 |
| 8.1 | Environments | 12 |
| 8.1.1 | Test environment | 12 |
| 8.1.2 | Operating environment | 13 |
| 8.1.3 | Storage environment | 14 |
| 8.1.4 | Transportation | 15 |
| 8.2 | Safety requirements | 15 |
| 8.3 | Flammability | 16 |
| 9 | Reference drive | 16 |
| 9.1 | General | 16 |
| 9.2 | Measurement conditions | 16 |
| 9.3 | Optical system | 16 |
| 9.4 | Optical beam | 17 |
| 9.5 | HF read channel | 18 |
| 9.6 | Radial PP read channel | 18 |
| 9.7 | Disk clamping | 18 |
| 9.8 | Rotation of disk and measurement velocity | 19 |
| 9.9 | Normalized servo transfer function | 19 |
| 9.10 | Measurement velocities and reference servos for axial tracking | 20 |
| 9.10.1 | General | 20 |
| 9.10.2 | Reference servo for axial tracking for 1x measurement velocity | 20 |
| 9.10.3 | reference servo for axial tracking for 2x measurement velocity | 21 |
| 9.11 | Measurement velocities and reference servos for radial tracking | 22 |
| 9.11.1 | General | 22 |
| 9.11.2 | Reference servo for radial tracking for 1x measurement velocity | 22 |

| | | |
|--------|---|----|
| 9.11.3 | Reference servo for radial tracking for 2x measurement velocity | 24 |
| 10 | Dimensional characteristics | 25 |
| 10.1 | General | 25 |
| 10.2 | Disk reference planes and reference axis | 25 |
| 10.3 | Overall dimensions | 27 |
| 10.4 | First transition area | 27 |
| 10.5 | Protection ring | 27 |
| 10.6 | Clamping zone | 27 |
| 10.7 | Second transition area | 28 |
| 10.8 | Information area | 28 |
| 10.8.1 | General | 28 |
| 10.8.2 | Subdivision of information zone on TL disk | 29 |
| 10.9 | Rim area | 30 |
| 11 | Mechanical characteristics | 30 |
| 11.1 | Mass | 30 |
| 11.2 | Moment of inertia | 30 |
| 11.3 | Dynamic imbalance | 30 |
| 11.4 | Axial runout | 30 |
| 11.4.1 | General | 30 |
| 11.4.2 | Residual axial tracking error for 1x measurement velocity | 31 |
| 11.4.3 | Residual axial tracking error for 2x measurement velocity | 31 |
| 11.5 | Radial runout | 31 |
| 11.5.1 | General | 31 |
| 11.5.2 | Residual radial tracking error for 1x measurement velocity | 32 |
| 11.5.3 | Residual radial tracking error for 2x measurement velocity | 32 |
| 11.6 | Durability of cover layer | 32 |
| 11.6.1 | Impact resistance of cover layer | 32 |
| 11.6.2 | Scratch resistance of cover layer | 33 |
| 11.6.3 | Repulsion of fingerprints by cover layer | 33 |
| 12 | Optical characteristics in information area | 33 |
| 12.1 | General | 33 |
| 12.2 | Refractive index of transmission stacks (TS) | 33 |
| 12.3 | Thickness of transmission stacks (TS) | 33 |
| 12.4 | Example of target thickness of spacer layers for TL disks | 34 |
| 12.5 | Reflectivity of recording layers | 35 |
| 12.6 | Birefringence | 36 |
| 12.7 | Angular deviation | 36 |
| 13 | Data format | 37 |
| 13.1 | General | 37 |
| 13.2 | Data frame | 40 |
| 13.3 | Error-detection code (EDC) | 40 |
| 13.4 | Scrambled data frame | 41 |
| 13.5 | Data block | 42 |
| 13.6 | LDC block | 42 |
| 13.7 | LDC code-words | 43 |
| 13.8 | LDC cluster | 44 |
| 13.8.1 | General | 44 |
| 13.8.2 | First interleaving step | 44 |
| 13.8.3 | Second interleaving step | 44 |
| 13.9 | Addressing and control data | 46 |
| 13.9.1 | General | 46 |
| 13.9.2 | Address units | 46 |
| 13.9.3 | User-control data | 51 |
| 13.9.4 | Byte/Bit assignment for user-control data | 52 |
| 13.10 | Access block | 54 |
| 13.11 | BIS block | 54 |
| 13.12 | BIS code-words | 55 |

| | | |
|---------|---|-----|
| 13.13 | BIS cluster | 56 |
| 13.14 | ECC cluster | 59 |
| 13.15 | Recording frames | 60 |
| 13.16 | Physical cluster | 61 |
| 13.17 | 17PP modulation for recordable data | 61 |
| 13.17.1 | General | 61 |
| 13.17.2 | Bit conversion rules | 61 |
| 13.17.3 | dc-control procedure | 62 |
| 13.17.4 | Frame sync | 62 |
| 13.18 | Modulation and NRZI conversion | 64 |
| 14 | Physical data allocating and linking | 64 |
| 14.1 | General | 64 |
| 14.2 | Recording-unit block (RUB) | 64 |
| 14.2.1 | General | 64 |
| 14.2.2 | Data run-in | 65 |
| 14.2.3 | Data run-out | 66 |
| 14.2.4 | Guard_3 field | 67 |
| 14.3 | Locating data relative to wobble addresses | 67 |
| 14.3.1 | General | 67 |
| 14.3.2 | Start-position shift (SPS) | 67 |
| 15 | Track format | 69 |
| 15.1 | General | 69 |
| 15.2 | Track shape | 69 |
| 15.3 | Track path | 71 |
| 15.4 | Track pitch | 71 |
| 15.4.1 | Track pitch in BCA zone | 71 |
| 15.4.2 | Track pitch in embossed HFM areas | 71 |
| 15.4.3 | Track pitch in rewritable areas | 71 |
| 15.4.4 | Track pitch between embossed HFM area and rewritable area | 72 |
| 15.5 | Track layout of HFM grooves | 72 |
| 15.5.1 | General | 72 |
| 15.5.2 | Data format | 72 |
| 15.5.3 | Addressing and control data | 73 |
| 15.5.4 | Recording frames | 76 |
| 15.6 | Track layout of wobbled grooves | 78 |
| 15.6.1 | General | 78 |
| 15.6.2 | Modulation of wobbles | 79 |
| 15.6.3 | Wobble polarity | 80 |
| 15.7 | ADIP information | 80 |
| 15.7.1 | General | 80 |
| 15.7.2 | ADIP-unit types | 81 |
| 15.7.3 | ADIP word structure | 82 |
| 15.7.4 | ADIP data structure | 83 |
| 15.7.5 | ADIP error correction | 86 |
| 15.8 | Disk information in ADIP aux frame | 88 |
| 15.8.1 | General | 88 |
| 15.8.2 | Error protection for disk information aux frames | 89 |
| 15.8.3 | Disk-Information data structure | 90 |
| 16 | General description of information zone | 139 |
| 16.1 | General | 139 |
| 16.2 | Format of information zone | 140 |
| 17 | Layout of rewritable area of information zone | 140 |
| 18 | Inner zone | 144 |
| 18.1 | General | 144 |
| 18.2 | Permanent information and control data (PIC) zone | 148 |
| 18.2.1 | General | 148 |
| 18.2.2 | Content of PIC zone | 148 |

| | | |
|---------|--|-----|
| 18.2.3 | Emergency brake | 149 |
| 18.3 | Rewritable area of inner zone(s) | 151 |
| 18.3.1 | Protection-zone 2 | 151 |
| 18.3.2 | Buffer | 151 |
| 18.3.3 | INFO 2/Reserved 8 | 151 |
| 18.3.4 | INFO 2/Reserved 7 | 152 |
| 18.3.5 | INFO 2/Reserved 6 | 152 |
| 18.3.6 | INFO 2/Reserved 5 | 152 |
| 18.3.7 | INFO 2/PAC 2 | 152 |
| 18.3.8 | INFO 2/Reserved | 152 |
| 18.3.9 | INFO 2/DMA 2 | 152 |
| 18.3.10 | INFO 2/Control data 2 | 152 |
| 18.3.11 | INFO 2/Buffer 2 | 152 |
| 18.3.12 | OPC/Test zone | 153 |
| 18.3.13 | Reserved | 153 |
| 18.3.14 | INFO 1/Buffer 1 | 153 |
| 18.3.15 | INFO 1/Drive area (optional) | 153 |
| 18.3.16 | INFO 1/Reserved 3 | 154 |
| 18.3.17 | INFO 1/Reserved 2 | 154 |
| 18.3.18 | INFO 1/Reserved 1 | 154 |
| 18.3.19 | INFO 1/DMA 1 | 154 |
| 18.3.20 | INFO 1/Control Data 1 | 154 |
| 18.3.21 | INFO 1/PAC 1 | 154 |
| 18.3.22 | INFO 1/Reserved | 154 |
| 19 | Data zone | 155 |
| 20 | Outer zone(s) | 155 |
| 20.1 | General | 155 |
| 20.2 | INFO 3/Buffer 3 | 155 |
| 20.3 | INFO 3/DMA 3 | 156 |
| 20.4 | INFO 3/Control data 3 | 156 |
| 20.5 | Angular buffer | 156 |
| 20.6 | INFO 4/DMA 4 | 156 |
| 20.7 | INFO 4/Control data 4 | 156 |
| 20.8 | INFO 4/Buffer 4 | 156 |
| 20.9 | DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone | 156 |
| 20.10 | Protection-zone 3 | 156 |
| 21 | Physical-access control clusters | 156 |
| 21.1 | General | 156 |
| 21.2 | Layout of PAC zones | 157 |
| 21.3 | General structure of PAC clusters | 157 |
| 21.4 | Primary PAC cluster (mandatory) | 162 |
| 21.5 | Disk write-protect PAC cluster (optional) | 165 |
| 21.6 | IS1 and IS2 PAC clusters | 169 |
| 22 | Disk management | 170 |
| 22.1 | General | 170 |
| 22.2 | Disk-management structure (DMS) | 171 |
| 22.2.1 | General | 171 |
| 22.2.2 | Disk-definition structure (DDS) | 172 |
| 22.2.3 | Defect list (DFL) | 176 |
| 23 | Assignment of logical-sector numbers (LSNs) | 181 |
| 24 | Characteristics of grooved areas | 182 |
| 25 | Method of testing for grooved area | 182 |
| 25.1 | General | 182 |
| 25.2 | Environment | 182 |
| 25.3 | Reference drive | 182 |

| | | |
|--------|---|-----|
| 25.3.1 | General | 182 |
| 25.3.2 | Read power | 182 |
| 25.3.3 | Read channels | 182 |
| 25.3.4 | Tracking requirements | 183 |
| 25.3.5 | Scanning velocities | 183 |
| 25.4 | Definition of signals | 183 |
| 26 | Signals from HFM grooves | 184 |
| 26.1 | Push-pull polarity | 184 |
| 26.2 | Push-pull signal | 184 |
| 26.3 | Wobble signal | 185 |
| 26.4 | Jitter of HFM signal | 185 |
| 27 | Signals from wobbled grooves | 185 |
| 27.1 | Phase depth | 185 |
| 27.2 | Push-pull signal | 185 |
| 27.3 | Wobble signal | 186 |
| 27.3.1 | General | 186 |
| 27.3.2 | Measurement of NWS | 186 |
| 27.3.3 | Measurement of the wobble CNR | 186 |
| 27.3.4 | Measurement of harmonic distortion of wobble | 186 |
| 28 | Characteristics of recording layer | 187 |
| 29 | Method of testing for recording layer | 187 |
| 29.1 | General | 187 |
| 29.2 | Environment | 187 |
| 29.3 | Reference drive | 187 |
| 29.3.1 | General | 187 |
| 29.3.2 | Read power | 187 |
| 29.3.3 | Read channels | 187 |
| 29.3.4 | Tracking requirements | 187 |
| 29.3.5 | Scanning velocities | 188 |
| 29.4 | Write conditions | 188 |
| 29.4.1 | Write-pulse waveform | 188 |
| 29.4.2 | Write powers | 188 |
| 29.4.3 | Average power | 189 |
| 29.4.4 | Write conditions for i-MLSE measurement | 189 |
| 29.4.5 | Write conditions for cross-erase measurements | 189 |
| 29.5 | Definition of signals | 189 |
| 30 | Signals from recorded areas | 189 |
| 30.1 | HF signals | 189 |
| 30.2 | Modulated amplitude | 189 |
| 30.3 | Reflectivity-modulation product | 191 |
| 30.4 | Asymmetry | 191 |
| 30.5 | i-MLSE@DOW(n) | 191 |
| 30.6 | Cross-erase @ DOW(n)XE | 191 |
| 30.7 | Read stability | 192 |
| 31 | Local defects | 193 |
| 32 | Characteristics of user data | 193 |
| 33 | Method of testing for user data | 193 |
| 33.1 | General | 193 |
| 33.2 | Environment | 193 |
| 33.3 | Reference drive | 193 |
| 33.3.1 | General | 193 |
| 33.3.2 | Read power | 193 |
| 33.3.3 | Read channels | 193 |
| 33.3.4 | Error correction | 194 |

| | | |
|--|---|-----|
| 33.3.5 | Tracking requirements | 194 |
| 33.3.6 | Scanning velocities | 194 |
| 33.4 | Definition of signals | 194 |
| 34 | Minimum quality of recorded information | 195 |
| 34.1 | General | 195 |
| 34.2 | Random symbol error rate | 195 |
| 34.3 | Maximum burst errors | 195 |
| 34.4 | User-written data | 195 |
| 35 | Burst-cutting area (BCA) | 195 |
| Annex A (normative) Thickness of transmission stacks in case of multiple layers | | 197 |
| Annex B (normative) Measurement of reflectivity | | 200 |
| Annex C (normative) Measurement of scratch resistance of cover layer | | 206 |
| Annex D (normative) Measurement of repulsion of grime by cover layer | | 208 |
| Annex E (normative) Measurement of wobble amplitude | | 211 |
| Annex F (normative) Write-pulse waveform for testing | | 216 |
| Annex G (normative) Optimum power control (OPC) procedure for disk | | 223 |
| Annex H (normative) HF signal pre-processing for integrated-maximum likelihood sequence error estimation (i-MLSE) measurements | | 226 |
| Annex I (normative) Measurement procedures | | 238 |
| Annex J (informative) Measurement of birefringence | | 250 |
| Annex K (informative) Measurement of thickness of cover layer and spacer layer | | 253 |
| Annex L (informative) Measurement of impact resistance of cover layer | | 256 |
| Annex M (informative) Groove deviation and wobble amplitude | | 258 |
| Annex N (informative) Guidelines for write pulse adjustment using L-SEAT edge-shift | | 260 |
| Bibliography | | 269 |