

ISO/IEC 30193:2020-03 (E)

Information technology - Digitally recorded media for information interchange and storage - 120 mm Triple Layer (100,0 Gbytes per disk) BD Rewritable disk

Contents		Page
Foreword		ix
Introduction		x
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	6
5	Conformance	9
5.1	Optical disk	9
5.2	Generating system	9
5.3	Receiving system	9
5.4	Compatibility statement	9
6	Conventions and notations	9
6.1	Levels of grouping	9
6.2	Representation of numbers	10
6.3	Integer calculus	11
7	General description of disk	11
8	General requirements	12
8.1	Environments	12
8.1.1	Test environment	12
8.1.2	Operating environment	13
8.1.3	Storage environment	14
8.1.4	Transportation	15
8.2	Safety requirements	15
8.3	Flammability	16
9	Reference drive	16
9.1	General	16
9.2	Measurement conditions	16
9.3	Optical system	16
9.4	Optical beam	17
9.5	HF read channel	18
9.6	Radial PP read channel	18
9.7	Disk clamping	18
9.8	Rotation of disk and measurement velocity	19
9.9	Normalized servo transfer function	19
9.10	Measurement velocities and reference servos for axial tracking	20
9.10.1	General	20
9.10.2	Reference servo for axial tracking for 1x measurement velocity	20
9.10.3	reference servo for axial tracking for 2x measurement velocity	21
9.11	Measurement velocities and reference servos for radial tracking	22
9.11.1	General	22
9.11.2	Reference servo for radial tracking for 1x measurement velocity	22

9.11.3	Reference servo for radial tracking for 2x measurement velocity	24
10	Dimensional characteristics	25
10.1	General	25
10.2	Disk reference planes and reference axis	25
10.3	Overall dimensions	27
10.4	First transition area	27
10.5	Protection ring	27
10.6	Clamping zone	27
10.7	Second transition area	28
10.8	Information area	28
10.8.1	General	28
10.8.2	Subdivision of information zone on TL disk	29
10.9	Rim area	30
11	Mechanical characteristics	30
11.1	Mass	30
11.2	Moment of inertia	30
11.3	Dynamic imbalance	30
11.4	Axial runout	30
11.4.1	General	30
11.4.2	Residual axial tracking error for 1x measurement velocity	31
11.4.3	Residual axial tracking error for 2x measurement velocity	31
11.5	Radial runout	31
11.5.1	General	31
11.5.2	Residual radial tracking error for 1x measurement velocity	32
11.5.3	Residual radial tracking error for 2x measurement velocity	32
11.6	Durability of cover layer	32
11.6.1	Impact resistance of cover layer	32
11.6.2	Scratch resistance of cover layer	33
11.6.3	Repulsion of fingerprints by cover layer	33
12	Optical characteristics in information area	33
12.1	General	33
12.2	Refractive index of transmission stacks (TS)	33
12.3	Thickness of transmission stacks (TS)	33
12.4	Example of target thickness of spacer layers for TL disks	34
12.5	Reflectivity of recording layers	35
12.6	Birefringence	36
12.7	Angular deviation	36
13	Data format	37
13.1	General	37
13.2	Data frame	40
13.3	Error-detection code (EDC)	40
13.4	Scrambled data frame	41
13.5	Data block	42
13.6	LDC block	42
13.7	LDC code-words	43
13.8	LDC cluster	44
13.8.1	General	44
13.8.2	First interleaving step	44
13.8.3	Second interleaving step	44
13.9	Addressing and control data	46
13.9.1	General	46
13.9.2	Address units	46
13.9.3	User-control data	51
13.9.4	Byte/Bit assignment for user-control data	52
13.10	Access block	54
13.11	BIS block	54
13.12	BIS code-words	55

13.13	BIS cluster	56
13.14	ECC cluster	59
13.15	Recording frames	60
13.16	Physical cluster	61
13.17	17PP modulation for recordable data	61
13.17.1	General	61
13.17.2	Bit conversion rules	61
13.17.3	dc-control procedure	62
13.17.4	Frame sync	62
13.18	Modulation and NRZI conversion	64
14	Physical data allocating and linking	64
14.1	General	64
14.2	Recording-unit block (RUB)	64
14.2.1	General	64
14.2.2	Data run-in	65
14.2.3	Data run-out	66
14.2.4	Guard_3 field	67
14.3	Locating data relative to wobble addresses	67
14.3.1	General	67
14.3.2	Start-position shift (SPS)	67
15	Track format	69
15.1	General	69
15.2	Track shape	69
15.3	Track path	71
15.4	Track pitch	71
15.4.1	Track pitch in BCA zone	71
15.4.2	Track pitch in embossed HFM areas	71
15.4.3	Track pitch in rewritable areas	71
15.4.4	Track pitch between embossed HFM area and rewritable area	72
15.5	Track layout of HFM grooves	72
15.5.1	General	72
15.5.2	Data format	72
15.5.3	Addressing and control data	73
15.5.4	Recording frames	76
15.6	Track layout of wobbled grooves	78
15.6.1	General	78
15.6.2	Modulation of wobbles	79
15.6.3	Wobble polarity	80
15.7	ADIP information	80
15.7.1	General	80
15.7.2	ADIP-unit types	81
15.7.3	ADIP word structure	82
15.7.4	ADIP data structure	83
15.7.5	ADIP error correction	86
15.8	Disk information in ADIP aux frame	88
15.8.1	General	88
15.8.2	Error protection for disk information aux frames	89
15.8.3	Disk-Information data structure	90
16	General description of information zone	139
16.1	General	139
16.2	Format of information zone	140
17	Layout of rewritable area of information zone	140
18	Inner zone	144
18.1	General	144
18.2	Permanent information and control data (PIC) zone	148
18.2.1	General	148
18.2.2	Content of PIC zone	148

18.2.3	Emergency brake	149
18.3	Rewritable area of inner zone(s)	151
18.3.1	Protection-zone 2	151
18.3.2	Buffer	151
18.3.3	INFO 2/Reserved 8	151
18.3.4	INFO 2/Reserved 7	152
18.3.5	INFO 2/Reserved 6	152
18.3.6	INFO 2/Reserved 5	152
18.3.7	INFO 2/PAC 2	152
18.3.8	INFO 2/Reserved	152
18.3.9	INFO 2/DMA 2	152
18.3.10	INFO 2/Control data 2	152
18.3.11	INFO 2/Buffer 2	152
18.3.12	OPC/Test zone	153
18.3.13	Reserved	153
18.3.14	INFO 1/Buffer 1	153
18.3.15	INFO 1/Drive area (optional)	153
18.3.16	INFO 1/Reserved 3	154
18.3.17	INFO 1/Reserved 2	154
18.3.18	INFO 1/Reserved 1	154
18.3.19	INFO 1/DMA 1	154
18.3.20	INFO 1/Control Data 1	154
18.3.21	INFO 1/PAC 1	154
18.3.22	INFO 1/Reserved	154
19	Data zone	155
20	Outer zone(s)	155
20.1	General	155
20.2	INFO 3/Buffer 3	155
20.3	INFO 3/DMA 3	156
20.4	INFO 3/Control data 3	156
20.5	Angular buffer	156
20.6	INFO 4/DMA 4	156
20.7	INFO 4/Control data 4	156
20.8	INFO 4/Buffer 4	156
20.9	DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone	156
20.10	Protection-zone 3	156
21	Physical-access control clusters	156
21.1	General	156
21.2	Layout of PAC zones	157
21.3	General structure of PAC clusters	157
21.4	Primary PAC cluster (mandatory)	162
21.5	Disk write-protect PAC cluster (optional)	165
21.6	IS1 and IS2 PAC clusters	169
22	Disk management	170
22.1	General	170
22.2	Disk-management structure (DMS)	171
22.2.1	General	171
22.2.2	Disk-definition structure (DDS)	172
22.2.3	Defect list (DFL)	176
23	Assignment of logical-sector numbers (LSNs)	181
24	Characteristics of grooved areas	182
25	Method of testing for grooved area	182
25.1	General	182
25.2	Environment	182
25.3	Reference drive	182

25.3.1	General	182
25.3.2	Read power	182
25.3.3	Read channels	182
25.3.4	Tracking requirements	183
25.3.5	Scanning velocities	183
25.4	Definition of signals	183
26	Signals from HFM grooves	184
26.1	Push-pull polarity	184
26.2	Push-pull signal	184
26.3	Wobble signal	185
26.4	Jitter of HFM signal	185
27	Signals from wobbled grooves	185
27.1	Phase depth	185
27.2	Push-pull signal	185
27.3	Wobble signal	186
27.3.1	General	186
27.3.2	Measurement of NWS	186
27.3.3	Measurement of the wobble CNR	186
27.3.4	Measurement of harmonic distortion of wobble	186
28	Characteristics of recording layer	187
29	Method of testing for recording layer	187
29.1	General	187
29.2	Environment	187
29.3	Reference drive	187
29.3.1	General	187
29.3.2	Read power	187
29.3.3	Read channels	187
29.3.4	Tracking requirements	187
29.3.5	Scanning velocities	188
29.4	Write conditions	188
29.4.1	Write-pulse waveform	188
29.4.2	Write powers	188
29.4.3	Average power	189
29.4.4	Write conditions for i-MLSE measurement	189
29.4.5	Write conditions for cross-erase measurements	189
29.5	Definition of signals	189
30	Signals from recorded areas	189
30.1	HF signals	189
30.2	Modulated amplitude	189
30.3	Reflectivity-modulation product	191
30.4	Asymmetry	191
30.5	i-MLSE@DOW(n)	191
30.6	Cross-erase @ DOW(n)XE	191
30.7	Read stability	192
31	Local defects	193
32	Characteristics of user data	193
33	Method of testing for user data	193
33.1	General	193
33.2	Environment	193
33.3	Reference drive	193
33.3.1	General	193
33.3.2	Read power	193
33.3.3	Read channels	193
33.3.4	Error correction	194

33.3.5	Tracking requirements	194
33.3.6	Scanning velocities	194
33.4	Definition of signals	194
34	Minimum quality of recorded information	195
34.1	General	195
34.2	Random symbol error rate	195
34.3	Maximum burst errors	195
34.4	User-written data	195
35	Burst-cutting area (BCA)	195
Annex A (normative) Thickness of transmission stacks in case of multiple layers		197
Annex B (normative) Measurement of reflectivity		200
Annex C (normative) Measurement of scratch resistance of cover layer		206
Annex D (normative) Measurement of repulsion of grime by cover layer		208
Annex E (normative) Measurement of wobble amplitude		211
Annex F (normative) Write-pulse waveform for testing		216
Annex G (normative) Optimum power control (OPC) procedure for disk		223
Annex H (normative) HF signal pre-processing for integrated-maximum likelihood sequence error estimation (i-MLSE) measurements		226
Annex I (normative) Measurement procedures		238
Annex J (informative) Measurement of birefringence		250
Annex K (informative) Measurement of thickness of cover layer and spacer layer		253
Annex L (informative) Measurement of impact resistance of cover layer		256
Annex M (informative) Groove deviation and wobble amplitude		258
Annex N (informative) Guidelines for write pulse adjustment using L-SEAT edge-shift		260
Bibliography		269