

ISO/IEC 14443-2:2020 (E)

Cards and security devices for personal identification — Contactless proximity objects — Part 2: Radio frequency power and signal interface

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	General considerations
5.1	Initial dialogue
5.2	Compliance
5.2.1	PICC compliance
5.2.2	PCD compliance
5.2.2.1	General
5.2.2.2	PCD supporting PICCs of particular class(es)
6	Power transfer
6.1	General
6.2	Frequency
6.3	Operating field strength
7	Signal interface
8	Communication signal interface Type A
8.1	Communication PCD to PICC
8.1.1	Bit rate
8.1.2	Modulation
8.1.2.1	General
8.1.2.2	Modulation for a bit rate of $f_c/128$
8.1.2.3	Modulation for bit rates of $f_c/64$, $f_c/32$, and $f_c/16$
8.1.2.4	Modulation for bit rates of $f_c/8$, $f_c/4$, and $f_c/2$
8.1.2.5	Modulation for bit rates of $3f_c/4$, f_c , $3f_c/2$, and $2f_c$
8.1.3	Bit representation and coding
8.1.3.1	Bit representation and coding for bit rates of $f_c/128$, $f_c/64$, $f_c/32$, and $f_c/16$
8.1.3.2	Bit representation and coding for bit rates of $f_c/8$, $f_c/4$, and $f_c/2$
8.1.3.3	Bit representation and coding for bit rates of $3f_c/4$ and $3f_c/2$
8.1.3.4	Bit representation and coding for bit rates of f_c and $2f_c$
8.2	Communication PICC to PCD
8.2.1	Bit rate
8.2.2	PICC load modulation transmission
8.2.2.1	General
8.2.2.2	Amplitude Requirements
8.2.2.3	Phase requirements
8.2.3	Subcarrier
8.2.3.1	General
8.2.3.2	Subcarrier for bit rates of $f_c/128$, $f_c/64$, $f_c/32$, and $f_c/16$
8.2.3.3	Subcarrier for bit rates of $f_c/8$, $f_c/4$, and $f_c/2$
8.2.4	Subcarrier modulation
8.2.5	PCD load modulation reception

8.2.5.1	Amplitude requirements
8.2.5.2	Phase requirements
8.2.6	Bit representation and coding
8.2.6.1	Bit representation and coding for a bit rate of $fc/128$
8.2.6.2	Bit representation and coding for bit rates of $fc/64$, $fc/32$, $fc/16$, $fc/8$, $fc/4$, and $fc/2$
9	Communication signal interface Type B
9.1	Communication PCD to PICC
9.1.1	Bit rate
9.1.2	Modulation for bit rates of $fc/128$, $fc/64$, $fc/32$, $fc/16$, $fc/8$, $fc/4$, and $fc/2$
9.1.3	Bit representation and coding
9.1.3.1	Bit representation and coding for bit rates of $fc/128$, $fc/64$, $fc/32$, $fc/16$, $fc/8$, $fc/4$, and $fc/2$
9.1.3.2	Bit representation and coding for bit rates of $3fc/4$, fc , $3fc/2$, and $2fc$
9.2	Communication PICC to PCD
9.2.1	Bit rate
9.2.2	PICC load modulation transmission
9.2.3	Subcarrier
9.2.4	Subcarrier modulation
9.2.5	PCD load modulation reception
9.2.6	Bit representation and coding
10	Electromagnetic disturbance levels
10.1	PCD limits
10.2	PICC limits
Annex A (informative) Complex envelope and constellation diagram	
Annex B (informative) Inter symbol interference	

Page count: 47