ISO/IEC 14443-2:2020 (E)

Cards and security devices for personal identification — Contactless proximity objects — Part 2: Radio frequency power and signal interface

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

5 General considerations

5.1 Initial dialogue
5.2 Compliance
5.2.1 PICC compliance
5.2.2 PCD compliance
5.2.2.1 General
5.2.2.2 PCD supporting PICCs of particular class(es)

6 Power transfer

6.1 General
6.2 Frequency
6.3 Operating field strength

7 Signal interface

8 Communication signal interface Type A

8.1 Communication PCD to PICC
8.1.1 Bit rate
8.1.2 Modulation
8.1.2.1 General
8.1.2.2 Modulation for a bit rate of fc/128
8.1.2.3 Modulation for bit rates of fc/64, fc/32, and fc/16
8.1.2.4 Modulation for bit rates of fc/8, fc/4, and fc/2
8.1.2.5 Modulation for bit rates of 3fc/4, fc, 3fc/2, and 2fc
8.1.3 Bit representation and coding
8.1.3.1 Bit representation and coding for bit rates of fc/128, fc/64, fc/32, and fc/16
8.1.3.2 Bit representation and coding for bit rates of fc/8, fc/4, and fc/2
8.1.3.3 Bit representation and coding for bit rates of 3fc/4 and 3fc/2
8.1.3.4 Bit representation and coding for bit rates of fc and 2fc
8.2 Communication PICC to PCD
8.2.1 Bit rate
8.2.2 PICC load modulation transmission
8.2.2.1 General
8.2.2.2 Amplitude Requirements
8.2.2.3 Phase requirements
8.2.3 Subcarrier
8.2.3.1 General
8.2.3.2 Subcarrier for bit rates of fc/128, fc/64, fc/32, and fc/16
8.2.3.3 Subcarrier for bit rates of fc/8, fc/4, and fc/2
8.2.4 Subcarrier modulation
8.2.5 PCD load modulation reception

8.2.5.1 Amplitude requirements
8.2.5.2 Phase requirements
8.2.6 Bit representation and coding
8.2.6.1 Bit representation and coding for a bit rate of fc/128
8.2.6.2 Bit representation and coding for bit rates of fc/64, fc/32, fc/16, fc/8, fc/4, and fc/2

9 Communication signal interface Type B

9.1 Communication PCD to PICC
9.1.1 Bit rate
9.1.2 Modulation for bit rates of fc/128, fc/64, fc/32, fc/16, fc/8, fc/4, and fc/2
9.1.3 Bit representation and coding
9.1.3.1 Bit representation and coding for bit rates of fc/128, fc/64, fc/32, fc/16, fc/8, fc/4, and fc/2

9.1.3.2 Bit representation and coding for bit rates of 3fc/4, fc, 3fc/2, and 2fc
9.2 Communication PICC to PCD
9.2.1 Bit rate
9.2.2 PICC load modulation transmission
9.2.3 Subcarrier
9.2.4 Subcarrier modulation
9.2.5 PCD load modulation reception
9.2.6 Bit representation and coding

10 Electromagnetic disturbance levels

10.1 PCD limits
10.2 PICC limits

Annex A (informative) Complex envelope and constellation diagram

Annex B (informative) Inter symbol interference

Page count: 47