

# ISO/IEC 11574:2000-03 (E)

## Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode 64 kbit/s bearer services — Service description, functional capabilities and information flows

---

<b>Contents</b>	<b>Page</b>
Foreword	vi
Introduction	vii
<b>Section 1: General</b>	<b>1</b>
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviations	2
5 Provision of services by a PISN	3
5.1 Bearer services	3
5.2 Teleservices	3
5.3 Control and signalling	4
5.4 Interworking considerations	4
5.5 Service model	4
<b>Section 2: Service Description (stage 1 description)</b>	<b>5</b>
6 Circuit-mode 64 kbit/s unrestricted 8 kHz structured bearer service category	5
6.1 Definition	5
6.2 Description	5
6.3 Procedures	6
6.4 Network capability for charging	6
6.5 Interworking considerations	6
6.5.1 Interworking with a public ISDN and certain other digital networks	6
6.5.2 Interworking with networks supporting only a restricted digital information transfer capability	6
6.5.3 Interworking with analogue networks	6
6.6 Static Description: Service Attributes	6
7 Circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for speech information transfer	7
7.1 Definition	7
7.2 Description	7
7.3 Procedures	7
7.4 Network capability for charging	7
7.5 Interworking considerations	7
7.5.1 Interworking with a public ISDN and certain other digital networks	7
7.5.2 Interworking with analogue networks	7
7.5.3 Encoding law conversion	7
7.6 Static Description: Service Attributes	8
8 Circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer	8
8.1 Definition	8
8.2 Description	8
8.3 Procedures	9
8.4 Network capability for charging	9
8.5 Interworking considerations	9
8.5.1 Interworking with a public ISDN and certain other digital networks	9
8.5.2 Interworking with analogue networks	9
8.5.3 Encoding law conversion	9

8.6	Static Description: Service Attributes	9
9	Common procedures for services within a PISN	10
9.1	Provision of services	10
9.2	Normal procedures	10
9.2.1	Call establishment at the calling PISN user	10
9.2.2	Call establishment at the called PISN user	11
9.2.3	Terminating the service (call release)	11
9.3	Exceptional procedures / unsuccessful outcome	12
10	Interworking	13
10.1	General Interworking considerations	13
10.1.1	Incoming calls	13
10.1.2	Outgoing calls	13
10.1.3	PISN transit calls	13
10.2	Interworking with public-ISDN	13
10.2.1	Receipt of service request from a public ISDN	13
10.2.2	Sending a service request to a public ISDN	14
10.2.3	Receipt of a service response from public ISDN	14
10.2.4	Sending service response to public ISDN	14
11	Dynamic Description	14
<b>Section 3: Functional capabilities and information flows (stage 2 description)</b>		<b>18</b>
12	Functional model	18
12.1	Functional model description	18
12.2	Description of the functional entities	18
12.2.1	Call Control Agent functional entity	18
12.2.2	Call Control functional entity	19
13	Definition of information flows	20
13.1	Conventions used within the description of information flows	20
13.1.1	Convention for the description of mandatory or optional information	20
13.1.2	Convention for the naming of information flows	21
13.2	SETUP	22
13.3	REPORT	25
13.4	CHANNEL_ACKNOWLEDGE	26
13.5	CHANNEL_CONNECT	26
13.6	DISCONNECT	26
13.7	RELEASE	27
13.8	INFORMATION	27
13.9	SETUP_REJECT	27
13.10	PROCEEDING	28
14	Information flow sequences	28
14.1	Functional entity actions	28
14.1.1	Originating CCA functional entity	28
14.1.2	Originating CC functional entity	29
14.1.3	Transit CC functional entity	30
14.1.4	Destination CC functional entity	31
14.1.5	Destination CCA functional entity	32
14.1.6	Incoming gateway CC functional entity	33
14.1.7	Outgoing gateway CC functional entity	34

<b>14.2</b>	Normal call establishment	<b>36</b>
<b>14.3</b>	Normal call establishment with digit-by-digit sending and automatic answer	<b>37</b>
<b>14.4</b>	Unsuccessful calls with the provision of tones and announcements	<b>38</b>
<b>14.5</b>	Unsuccessful calls without the provision of tones and announcements	<b>39</b>
<b>14.6</b>	Incoming interworking with a non-ISDN	<b>40</b>
<b>14.7</b>	Outgoing interworking with a non-ISDN	<b>41</b>
<b>14.8</b>	Outgoing interworking with digit-by-digit sending	<b>42</b>
<b>14.9</b>	Basic call clearing	<b>43</b>
<b>14.10</b>	Incoming interworking with a public ISDN	<b>44</b>
<b>14.11</b>	Outgoing interworking with a public ISDN	<b>45</b>
<b>15</b>	SDL diagrams for functional entities	<b>46</b>
<b>15.1</b>	Originating CCA functional entity SDL diagrams	<b>46</b>
<b>15.1.1</b>	Originating CCA states used in SDL diagrams	<b>46</b>
<b>15.1.2</b>	Originating CCA SDL diagrams	<b>47</b>
<b>15.2</b>	Originating CC functional entity SDL diagrams	<b>51</b>
<b>15.2.1</b>	Originating CC states used in SDL diagrams	<b>51</b>
<b>15.2.2</b>	Originating CC SDL diagrams	<b>52</b>
<b>15.3</b>	Transit CC functional entity SDL diagrams	<b>59</b>
<b>15.3.1</b>	Transit CC states used in SDL diagrams	<b>59</b>
<b>15.3.2</b>	Transit CC SDL diagrams	<b>60</b>
<b>15.4</b>	Destination CC functional entity SDL diagrams	<b>65</b>
<b>15.4.1</b>	Destination CC states used in SDL diagrams	<b>65</b>
<b>15.4.2</b>	Destination CC SDL diagrams	<b>66</b>
<b>15.5</b>	Destination CCA functional entity SDL diagrams	<b>73</b>
<b>15.5.1</b>	Destination CCA states used in SDL diagrams	<b>73</b>
<b>15.5.2</b>	Destination CCA SDL diagrams	<b>73</b>
<b>16</b>	Allocation of functional entities to physical entities	<b>77</b>
<b>Annex A</b>	(normative) Service attributes	<b>78</b>
<b>Annex B</b>	(normative) Teleservices	<b>79</b>
<b>Annex C</b>	(informative) Bibliography	<b>81</b>
<b>Annex D</b>	(informative) Errors in ISO/IEC 11574 1st edition	<b>82</b>