

ISO/IEC 17982:2021 (E)

Information technology — Telecommunications and information exchange between systems — Close capacitive coupling communication physical layer (CCCC PHY)

Contents

	Foreword
1	Scope
2	Normative references
3	Terms, definitions and abbreviated terms
3.1	Terms and definitions
3.2	Abbreviated terms
4	Conventions and notations
5	Conformance
6	Architecture
7	Reference plate-electrode assembly
8	PHY parameters
8.1	Voltage conditions
8.2	Bit representation
8.2.1	Bit duration
8.2.2	Bit encoding
8.3	Transmission
8.4	DC balance of a P-PDU
8.5	Reception of a P-PDU
9	P-PDU
9.1	Structure
9.2	Space
9.3	Level adjust
9.4	Pre-amble and Sync
9.5	Attribute
9.6	TDS number
9.7	Sequence number
9.7.1	Initial and range
9.7.2	Acknowledgement
9.8	Payload
9.9	CRC
9.10	Post-amble
9.11	Null P-PDU
9.12	Data P-PDU
10	PHY data unit (P-DU)
11	Segmentation and reassembly
12	TDS
13	LBT and synchronisation
13.1	LBT
13.2	Synchronisation

14 Association procedure

15 Communication

15.1 General

15.2 Full duplex communication

15.3 Broadcast communication

Annex A (normative) Tests

A.1 Reference plate-electrode test

A.2 P-PDU DC balance test

A.3 Protocol test

A.3.1 Test setup

A.3.2 Test scenario 1

A.3.3 Test scenario 2

A.3.4 Test scenario 3

A.3.5 Test scenario 4

A.3.6 Test scenario 5

A.3.7 Test scenario 6

A.3.8 Test scenario 7

A.3.9 Test scenario 8

Annex B (informative) Guidance for implementation of this document

Page count: 58