ISO/IEC TS 22924:2021 (E)

Identification cards — Transport layer topologies — Configuration for HCI/HCP interchange

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

5 Architecture

- 5.1 System architecture view
- 5.1.1 General
- 5.1.2 Hosts
- 5.1.3 Gates
- 5.1.4 Pipes
- 5.1.5 Host controller
- 5.1.6 General aspects on APDU gate
- 5.2 System architecture with legacy COS

6 Configuration requirements

- 6.1 General
- 6.2 Logical components of an APDU-enabled host
- 6.3 Gates registry
- 6.3.1 General
- 6.3.2 Administration gate registry
- 6.3.2.1 Host controller administration gate
- 6.3.2.2 Host administration gate
- 6.3.3 Link management gate
- 6.3.4 Identity management gate
- 6.3.5 Loop back gate
- 6.3.6 APDU gate
- 6.3.7 APDU application gate registry
- 6.4 Example of exchanging APDU via HCI/HCP
- 6.5 APDU transport versus HCP frames
- 6.5.1 General
- 6.5.2 Chaining of T=1 message blocks wrapping HCP packets
- 6.5.3 Handling of error recovery with T=1 features
- 6.6 APDU fragmentation
- 6.7 Supported set of commands and events

Annex A (informative) Examples of architecture variants

- A.1 Architecture variants
- A.1.1 Variant with full legacy secure element
- A.1.2 Variant with ICC-managed device
- A.1.3 Variant with application interface to secure element
- A.1.4 Variant in a simplified HCI architecture when only two hosts are present

Annex B (informative) Background information

- B.1 ICC communication within the OSI model
- B.2 HCI/HCP communication within the OSI model

B.3 Comparison of HCI/HCP versus T=1
B.4 Area for new investigations
B.5 Differences between HCP and T=1
B.6 HCP packets
B.7 HCP message structure

Page count: 26