ISO/IEC 23200-1:2021 (E)

Information technology — Radio frequency identification for item management — Part 1: Interference rejection performance test method between a tag as defined in ISO/IEC 18000-63 and a heterogeneous wireless system

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

5 Conditions applicable to the test methods

- 5.1 Test environment
- 5.2 Radio frequency (FR) environment
- 5.3 Pre-conditioning
- 5.4 Default tolerance
- 5.5 Total measurement uncertainty
- 5.6 Test result reporting
- 5.7 Test mounting material
- 5.8 Test communication parameters

6 Test set-up

- 6.1 DUT placement
- 6.2 Test setup for tag's RX sensitivity power measurement under non-interference environment
- 6.2.1 Test apparatus and test circuits
- 6.2.2 Setup of the devices
- 6.2.3 Antenna polarization and requirements
- 6.3 Test setup for tag's RX sensitivity power measurement under interference environment
- 6.3.1 Sub-1GHz wireless communications technologies
- 6.3.2 Setup of the devices
- 6.3.3 Antenna polarization and requirements

7 Test procedure

- 7.1 General description
- 7.2 Tag's RX sensitivity power measurement under non-interference environment
- 7.2.1 Purpose
- 7.2.2 Test procedure
- 7.3 Tag's RX sensitivity power measurement under interference environment
- 7.3.1 Purpose
- 7.3.2 Test procedure
- 7.4 Test report

Page count: 13