ISO/IEC/IEEE 8802-1AX:2021-09 (E)

Telecommunications and exchange between information technology systems - Requirements for local and metropolitan area networks - Part 1AX: Link aggregation

Contents

Page

1. Overview ... 18

1.1 Scope ... 18
1.2 Purpose ... 18
1.3 State diagram conventions ... 19

2. Normative references ... 20

3. Definitions ... 21

4. Acronyms and abbreviations ... 24

5. Conformance ... 25

5.1 Requirements terminology ... 25
5.2 Protocol implementation conformance statement ... 25
5.3 Link Aggregation ... 25
5.3.2 Link Aggregation options ... 26
5.4 Distributed Resilient Network Interconnect (DRNI) ... 26
5.4.2 DRNI options ... 27

6. Link Aggregation ... 28

6.1 Overview ... 28
6.1.1 Goals and objectives ... 28
6.1.2 Positioning of Link Aggregation within the IEEE 802 architecture ... 29
6.1.3 Protocol Parser/Multiplexer ... 29
6.1.3.1 Protocol Parser state diagram ... 30
6.2 Link Aggregation operation ... 31
6.2.1 Principles of Link Aggregation ... 33
6.2.2 Service interfaces ... 34
6.2.3 Frame Collector ... 34
6.2.3.1 Frame Collector state diagram ... 35
6.2.4 Frame Distributor ... 36
6.2.4.1 Frame Distributor state diagram ... 36
6.2.5 Marker Generator/Receiver (optional) ... 37
6.2.6 Marker Responder ... 38
6.2.7 Aggregator Parser/Multiplexer ... 38
6.2.7.1 Aggregator Parser/Multiplexer state diagrams ... 38
6.2.8 Aggregator ... 42
6.2.9 LACP Parser/Multiplexer ... 43
6.2.10 Addressing ... 43
6.2.10.1 Source address (SA) ... 43
6.2.10.2 Destination address (DA) ... 43
6.3 Link Aggregation Control ... 44
6.3.1 Characteristics of Link Aggregation Control ... 45
6.3.2 System identification ... 46
6.3.3 Aggregator identification ... 46
6.3.4 Port identification ... 46
6.3.5 Capability identification ... 47
6.3.6 Link Aggregation Group identification ... 48

6.3.6.1 Construction of the Link Aggregation Group Identifier 48
6.3.6.2 Representation of the Link Aggregation Group Identifier 48
6.3.7 Selecting a Link Aggregation Group 49
6.3.8 Agreeing on a Link Aggregation Group 49
6.3.9 Attaching a link to an Aggregator 50
6.3.10 Signaling readiness to transfer user data 50
6.3.11 Enabling the Frame Collector and Frame Distributor 50
6.3.12 MAC_Operational status 51
6.3.13 Monitoring the membership of a Link Aggregation Group 51
6.3.14 Detaching a link from an Aggregator 51
6.3.15 Configuration and administrative control of Link Aggregation 52
6.3.16 Link Aggregation Control state information 52
6.4 Link Aggregation Control Protocol 52
6.4.1 LACP design elements 52
6.4.2 LACPDU structure and encoding 53
6.4.2.1 Transmission and representation of octets 53
6.4.2.2 Encapsulation of LACPDUs in frames 53
6.4.2.3 LACPDU structure 54
6.4.2.4 Version 2 TLVs 57
6.4.3 LACP state machine overview 59
6.4.4 Constants 60
6.4.5 Variables associated with each Aggregator 61
6.4.6 Variables associated with each Aggregation Port 63
6.4.7 Variables used for managing the operation of the state machines 68
6.4.8 Functions 69
6.4.9 Timers 72
6.4.10 Messages 72
6.4.11 LACP Receive machine 72
6.4.12 Selection Logic 74
6.4.12.1 Selection Logic—Requirements 75
6.4.12.2 Selection Logic—Recommended default operation 77
6.4.13 Mux machine 78
6.4.14 LACP Transmit machine 81
6.5 Marker protocol 82
6.5.1 Introduction 82
6.5.2 Sequence of operations 83
6.5.3 Marker and Marker Response PDU structure and encoding 83
6.5.3.1 Transmission and representation of octets 83
6.5.3.2 Encapsulation of Marker and Marker Response PDU in frames 83
6.5.3.3 Marker and Marker Response PDU structure 84
6.5.4 Protocol definition 85
6.5.4.1 Operation of the marker protocol 85
6.5.4.2 Marker Responder state diagram 86
6.6 Conversation-Sensitive Collection and Distribution 87
6.6.1 Port Algorithms and Port Conversation IDs 89
6.6.2 Link numbers and link selection 89
6.6.3 Conversation-sensitive LACP 90
6.6.3.1 Per-Aggregator variables 91
6.6.3.2 Variables associated with each Aggregation Port 94
6.6.3.3 Variables used for managing the operation of the state diagrams 95
6.6.3.4 Functions 96
6.6.3.5 Update Mask machine 100
6.7 Configuration capabilities and restrictions 102
6.7.1 Use of system and port priorities 102

6.7.2 Dynamic allocation of operational Keys 103
6.7.3 Link Aggregation on shared-medium links 103
6.7.4 Selection Logic variants 104
6.7.4.1 Reduced reconfiguration 104
6.7.4.2 Limited Aggregator availability 104
6.7.5 LACP configuration for dual-homed Systems 104

7. Management 106

7.1 Overview 106
7.1.1 Systems management overview 106
7.1.2 Management model 107
7.2 Managed objects 107
7.2.1 Introduction 107
7.2.2 Overview of managed objects 108
7.2.2.1 Text description of managed objects 108
7.2.3 Containment 108
7.2.4 Naming 109
7.2.5 Capabilities 109
7.3 Management for Link Aggregation 114
7.3.1 Aggregator managed object class 114
7.3.1.1 Aggregator attributes 115
7.3.1.2 Aggregator Notifications 125
7.3.2 Aggregation Port managed object class 125
7.3.2.1 Aggregation Port Attributes 125
7.3.2.2 Aggregation Port Extension Attributes 132
7.3.3 Aggregation Port Statistics managed object class 133
7.3.3.1 Aggregation Port Statistics attributes 133
7.3.4 Aggregation Port Debug Information managed object class 134
7.3.4.1 Aggregation Port Debug Information attributes 135
7.4 Management for Distributed Resilient Network Interconnect 137
7.4.1 DRNI Managed Object Class 137
7.4.1.1 DRNI Attributes 137

8. Distribution algorithms 148

8.1 Distribution algorithm identification 148
8.2 Per-Service Frame Distribution 149
8.2.1 Distribution based on C-VLAN Identifier (C-VID) 149
8.2.2 Distribution based on S-VLAN Identifier (S-VID) 150
8.2.3 Distribution based on Backbone Service Instance Identifier (I-SID) 150
8.2.4 Distribution based on Traffic Engineering Service Instance Identifier (TE-SID) 150
8.2.5 Distribution based on Flow Hash 150

9. Distributed Resilient Network Interconnect 151

9.1 Goals 151
9.2 Distributed Relay operation 152
9.3 Intra-Relay Connection 154
9.4 Using DRNI 155
9.4.1 DRNI connectivity 155
9.4.2 DRNI fault recovery 157
9.4.3 DRNI configuration 158

9.5 DRNI Gateway 159
9.5.1 DRCP Parser/Multiplexer 160
9.5.2 DRNI Gateway Relay 160
9.5.2.1 Service interfaces 160
9.5.2.2 variables 161
9.5.2.3 Functions 162
9.5.2.4 Messages 162
9.5.2.5 DR_Gateway Collector/Distributor 162
9.5.2.6 DR_Aggregator Parser/Multiplexer 163
9.5.2.7 DR_IRP Parser/Multiplexer 164
9.5.3 DRNI Gateway Control 165
9.5.3.1 DRNI Gateway and DRNI Identification 165
9.5.3.2 Forming the DRNI 166
9.5.3.3 Partner Selection and Forming a LAG 166
9.5.3.4 Port Algorithm and Aggregator Port Selection 166
9.5.3.5 Gateway Algorithm and DRNI Gateway Port selection 167
9.6 Distributed Relay Control Protocol 168
9.6.1 DRCPDU transmission, addressing, and protocol identification 169
9.6.1.1 Destination MAC Address 169
9.6.1.2 Source MAC Address 170
9.6.1.3 Priority 170
9.6.1.4 Protocol Identification 170
9.6.1.5 Encapsulation of DRCPDUs in frames 170
9.6.2 DRCPDU structure and encoding 170
9.6.2.1 Transmission and representation of octets 170
9.6.2.2 DRCP TLV structure 171
9.6.2.3 DRCPDU structure 172
9.6.2.4 Aggregator State TLV 174
9.6.2.5 Gateway State TLV 176
9.6.2.6 Gateway Preference TLV 176
9.6.2.7 Organization-Specific TLV 177
9.6.3 DRCP state machine overview 178
9.6.4 Constants 179
9.6.5 Variables associated with the DRNI Gateway 179
9.6.6 Variables used for managing the operation of the state machines 185
9.6.7 Functions 187
9.6.8 Timers 194
9.6.9 Messages 194
9.6.10 DRCP Receive machine 195
9.6.11 Distributed Relay machine 197
9.6.12 DRNI Gateway and Aggregator machine 198
9.6.13 DRCP Transmit machine 199

Annex A (normative) Protocol implementation conformance statement (PICS) proforma 200
A.1 Introduction 200
A.1.1 Abbreviations and special symbols 200
A.1.2 Instructions for completing the PICS proforma 201
A.1.3 Additional information 201
A.1.4 Exceptional information 201
A.1.5 Conditional items 202
A.1.6 Identification 202
A.1.6.1 Implementation identification 202
A.1.6.2 Protocol summary 202

A.2 PICS proforma for Clause 6 ... 203
A.2.1 Major capabilities/options ... 203
A.2.3 Protocol Parser/Multiplexer support ... 204
A.2.4 Frame Collector ... 204
A.2.5 Frame Distributor ... 204
A.2.2 LLDP Port connectivity ... 204
A.2.7 Aggregator Parser/Multiplexer ... 205
A.2.8 LACP Parser/Multiplexer ... 205
A.2.6 Marker protocol ... 205
A.2.10 Aggregator identification ... 206
A.2.11 Port identification ... 206
A.2.12 Capability identification ... 206
A.2.9 System identification ... 206
A.2.14 Detaching a link from an Aggregator ... 207
A.2.15 LACPDU structure ... 207
A.2.16 Receive machine ... 207
A.2.13 Link Aggregation Group identification ... 207
A.2.18 Mux machine ... 208
A.2.17 Selection Logic ... 208
A.2.20 Marker protocol ... 209
A.2.19 Transmit machine ... 209
A.2.21 Management ... 210
A.2.23 Conversation-sensitive frame collection and distribution ... 211
A.2.22 Per-Service Frame Distribution ... 211
A.2.25 Link Aggregation on shared-medium links ... 212
A.2.24 Configuration capabilities and restrictions ... 212
A.2.27 DRCPDU structure ... 213
A.2.26 Distributed Resilient Network Interconnect ... 213

Annex B (informative) Collection and distribution algorithms ... 214
B.1 Introduction ... 214
B.2 Port selection ... 215
B.3 Dynamic reallocation of conversations to different Aggregation Ports ... 215
B.4 Topology considerations in the choice of distribution algorithm ... 216

Annex C (informative) LACP standby link selection and dynamic Key management ... 218
C.1 Introduction ... 218
C.2 Goals ... 218
C.3 Standby link selection ... 219
C.4 Dynamic Key management ... 219
C.5 A dynamic Key management algorithm ... 219
C.6 Example 1 ... 221
C.7 Example 2 ... 221

Annex D (normative) SMIv2 MIB definitions for Link Aggregation ... 223
D.1 Introduction ... 223
D.2 SNMP Management Framework ... 223
D.3 Security considerations ... 223
D.4 Structure of the MIB module ... 224
D.4.1 Relationship to the managed objects defined in Clause 7 ... 225
D.4.2 MIB Subtrees ... 232
D.4.2.1 The dot3adAgg Subtree ... 232
D.4.2.2 The dot3adAggPort Subtree ... 232

D.4.2.3 The dot3adAggNotifications Subtree ... 232
D.4.2.4 The dot3adDrni Subtree ... 232
D.5 Relationship to other MIBs ... 233
D.5.1 Relationship to the Interfaces MIB ... 233
D.5.2 Layering model ... 233
D.5.3 ifStackTable ... 234
D.5.4 ifRcvAddressTable ... 234
D.6 Definitions for Link Aggregation MIB ... 234

Annex E (informative) DRNI on Bridges ... 325
E.1 DRNI on VLAN Bridges ... 325
E.2 DRNI on Provider Bridges and Provider Edge Bridges ... 326
E.3 DRNI on Backbone Edge Bridges ... 327

Annex F (normative) Link Aggregation and Link Layer Discovery Protocol ... 328
F.1 Positioning Link Layer Discovery Protocol (LLDP) relative to Link Aggregation ... 328
F.1.1 LLDP Parser/Multiplexer ... 328
F.2 Link Aggregation TLV ... 328
F.2.1 aggregation status ... 329
F.2.2 aggregated Port ID ... 329
F.2.3 Link Aggregation TLV usage rules ... 329
F.2.4 Use of other TLVs on an Aggregator or Aggregation Link ... 330

Annex G (informative) Bibliography ... 331

Figures

Figure 6-1 Architectural positioning of Link Aggregation sublayer 29
Figure 6-2 Protocol Parser state diagram 31
Figure 6-3 Link Aggregation sublayer block diagram 32
Figure 6-4 Frame Collector state diagram 36
Figure 6-5 Frame Distributor state diagram 37
Figure 6-6 Aggregator Parser state diagram 41
Figure 6-7 Aggregator Multiplexer state diagram 42
Figure 6-8 LACPDU structure 54
Figure 6-9 Bit encoding of the Actor_State and Partner_State fields 55
Figure 6-10 Port Algorithm TLV 57
Figure 6-11 Port Conversation Link Digest TLV 58
Figure 6-12 Port Conversation Service Digest TLV 58
Figure 6-13 LACP state machine overview 59
Figure 6-14 LACP Receive state diagram 73
Figure 6-15 Selection of Aggregators 78
Figure 6-16 Mux state diagram 79
Figure 6-17 LACP Transmit state diagram 81
Figure 6-18 Marker protocol time sequence diagram 83
Figure 6-19 Marker PDU and Marker Response PDU structure 84
Figure 6-20 Marker Responder state diagram 86
Figure 6-21 Conversation-Sensitive Collection and Distribution overview 88
Figure 6-22 Distribution algorithm information flow 91
Figure 6-23 Update Mask state diagram 101
Figure 6-24 Dual-homed System examples 105
Figure 7-1 Link aggregation entity relationship diagram 109
Figure 8-1 Distribution algorithm identifiers 148
Figure 9-1 A DRNI 153
Figure 9-2 Transmission and reception via the IRC 154
Figure 9-3 DRNI with dedicated IRC Link 155
Figure 9-4 DRNI with dedicated IRC LAG 155
Figure 9-5 DRNI end station attach 156
Figure 9-6 DRNI network attach 156
Figure 9-7 DRNI Gateway block diagram 159
Figure 9-8 DR_Gateway state machine 163
Figure 9-9 DR_Aggregator state machine 164
Figure 9-10 DR_IRP state machine 165
Figure 9-11 Basic TLV format 171
Figure 9-12 DRCPDU structure 172
Figure 9-13 Bit encoding of the Home_IRP_State and Neighbor_IRP_State fields 173
Figure 9-14 Aggregator State TLV 174
Figure 9-15 Bit encoding of the Aggregator_CSCD_State fields 175
Figure 9-16 Gateway State TLV 176
Figure 9-17 Gateway Preference TLV 176
Figure 9-18 Organization-Specific TLV 177
Figure 9-19 DRCP state machine overview 178
Figure 9-20 DRCP Receive machine state diagram 195
Figure 9-21 Distributed Relay machine state diagram 197
Figure 9-22 DRNI Gateway and Aggregator machine state diagram 198
Figure 9-23 DRCP Transmit state diagram 199
Figure B-1 Link aggregation topology examples 217
Figure C-1 Example 1 221

Figure C-2 Example 2a 222
Figure C-3 Example 2b 222
Figure E-1 DRNI on VLAN Bridges 325
Figure E-2 DRNI on Provider Edge Bridges 326
Figure E-3 DRNI on Backbone Edge Bridges 327
Figure F-1 Link Aggregation TLV format 328

Tables

Table 6-1 Link Aggregation protocol destination addresses 44
Table 6-2 Example Partner parameters 49
Table 6-3 Slow Protocols EtherType Assignment 53
Table 6-4 Type field values of Version 2 TLVs 57
Table 7–1 Link Aggregation capabilities 110
Table 8-1 IEEE per-service distribution algorithms 149
Table 9-1 Distributed Relay Control Protocol destination addresses 169
Table 9-2 DRNI EtherType Assignment 170
Table 9-3 DRNI Protocol subtypes 170
Table 9-4 Type field values of DRCP TLVs 171
Table F.1 Link aggregation capability/status 329