

ISO/IEC 28360-1:2021-10 (E)

Information technology - Determination of chemical emission rates from electronic equipment - Part 1: Using consumables

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Conformance | 2 |
| 3 | Normative references | 2 |
| 4 | Terms and definitions | 2 |
| 5 | Symbols and Abbreviated terms | 6 |
| 5.1 | Abbreviated terms | 6 |
| 5.2 | Symbols | 7 |
| 6 | Method overview | 8 |
| 7 | ETC requirements | 9 |
| 7.1 | Construction materials | 9 |
| 7.2 | Air tightness | 9 |
| 7.3 | Air mixing efficiency | 10 |
| 8 | Determination method | 10 |
| 8.1 | Test conditions | 10 |
| 8.1.1 | General | 10 |
| 8.1.2 | Operating temperature and relative humidity (RH) | 10 |
| 8.1.3 | Air exchange rate (n) | 10 |
| 8.1.4 | Air velocity | 10 |
| 8.1.5 | Sampled air flow | 10 |
| 8.2 | Handling of EUT and ETC | 10 |
| 8.2.1 | Selection and storage of EUT | 10 |
| 8.2.2 | Loading Factor | 11 |
| 8.2.3 | ETC purging | 11 |
| 8.2.4 | Background concentrations (C_{bg} and C_{pbg}) | 11 |
| 8.2.5 | EUT unpacking | 12 |
| 8.2.6 | Preparation of the EUT before testing | 12 |
| 8.2.7 | EUT installation | 12 |
| 8.3 | EUT Operation during Test | 13 |
| 8.3.1 | General | 13 |
| 8.3.2 | Pre-operating phase | 13 |
| 8.3.3 | Operating phase | 13 |
| 8.3.4 | Post-operating phase | 14 |
| 8.3.5 | Recording of EUT operation | 14 |
| 8.4 | VOC and carbonyl compounds | 14 |
| 8.4.1 | Sorbents | 14 |
| 8.4.2 | Sample collection | 14 |
| 8.4.3 | Emission rate calculation | 15 |
| 8.4.4 | Total VOC emission rate | 17 |
| 8.5 | Ozone | 17 |
| 8.5.1 | Analyser and sampling line requirements | 18 |

| | | |
|---|--|----|
| 8.5.2 | Monitoring | 18 |
| 8.5.3 | Emission rate calculation | 18 |
| 8.6 | Particulate matter | 19 |
| 8.6.1 | Weighing and Filter conditioning | 20 |
| 8.6.2 | Sampling | 20 |
| 8.6.3 | Emission rate calculation | 20 |
| 8.7 | Fine and Ultrafine Particles (FP and UFP) | 21 |
| 8.7.1 | General Requirements for Aerosol Measuring Systems (AMS) | 22 |
| 8.7.2 | Measurement | 24 |
| 8.7.3 | Calculation | 24 |
| 9 | Test report | 28 |
| Annex A (normative) Print Patterns | | 31 |
| A.1 | Monochrome print pattern, 5% coverage | 31 |
| A.2 | Colour print pattern, 20% coverage | 33 |
| Annex B (normative) Preparatory AMS Test Procedures | | 34 |
| B.1 | Procedures for operational readiness of AMS | 34 |
| B.1.1 | Particle size concentration range measurements | 34 |
| B.1.2 | Particle number concentration range measurements | 34 |
| B.2 | Procedures for operational readiness test of Fast AMS | 35 |
| B.2.1 | Set up of instrument | 35 |
| B.2.2 | Preparation for measurement | 35 |
| B.3 | Procedures for operational readiness test of CPC | 36 |
| B.3.1 | Set up the instrument | 36 |
| B.3.2 | Preparation for measurement | 37 |
| Annex C (informative) Model for QEM | | 38 |
| C.1 | Objectives | 38 |
| C.2 | Approach | 38 |
| C.3 | General mass balance and concentration equations | 40 |
| C.4 | Background Concentration | 40 |
| C.5 | Emission rate calculation | 41 |
| C.5.1 | Emission during pre-operating phase | 41 |
| C.5.2 | Emission during operating phase | 41 |
| Annex D (informative) Model for CEM | | 45 |
| D.1 | Objectives | 45 |
| D.2 | Approach | 45 |
| D.3 | General mass balance and concentration equations | 47 |
| D.4 | Background concentrations | 47 |
| D.5 | Emission rate calculation | 47 |
| D.5.1 | Emission during pre-operating phase | 47 |
| D.5.2 | Emission during operating and post-operating phase | 48 |
| Annex E (Informative) DE-UZ 205 Options | | 52 |
| Bibliography | | 54 |