

ISO/IEC/IEEE 8802-1AS:2021-11 (E)

Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Part 1AS: Timing and synchronization for time-sensitive applications in bridged local area networks

Contents

1. Overview.....	17
1.1 Scope.....	17
1.2 Purpose.....	17
2. Normative references.....	18
3. Definitions.....	20
4. Acronyms and abbreviations.....	23
5. Conformance.....	26
5.1 Requirements terminology.....	26
5.2 Protocol Implementation Conformance Statement (PICS).....	26
5.3 Time-aware system requirements.....	26
5.4 PTP Instance requirements and options.....	26
5.5 MAC-specific timing and synchronization methods for full-duplex IEEE 802.3 links.....	28
5.6 MAC-specific timing and synchronization methods for IEEE Std 802.11-2016.....	29
5.7 MAC-specific timing and synchronization methods for IEEE 802.3 EPON.....	29
5.8 MAC-specific timing and synchronization methods for coordinated shared network (CSN).....	29
6. Conventions.....	30
6.1 General.....	30
6.2 Service specification method and notation.....	30
6.3 Lexical form syntax.....	30
6.4 Data types and on-the-wire formats.....	30
7. Time-synchronization model for a packet network.....	35
7.1 General.....	35
7.2 Architecture of a time-aware network.....	35
7.3 Time synchronization.....	42
7.4 PTP Instance architecture.....	45
7.5 Differences between gPTP (IEEE Std 802.1AS) and PTP (IEEE Std 1588-2019).....	46
8. IEEE 802.1AS concepts and terminology.....	48
8.1 gPTP domain.....	48
8.2 Timescale.....	48
8.3 Link asymmetry.....	50
8.4 Messages.....	51
8.5 Ports.....	53
8.6 PTP Instance characterization.....	54
9. Application interfaces.....	59
9.1 Overview of the interfaces.....	59
9.2 ClockSourceTime interface.....	60
9.3 ClockTargetEventCapture interface.....	60
9.4 ClockTargetTriggerGenerate interface.....	61
9.5 ClockTargetClockGenerator interface.....	63

9.6	ClockTargetPhaseDiscontinuity interface	64
10.	Media-independent layer specification	65
10.1	Overview	65
10.2	Time-synchronization state machines	67
10.3	Best master clock selection, external port configuration, and announce interval setting state machines	98
10.4	State machines related to signaling gPTP capability	135
10.5	Message attributes	142
10.6	Message formats	143
10.7	Protocol timing characterization	156
11.	Media-dependent layer specification for full-duplex point-to-point links	160
11.1	Overview	160
11.2	State machines for MD entity specific to full-duplex point-to-point links	166
11.3	Message attributes	195
11.4	Message formats	197
11.5	Protocol timing characterization	205
11.6	Control of computation of neighborRateRatio	206
11.7	Control of computation of meanLinkDelay	207
12.	Media-dependent layer specification for IEEE 802.11 links	208
12.1	Overview	208
12.2	Messages	212
12.3	Determination of Timing Measurement and Fine Timing Measurement capability	214
12.4	Determination of asCapable	214
12.5	State machines	215
12.6	FTM parameters	227
12.7	Format of VendorSpecific information element	228
12.8	Synchronization message interval	229
13.	Media-dependent layer specification for interface to IEEE 802.3 Ethernet passive optical network link	230
13.1	Overview	230
13.2	Message attributes	234
13.3	Message format	234
13.4	Determination of asCapable	237
13.5	Layering for IEEE 802.3 EPON links	237
13.6	Service interface definitions	238
13.7	MD entity global variables	240
13.8	State machines	241
13.9	Message transmission intervals	244
14.	Timing and synchronization management	245
14.1	General	245
14.2	Default Parameter Data Set (defaultDS)	248
14.3	Current Parameter Data Set (currentDS)	251
14.4	Parent Parameter Data Set (parentDS)	253
14.5	Time Properties Parameter Data Set (timePropertiesDS)	255
14.6	Path Trace Parameter Data Set (pathTraceDS)	256
14.7	Acceptable Master Table Parameter Data Set (acceptableMasterTableDS)	257

14.8	Port Parameter Data Set (portDS).....	258
14.9	Description Port Parameter Data Set (descriptionPortDS).....	269
14.10	Port Parameter Statistics Data Set (portStatisticsDS).....	269
14.11	Acceptable Master Port Parameter Data Set (acceptableMasterPortDS).....	273
14.12	External Port Configuration Port Parameter Data Set (externalPortConfigurationPortDS).....	273
14.13	Asymmetry Measurement Mode Parameter Data Set (asymmetryMeasurementModeDS).....	274
14.14	Common Services Port Parameter Data Set (commonServicesPortDS).....	275
14.15	Common Mean Link Delay Service Default Parameter Data Set (cmlDsDefaultDS).....	275
14.16	Common Mean Link Delay Service Link Port Parameter Data Set (cmlDsLinkPortDS)....	276
14.17	Common Mean Link Delay Service Link Port Parameter Statistics Data Set (cmlDsLinkPortStatisticsDS).....	281
14.18	Common Mean Link Delay Service Asymmetry Measurement Mode Parameter Data Set (cmlDsAsymmetryMeasurementModeDS).....	283
15.	Managed object definitions.....	284
15.1	Internet Standard Management Framework.....	284
15.2	Structure of the MIB.....	284
15.3	Relationship to MIB in IEEE Std 802.1AS-2011.....	291
15.4	Security considerations.....	291
15.5	Textual conventions defined in this MIB.....	293
15.6	IEEE 802.1AS MIB module.....	293
16.	Media-dependent layer specification for CSN.....	368
16.1	Overview.....	368
16.2	Coordinated Shared Network characteristics.....	368
16.3	Layering for CSN links.....	369
16.4	Path delay measurement over a CSN backbone.....	370
16.5	Synchronization messages.....	373
16.6	Specific CSN requirements.....	377
16.7	Grandmaster PTP Instance capability.....	378
16.8	CSN clock and node performance requirements.....	378
Annex A	(normative) Protocol Implementation Conformance Statement (PICS) proforma.....	379
A.1	Introduction.....	379
A.2	Abbreviations and special symbols.....	379
A.3	Instructions for completing the PICS proforma.....	380
A.4	PICS proforma for IEEE Std 802.1AS-2020.....	382
A.5	Major capabilities.....	383
A.6	Media access control methods.....	384
A.7	Minimal time-aware system.....	384
A.8	Signaling.....	386
A.9	Best master clock.....	387
A.11	Media-independent master.....	389
A.10	Grandmaster-capable PTP Instance.....	389
A.12	Media-independent performance requirements.....	390
A.13	Media-dependent, full-duplex point-to-point link.....	391
A.15	Media-dependent IEEE 802.3 EPON link.....	394
A.14	Media-dependent IEEE 802.11 link.....	394
A.16	Media-dependent CSN link.....	395
A.17	Media-dependent MoCA link.....	395

A.19	Remote management.....	396
A.20	Application interfaces	396
A.21	External port configuration.....	396
A.18	Media-dependent ITU-T G.hn link	396
Annex B	(normative) Performance requirements	397
B.1	LocalClock requirements	397
B.2	PTP Instance requirements	402
B.3	End-to-end time-synchronization performance	403
B.4	End-to-end jitter and wander performance	403
Annex C	(informative) Timescales and epochs	405
C.1	Overview	405
C.2	TAI and UTC	405
C.3	NTP and GPS.....	407
C.4	Timescale conversions.....	407
C.5	Time zones and GMT	408
Annex D	Reserved for future use	409
Annex E	Reserved for future use	410
Annex F	(informative) PTP profile included in this standard	411
F.1	General.....	411
F.2	Identification.....	411
F.3	PTP attribute values	412
F.4	PTP options.....	412
F.5	LocalClock and PTP Instance performance requirements.....	413
Annex G	(informative) The asymmetry compensation measurement procedure based on line-swapping	414
G.1	Introduction.....	414
G.2	Pre-conditions for measurement	414
G.3	Measurement procedure.....	414
Annex H	(informative) Bibliography	417

List of figures

Figure 7-1—Time-aware network example.....	36
Figure 7-2—Time-aware network of Figure 7-1 after an access network link failure	37
Figure 7-3—Time-aware network example for multiple gPTP domains	38
Figure 7-4—Time-aware network example for synchronization path redundancy, with one clock source providing time to two domains	40
Figure 7-5—Time-aware network example for GM redundancy with one primary GM and one hot-standby GM, which are separated in two gPTP domains	41
Figure 7-6—Time-aware network example for GM+synchronziation path redundancy, with one primary and one hot-standby GM. Each GM establishes two sync trees, resulting in a total of four Sync trees that are separated in four gPTP domains.....	42
Figure 7-7—Conceptual medium delay measurement	43
Figure 7-8—PTP Instance model	45
Figure 8-1—Propagation asymmetry.....	50
Figure 8-2—Definition of message timestamp point, reference plane, timestamp measurement plane, and latency constants	52
Figure 9-1—Application interfaces	59
Figure 10-1—Model for media-independent layer of PTP Instance	66
Figure 10-2—Time-synchronization state machines—overview and interrelationships.....	68
Figure 10-3—SiteSyncSync state machine.....	84
Figure 10-4—PortSyncSyncReceive state machine	86
Figure 10-5—ClockMasterSyncSend state machine	88
Figure 10-6—ClockMasterSyncOffset state machine	90
Figure 10-7—ClockMasterSyncReceive state machine	92
Figure 10-8—PortSyncSyncSend state machine	95
Figure 10-9—ClockSlaveSync state machine	97
Figure 10-10—Example master/slave hierarchy of PTP Instances	99
Figure 10-11—Best master clock selection state machines—overview and interrelationships	105
Figure 10-12—External port configuration state machines—overview and interrelationships	106
Figure 10-13—PortAnnounceReceive state machine.....	116
Figure 10-14—PortAnnounceInformation state machine.....	118
Figure 10-15—PortStateSelection state machine	121
Figure 10-16—PortAnnounceInformationExt state machine	123
Figure 10-17—PortStateSettingExt state machine	126
Figure 10-18—PortAnnounceTransmit state machine	128
Figure 10-19—AnnounceIntervalSetting state machine.....	131
Figure 10-20—SyncIntervalSetting state machine	134
Figure 10-21—GptpCapableTransmit state machine	136
Figure 10-22—GptpCapableReceive state machine.....	138
Figure 10-23—GptpCapableIntervalSetting state machine.....	141
Figure 11-1—Propagation delay measurement using peer-to-peer delay mechanism	161
Figure 11-2—Transport of time-synchronization information.....	163
Figure 11-3—Model for a PTP Instance of a time-aware system with full-duplex point-to-point links ...	166
Figure 11-4—Detail of MD entity time-synchronization state machines for full-duplex point-to-point links	167
Figure 11-5—Peer-to-peer delay mechanism state machines—overview and interrelationships	167
Figure 11-6—MDSyncReceiveSM state machine.....	175
Figure 11-7—MDSyncSendSM state machine.....	179
Figure 11-8—OneStepTxOperSetting state machine	181
Figure 11-9—MDPdelayReq state machine	188
Figure 11-10—MDPdelayResp state machine	191
Figure 11-11—LinkDelayIntervalSetting state machine.....	194

Figure 12-1—Timing measurement procedure for IEEE 802.11 links	209
Figure 12-2—Fine Timing Measurement procedure for IEEE 802.11 links	209
Figure 12-3—Illustration of Fine Timing Measurement burst	211
Figure 12-4—Media-dependent and lower entities in stations with IEEE 802.11 links	213
Figure 12-5—Master state machine A: (a) For TM, receives information from the PortSync entity and sends to slave, and (b) for FTM, receives and stores information from the PortSync entity	216
Figure 12-6—Master state machine B: (a) For TM, not invoked and (b) for FTM, receives initial FTM request from slave and sends information received from upstream to slave in successive FTM frames...	217
Figure 12-7—Slave state machine	223
Figure 12-8—Format of VendorSpecific information element when Type = 0	228
Figure 13-1—IEEE 802.3 EPON time-synchronization interfaces	233
Figure 13-2—IEEE 802.3 EPON interface model.....	238
Figure 13-3—State machine for IEEE 802.3 EPON requester.....	242
Figure 13-4—State machine for IEEE 802.3 EPON responder.....	244
Figure 16-1—Example of CSN backbone in a TSN LAN	368
Figure 16-2—Media-dependent and lower entities in CSN nodes	369
Figure 16-3—Path types over CSN as IEEE 802.1AS backbone.....	370
Figure 16-4—Propagation delay and residence time over a CSN backbone.....	370
Figure 16-5—CSN node-to-node path delay measurement.....	371
Figure 16-6—IEEE 802.1AS Sync message propagation over the CSN backbone	373
Figure B-1—Wander generation (TDEV) requirement for LocalClock entity	399
Figure B-2—ADEV limit corresponding to wander generation requirement of Figure B-1.....	400
Figure B-3—PTPDEV limit corresponding to wander generation requirement of Figure B-1.....	401
Figure B-4—MTIE masks met for maximum endpoint filter bandwidths of Table B-4.....	404
Figure G-1—Asymmetry compensation measurement procedure	415

List of tables

Table 6-1—Primitive data types	31
Table 8-1—Default values for priority1, for the respective media.....	55
Table 8-2—TimeSource enumeration	57
Table 10-1—Summary of scope of global variables used by time synchronization state machines (see 10.2.4 and 10.2.5).....	76
Table 10-2—PTP Port state definitions	98
Table 10-3—Summary of scope of global variables used by best master clock selection, external port configuration, and announce interval setting state machines (see 10.3.9 and 10.3.10).....	107
Table 10-4—Destination address for Announce and Signaling messages	142
Table 10-5—EtherType for Announce and Signaling messages.....	142
Table 10-6—Propagate TLVs of IEEE Std 1588-2019	144
Table 10-7—PTP message header.....	144
Table 10-8—Values for messageType field	145
Table 10-9—Values of flag bits.....	146
Table 10-10—messageTypeSpecific semantics	147
Table 10-11—Announce message fields	148
Table 10-12—Path trace TLV	149
Table 10-13—Signaling message fields	150
Table 10-14—Message interval request TLV	151
Table 10-15—Interpretation of special values of logLinkDelayInterval.....	152
Table 10-16—Interpretation of special values of logTimeSyncInterval	152
Table 10-17—Interpretation of special values of logAnnounceInterval	153
Table 10-18—Definitions of bits of flags field of message interval request TLV	153
Table 10-19—gPTP-capable TLV.....	154
Table 10-20—gPTP-capable message interval request TLV.....	155
Table 10-21—Interpretation of special values of logGtpCapableMessageInterval.....	156
Table 11-1—Value of meanLinkDelayThresh for various links	169
Table 11-2—Summary of scope of global variables used by time synchronization state machines (see 10.2.4 and 10.2.5).....	171
Table 11-3—Destination address for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages	196
Table 11-4—EtherType for Sync, Follow_Up, Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages	196
Table 11-5—Values for messageType field	198
Table 11-6—Value of correctionField.....	199
Table 11-7—References for sequenceId value exceptions.....	199
Table 11-8—Sync message fields if twoStep flag is TRUE.....	200
Table 11-9—Sync message fields if twoStep flag is FALSE.....	200
Table 11-10—Follow_Up message fields	201
Table 11-11—Follow_Up information TLV	202
Table 11-12—Pdelay_Req message fields	203
Table 11-13—Pdelay_Resp message fields.....	204
Table 11-14—Pdelay_Resp_Follow_Up message fields	204
Table 12-1—Values of bits of tmFtmSupport	214
Table 12-2—FTM parameters relevant to time-synchronization transport	227
Table 12-3—Values of Burst Duration and Min Delta FTM, for each value of currentLogSyncInterval .	228
Table 12-4—Values of the Type field in the VendorSpecific information element.....	228
Table 13-1—TIMESYNC message fields	235
Table 14-1—defaultDS table	251
Table 14-2—currentDS table.....	253
Table 14-3—parentDS table	255

Table 14-4—timePropertiesDS table.....	256
Table 14-5—pathTraceDS table	257
Table 14-6—acceptableMasterTableDS table	258
Table 14-7—portState enumeration.....	258
Table 14-8—delayMechanism enumeration.....	259
Table 14-9—Description of pdelayTruncatedTimestampsArray	266
Table 14-10—portDS table.....	267
Table 14-11—descriptionPortDS table.....	269
Table 14-12—portStatisticsDS table	272
Table 14-13—acceptableMasterPortDS table	273
Table 14-14—externalPortConfigurationPortDS table	274
Table 14-15—asymmetryMeasurementModeDS table	274
Table 14-16—commonServicesPortDS table.....	275
Table 14-17—cmlDsDefaultDS table.....	276
Table 14-18—cmlDsLinkPortDS table	280
Table 14-19—cmlDsLinkPortStatisticsDS table.....	282
Table 14-20—cmlDsAsymmetryMeasurementModeDS table.....	283
Table 15-1—IEEE8021-AS-V2 MIB structure and object cross reference.....	285
Table 16-1—CSN TLV	375
Table 16-2—Definitions and option selections per link technology	377
Table B-1—Wander generation TDEV requirement for LocalClock entity	399
Table B-2—ADEV limit corresponding to wander generation requirement of Table B-1	400
Table B-3—PTPDEV limit corresponding to wander generation requirement of Table B-1	401
Table B-4—Maximum endpoint filter bandwidths needed to meet respective MTIE masks and peak-to-peak jitter limits	403
Table B-5—Breakpoints for Mask 1	404
Table B-6—Breakpoints for Mask 2	404
Table C-1—Timescale parameters	405
Table C-2—Timescale conversions.....	408