

# ISO/IEC 18000-63:2021-11 (E)

## Information technology - Radio frequency identification for item management - Part 63: Parameters for air interface communications at 860 MHz to 960 MHz Type C

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Symbols, abbreviated terms and notation .....	5
4.1	Symbols .....	5
4.2	Abbreviated terms .....	7
4.3	Notation .....	8
5	Conformance .....	9
5.1	Claiming conformance .....	9
5.2	General conformance requirements .....	9
5.2.1	Interrogators .....	9
5.2.2	Tags .....	10
5.3	Command structure and extensibility .....	10
5.3.1	General .....	10
5.3.2	Mandatory commands .....	10
5.3.3	Optional commands .....	10
5.3.4	Proprietary commands .....	10
5.3.5	Custom commands .....	10
5.4	Reserved for Future Use (RFU) .....	11
5.5	Cryptographic Suite Indicators .....	11
6	Protocol requirements .....	11
6.1	Protocol overview .....	11
6.1.1	Physical layer .....	11
6.1.2	Tag-identification layer .....	11
6.2	Protocol parameters .....	12
6.2.1	Signaling -- Physical and media access control parameters .....	12
6.2.2	Logical -- Operating procedure parameters .....	15
6.3	Description of operating procedure .....	15
6.3.1	Physical interface .....	16
6.3.2	Logical interface .....	37
7	Battery Assisted Passive (BAP) Interrogator Talks First systems (optional) .....	112
7.1	Applicability .....	112
7.2	General overview, definitions, and requirements of BAP .....	113
7.3	BAP inventoried flag and state machine behaviour modifications .....	114
7.3.1	Modification to ready state and power-down support for BAP Tags .....	114
7.3.2	Signal loss tolerance via timer (mandatory) .....	115
7.3.3	Modified persistence of BAP PIE inventory flags (optional) .....	117
7.4	BAP PIE (optional) .....	119
7.4.1	Flex_Query command (optional) .....	119
7.4.2	BAP PIE detailed operation including optional Battery Saver Mode .....	121
7.5	Manchester mode Battery Assisted operation protocol extensions .....	126

7.5.1	General .....	126
7.5.2	Physical layer .....	127
7.5.3	Manchester activation .....	133
7.5.4	Commands summary .....	148
8	Sensor support (optional) .....	163
8.1	Applicability .....	163
8.2	Overview .....	163
8.3	Real Time Clock (RTC) .....	164
8.3.1	General .....	164
8.3.2	Setting the RTC .....	164
8.3.3	BroadcastSync command (optional) .....	165
8.3.4	Time synchronisation .....	165
8.4	HandleSensor command (optional) .....	166
8.5	Simple Sensors .....	167
8.5.1	Simple Sensor implementation .....	167
8.6	Full Function Sensors and Sensor Directory System .....	169
8.6.1	General .....	169
8.6.2	Sensor Access -- General approach .....	170
8.7	Snapshot Sensors .....	176
8.7.1	General .....	176
8.7.2	Initiating Snapshot Sensor measurements .....	179
8.7.3	Reporting Snapshot Sensor Information .....	180
Annex A (normative) Extensible bit vectors (EBV) .....		182
Annex B (normative) State-transition tables .....		183
Annex C (normative) Command-response tables .....		240
Annex D (informative) Example slot-count (Q) selection algorithm .....		267
Annex E (informative) Example Tag inventory and access .....		268
Annex F (informative) Calculation of 5-bit and 16-bit cyclic redundancy checks .....		269
Annex G (normative) Multiple- and dense-Interrogator channelized signaling .....		271
Annex H (informative) Interrogator-to-Tag link modulation .....		274
Annex I (normative) Error codes .....		276
Annex J (normative) Slot counter .....		278
Annex K (informative) Example data-flow exchange .....		279
Annex L (informative) Optional Tag features .....		282
Annex M (informative) Cryptographic-Suite checklist .....		285
Annex N (informative) Battery Assisted Tag to Interrogator synchronization .....		286
Annex O (normative) Simple Sensors Data Block .....		289
Annex P (normative) Record structures and commands for Ported Simple Sensors .....		300
Annex Q (informative) Battery Assisted Passive (BAP) PIE and Manchester mode tutorial guide ...		316
Annex R (informative) Manchester mode RF power control .....		327
Bibliography .....		332