

ISO/IEC 17913:2000-06 (E)

Information technology - 12,7 mm 128-track magnetic tape cartridge for information interchange - Parallel serpentine format

| Contents | | Page |
|----------------------------|--|-------------|
| Section 1 - General | | 1 |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 2.1 | Magnetic tape cartridge | 1 |
| 2.2 | Generating system | 1 |
| 2.3 | Receiving system | 1 |
| 3 | Normative references | 1 |
| 4 | Definitions | 1 |
| 4.1 | algorithm | 1 |
| 4.2 | anhysteretic erase | 1 |
| 4.3 | average signal amplitude | 2 |
| 4.4 | azimuth | 2 |
| 4.5 | back surface | 2 |
| 4.6 | beginning of partition (BOP) | 2 |
| 4.7 | beginning of tape (BOT) | 2 |
| 4.8 | cartridge | 2 |
| 4.9 | cyclic redundancy check (CRC) character | 2 |
| 4.10 | end of tape (EOT) | 2 |
| 4.11 | error-correcting code (ECC) | 2 |
| 4.12 | error-detecting code (EDC) | 2 |
| 4.13 | File Mark | 2 |
| 4.14 | flux transition position | 2 |
| 4.15 | flux transition spacing | 2 |
| 4.16 | half-wrap | 2 |
| 4.17 | logical block | 2 |
| 4.18 | logical forward | 2 |
| 4.19 | logical reverse | 2 |
| 4.20 | magnetic tape | 2 |
| 4.21 | mark tach count | 2 |
| 4.22 | Master Standard Reference Tape | 2 |
| 4.23 | physical recording density | 2 |
| 4.24 | pre-record condition | 2 |
| 4.25 | recorded element | 2 |
| 4.26 | Reference Field | 2 |
| 4.27 | resync character | 2 |
| 4.28 | SDM set | 2 |
| 4.29 | Secondary Standard Reference Tape (SSRT) | 2 |
| 4.30 | servo track | 3 |
| 4.31 | Standard Reference Amplitude (SRA) | 3 |
| 4.32 | Standard Reference Current (I_r) | 3 |
| 4.33 | Test Recording Current (I_m) | 3 |
| 4.34 | track | 3 |
| 4.35 | track group | 3 |
| 4.36 | trailer | 3 |
| 4.37 | Typical Field | 3 |
| 4.38 | write equalisation | 3 |

| | | |
|---|--|----------|
| 5 | Conventions and notations | 3 |
| 5.1 | Representation of numbers | 3 |
| 5.2 | Dimensions | 3 |
| 5.3 | Names | 3 |
| 5.4 | Acronyms | 3 |
| 6 | Environment and safety | 4 |
| 6.1 | Cartridge and tape testing environment | 4 |
| 6.2 | Cartridge operating environment | 4 |
| 6.3 | Cartridge storage environment | 4 |
| 6.4 | Safety | 5 |
| 6.4.1 | Safeness | 5 |
| 6.4.2 | Flammability | 5 |
| 6.5 | Transportation | 5 |
| Section 2 - Requirements for the unrecorded tape | | 5 |
| 7 | Mechanical and electrical requirements | 5 |
| 7.1 | Material | 5 |
| 7.2 | Tape length | 5 |
| 7.3 | Width | 5 |
| 7.4 | Total thickness | 5 |
| 7.5 | Base material thickness | 5 |
| 7.6 | Discontinuity | 5 |
| 7.7 | Longitudinal curvature | 5 |
| 7.7.1 | Requirement | 5 |
| 7.7.2 | Procedure | 5 |
| 7.8 | Out-of-Plane distortions | 5 |
| 7.9 | Cupping | 6 |
| 7.9.1 | Requirement | 6 |
| 7.9.2 | Procedure | 6 |
| 7.10 | Coefficient of dynamic friction | 6 |
| 7.10.1 | Requirements | 6 |
| 7.10.2 | Procedure | 6 |
| 7.11 | Coating adhesion | 7 |
| 7.12 | Layer-to-layer adhesion | 7 |
| 7.12.1 | Requirements | 7 |
| 7.12.2 | Procedure | 7 |
| 7.13 | Electrical resistance | 8 |
| 7.13.1 | Requirement | 8 |
| 7.13.2 | Procedure | 8 |
| 7.14 | Abrasivity | 9 |
| 7.15 | Friction characteristics after stress | 9 |
| 7.15.1 | Requirements | 9 |
| 7.15.2 | Procedure | 9 |
| 7.16 | Surface roughness | 9 |
| 7.16.1 | Requirement | 9 |
| 7.16.2 | Procedure | 9 |
| 7.17 | Inhibitor tape | 10 |

| | | |
|--|---|-----------|
| 8 | Magnetic recording characteristics | 10 |
| 8.1 | Typical Field | 10 |
| 8.2 | Signal amplitude | 10 |
| 8.3 | Resolution | 10 |
| 8.4 | Broad-band signal-to-noise ratio (BBSNR) | 10 |
| 8.4.1 | Requirement | 10 |
| 8.4.2 | Procedure | 10 |
| 9 | Tape quality | 11 |
| 9.1 | Missing pulse | 11 |
| 9.1.1 | Requirement | 11 |
| 9.1.2 | Procedure | 11 |
| 9.2 | Coincident missing pulse | 11 |
| 9.2.1 | Requirement | 11 |
| 9.2.2 | Procedure | 11 |
| 9.3 | Missing pulse density | 12 |
| 9.3.1 | Requirement | 12 |
| 9.3.2 | Procedure | 12 |
| 9.4 | Tape durability | 12 |
| Section 3 - Mechanical specifications of the tape cartridge | | 12 |
| 10 | General | 12 |
| 10.1 | Overall dimensions | 13 |
| 10.2 | Write-inhibit mechanism | 13 |
| 10.3 | Label areas of the rear side | 13 |
| 10.4 | Label area on the top side | 14 |
| 10.5 | Case opening | 14 |
| 10.6 | Locating notches | 14 |
| 10.7 | Locating areas | 15 |
| 10.8 | Inside configuration of the case around the case opening | 15 |
| 10.9 | Other external dimensions of the case | 15 |
| 10.10 | Central window | 15 |
| 10.11 | Stacking ribs | 16 |
| 10.12 | Recessed area | 16 |
| 10.13 | Flexibility of the case | 16 |
| 10.13.1 | Requirements | 16 |
| 10.13.2 | Procedure | 17 |
| 10.14 | Tape reel | 17 |
| 10.14.1 | Locking mechanism | 17 |
| 10.14.2 | Axis of rotation of the reel | 17 |
| 10.14.3 | Metallic insert | 17 |
| 10.14.4 | Toothed rim | 17 |
| 10.14.5 | Hub of the reel | 18 |
| 10.14.6 | Relative positions | 18 |
| 10.14.7 | Characteristics of the toothed rim | 19 |
| 10.15 | Leader block | 19 |
| 10.16 | Attachment of the tape to the leader block | 20 |
| 10.17 | Latching mechanism | 20 |
| 10.18 | Tape wind | 20 |
| 10.19 | Wind tension | 20 |
| 10.20 | Circumference of the tape reel | 20 |
| 10.21 | Moment of inertia | 21 |
| 10.22 | Material | 21 |

| | | |
|--|--|-----------|
| 10.23 | Cartridge identification notches | 21 |
| 10.24 | Finger slot | 21 |
| Section 4 - Requirements for an interchanged tape | | 31 |
| 11 | Method of recording | 31 |
| 11.1 | Physical recording density | 31 |
| 11.2 | Bit cell length | 31 |
| 11.3 | Average bit cell length | 31 |
| 11.3.1 | Long-term average RLL bit cell length | 31 |
| 11.3.2 | Short-term average RLL bit cell length | 31 |
| 11.4 | Rate of change of the short-term average RLL bit cell length | 31 |
| 11.5 | Bit shift | 31 |
| 11.6 | Total character skew | 31 |
| 11.7 | Missing zero-crossing zones | 32 |
| 11.8 | Coincident missing zero-crossing zones | 32 |
| 12 | Servo tracks | 32 |
| 12.1 | Locations of the servo tracks | 32 |
| 12.2 | Physical width of the servo tracks | 33 |
| 12.3 | Format of the servo tracks | 33 |
| 12.4 | Servo requirements | 34 |
| 12.4.1 | Servo amplitude | 34 |
| 12.4.2 | Servo azimuth | 34 |
| 12.4.3 | Servo errors | 34 |
| 12.4.4 | Servo edge spacing | 35 |
| 12.5 | Procedure | 35 |
| 13 | Data track format | 35 |
| 13.1 | Number of data tracks | 35 |
| 13.2 | Track positions | 35 |
| 13.3 | Track width | 37 |
| 13.4 | Data azimuth | 37 |
| 13.5 | Half-wraps | 37 |
| 14 | Tape format | 37 |
| 14.1 | General | 37 |
| 14.2 | Recording area | 37 |
| 14.3 | Tach count | 39 |
| 14.4 | Physical blocks | 39 |
| 14.5 | Servo acquisition region | 40 |
| 14.6 | Volume control region | 40 |
| 14.7 | Data region | 40 |
| 14.8 | Data entities | 40 |
| 15 | Packet format | 42 |
| 15.1 | Packet header | 43 |
| 15.2 | Packet data | 45 |
| 15.3 | Packet trailer | 45 |
| 16 | Device blocks | 45 |
| 16.1 | Data device blocks | 45 |
| 16.2 | Mark device blocks | 45 |
| 16.3 | File Mark | 45 |
| 16.4 | Void mark | 46 |
| 16.5 | Beginning of half-wrap mark | 46 |
| 16.6 | End of half-wrap mark | 46 |
| 16.7 | BOP mark | 46 |

| | | |
|----------------|--|-----------|
| 16.8 | EOD mark | 46 |
| 16.9 | SDM mark | 46 |
| 16.10 | FID mark | 47 |
| 16.11 | DBM mark | 48 |
| 16.11.1 | DBM general information packet | 48 |
| 16.11.2 | DBM wrap region packet | 49 |
| 16.11.3 | DBM partitions packet | 49 |
| 16.11.4 | DBM servo demark packet | 50 |
| 16.11.5 | DBM File Mark packet | 50 |
| 16.12 | SARS mark | 51 |
| 16.13 | DBM checked out mark | 51 |
| 16.14 | DBM valid mark | 51 |
| 17 | Device block format | 51 |
| 17.1 | Device block header | 51 |
| 17.1.1 | Device block control | 52 |
| 17.1.2 | Device block sequence control | 54 |
| 17.1.3 | Vendor identification code | 54 |
| 17.2 | Device block data | 54 |
| 17.3 | Device block trailer | 54 |
| 18 | ECC | 54 |
| 18.1 | CRC | 54 |
| 18.2 | Code block | 55 |
| 18.3 | ECC encoded code block | 55 |
| 18.4 | Codeword correction code generation | 56 |
| 18.5 | MIE pointer code generation | 57 |
| 18.6 | ECC encoded interleave unit | 57 |
| 18.7 | Short error correction code generation | 57 |
| 19 | Recording of bytes on tape | 59 |
| 19.1 | Synchronisation format | 59 |
| 19.2 | Interblock gap formatting | 62 |
| 19.3 | RLL byte translation | 63 |
| 19.4 | Write equalisation bit translation | 63 |
| 19.5 | Writing bits on tape | 63 |
| Annexes | | |
| A | Tape abrasivity measurement procedure | 64 |
| B | Media type label | 66 |
| C | Measurement of bit shift | 70 |
| D | Vendor Identification Code | 72 |
| E | Recommendations for transportation | 73 |
| F | Inhibitor tape | 74 |
| G | Tape durability | 75 |