ISO/IEC 23090-10:2022-05 (E)

Information technology - Coded representation of immersive media - Part 10: Carriage of visual volumetric video-based coding data

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Abbreviated terms 2

5 Overview 3
5.1 General 3
5.2 Overall architecture for carriage of V3C data 3
5.3 Summary of referenceable code points 4
5.3.1 Brands 4
5.3.2 Uniform resource names 4
5.3.3 Restricted scheme types 4
5.3.4 Sample entry types 4
5.3.5 Box types 5
5.3.6 Track reference types 6
5.3.7 Track grouping types 6
5.3.8 Entity grouping types 6
5.3.9 Sample grouping types 7

6 Volumetric media 7
6.1 General 7
6.2 Volumetric visual media 7
6.3 Volumetric visual media header 7
6.3.1 Definition 7
6.3.2 Syntax 7
6.3.3 Semantics 7
6.4 Volumetric visual sample entry 7
6.4.1 Definition 7
6.4.2 Syntax 7
6.4.3 Semantics 8
6.5 Volumetric visual sample group entry 8
6.6 Volumetric visual samples 8

7 Carriage of visual volumetric video-based coding data 8
7.1 General 8
7.2 Common boxes and data structures 8
7.2.1 V3C decoder configuration record 8
7.2.2 V3C decoder configuration box 10
7.2.3 V3C unit header box 10
7.2.4 V3C atlas parameter set sample group 10
7.2.5 Object switch alternatives box 11
7.3 Single track encapsulation of V3C data 11
7.3.1 General 11
7.3.2 V3C bitstream sample entry 12

7.3.3 V3C bitstream track sample format 12
7.4 Multi-track encapsulation of V3C data 13
7.4.1 General 13
7.4.2 V3C atlas sample entry 14
7.4.3 V3C atlas tile sample entry 16
7.4.4 V3C atlas sample format 17
7.4.5 V3C video component track 18
7.4.6 Track references 19
7.4.7 Track alternatives and track grouping 19
7.4.8 Playout groups 20
7.4.9 Summary 20

8 Carriage of non-timed visual volumetric video-based coding data 21
8.1 General 21
8.2 V3C atlas item 22
8.3 V3C atlas tile item 22
8.4 V3C component item 22
8.5 V3C-related item properties 23
8.5.1 General 23
8.5.2 V3C configuration item property 23
8.5.3 V3C unit header item property 23
8.5.4 V3C atlas tile configuration item property 24
8.5.5 Playout groups 24

9 Partial access of volumetric visual data 25
9.1 General 25
9.2 Common data structures 25
9.2.1 3D vector 25
9.2.2 Spatial region bounding box 25
9.2.3 Tile mapping 26
9.2.4 Object collection 27
9.3 Spatial region information structure 29
9.3.1 Definition 29
9.3.2 Syntax 29
9.3.3 Semantics 29
9.4 V3C tile video component track grouping 29
9.4.1 Definition 29
9.4.2 Syntax 30
9.4.3 Semantics 30
9.5 Volumetric media bounding box 30
9.5.1 Definition 30
9.5.2 Syntax 31
9.6 Static spatial region collection box 31
9.6.1 Definition 31
9.6.2 Syntax 31
9.6.3 Semantics 31
9.7 Dynamic spatial region information 31
9.7.1 General 31
9.7.2 Sample entry 32
9.7.3 Sample format 32
9.7.4 Sync samples 32
9.8 Storage of atlas tiles using NALUMapEntry 32

10 Viewport information 33
10.1 General 33
10.2 Structures 33
10.2.1 Extrinsic camera information 33
10.2.2 Intrinsic camera information 34
10.2.3 Viewport information 35
10.3 Viewport information timed-metadata track 35
10.3.1 General 35

10.3.2 Viewport information sample entry 35
10.3.3 Viewport information sample format 37

11 Encapsulation and signalling in MPEG-DASH 38
11.1 Single track mode 38
11.2 Multi-track mode 38
11.2.1 General 38
11.2.2 V3C preselections 39
11.2.3 V3C atlas tile preselections 40
11.3 DASH MPD descriptors for V3C content 40
11.3.1 XML namespace and schema 40
11.3.2 V3C video component descriptor 40
11.3.3 V3C descriptor 43
11.4 Supporting multiple versions of a V3C media 44
11.5 Switching codecs for V3C video components 44
11.6 Signalling spatial regions for partial access 44
11.6.1 Static spatial regions 44
11.6.2 Dynamic spatial regions 47
11.7 Signalling recommended viewports 47
11.7.1 Static viewports 47
11.7.2 Dynamic viewports 49

12 Encapsulation and signalling MMT 49
12.1 Introduction 49
12.2 MMT signalling descriptors for V3C content 50
12.2.1 Asset reference descriptor 50
12.2.2 V3C Asset descriptor 51
12.3 MMT signalling messages for V3C Content 52
12.3.1 General 52
12.3.2 V3C Asset Group message 52
12.3.3 V3C Selection message 54
12.3.4 V3C View Change Feedback message 55

Annex A (normative) File format toolsets and brands 58

Annex B (normative) V3C DASH schema 59

Annex C (normative) MIME types and sub-parameters 61

Annex D (informative) DASH MPD examples 62

Annex E (informative) Partial access utilizing V3C volumetric annotation SEI message family 77

Annex F (informative) Partial access using volumetric information timed-metadata tracks 80

Annex G (informative) Partial access for overlapping spatial subdivisions 82

Annex H (informative) Examples of using alternate groups 83

Bibliography 85