

# ISO/IEC TR 18053:2000-07 (E)

## Information technology\_ - Telecommunications and information exchange between systems\_ - Glossary of definitions and terminology for Computer Supported Telecommunications Applications (CSTA) phase\_III

---

### Contents

Foreword	x
Introduction	xi
1 Scope	1
2 Normative references	1
3 Definitions and Acronyms	1
3.1 Account Code	1
3.2 ACD	1
3.3 ACD Group	1
3.4 ACD Group Device	1
3.5 Acknowledgement	1
3.6 Acknowledgement Model	1
3.7 ACSE	1
3.8 Active Call	1
3.9 Active Participation	1
3.10 Addressability	1
3.11 Addressable Appearance	1
3.12 Addressable Device	2
3.13 Agent	2
3.14 Agent Group Association	2
3.15 Agent Identifier	2
3.16 Agent Logging State	2
3.17 Agent Password	2
3.18 Agent State	2
3.19 Agent State Model	2
3.20 Alerting	2
3.21 Alerting Call	2
3.22 Alerting Connection State	2
3.23 Allocation Condition	2
3.24 Analogue	2
3.25 Analogue Line	2
3.26 ANI	2
3.27 API	2
3.28 Appearance	2
3.29 Appearance Type	3
3.30 Application Association	3
3.31 Application Context	3
3.32 Application Domain	3
3.33 Application Entity	3
3.34 Application Entity Type	3
3.35 Application Service Element	3
3.36 Application Working Domain	3
3.37 ASE	3
3.38 ASN	3
3.39 Association Control Service Element	3
3.40 Asynchronous	3
3.41 ATM	3
3.42 Atomic Acknowledgement Model	3
3.43 Auditory Apparatus	3
3.44 Auditory Apparatus Identifier	3
3.45 Auditory Apparatus Type	4
3.46 Authorisation Code	4
3.47 Auto-Answer	4
3.48 Auto Work Mode	4

<b>3.49</b>	Automatic Call Distributor <sup>4</sup>	
<b>3.50</b>	Automatic Number Identification	<b>4</b>
<b>3.51</b>	B Channel	<b>4</b>
<b>3.52</b>	Bandwidth	<b>4</b>
<b>3.53</b>	Bearer Mode	<b>4</b>
<b>3.54</b>	Bearer Services	<b>4</b>
<b>3.55</b>	Bit Rate	<b>4</b>
<b>3.56</b>	BRI	<b>4</b>
<b>3.57</b>	Bridging	<b>4</b>
<b>3.58</b>	BRI-ISDN	<b>4</b>
<b>3.59</b>	Button	<b>5</b>
<b>3.60</b>	Button Associated Number	<b>5</b>
<b>3.61</b>	Button Association	<b>5</b>
<b>3.62</b>	Button Function	<b>5</b>
<b>3.63</b>	Button Identifier	<b>5</b>
<b>3.64</b>	Button Label	<b>5</b>
<b>3.65</b>	Call	<b>5</b>
<b>3.66</b>	Call Appearance	<b>5</b>
<b>3.67</b>	Call Associated Event	<b>5</b>
<b>3.68</b>	Call Associated Feature	<b>5</b>
<b>3.69</b>	Call Control Event	<b>5</b>
<b>3.70</b>	Call Control Information Element	<b>5</b>
<b>3.71</b>	Call Detail Record	<b>5</b>
<b>3.72</b>	Call Event Report	<b>5</b>
<b>3.73</b>	Call Identifier	<b>5</b>
<b>3.74</b>	Call Linkage	<b>5</b>
<b>3.75</b>	Call Qualification Data	<b>5</b>
<b>3.76</b>	Call Related Information	<b>6</b>
<b>3.77</b>	Call State	<b>6</b>
<b>3.78</b>	Call Thread	<b>6</b>
<b>3.79</b>	Callback	<b>6</b>
<b>3.80</b>	CallBack Call	<b>6</b>
<b>3.81</b>	Called Line Identity	<b>6</b>
<b>3.82</b>	CallID Only Connection ID	<b>6</b>
<b>3.83</b>	Calling Line Identification	<b>6</b>
<b>3.84</b>	Call-Type Monitor	<b>6</b>
<b>3.85</b>	Capabilities Exchange	<b>6</b>
<b>3.86</b>	CCIE	<b>6</b>
<b>3.87</b>	CDR	<b>6</b>
<b>3.88</b>	Central Office (CO) Line	<b>6</b>
<b>3.89</b>	Central Office (CO) Switch	<b>6</b>
<b>3.90</b>	Channel	<b>6</b>
<b>3.91</b>	Character Set	<b>7</b>
<b>3.92</b>	Classifier	<b>7</b>
<b>3.93</b>	CODEC	<b>7</b>
<b>3.94</b>	Complete Connection ID	<b>7</b>
<b>3.95</b>	Compound Call State	<b>7</b>
<b>3.96</b>	Computing Domain	<b>7</b>
<b>3.97</b>	Computing Function	<b>7</b>
<b>3.98</b>	Computing Sub-Domain	<b>7</b>
<b>3.99</b>	Conference Call	<b>7</b>
<b>3.100</b>	Connected State	<b>7</b>
<b>3.101</b>	Connection	<b>7</b>
<b>3.102</b>	Connection Identifier	<b>7</b>
<b>3.103</b>	Connection Mode	<b>7</b>
<b>3.104</b>	Connection Rate	<b>7</b>
<b>3.105</b>	Connection State	<b>7</b>
<b>3.106</b>	Connection State Transition	<b>7</b>

<b>3.107</b>	Connection State Transition Graph	<b>8</b>
<b>3.108</b>	Consultation Call	<b>8</b>
<b>3.109</b>	Correlator Data	<b>8</b>
<b>3.110</b>	CSTA	<b>8</b>
<b>3.111</b>	CSTA Application	<b>8</b>
<b>3.112</b>	CSTA Client	<b>8</b>
<b>3.113</b>	CSTA Device	<b>8</b>
<b>3.114</b>	CSTA Domain	<b>8</b>
<b>3.115</b>	CSTA Object	<b>8</b>
<b>3.116</b>	CTI	<b>8</b>
<b>3.117</b>	D Channel	<b>8</b>
<b>3.118</b>	Data Call	<b>8</b>
<b>3.119</b>	Data Connection	<b>8</b>
<b>3.120</b>	Data Path	<b>8</b>
<b>3.121</b>	Data Path State	<b>8</b>
<b>3.122</b>	Data Rate	<b>8</b>
<b>3.123</b>	DD	<b>8</b>
<b>3.124</b>	Default Value	<b>8</b>
<b>3.125</b>	Defined Parameter Type	<b>9</b>
<b>3.126</b>	Delay Tolerance	<b>9</b>
<b>3.127</b>	Device	<b>9</b>
<b>3.128</b>	Device Capabilities	<b>9</b>
<b>3.129</b>	Device Category	<b>9</b>
<b>3.130</b>	Device Configuration	<b>9</b>
<b>3.131</b>	Device Element	<b>9</b>
<b>3.132</b>	Device Element Combination	<b>9</b>
<b>3.133</b>	Device Feature	<b>9</b>
<b>3.134</b>	Device Identifier	<b>9</b>
<b>3.135</b>	Device Identifier Format	<b>9</b>
<b>3.136</b>	Device Identifier Status	<b>9</b>
<b>3.137</b>	Device Media Characteristics	<b>9</b>
<b>3.138</b>	Device Only Connection ID	<b>9</b>
<b>3.139</b>	Device State	<b>9</b>
<b>3.140</b>	Device Type	<b>10</b>
<b>3.141</b>	Device-Type Monitor	<b>10</b>
<b>3.142</b>	Dialled Number Identification Service	<b>10</b>
<b>3.143</b>	Digital Line	<b>10</b>
<b>3.144</b>	Directory Number	<b>10</b>
<b>3.145</b>	Display	<b>10</b>
<b>3.146</b>	Display ID	<b>10</b>
<b>3.147</b>	DND	<b>10</b>
<b>3.148</b>	DNIS	<b>10</b>
<b>3.149</b>	Do Not Disturb	<b>10</b>
<b>3.150</b>	Domain	<b>10</b>
<b>3.151</b>	DTMF	<b>10</b>
<b>3.152</b>	Dual Tone Multiple Frequency	<b>10</b>
<b>3.153</b>	Dynamic Device Identifier	<b>10</b>
<b>3.154</b>	Dynamic Feature Availability	<b>10</b>
<b>3.155</b>	Encoding Algorithm	<b>11</b>
<b>3.156</b>	End-to-End	<b>11</b>
<b>3.157</b>	Entering Distribution	<b>11</b>
<b>3.158</b>	Error Value	<b>11</b>
<b>3.159</b>	Event	<b>11</b>
<b>3.160</b>	Event Cause	<b>11</b>
<b>3.161</b>	Event Report	<b>11</b>
<b>3.162</b>	Event Template	<b>11</b>
<b>3.163</b>	Extension	<b>11</b>
<b>3.164</b>	Flow Direction	<b>11</b>

<b>3.165</b>	Forwarding	<b>11</b>
<b>3.166</b>	Forwarding Condition	<b>11</b>
<b>3.167</b>	Gain	<b>11</b>
<b>3.168</b>	Global Call	<b>11</b>
<b>3.169</b>	Global Call ID	<b>11</b>
<b>3.170</b>	Group Device	<b>12</b>
<b>3.171</b>	Held Call	<b>12</b>
<b>3.172</b>	Hold	<b>12</b>
<b>3.173</b>	Hold Connection State	<b>12</b>
<b>3.174</b>	Holding Device	<b>12</b>
<b>3.175</b>	Hookswitch	<b>12</b>
<b>3.176</b>	Hookswitch Association	<b>12</b>
<b>3.177</b>	Hunt Group	<b>12</b>
<b>3.178</b>	ID	<b>12</b>
<b>3.179</b>	Identifier Parameter Type	<b>12</b>
<b>3.180</b>	Inband	<b>12</b>
<b>3.181</b>	Inbound Call	<b>12</b>
<b>3.182</b>	Incoming Call	<b>12</b>
<b>3.183</b>	Integrated Services Digital Network	<b>12</b>
<b>3.184</b>	Intrude	<b>13</b>
<b>3.185</b>	I/O Cross Reference Identifier	<b>13</b>
<b>3.186</b>	I/O Services	<b>13</b>
<b>3.187</b>	ISDN	<b>13</b>
<b>3.188</b>	ISO	<b>13</b>
<b>3.189</b>	ITU-T	<b>13</b>
<b>3.190</b>	Join	<b>13</b>
<b>3.191</b>	KBPS	<b>13</b>
<b>3.192</b>	Lamp	<b>13</b>
<b>3.193</b>	Lamp Colour	<b>13</b>
<b>3.194</b>	Lamp Identifier	<b>13</b>
<b>3.195</b>	Lamp Label	<b>13</b>
<b>3.196</b>	Lamp Mode	<b>13</b>
<b>3.197</b>	LAN	<b>13</b>
<b>3.198</b>	Last Redirection Device	<b>13</b>
<b>3.199</b>	Line	<b>13</b>
<b>3.200</b>	Logical Device Event	<b>13</b>
<b>3.201</b>	Logical Device Features	<b>14</b>
<b>3.202</b>	Logical Display	<b>14</b>
<b>3.203</b>	Logical Element	<b>14</b>
<b>3.204</b>	MAD	<b>14</b>
<b>3.205</b>	Maintenance Event	<b>14</b>
<b>3.206</b>	Manual Mode	<b>14</b>
<b>3.207</b>	Media	<b>14</b>
<b>3.208</b>	Media Access Device	<b>14</b>
<b>3.209</b>	Media Call Characteristics	<b>14</b>
<b>3.210</b>	Media Class	<b>14</b>
<b>3.211</b>	Media Service	<b>14</b>
<b>3.212</b>	Media Service Instance	<b>14</b>
<b>3.213</b>	Media Service Type	<b>14</b>
<b>3.214</b>	Media Stream	<b>14</b>
<b>3.215</b>	Media Stream Channel	<b>14</b>
<b>3.216</b>	Media Stream Event	<b>14</b>
<b>3.217</b>	Media Stream ID	<b>14</b>
<b>3.218</b>	Media Stream Information	<b>14</b>
<b>3.219</b>	Media Type	<b>14</b>
<b>3.220</b>	Message	<b>15</b>
<b>3.221</b>	Message Identifier	<b>15</b>
<b>3.222</b>	Meta Parameter Type	<b>15</b>

<b>3.223</b>	Microphone	<b>15</b>
<b>3.224</b>	Monitor Type	<b>15</b>
<b>3.225</b>	Monitoring Services	<b>15</b>
<b>3.226</b>	Multi-Stage Dialling	<b>15</b>
<b>3.227</b>	Multi-Step Acknowledgement Model	<b>15</b>
<b>3.228</b>	Mute	<b>15</b>
<b>3.229</b>	Named Device Type	<b>15</b>
<b>3.230</b>	Network Interface Device	<b>15</b>
<b>3.231</b>	NID	<b>15</b>
<b>3.232</b>	Null Connection State	<b>15</b>
<b>3.233</b>	Null Correlator Data	<b>15</b>
<b>3.234</b>	ODP	<b>15</b>
<b>3.235</b>	Offered Mode	<b>16</b>
<b>3.236</b>	Off-Hook	<b>16</b>
<b>3.237</b>	On-Hook	<b>16</b>
<b>3.238</b>	Operator Device	<b>16</b>
<b>3.239</b>	Operator Group Device	<b>16</b>
<b>3.240</b>	OSI	<b>16</b>
<b>3.241</b>	Other Device	<b>16</b>
<b>3.242</b>	Other Group Device	<b>16</b>
<b>3.243</b>	Outband (Out of Band)	<b>16</b>
<b>3.244</b>	Outbound Call	<b>16</b>
<b>3.245</b>	Outgoing Call	<b>16</b>
<b>3.246</b>	PAC	<b>16</b>
<b>3.247</b>	Parameter Type	<b>16</b>
<b>3.248</b>	Parameter Type Template	<b>16</b>
<b>3.249</b>	Park	<b>16</b>
<b>3.250</b>	Park Device	<b>16</b>
<b>3.251</b>	Party	<b>17</b>
<b>3.252</b>	PBX	<b>17</b>
<b>3.253</b>	PDU	<b>17</b>
<b>3.254</b>	Physical Base	<b>17</b>
<b>3.255</b>	Physical Component	<b>17</b>
<b>3.256</b>	Physical Device Event	<b>17</b>
<b>3.257</b>	Physical Device Features	<b>17</b>
<b>3.258</b>	Physical Display	<b>17</b>
<b>3.259</b>	Physical Element	<b>17</b>
<b>3.260</b>	Pick	<b>17</b>
<b>3.261</b>	Pick Group	<b>17</b>
<b>3.262</b>	PICS	<b>17</b>
<b>3.263</b>	PICS Proforma	<b>17</b>
<b>3.264</b>	PISN	<b>17</b>
<b>3.265</b>	Plain Old Telephone Service	<b>17</b>
<b>3.266</b>	Position Pointer	<b>17</b>
<b>3.267</b>	POTS	<b>18</b>
<b>3.268</b>	Pre-Delivery	<b>18</b>
<b>3.269</b>	Predictive Dial Call	<b>18</b>
<b>3.270</b>	Predictive Dialling	<b>18</b>
<b>3.271</b>	PRI-ISDN	<b>18</b>
<b>3.272</b>	Primary Call	<b>18</b>
<b>3.273</b>	Private Event	<b>18</b>
<b>3.274</b>	Profile	<b>18</b>
<b>3.275</b>	Prompting	<b>18</b>
<b>3.276</b>	Protocol Information Conformance Statement	<b>18</b>
<b>3.277</b>	Protocol Specific Information	<b>18</b>
<b>3.278</b>	PSTN	<b>18</b>
<b>3.279</b>	PTN	<b>18</b>
<b>3.280</b>	Queue	<b>18</b>

<b>3.281</b>	Queued Call	<b>18</b>
<b>3.282</b>	Recall	<b>18</b>
<b>3.283</b>	Redirection Device	<b>18</b>
<b>3.284</b>	Remote Operations	<b>19</b>
<b>3.285</b>	Reorder Condition	<b>19</b>
<b>3.286</b>	Reporting Criteria	<b>19</b>
<b>3.287</b>	Request	<b>19</b>
<b>3.288</b>	Response	<b>19</b>
<b>3.289</b>	Ring Count	<b>19</b>
<b>3.290</b>	Ring Cycle	<b>19</b>
<b>3.291</b>	Ring Mode	<b>19</b>
<b>3.292</b>	Ring Pattern	<b>19</b>
<b>3.293</b>	Ringback Tone	<b>19</b>
<b>3.294</b>	Ringer	<b>19</b>
<b>3.295</b>	Ringer Identifier	<b>19</b>
<b>3.296</b>	Ringling Mode	<b>19</b>
<b>3.297</b>	ROSE	<b>19</b>
<b>3.298</b>	Routeing Cross Reference Identifier	<b>19</b>
<b>3.299</b>	Routeing Device	<b>19</b>
<b>3.300</b>	Routeing Dialogue	<b>19</b>
<b>3.301</b>	Routeing Registration Identifier	<b>20</b>
<b>3.302</b>	Routeing Server	<b>20</b>
<b>3.303</b>	RSVP	<b>20</b>
<b>3.304</b>	Secondary Call	<b>20</b>
<b>3.305</b>	Service	<b>20</b>
<b>3.306</b>	Service Boundary	<b>20</b>
<b>3.307</b>	Service Request	<b>20</b>
<b>3.308</b>	Service Response	<b>20</b>
<b>3.309</b>	Service Template	<b>20</b>
<b>3.310</b>	Signalling Capability	<b>20</b>
<b>3.311</b>	Silent Intrusion	<b>20</b>
<b>3.312</b>	Silent Monitoring	<b>20</b>
<b>3.313</b>	Silent Participation	<b>20</b>
<b>3.314</b>	Simple Call State	<b>20</b>
<b>3.315</b>	Snapshot Services	<b>20</b>
<b>3.316</b>	Speaker	<b>20</b>
<b>3.317</b>	Special Resource	<b>21</b>
<b>3.318</b>	Special Resource Domain	<b>21</b>
<b>3.319</b>	Special Resource Function	<b>21</b>
<b>3.320</b>	Special Resource Sub-Domain	<b>21</b>
<b>3.321</b>	Speech	<b>21</b>
<b>3.322</b>	SRF	<b>21</b>
<b>3.323</b>	State	<b>21</b>
<b>3.324</b>	Static Device Identifier	<b>21</b>
<b>3.325</b>	Station	<b>21</b>
<b>3.326</b>	Status Filter	<b>21</b>
<b>3.327</b>	Status Reporting Services	<b>21</b>
<b>3.328</b>	Switching Domain	<b>21</b>
<b>3.329</b>	Switching Function	<b>21</b>
<b>3.330</b>	Switching Function Capabilities	<b>21</b>
<b>3.331</b>	Switching Function Service	<b>21</b>
<b>3.332</b>	Switching Sub-Domain	<b>21</b>
<b>3.333</b>	Switching Sub-Domain Name	<b>21</b>
<b>3.334</b>	System Status Registration Identifier	<b>22</b>
<b>3.335</b>	System Status Services	<b>22</b>
<b>3.336</b>	TE	<b>22</b>
<b>3.337</b>	Telephony Process	<b>22</b>
<b>3.338</b>	Telephony Service	<b>22</b>

<b>3.339</b>	Telephony Tone	22
<b>3.340</b>	Template	22
<b>3.341</b>	TON	22
<b>3.342</b>	Trunk	22
<b>3.343</b>	User	22
<b>3.344</b>	User Data	22
<b>3.345</b>	User-User Information Element	22
<b>3.346</b>	UUIE	22
<b>3.347</b>	Voice	22
<b>3.348</b>	Voice Attribute	22
<b>3.349</b>	Voice Call	22
<b>3.350</b>	Voice Response Unit	23
<b>3.351</b>	Voice Stream Data	23
<b>3.352</b>	Voice Unit	23
<b>3.353</b>	Voice Unit State	23
<b>3.354</b>	VRU	23
<b>4</b>	Terms defined elsewhere	23