ISO/IEC 30161-2:2023-03 (E)

Internet of Things (IoT) - Data exchange platform for IoT services - Part 2: Transport interoperability between nodal points

Contents

Page

FOREWORD 3
INTRODUCTION 4
1 Scope 5
2 Normative references 5
3 Terms and definitions 5
4 Abbreviated terms 6
5 Overview 6
6 Functional requirements 8
6.1 General 8
6.2 Transport interoperability among nodal points 8
6.3 System parameters for an IoT system 9
6.4 Data exchange types and data transfer types 10
7 Functional sub-blocks 11
7.1 General 11
7.2 Definitions of functional sub-blocks 11
7.3 Interworking functional sub-block 12
7.3.1 General 12
7.3.2 Routing function 12
7.3.3 Forwarding function 13
7.4 Interoperability management functional sub-block 13
7.5 Interoperability control functional sub-block 14
8 Operation mechanism 14
8.1 General 14
8.2 Request-based transfer by static assignment 15
8.3 Request-based transfer by dynamic discovery 15
8.4 Data-based transfer by static assignment 15
8.5 Data-based transfer by dynamic discovery 15
Annex A (informative) Latency-critical IoT services 16
Annex B (informative) Storage strategy for latency-critical IoT services at a nodal point 17
B.1 General 17
B.2 Operation for latency critical IoT services 17
B.3 Operation for quick IoT data acquisition 18
B.4 Operation for data collection services 18
Bibliography 20

Figure 1 – Relationship with IoT Reference model 7
Figure 2 – IoT DEP network by multiple nodal points 8
Figure 3 – IoT data exchanged among IoT DEPs 8

Figure 4 – Functions and positions of nodal points 9
Figure 5 – Data exchange types and data transfer types 11
Figure 6 – Detailed functional blocks with functional sub-blocks in IoT DEP 12
Figure B.1 – Assignment process of latency-tolerant periods 17
Figure B.2 – Operation for quick IoT data acquisition 18
Figure B.3 – Operation for data collection services 19

Table 1 – System parameters for IoT system 10
Table 2 – Classification of operations of transferring IoT data among nodal points 14