

ISO/IEC 30161-2:2023-03 (E)

Internet of Things (IoT) - Data exchange platform for IoT services - Part 2: Transport interoperability between nodal points

Contents	Page
FOREWORD.....	3
INTRODUCTION.....	4
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	5
4 Abbreviated terms	6
5 Overview	6
6 Functional requirements	8
6.1 General.....	8
6.2 Transport interoperability among nodal points	8
6.3 System parameters for an IoT system	9
6.4 Data exchange types and data transfer types.....	10
7 Functional sub-blocks.....	11
7.1 General.....	11
7.2 Definitions of functional sub-blocks	11
7.3 Interworking functional sub-block	12
7.3.1 General	12
7.3.2 Routing function	12
7.3.3 Forwarding function	13
7.4 Interoperability management functional sub-block	13
7.5 Interoperability control functional sub-block	14
8 Operation mechanism.....	14
8.1 General.....	14
8.2 Request-based transfer by static assignment	15
8.3 Request-based transfer by dynamic discovery	15
8.4 Data-based transfer by static assignment.....	15
8.5 Data-based transfer by dynamic discovery	15
Annex A (informative) Latency-critical IoT services	16
Annex B (informative) Storage strategy for latency-critical IoT services at a nodal point	17
B.1 General.....	17
B.2 Operation for latency critical IoT services.....	17
B.3 Operation for quick IoT data acquisition	18
B.4 Operation for data collection services	18
Bibliography.....	20
Figure 1 – Relationship with IoT Reference model	7
Figure 2 – IoT DEP network by multiple nodal points	8
Figure 3 – IoT data exchanged among IoT DEPs	8

Figure 4 – Functions and positions of nodal points9

Figure 5 – Data exchange types and data transfer types 11

Figure 6 – Detailed functional blocks with functional sub-blocks in IoT DEP 12

Figure B.1 – Assignment process of latency-tolerant periods 17

Figure B.2 – Operation for quick IoT data acquisition 18

Figure B.3 – Operation for data collection services 19

Table 1 – System parameters for IoT system 10

Table 2 – Classification of operations of transferring IoT data among nodal points..... 14