ISO/IEC 15444-9:2023-05 (E)

Information technology - JPEG 2000 image coding system - Part 9: Interactivity tools, APIs and protocols

Contents

Page

1 Scope 1
2 Normative references 1
3 Definitions 2
3.1 JPEG 2000 definitions 2
3.2 HTTP definitions 2
3.3 JPIP definitions 2
3.4 Symbols 4
4 Abbreviations 6
5 Conventions 6
5.1 ABNF rules 6
5.2 File format ABNF rules 7
5.3 Key to graphical descriptions of boxes (informative) 7
6 General description 8
6.1 JPIP protocol 8
6.2 Purpose 9
7 Conformance 10
Annex A – The JPP-stream and JPT-stream media types 11
A.1 Introduction 11
A.2 Message header structure 12
A.3 Data-bins 14
A.4 Conventions for parsing and delivery of JPP-streams and JPT-streams 22
A.5 Conventions for JPP-stream or JPT-stream interoperability (informative) 22
Annex B – Sessions, channels, cache model and model-sets 23
B.1 Requests within a session vs. stateless requests 23
B.2 Channels and sessions 23
B.3 Cache model management 24
B.4 Interrogation and manipulation of model-sets 24
Annex C – Client request 25
C.1 Request syntax 25
C.2 Target identification fields 26
C.3 Fields for working with sessions and channels 28
C.4 View-window request fields 29
C.5 Metadata request fields 42
C.6 Data limiting request fields 48
C.7 Server control request fields 48
C.8 Cache management request fields 52
C.9 Upload request parameters 57
C.10 Client capability and preference request fields 57
Annex D – Server response signalling 65
D.1 Reply syntax 65
D.2 JPIP response headers 67
D.3 Response data 72

Annex E – Uploading images to the server 73
E.1 Introduction 73
E.2 Upload request 73
E.3 Server response 73
E.4 Merging data on the server 74
Annex F – Using JPIP over HTTP 76
F.1 Introduction 76
F.2 Requests 76
F.3 Session establishment 77
F.4 Responses 77
F.5 Additional HTTP features 78
F.6 HTTP and length request field (informative) 79
Annex G – Using JPIP with HTTP requests and TCP returns 80
G.1 Introduction 80
G.2 Client requests 80
G.3 Session establishment 80
G.4 Server responses 81
G.5 TCP and length request field (informative) 81
Annex H – Using JPIP with alternate transports 82
H.1 Introduction 82
H.2 Reliable requests with unreliable data 82
H.3 Unreliable requests with unreliable data 83
H.4 Request and response syntax 83
H.5 Session establishment 84
Annex I – Indexing JPEG 2000 files for JPIP 85
I.1 Introduction (informative) 85
I.2 Identifying the use of JPIP index boxes in the JPEG 2000 file format compatibility list 86
I.3 Defined boxes 86
I.4 Association of codestream indexes with codestreams 94
I.5 Placement restrictions (informative) 94
Annex J – Profiles and variants for interoperability and testing 95
J.1 Introduction 95
J.2 Definition of variants 95
J.3 Definition of profiles 96
J.4 Testing methodology 98
Annex K – Using JPIP with HTTP requests and UDP returns 103
K.1 Introduction 103
K.2 Client requests 103
K.3 Response data delivery and channel establishment 103
K.4 Server responses 104
K.5 Framing of response data into chunks 104
K.6 Client acknowledgement of server responses 105
K.7 UDP and Maximum Response Length Field (informative) 106
K.8 Implementation strategies for acknowledged communication (informative) 106
K.9 Implementation strategies for unacknowledged communication (informative) 106
Annex L – Registration of extensions 108
Annex M – Application examples 109
M.1 Introduction 109
M.2 Use of JPIP with codestreams in other file formats 109
M.3 Tile-part implementation techniques 109
M.4 Precinct-based implementation techniques 110
M.5 JPIP protocol transcripts 111
M.6 Using JPIP with HTML 114

Annex N – JPIP ABNF collection 115
N.1 JPIP Request ABNF 115
N.2 JPIP Response BNF 122
Annex O – Media type specifications and registrations 126
O.1 General 126
O.2 JPP-stream 126
O.3 JPT-stream 127
Bibliography 128

Figures

Page

Figure 1 – Example of the box description figures 8
Figure 2 – Example of the superbox description figures 8
Figure 3 – JPIP protocol overview 8
Figure 4 – JPIP protocol stack 9
Figure A.1 – Examples of a JPEG 2000 file, JPIP data-bins and JPIP-stream relationships (after G.J. Colyer and R.A. Clark, IEEE Trans. Consumer Electronics, 49 (2003), pp. 850–854) 11
Figure A.2 – VBAS structure 12
Figure A.3 – Bin-ID VBAS structure 12
Figure A.4 – Example precinct data-bin 15
Figure A.5 – Metadata-bin example colour scheme 16
Figure A.6 – A sample JP2 file 17
Figure A.7 – A sample JP2 file divided into three metadata-bins 17
Figure A.8 – A superbox with a referenced metadata-bin 18
Figure A.9 – An invalid division of the file into metadata-bins 18
Figure A.10 – Example of the use of stream equivalents 19
Figure A.11 – Placeholder box structure 20
Figure C.1 –Desired region within an image 30
Figure C.2 – Desired region with respect to the subsampled reference grid 30
Figure C.3 – Colourspace specification box selection procedure 61
Figure G.1 – Response data structure on http-tcp connection 81
Figure I.1 – Part of an example JPEG 2000 file containing JPIP index boxes 86
Figure I.2 – Organization of the contents of a Codestream Index box 87
Figure I.3 – Organization of the contents of a Codestream Finder box 88
Figure I.4 – Organization of the contents of a Manifest box 88
Figure I.5 – Organization of the contents of a Fragment Array Index box 89
Figure I.6 – Organization of the contents of a Header Index Table box 90
Figure I.7 – Organization of the contents of a Tile-part Index Table box 91
Figure I.8 – Organization of the contents of a Tile Header Index Table box 91
Figure I.9 – Organization of the contents of a Precinct Packet Index Table box 91
Figure I.10 – Organization of the contents of a Packet Header Index Table box 92
Figure I.11 – Organization of the contents of a File Index box 92

Figure I.12 – Organization of the contents of a File Finder box 93
Figure I.13 – Organization of the contents of a Proxy box 93
Figure I.14 – Organization of the contents of an Index Finder box 94
Figure K.1 – Response data structure on http-udp connection 104

Tables

Page

Table A.1 – Bin-ID additional VBAS indication 13
Table A.2 – Class identifiers for different data-bin message classes 13
Table A.3 – Valid values for the Flags field of a Placeholder box 21
Table C.1 – Round direction options 33
Table C.2 – Metadata request qualifier flags 47
Table C.3 – Alignment boundaries based on bin type 49
Table C.4 – Valid image return types 49
Table C.5 – Cache descriptor option summary 55
Table C.6 – Valid capabilities of the `processing-capabilities` element 58
Table C.7 – Valid values of the `config-capability` parameter 58
Table C.8 – View-window handling preferences 60
Table C.9 – Colourspace method client preferences 60
Table C.10 – Placeholder preferences 62
Table C.11 – Codestream sequencing preferences 63
Table C.12 – Conciseness preferences 63
Table D.1 – Valid values of transport-param 67
Table D.2 – Defined reason codes 72
Table D.3 – Additional `handled-req-option` values for particular request fields 72
Table I.1 – Defined boxes (Informative) 87
Table I.2 – Container type values 88
Table I.3 – Version values 90
Table J.1 – Defining requirements of variants 96
Table J.2 – Set of fields included in each profile 97
Table K.1 – Interpretation of the "control" field in each data chunk header 105
Table M.1 – Example of the use of auxiliary fields in a simple case 110
Table M.2 – Example of the use of auxiliary fields in a more complicated case 110