

ISO/IEC 23200-2:2023-07 (E)

Information technology - Radio frequency identification for item management - Part 2: Interference rejection performance test method between an Interrogator as defined in ISO/IEC 18000-63 and a heterogeneous wireless system

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
4.1	Symbols	2
4.2	Abbreviated terms	2
5	Conditions applicable to the test methods	3
5.1	Number of UHF RFID interrogator for testing	3
5.2	Test environment	3
5.3	RF environment	3
5.4	Pre-conditioning	3
5.5	Default tolerance	3
5.6	Total measurement uncertainty	3
5.7	Test result reporting	3
5.8	Test mounting material	3
5.9	Test communication parameters	3
6	Test set-up	4
6.1	Test setup for UHF RFID interrogator's receiver sensitivity under non-interference environment	4
6.2	Reader sends ACK with the correct RN16Test setup for UHF RFID interrogator's receiver sensitivity under interference environment	5
7	Test procedure	6
7.1	General description	6
7.2	UHF RFID interrogator's receiver sensitivity power measurement under non- interference environment	7
7.2.1	Purpose	7
7.2.2	Test procedure	7
7.3	UHF RFID interrogator's receiver sensitivity power measurement under interference environment	9
7.3.1	Purpose	9
7.3.2	Test procedure	9
7.4	Test report	10
Bibliography		13