

ISO/IEC 17309:2000-09 (E)

Information technology - Telecommunications and information exchange between systems; Private integrated Services Network - Mapping functions for the employment of a circuit mode basic service and the supplementary service user-to-user signalling as a pair of on-d emand inter-PINX connections

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Definitions	2
4.1	External definitions	2
4.2	Special definitions	2
4.2.1	Calling PINX	2
4.2.2	Called PINX	2
4.2.3	Channel	2
4.2.4	Inter-PINX Connection	2
4.2.5	Inter-PINX Link	2
5	List of acronyms	2
6	Introduction	3
7	Capabilities at the Q reference point	3
8	Mapping functions	3
8.1	Physical adaptation	4
8.1.1	ISDN primary rate user-network Layer 1 interface (1544 kbit/s)	4
8.1.2	ISDN primary rate user-network Layer 1 interface (2048 kbit/s)	4
8.1.3	ISDN basic user-network Layer 1 interface	4
8.2	Mapping matrix	5
8.2.1	Channel allocation	5
8.2.2	Bearer conditioning for the DQ-channel	5
9	IPC control functions	5
9.1	IPC establishment	5
9.2	IPC clearing	6
10	IPL control functions	6
10.1	Static pre-conditions for IPL establishment	6
10.2	IPL establishment	6
10.3	Transfer of inter-PINX signalling Layer 2 information	6
10.4	Use of message segmentation	6
Annex A Implementation Conformance Statement (ICS) Proforma		7