

# ISO/IEC 17309:2000-09 (E)

Information technology - Telecommunications and information exchange between systems; Private integrated Services Network - Mapping functions for the employment of a circuit mode basic service and the supplementary service user-to-user signalling as a pair of on-d emand inter-PINX connections

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Conformance .....	1
3	Normative references .....	1
4	Definitions .....	2
4.1	External definitions .....	2
4.2	Special definitions .....	2
4.2.1	Calling PINX .....	2
4.2.2	Called PINX .....	2
4.2.3	Channel .....	2
4.2.4	Inter-PINX Connection .....	2
4.2.5	Inter-PINX Link .....	2
5	List of acronyms .....	2
6	Introduction .....	3
7	Capabilities at the Q reference point .....	3
8	Mapping functions .....	3
8.1	Physical adaptation .....	4
8.1.1	ISDN primary rate user-network Layer 1 interface (1544 kbit/s) .....	4
8.1.2	ISDN primary rate user-network Layer 1 interface (2048 kbit/s) .....	4
8.1.3	ISDN basic user-network Layer 1 interface .....	4
8.2	Mapping matrix .....	5
8.2.1	Channel allocation .....	5
8.2.2	Bearer conditioning for the DQ-channel .....	5
9	IPC control functions .....	5
9.1	IPC establishment .....	5
9.2	IPC clearing .....	6
10	IPL control functions .....	6
10.1	Static pre-conditions for IPL establishment .....	6
10.2	IPL establishment .....	6
10.3	Transfer of inter-PINX signalling Layer 2 information .....	6
10.4	Use of message segmentation .....	6
Annex A	Implementation Conformance Statement (ICS) Proforma .....	7