

ISO/IEC 17462:2000-09 (E)

Information technology - 3,81 mm wide magnetic tape cartridge for information interchange -
Helical scan recording - DDS-4 format

Contents

Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridge	1
2.2 Generating drive	1
2.3 Receiving drive	1
3 Normative references	2
4 Definitions	2
4.1 Absolute Frame Number (AFN)	2
4.2 a.c. erase	2
4.3 Access Point	2
4.4 algorithm	2
4.5 Area ID	2
4.6 Average Signal Amplitude	2
4.7 azimuth	2
4.8 back surface	2
4.9 byte	2
4.10 cartridge	2
4.11 Channel bit	2
4.12 Codeword	2
4.13 Data Format ID	2
4.14 Early Warning Point (EWP)	2
4.15 End of Data (EOD)	2
4.16 Entity	2
4.17 Error Correcting Code (ECC)	2
4.18 flux transition position	2
4.19 flux transition spacing	2
4.20 Fragment	2
4.21 Frame	3
4.22 Housekeeping Frame	3
4.23 Logical Beginning of Tape (LBOT)	3
4.24 magnetic tape	3
4.25 Master Standard Amplitude Calibration Tape	3
4.26 Master Standard Reference Tape	3
4.27 Optimum Recording Field	3
4.28 Partition Boundary	3
4.29 Physical Beginning of Tape (PBOT)	3
4.30 Physical End of Tape (PEOT)	3
4.31 physical recording density	3
4.32 pre-recording condition	3
4.33 processing	3
4.34 processed data	3
4.35 Processed Record	3
4.36 Processed Record Sequence	3

4.37	record	3
4.38	Reference Recording Field ³	
4.39	reprocessing	3
4.40	Secondary Standard Amplitude Calibration Tape	3
4.41	Secondary Standard Reference Tape	3
4.42	Separator Mark	4
4.43	Standard Reference Amplitude	4
4.44	Tape Reference Edge	4
4.45	Test Recording Current	4
4.46	track	4
4.47	Unprocessed Record	4
4.48	Virtual End of Tape (VEOT)	4
5	Conventions and Notations	4
6	Acronyms	4
7	Environment and safety	4
7.1	Testing environment	4
7.2	Operating environment	5
7.3	Storage environment	5
7.4	Transportation	5
7.5	Safety	5
7.6	Flammability	5
Section 2 - Requirements for the case		6
8	Dimensional and mechanical characteristics of the case	6
8.1	General	6
8.2	Overall dimensions	6
8.3	Loading grip	7
8.4	Holding areas	7
8.5	Notches of the lid	7
8.6	Lid dimensions	7
8.7	Optical detection of the beginning and end of tape	8
8.8	Bottom side	8
8.8.1	Locking mechanism of the slider	8
8.8.2	Access holes	9
8.8.3	Recognition, sub-datums, and write-inhibit holes	9
8.8.4	Datum holes	11
8.8.5	Access room for tape guides	11
8.8.6	Holes for accessing the hubs	11
8.8.7	Internal structure of the lower half	11
8.8.8	Light path	12
8.8.9	Support Areas	13
8.8.10	Datum Areas	13
8.8.11	Relationship between Support and Datum Areas and Reference Plane Z	13
8.9	Hubs	13
8.10	Attachment of leader and trailer tapes	14
8.11	Interface between the hubs and the drive spindles	14
8.12	Opening of the lid	14
8.13	Release of the hub locking mechanism	14
8.14	Label areas	14
8.15	Requirement for autoloaders	15
Section 3 - Requirements for the unrecorded tape		28
9	Mechanical, physical and dimensional characteristics of the tape	28
9.1	Materials	28

9.2	Tape length	28
9.2.1	Length of magnetic tape	28
9.2.2	Length of leader and trailer tapes	28
9.2.3	Length of splicing tapes	28
9.3	Tape width	28
9.3.1	Width of magnetic tape	28
9.3.2	Width of leader and trailer tapes	28
9.3.3	Width and position of splicing tape	28
9.3.4	Edge weave	28
9.4	Discontinuities	29
9.5	Tape thickness	30
9.5.1	Thickness of magnetic tape	30
9.5.2	Thickness of leader and trailer tape	30
9.5.3	Thickness of splicing tape	30
9.6	Longitudinal curvature	30
9.7	Cupping	30
9.8	Coating adhesion	30
9.9	Layer-to-layer adhesion	31
9.10	Tensile strength	31
9.10.1	Breaking strength	31
9.10.2	Yield strength	31
9.11	Residual elongation	31
9.12	Flexural rigidity	31
9.13	Electrical resistance of coated surfaces	32
9.14	Abrasivity	32
9.15	Light transmittance of the tape	32
9.16	Media Recognition System (MRS)	33
10	Magnetic recording characteristics	33
10.1	Optimum Recording Field	34
10.2	Signal Amplitude	34
10.3	Resolution	34
10.4	Overwrite	34
10.5	Ease of erasure	35
10.6	Tape quality	35
10.6.1	Missing pulses	35
10.6.2	Missing pulse zone	35
10.7	Signal-to-Noise Ratio (SNR) characteristic	35
Section 4 - Requirements for an interchanged tape		35
11	Format	35
11.1	General	35
11.2	Basic Groups	36
11.2.1	Entity	36
11.2.2	Group Information Table	37
11.2.3	Block Access Table (BAT)	39
11.3	Sub-Groups	42
11.3.1	G1 Sub-Group	42
11.3.2	G2 Sub-Group - Randomizing	42
11.3.3	G3 Sub-Group	43
11.3.4	G4 Sub-Group	44
11.3.5	Main Data Fragment	48
11.3.6	Summary of the transformation of a Basic Group	50
11.4	Sub code information	50
11.4.1	Pack Item Number 0	50
11.4.2	Pack Item Number 1	50

11.4.3	Pack Item Number 2	51
11.4.4	Pack Item Number 3	51
11.4.5	Pack Item Number 4	51
11.4.6	Pack Item Number 5	52
11.4.7	Pack Item Number 6	53
11.4.8	Pack Item Number 7	53
11.4.9	Pack Item Number 8	54
11.4.10	Pack Item Number 9	54
11.4.11	Pack Item Number 10	54
11.4.12	Pack Item Number 11	55
11.4.13	Pack Item Number 12	55
11.4.14	Pack Item Number 13	56
11.4.15	Pack Item Number 14	56
11.4.16	Pack Item Number 15	57
11.5	Sub code location	57
11.5.1	Sub code Pack Items on a Single Data Space tape	57
11.5.2	Sub code Pack Items on a partitioned tape	57
12	Method of recording	58
12.1	Physical recording density	58
12.2	Long-term average bit cell length	58
12.3	Short-term average bit cell length	58
12.4	Rate of change	58
12.5	Bit shift	58
12.6	Read signal amplitude	58
12.7	Maximum recorded levels	58
13	Track geometry	58
13.1	Track configuration	58
13.2	Average track pitch	59
13.3	Variations of the track pitch	59
13.4	Track width	59
13.5	Track angle	59
13.6	Track edge linearity	59
13.7	Track length	60
13.8	Ideal tape centreline	60
13.9	Azimuth angles	60
14	Recorded patterns	60
14.1	Recorded Main Data Fragment	60
14.2	Preamble Zone, Margin Zones	60
15	Format of a track	60
15.1	Format of a track	60
15.2	Positioning accuracy	60
15.3	Tracking scheme	61
16	Layout of a Single Data Space tape	61
16.1	Device Area	61
16.2	Reference Area	62
16.3	Position Tolerance Band No. 1	62
16.4	System Area	62
16.4.1	System Preamble	62
16.4.2	System Log	62
16.4.3	System Postamble	62
16.4.4	Position Tolerance Band No. 2	62
16.4.5	Vendor Group Preamble	62

16.5	Data Area	62
16.5.1	Vendor Group	62
16.5.2	Recorded Data Group	63
16.5.3	ECC3	63
16.5.4	Repeated Frames	63
16.5.5	Appending and overwriting	64
16.6	EOD Area	65
16.7	Post-EOD Area	65
16.8	Early Warning Point - (EWP)	66
16.9	Initialization	66
17	Layout of a partitioned tape	66
17.1	Overall magnetic tape layout	67
17.1.1	Device Area	67
17.1.2	Partition 1	67
17.1.3	Partition 0	68
17.2	Area ID	68
17.3	System Area Pack Items No. 6	68
17.4	Empty partitions	69
17.4.1	Empty partition 1	69
17.4.2	Empty partition 0	69
17.5	Initialization of partitioned tapes	69
18	Housekeeping Frames	69
18.1	Amble Frames	69
18.2	System Log Frames	69
18.3	Tape Management Frames	70
Annexes		
A	- Measurement of the light transmittance of the prisms	71
B	- Measurement of light transmittance of tape and leaders	73
C	- Measurement of Signal-to-Noise Ratio	76
D	- Method for determining the Nominal and the Maximum Allowable Recorded Levels	77
E	- Representation of 8-bit bytes by 10-bit patterns	78
F	- Measurement of bit shift	90
G	- Measurement of track edge linearity	92
H	- Tape abrasivity measurement procedure	93
J	- Method of measurement of the track width	95
K	- Recognition Holes	97
L	- Means to open the lid	98
M	- Recommendations for transportation	100
N	- Read-After-Write	101
P	- Example of the content of a Basic Group No. 0	102