

# ISO/IEC/IEEE 8802-15-4:2024-07 (E)

## Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 15-4: Wireless medium access control (MAC) and physical layer (PHY) specifications for low-rate wireless personal area networks (WPANs)

---

Contents	Page
1. Overview.....	33
1.1 Scope.....	33
1.2 Purpose.....	33
2. Normative references.....	34
3. Definitions, acronyms, and abbreviations.....	35
3.1 Definitions.....	35
3.2 Acronyms and abbreviations.....	36
4. Format conventions.....	40
4.1 General.....	40
4.2 Fields.....	40
4.3 Numbers.....	41
4.4 Strings.....	41
4.5 Transmission order.....	41
4.5.1 General.....	41
4.5.2 Vendor OUI transmission order.....	42
4.6 Reserved fields and values.....	42
5. General description.....	43
5.1 Introduction.....	43
5.2 Special application spaces.....	43
5.2.1 General.....	43
5.2.2 Smart utility network (SUN).....	43
5.2.3 Rail communications and control (RCC).....	43
5.2.4 Television white space (TVWS).....	44
5.2.5 Radio frequency identification (RFID).....	44
5.2.6 Low-energy, critical infrastructure monitoring (LECIM).....	44
5.2.7 Medical body area network (MBAN) services.....	44
5.2.8 China medical band (CMB).....	44
5.3 Components of the IEEE 802.15.4 WPAN.....	45
5.4 Multi-PHY management (MPM) of the SUN WPAN.....	45
5.5 Network topologies.....	45
5.5.1 General.....	45
5.5.2 Star network formation.....	46
5.5.3 Peer-to-peer network formation.....	46
5.6 Architecture.....	47
5.6.1 General.....	47
5.6.2 PHY.....	48
5.6.3 MAC sublayer.....	49
5.7 Functional overview.....	49
5.7.1 Superframe structure.....	49
5.7.2 Data transfer model.....	51
5.7.3 Frame structure.....	52
5.7.4 Information element (IEs).....	52
5.7.5 Access methods.....	52
5.7.6 Power consumption considerations.....	53

5.7.7	Security .....	54
5.7.8	Enabling spectrum resource measurement capability .....	55
5.8	Concept of primitives .....	56
6.	MAC functional description .....	57
6.1	Device types and conventions .....	57
6.2	Channel access .....	57
6.2.1	Superframe structure .....	57
6.2.2	Incoming and outgoing superframe timing .....	59
6.2.3	Enhanced Beacon frame timing for MPM procedure .....	60
6.2.4	IFS .....	61
6.2.5	Random access methods .....	62
6.2.6	TSCH slotframe structure .....	69
6.2.7	LE functional description .....	71
6.2.8	Superframe use for TMCTP operation .....	71
6.2.9	Rail communications and control network (RCCN) superframe structure .....	72
6.2.10	Channel hopping .....	73
6.3	Starting and maintaining PANs .....	75
6.3.1	Scanning through channels .....	75
6.3.2	PAN ID conflict resolution .....	81
6.3.3	Starting and realigning a PAN .....	82
6.3.4	Beacon generation .....	84
6.3.5	Device discovery .....	86
6.3.6	TSCH PAN formation .....	86
6.4	Association and disassociation .....	88
6.4.1	Association .....	88
6.4.2	Disassociation .....	91
6.4.3	Fast association .....	92
6.5	Synchronization .....	93
6.5.1	General .....	93
6.5.2	Synchronization with beacons .....	93
6.5.3	Synchronization without beacons .....	95
6.5.4	Synchronization in TSCH PAN .....	95
6.5.5	Orphaned device realignment .....	98
6.6	Transaction handling .....	98
6.7	Transmission, reception, and acknowledgment .....	100
6.7.1	Transmission .....	100
6.7.2	Reception and rejection .....	101
6.7.3	Extracting pending data from a coordinator .....	103
6.7.4	Use of acknowledgments and retransmissions .....	104
6.7.5	Transmission timing restrictions .....	107
6.7.6	Guard time .....	108
6.7.7	Promiscuous mode .....	109
6.7.8	Transmission scenarios .....	109
6.7.9	Device announcement .....	111
6.8	GTS allocation and management .....	111
6.8.1	GTS general requirements .....	111
6.8.2	CAP maintenance .....	112
6.8.3	GTS allocation .....	112
6.8.4	GTS usage .....	113
6.8.5	GTS deallocation .....	114
6.8.6	GTS reallocation .....	115
6.8.7	GTS expiration .....	117

6.9	Ranging.....	117
6.9.1	Ranging requirements .....	117
6.9.2	Set-up activities before a ranging exchange .....	118
6.9.3	Finish-up activities after a ranging exchange .....	118
6.9.4	Managing DPS .....	118
6.9.5	The ranging exchange .....	120
6.10	PHY parameter change notification procedure.....	120
6.10.1	Signaling using Beacon frames.....	120
6.10.2	Signaling using multipurpose frames .....	121
6.11	Deterministic and synchronous multichannel extension (DSME).....	122
6.11.1	DSME command requirements.....	122
6.11.2	DSME multi-superframe structure.....	122
6.11.3	Channel diversity .....	124
6.11.4	CAP reduction.....	126
6.11.5	DSME GTS allocation and management.....	127
6.11.6	Beacon scheduling .....	133
6.11.7	Time synchronization .....	134
6.11.8	Deferred beacon.....	135
6.11.9	Passive channel scan.....	135
6.12	LE transmission, reception, and acknowledgment .....	136
6.12.1	LE transmission, reception, and acknowledgment with positive handshakes .....	136
6.12.2	Coordinated sampled listening (CSL).....	136
6.12.3	RIT .....	140
6.12.4	Implicit RIT (I-RIT).....	143
6.13	Starting and maintaining TMCTPs.....	143
6.14	MPM procedure for inter-PHY coexistence .....	147
6.15	TVWS access procedures .....	149
6.15.1	General.....	149
6.15.2	Channel timing management (CTM).....	150
6.16	Spectrum Resource Measurement (SRM) .....	151
6.16.1	General.....	151
6.16.2	SRM Performance Metrics .....	151
6.16.3	SRM functionality.....	157
6.17	Using Link Margin IE.....	160
7.	MAC frame formats.....	161
7.1	Device extended address.....	161
7.2	General MAC frame format.....	161
7.2.1	General.....	161
7.2.2	Frame Control field.....	162
7.2.3	Sequence Number field.....	165
7.2.4	Destination PAN ID field .....	166
7.2.5	Destination Address field.....	166
7.2.6	Source PAN ID field.....	166
7.2.7	Source Address field.....	166
7.2.8	Auxiliary Security Header field.....	166
7.2.9	IE field .....	166
7.2.10	Frame Payload field.....	167
7.2.11	FCS field.....	167
7.3	Format of individual frame types.....	169
7.3.1	Beacon frame format .....	169
7.3.2	Data frame format.....	173
7.3.3	Ack frame format.....	174

7.3.4	MAC command frame format.....	175
7.3.5	Multipurpose frame format.....	176
7.3.6	Extended frame format .....	179
7.4	IEs .....	179
7.4.1	IE list termination .....	179
7.4.2	Header IEs.....	180
7.4.3	Payload IEs .....	197
7.4.4	Nested IE.....	198
7.5	MAC commands .....	237
7.5.1	Command ID field .....	237
7.5.2	Association Request command.....	239
7.5.3	Association Response command .....	240
7.5.4	Disassociation Notification command.....	241
7.5.5	Data Request command .....	242
7.5.6	PAN ID Conflict Notification command.....	243
7.5.7	Orphan Notification command .....	243
7.5.8	Beacon Request command.....	243
7.5.9	Enhanced Beacon Request command.....	243
7.5.10	Coordinator Realignment command.....	244
7.5.11	GTS request command.....	245
7.5.12	DSME Association Request command.....	246
7.5.13	DSME Association Response command .....	247
7.5.14	DSME GTS Request command .....	249
7.5.15	DSME GTS Response command.....	251
7.5.16	DSME GTS Notify command.....	253
7.5.17	DSME Information Request command.....	254
7.5.18	DSME Information Response command .....	254
7.5.19	DSME Beacon Allocation Notification command .....	255
7.5.20	DSME Beacon Collision Notification command.....	256
7.5.21	DSME Link Report command .....	256
7.5.22	RIT Data Request command.....	257
7.5.23	DBS Request command .....	258
7.5.24	DBS Response command.....	259
7.5.25	RIT Data Response command .....	260
7.5.26	SRM Request command .....	260
7.5.27	SRM Response command.....	262
7.5.28	SRM Report command .....	262
7.5.29	SRM Information command .....	263
7.5.30	Vendor Specific command.....	264
8.	MAC services .....	265
8.1	Overview.....	265
8.2	MAC management service.....	265
8.2.1	Primitives supported by the MLME-SAP interface.....	265
8.2.2	Common requirements for MLME primitives.....	267
8.2.3	Association primitives .....	268
8.2.4	Disassociation primitives .....	275
8.2.5	Communications notification primitives .....	278
8.2.6	Primitives for reading and writing PIB attributes .....	285
8.2.7	GTS management primitives .....	288
8.2.8	Primitives for orphan notification.....	291
8.2.9	Primitives for resetting the MAC sublayer .....	293
8.2.10	Primitives for specifying the receiver enable time .....	294

8.2.11	Primitives for channel scanning.....	296
8.2.12	Primitives for updating the superframe configuration.....	301
8.2.13	Primitives for synchronizing with a coordinator.....	305
8.2.14	Primitives for requesting data from a coordinator.....	308
8.2.15	Primitives for specifying dynamic preamble.....	310
8.2.16	Primitives for channel sounding.....	311
8.2.17	Primitives for ranging calibration.....	313
8.2.18	Primitives for Beacon Generation.....	314
8.2.19	Primitives for TSCH.....	318
8.2.20	Primitives for DSME GTS management.....	325
8.2.21	Primitives for reporting the link status.....	332
8.2.22	Operating parameter change primitives.....	334
8.2.23	TMCTP DBS allocation primitives.....	338
8.2.24	Primitives for device announcement.....	342
8.2.25	RIT data commands.....	344
8.2.26	Primitives for SRM.....	350
8.3	MAC data service.....	365
8.3.1	General.....	365
8.3.2	MCPS-DATA.request.....	365
8.3.3	MCPS-DATA.confirm.....	370
8.3.4	MCPS-DATA.indication.....	373
8.3.5	MCPS-PURGE.request.....	376
8.3.6	MCPS-PURGE.confirm.....	376
8.4	MAC constants and PIB attributes.....	377
8.4.1	General.....	377
8.4.2	MAC constants.....	377
8.4.3	MAC PIB attributes.....	378
9.	Security.....	400
9.1	Overview.....	400
9.2	Functional description.....	400
9.2.1	General.....	400
9.2.2	Outgoing frame security procedure.....	400
9.2.3	KeyDescriptor lookup procedure.....	402
9.2.4	Incoming frame security procedure, Security Enabled field is set to one.....	402
9.2.5	Incoming frame security procedure, Security Enabled field is set to zero.....	404
9.2.6	DeviceDescriptor lookup procedure.....	405
9.2.7	SecurityLevelDescriptor lookup procedure.....	406
9.2.8	Incoming IE security level checking procedure.....	406
9.2.9	Incoming IE key usage policy checking procedure.....	407
9.2.10	Incoming security level checking procedure.....	407
9.2.11	Incoming key usage policy checking procedure.....	407
9.3	Security operations.....	408
9.3.1	General.....	408
9.3.2	Integer and octet representation.....	408
9.3.3	AEAD nonce.....	408
9.3.4	AEAD prerequisites.....	410
9.3.5	AEAD transformation data representation.....	410
9.3.6	AEAD inverse transformation data representation.....	411
9.4	Auxiliary security header.....	412
9.4.1	General.....	412
9.4.2	Security Control field.....	412
9.4.3	Frame Counter field.....	414

9.4.4	Key Identifier field.....	415
9.5	Security-related MAC PIB attributes.....	415
10.	General PHY requirements.....	421
10.1	General.....	421
10.1.1	Requirements and definitions .....	421
10.1.2	Operating frequency range.....	422
10.1.3	Channel assignments.....	429
10.1.4	Minimum LIFS and SIFS periods.....	454
10.1.5	RF power measurement .....	454
10.1.6	Transmit power .....	454
10.1.7	Out-of-band spurious emission.....	454
10.1.8	Receiver sensitivity definitions.....	454
10.1.9	Common signaling mode (CSM) for SUN PHY .....	454
10.2	General radio specifications.....	455
10.2.1	General.....	455
10.2.2	TX-to-RX turnaround time .....	455
10.2.3	RX-to-TX turnaround time .....	455
10.2.4	Error-vector magnitude (EVM) definition.....	456
10.2.5	Receiver maximum input level of desired signal.....	456
10.2.6	Receiver ED.....	457
10.2.7	Link quality indicator (LQI) .....	457
10.2.8	Clear channel assessment (CCA).....	457
11.	PHY services .....	459
11.1	Overview.....	459
11.2	PHY constants.....	459
11.3	PHY PIB attributes .....	459
12.	O-QPSK PHY .....	467
12.1	PPDU format.....	467
12.1.1	General.....	467
12.1.2	SHR field format.....	467
12.1.3	PHR field format.....	467
12.2	Modulation and spreading .....	468
12.2.1	General.....	468
12.2.2	Data rate.....	468
12.2.3	Reference modulator diagram.....	468
12.2.4	Bit-to-symbol mapping .....	468
12.2.5	Symbol-to-chip mapping .....	469
12.2.6	O-QPSK modulation.....	470
12.2.7	Pulse shape.....	470
12.2.8	Chip transmission order .....	471
12.3	O-QPSK PHY RF requirements .....	471
12.3.1	Operating frequency range.....	471
12.3.2	Transmit power spectral density (PSD) mask.....	472
12.3.3	Symbol rate .....	472
12.3.4	Receiver sensitivity.....	472
12.3.5	Receiver interference rejection .....	472
12.3.6	TX-to-RX turnaround time .....	473
12.3.7	RX-to-TX turnaround time .....	473

12.3.8	EVM.....	473
12.3.9	Transmit center frequency tolerance.....	473
12.3.10	Transmit power.....	473
12.3.11	Receiver maximum input level of desired signal.....	473
12.3.12	Receiver ED.....	473
12.3.13	LQI.....	473
13.	Binary phase-shift keying (BPSK) PHY .....	474
13.1	PPDU format.....	474
13.2	Modulation and spreading .....	474
13.2.1	General.....	474
13.2.2	BPSK PHY data rates .....	474
13.2.3	Reference modulator.....	474
13.2.4	Differential encoding.....	474
13.2.5	Bit-to-chip mapping.....	475
13.2.6	BPSK modulation .....	475
13.3	BPSK PHY RF requirements.....	475
13.3.1	Operating frequency range.....	475
13.3.2	915 MHz band transmit PSD mask.....	475
13.3.3	Symbol rate.....	476
13.3.4	Receiver sensitivity.....	476
13.3.5	Receiver interference rejection .....	476
13.3.6	TX-to-RX turnaround time .....	476
13.3.7	RX-to-TX turnaround time .....	477
13.3.8	EVM.....	477
13.3.9	Transmit center frequency tolerance.....	477
13.3.10	Transmit power.....	477
13.3.11	Receiver maximum input level of desired signal.....	477
13.3.12	Receiver ED.....	477
13.3.13	LQI.....	477
14.	Chirp spread spectrum (CSS) PHY .....	478
14.1	CSS PPDU format .....	478
14.1.1	General.....	478
14.1.2	Preamble field.....	478
14.1.3	SFD field.....	478
14.1.4	PHR field .....	479
14.1.5	PHY Payload field .....	479
14.2	Modulation and spreading .....	479
14.2.1	General.....	479
14.2.2	Data rates .....	479
14.2.3	Reference modulator.....	479
14.2.4	De-multiplexer (DEMUX).....	479
14.2.5	Serial-to-parallel mapping .....	479
14.2.6	Data-symbol-to-bi-orthogonal-codeword mapping .....	480
14.2.7	Parallel-to-serial converter and QPSK symbol mapping.....	484
14.2.8	DQPSK coding .....	484
14.2.9	DQPSK-to-DQCSK modulation.....	485
14.2.10	CSK generator.....	485
14.2.11	Bit interleaver .....	485
14.3	Waveform and subchirp sequences.....	486
14.3.1	General.....	486

14.3.2	Graphical presentation of chirp symbols (subchirp sequences).....	486
14.3.3	Active usage of time gaps.....	486
14.3.4	Mathematical representation of the continuous time CSS base-band signal.....	487
14.3.5	Raised cosine window for chirp pulse shaping.....	489
14.3.6	Subchirp transmission order.....	489
14.3.7	Example of CSK signal generation.....	490
14.4	CSS RF requirements.....	491
14.4.1	General.....	491
14.4.2	Transmit power spectral density (PSD) mask and signal tolerance.....	491
14.4.3	Symbol rate.....	491
14.4.4	Receiver sensitivity.....	491
14.4.5	Receiver interference rejection.....	491
14.4.6	TX-to-RX turnaround time.....	492
14.4.7	RX-to-TX turnaround time.....	492
14.4.8	Transmit center frequency tolerance.....	493
14.4.9	Transmit power.....	493
14.4.10	Receiver maximum input level of desired signal.....	493
14.4.11	Receiver ED.....	493
14.4.12	LQI.....	493
15.	HRP UWB PHY.....	494
15.1	General.....	494
15.2	HRP UWB PPDU format.....	495
15.2.1	General.....	495
15.2.2	PPDU encoding process.....	495
15.2.3	Symbol structure.....	496
15.2.4	PSDU timing parameters.....	498
15.2.5	Preamble timing parameters.....	500
15.2.6	SHR field.....	502
15.2.7	PHR field.....	505
15.2.8	PHY Payload field.....	506
15.3	Modulation.....	507
15.3.1	Modulation mathematical framework.....	507
15.3.2	Spreading.....	507
15.3.3	FEC.....	509
15.4	RF requirements.....	511
15.4.1	Operating frequency bands.....	511
15.4.2	Channel assignments.....	513
15.4.3	Regulatory compliance.....	513
15.4.4	Baseband impulse response.....	513
15.4.5	Transmit PSD mask.....	514
15.4.6	Chip rate clock and chip carrier alignment.....	514
15.4.7	TX-to-RX turnaround time.....	515
15.4.8	RX-to-TX turnaround time.....	515
15.4.9	Transmit center frequency tolerance.....	515
15.4.10	Receiver maximum input level of desired signal.....	515
15.4.11	Receiver ED.....	515
15.4.12	LQI.....	515
15.4.13	CCA.....	516
15.5	HRP UWB PHY optional pulse shapes.....	516
15.5.1	Overview.....	516
15.5.2	HRP UWB PHY optional chirp on UWB (CoU) pulses.....	516
15.5.3	HRP UWB PHY optional continuous spectrum (CS) pulses.....	517

15.5.4	HRP UWB PHY linear combination of pulses (LCP).....	519
15.6	Extended preamble for optional CCA mode 6.....	519
15.7	Ranging.....	520
15.7.1	Overview.....	520
15.7.2	Ranging counter.....	520
15.7.3	Crystal characterization .....	520
15.7.4	Ranging FoM .....	521
16.	GFSK PHY .....	523
16.1	PPDU formats.....	523
16.2	Modulation.....	523
16.2.1	GFSK PHY data rates .....	523
16.2.2	Reference modulator diagram.....	523
16.2.3	Data whitening .....	523
16.2.4	GFSK modulation.....	524
16.3	GFSK PHY RF requirements .....	524
16.3.1	Operating frequency range.....	524
16.3.2	Transmit PSD mask .....	524
16.3.3	Symbol rate.....	525
16.3.4	Receiver sensitivity.....	525
16.3.5	Receiver interference rejection .....	525
16.3.6	TX-to-RX turnaround time .....	525
16.3.7	RX-to-TX turnaround time .....	525
16.3.8	Transmit center frequency tolerance.....	525
16.3.9	Transmit power .....	525
16.3.10	Receiver maximum input level of desired signal.....	525
16.3.11	Receiver ED.....	526
16.3.12	LQI.....	526
17.	MSK PHY .....	527
17.1	PPDU formats.....	527
17.1.1	Overview.....	527
17.1.2	Frame Length LSB field .....	527
17.1.3	Extended PHR field .....	527
17.1.4	Frame Length MSB field .....	527
17.2	Data rate.....	528
17.3	Multi-PHY functionality.....	528
17.4	SFD for the MSK PHY .....	528
17.5	MSK modulation.....	529
17.5.1	Reference modulator diagram.....	529
17.5.2	Data whitening .....	529
17.5.3	Bit-to-symbol mapping.....	529
17.5.4	Signal modulation .....	529
17.6	MSK PHY requirements .....	530
17.6.1	Operating frequency range.....	530
17.6.2	Transmit PSD mask .....	530
17.6.3	Symbol rate.....	530
17.6.4	Transmit center frequency tolerance.....	531
17.6.5	Transmit power .....	531
17.6.6	Receiver maximum input level of desired signal.....	531
17.6.7	Modulation frequency deviation tolerance .....	531
17.6.8	Zero crossing tolerance.....	531

18.	LRP UWB PHY specification .....	532
18.1	Overview.....	532
18.2	LRP UWB PHY symbol structure .....	532
18.2.1	Overview.....	532
18.2.2	Base mode LRP UWB PHY symbol structure .....	533
18.2.3	Extended mode LRP UWB PHY symbol structure .....	533
18.2.4	Long-range mode LRP UWB PHY symbol structure .....	535
18.3	LRP UWB SHR .....	535
18.3.1	General.....	535
18.3.2	LRP UWB SHR preamble .....	536
18.3.3	LRP UWB SHR SFD.....	536
18.4	LRP UWB PHR .....	536
18.4.1	General.....	536
18.4.2	Encoding Type field.....	537
18.4.3	Header Extension field.....	537
18.4.4	SECEDED field.....	538
18.4.5	Frame Length field.....	538
18.4.6	LEIP Length field .....	538
18.4.7	LEIP Position field.....	538
18.5	LRP UWB PSDU.....	539
18.6	LRP UWB location enhancing information postamble .....	539
18.7	LRP UWB transmitter specification .....	539
18.7.1	Pulse shape.....	539
18.7.2	Pulse timing .....	539
18.7.3	Transmit PSD mask .....	540
18.8	LRP UWB receiver specification .....	540
19.	SUN FSK PHY .....	541
19.1	Introduction.....	541
19.2	PPDU format for SUN FSK.....	542
19.2.1	General.....	542
19.2.2	SHR field format.....	542
19.2.3	General.....	542
19.2.4	PHR field format.....	543
19.2.5	Mode Switch PHR .....	543
19.2.6	PHY Payload field .....	545
19.3	Modulation and coding for SUN FSK .....	546
19.3.1	General.....	546
19.3.2	Reference modulator .....	549
19.3.3	Bit-to-symbol mapping.....	550
19.3.4	Modulation quality.....	551
19.3.5	FEC .....	552
19.3.6	Code-symbol interleaving.....	555
19.4	Data whitening for SUN FSK.....	556
19.5	Mode switch mechanism for SUN FSK .....	556
19.6	SUN FSK PHY RF requirements .....	559
19.6.1	Operating frequency range.....	559
19.6.2	Regulatory compliance .....	559
19.6.3	Radio frequency tolerance .....	559
19.6.4	Channel switch time.....	560
19.6.5	Transmitter symbol rate .....	560
19.6.6	Transmit spectral mask.....	560

19.6.7	Receiver sensitivity.....	561
19.6.8	Receiver interference rejection.....	561
19.6.9	TX-to-RX turnaround time.....	561
19.6.10	RX-to-TX turnaround time.....	561
19.6.11	Transmit power.....	562
19.6.12	Receiver maximum input level of desired signal.....	562
19.6.13	Receiver ED.....	562
19.6.14	LQI.....	562
20.	SUN OFDM PHY.....	563
20.1	Introduction.....	563
20.2	PPDU format for SUN OFDM.....	563
20.2.1	General.....	563
20.2.2	Short Training field (STF).....	563
20.2.3	Long Training field (LTF).....	567
20.2.4	PHR.....	570
20.2.5	PSDU field.....	572
20.3	Data rates for SUN OFDM.....	572
20.4	Modulation and coding for SUN OFDM.....	573
20.4.1	Reference modulator diagram.....	573
20.4.2	Bit-to-symbol mapping.....	573
20.4.3	PIB attribute values for phySymbolsPerOctet.....	574
20.4.4	FEC.....	574
20.4.5	Interleaver.....	575
20.4.6	Frequency spreading.....	577
20.4.7	Pilot tones/null tones.....	578
20.4.8	Cyclic prefix (CP).....	581
20.4.9	PPDU Tail field.....	581
20.4.10	Pad field.....	581
20.4.11	Scrambler and scrambler seeds.....	582
20.5	SUN OFDM PHY RF requirements.....	583
20.5.1	Operating frequency range.....	583
20.5.2	Transmit power spectral density (PSD) mask.....	583
20.5.3	Receiver sensitivity.....	583
20.5.4	Adjacent channel rejection.....	584
20.5.5	Alternate channel rejection.....	584
20.5.6	TX-to-RX turnaround time.....	585
20.5.7	RX-to-TX turnaround time.....	585
20.5.8	EVM definition.....	585
20.5.9	Transmit center frequency and symbol tolerance.....	586
20.5.10	Transmit power.....	586
20.5.11	Receiver maximum input level of desired signal.....	586
20.5.12	Receiver ED.....	586
20.5.13	LQI.....	586
21.	SUN O-QPSK PHY.....	587
21.1	Introduction.....	587
21.2	PPDU format for SUN O-QPSK.....	587
21.2.1	General.....	587
21.2.2	SHR field format.....	587
21.2.3	PHR field format.....	588
21.2.4	PHY Payload field.....	589

21.3	Modulation and coding for SUN O-QPSK .....	589
21.3.1	Reference modulator .....	589
21.3.2	SHR coding and spreading .....	590
21.3.3	PHR coding and spreading .....	591
21.3.4	PSDU coding and spreading for DSSS .....	592
21.3.5	PSDU coding and spreading for MDSSS .....	596
21.3.6	FEC .....	598
21.3.7	Code-bit interleaving .....	600
21.3.8	Bit differential encoding (BDE) .....	601
21.3.9	DSSS bit-to-chip mapping .....	602
21.3.10	MDSSS bit-to-chip mapping .....	606
21.3.11	Chip whitening .....	609
21.3.12	Pilot insertion .....	611
21.3.13	Modulation parameters for O-QPSK .....	613
21.4	Support of legacy devices of the 780 MHz, 915 MHz, and 2450 MHz O-QPSK PHYs .....	614
21.5	SUN O-QPSK PHY RF requirements .....	614
21.5.1	Operating frequency range .....	614
21.5.2	Transmit power spectral density (PSD) mask .....	615
21.5.3	Receiver sensitivity .....	615
21.5.4	Adjacent channel rejection .....	617
21.5.5	TX-to-RX turnaround time .....	619
21.5.6	RX-to-TX turnaround time .....	619
21.5.7	EVM definition .....	619
21.5.8	Transmit center frequency and symbol tolerance .....	619
21.5.9	Transmit power .....	619
21.5.10	Receiver maximum input level of desired signal .....	619
21.5.11	Receiver ED .....	619
21.5.12	LQI .....	619
21.5.13	CCA .....	619
22.	LECIM DSSS PHYs .....	621
22.1	PPDU format for DSSS .....	621
22.2	Modulation and spreading .....	621
22.2.1	General .....	621
22.2.2	Data rate .....	621
22.2.3	Reference modulator diagram .....	622
22.2.4	Convolutional FEC encoding .....	622
22.2.5	Interleaver .....	623
22.2.6	Differential encoding .....	624
22.2.7	Bit-to-symbol and symbol-to-chip encoding .....	625
22.2.8	BPSK/O-QPSK modulation .....	627
22.3	PSDU fragmentation .....	629
22.3.1	General .....	629
22.3.2	Configuration .....	630
22.3.3	Fragmentation .....	630
22.3.4	Fragment packet .....	630
22.3.5	Calculating FICS field using MIC .....	631
22.3.6	Fragment acknowledgment and retransmission .....	631
22.3.7	Frak .....	632
22.3.8	Reassembly .....	634
22.4	DSSS PHY RF requirements .....	634
22.4.1	Radio frequency tolerance .....	634
22.4.2	Channel switch time .....	634

22.4.3	Transmit spectral mask .....	634
22.4.4	Receiver sensitivity .....	634
22.4.5	Receiver interference rejection .....	634
22.4.6	TX-to-RX turnaround time .....	635
22.4.7	RX-to-TX turnaround time .....	635
22.4.8	Transmit power .....	635
23.	LECIM FSK PHY specification .....	636
23.1	General .....	636
23.2	PPDU format for LECIM FSK PHY .....	636
23.2.1	General .....	636
23.2.2	SHR field format .....	636
23.2.3	PHR field format .....	637
23.2.4	PHY Payload field .....	637
23.3	Modulation and coding for LECIM FSK PHY .....	637
23.3.1	General .....	637
23.3.2	Reference modulator .....	638
23.3.3	Bit-to-symbol mapping .....	638
23.3.4	Modulation quality .....	638
23.3.5	FEC .....	639
23.3.6	Code-bit interleaving .....	640
23.3.7	Spreading .....	641
23.4	Data whitening for LECIM FSK PHY .....	642
23.5	LECIM FSK PHY RF requirements .....	643
23.5.1	Operating frequency range .....	643
23.5.2	Radio frequency tolerance .....	643
23.5.3	Channel switch time .....	643
23.5.4	Transmit spectral mask .....	643
23.5.5	Receiver sensitivity .....	643
23.5.6	TX-to-RX turnaround time .....	644
23.5.7	RX-to-TX turnaround time .....	644
23.5.8	Transmit power .....	644
24.	TVWS-FSK PHY .....	645
24.1	PPDU format for TVWS-FSK .....	645
24.1.1	General .....	645
24.1.2	SHR field format .....	645
24.1.3	PHR field format .....	646
24.1.4	PHY Payload field .....	646
24.2	Modulation and coding for TVWS-FSK .....	646
24.2.1	General .....	646
24.2.2	Reference modulator .....	646
24.2.3	FEC and interleaving .....	647
24.2.4	Data whitening .....	648
24.2.5	Spreading .....	648
24.2.6	Bit-to-symbol mapping .....	648
24.2.7	Modulation quality .....	648
24.2.8	Values for phySymbolsPerOctet .....	648
24.3	TVWS-FSK RF requirements .....	649
24.3.1	Operating frequency range .....	649
24.3.2	Clock frequency and timing accuracy .....	649
24.3.3	Channel switch time .....	649

24.3.4	Receiver sensitivity.....	649
24.3.5	TX-to-RX turnaround time.....	649
24.3.6	RX-to-TX turnaround time.....	649
24.3.7	Receiver maximum input level of desired signal.....	649
24.3.8	Receiver ED.....	649
24.3.9	LQI.....	649
25.	TVWS-OFDM PHY.....	650
25.1	General.....	650
25.2	PPDU format for TVWS-OFDM.....	650
25.2.1	General.....	650
25.2.2	STF.....	650
25.2.3	LTF.....	652
25.2.4	PHR field format.....	654
25.2.5	PSDU field.....	654
25.3	System parameters for TVWS-OFDM.....	654
25.4	Modulation and coding for TVWS-OFDM.....	655
25.4.1	Reference modulator.....	655
25.4.2	Bit-to-symbol mapping.....	655
25.4.3	FEC.....	656
25.4.4	Interleaver.....	657
25.4.5	Pilot tones/null tones.....	659
25.4.6	CP.....	660
25.4.7	PPDU Tail field.....	660
25.4.8	Pad field.....	660
25.4.9	Scrambler and scrambler seeds.....	660
25.5	TVWS-OFDM RF requirements.....	660
25.5.1	Operating frequency range.....	660
25.5.2	Pulse shaping.....	661
25.5.3	Transmit power spectral density (PSD) mask.....	661
25.5.4	Receiver sensitivity.....	661
25.5.5	TX-to-RX turnaround time.....	661
25.5.6	RX-to-TX turnaround time.....	661
25.5.7	EVM definition.....	661
25.5.8	Transmit center frequency and symbol tolerance.....	662
26.	TVWS-NB-OFDM PHY.....	663
26.1	PPDU format for TVWS-NB-OFDM.....	663
26.1.1	General.....	663
26.1.2	Short Training field (STF).....	663
26.1.3	Long training field (LTF).....	667
26.1.4	PHR.....	671
26.1.5	PHY Payload field.....	672
26.2	System parameters for TVWS-NB-OFDM.....	672
26.3	Modulation and coding parameters for TVWS-NB-OFDM.....	673
26.3.1	General.....	673
26.3.2	Reference modulator.....	673
26.3.3	Scrambler and scrambler seed.....	673
26.3.4	Outer encoding.....	673
26.3.5	Inner encoding.....	674
26.3.6	Pad bit insertion.....	677
26.3.7	Spreader.....	677

26.3.8	Bit interleaving .....	678
26.3.9	Subcarrier mapping.....	678
26.3.10	Frequency interleaving .....	680
26.3.11	Pilot tones .....	681
26.3.12	Cyclic prefix .....	681
26.3.13	Pulse shaping .....	681
26.3.14	PIB attribute values for phySymbolsPerOctet .....	682
26.4	Channel aggregation for TVWS-NB-OFDM .....	682
26.5	TVWS-NB-OFDM RF requirements.....	682
26.5.1	Operating frequency range.....	682
26.5.2	Receiver sensitivity.....	682
26.5.3	TX-to-RX turnaround time .....	683
26.5.4	RX-to-TX turnaround time .....	683
26.5.5	EVM definition .....	683
26.5.6	Transmit center frequency and symbol tolerance .....	684
27.	RCC LMR PHY .....	685
27.1	RCC PHY overview.....	685
27.2	PPDU format.....	685
27.2.1	General.....	685
27.2.2	SHR.....	685
27.2.3	PHR.....	686
27.2.4	PHY payload.....	686
27.2.5	Tail bits .....	686
27.3	FEC .....	686
27.4	Interleaver .....	687
27.5	Data whitening.....	687
27.6	Modulation.....	688
27.6.1	GMSK.....	688
27.6.2	4-FSK.....	688
27.6.3	QPSK .....	689
27.6.4	p/4 DQPSK .....	689
27.6.5	DSSS DPSK.....	690
27.7	Reference modulator.....	692
27.8	LMR PHY RF requirements .....	692
27.8.1	Transmitter symbol rate tolerance .....	692
27.8.2	Channel switching time .....	692
27.8.3	Error vector magnitude .....	692
27.8.4	Receiver sensitivity.....	692
27.8.5	Receiver interference rejection .....	692
27.8.6	Receiver maximum input level of desired signal.....	693
27.8.7	TX-to-RX turnaround time .....	693
27.8.8	RX-to-TX turnaround time .....	693
27.8.9	Receiver ED.....	693
27.8.10	LQI.....	693
28.	RCC DSSS BPSK PHY .....	694
28.1	Overview.....	694
28.2	RCC DSSS BPSK PHY specification .....	694
29.	CMB PHY.....	695

29.1	CMB O-QPSK PHY specification.....	695
29.1.1	PPDU format for the CMB O-QPSK PHY .....	695
29.1.2	Modulation and coding for CMB O-QPSK PHY .....	696
29.1.3	CMB O-QPSK PHY RF requirements .....	697
29.2	CMB GFSK PHY specification.....	699
29.2.1	PPDU format for CMB GFSK PHY .....	699
29.2.2	Modulation and coding for CMB GFSK PHY .....	700
29.2.3	Data whitening for CBM GFSK PHY .....	702
29.2.4	CMB GFSK PHY RF requirements.....	702
30.	TASK PHY .....	705
30.1	General.....	705
30.2	PPDU .....	705
30.2.1	General.....	705
30.2.2	PPDU format.....	705
30.2.3	Generation of PPDU signal.....	708
30.3	MCS mode, MCS, data rates, and related parameters .....	709
30.3.1	MCS mode .....	709
30.3.2	Data rates in the 2450 MHz band .....	709
30.3.3	Data rates in the 780 MHz, 863 MHz, and 915 MHz bands.....	710
30.3.4	Data rates in the 433 MHz and 470 MHz bands.....	710
30.4	FEC, ternary sequence spreading, and pseudo-random chip inversion .....	711
30.4.1	General.....	711
30.4.2	FEC codes .....	712
30.4.3	Ternary sequence spreading: Data-symbol-to-chip conversion.....	717
30.4.4	Pseudo-random chip inversion.....	719
30.5	Modulation.....	721
30.6	Pulse shaping .....	722
30.7	Representation of the modulated waveforms.....	722
30.8	RF requirements.....	722
30.8.1	Transmit PSD mask .....	722
30.8.2	Receiver sensitivity.....	723
30.8.3	Interference rejection capability .....	723
30.8.4	TX-to-RX turnaround time .....	724
30.8.5	RX-to-TX turnaround time .....	724
30.8.6	EVM.....	724
30.8.7	Transmit power .....	724
30.8.8	Transmit center frequency tolerance.....	724
30.8.9	Receiver maximum input level of desired signal.....	724
30.8.10	Receiver ED .....	724
30.8.11	SNR measurement .....	724
30.8.12	CCA .....	724
31.	RS-GFSK PHY .....	725
31.1	PPDU format.....	725
31.1.1	General.....	725
31.1.2	Preamble field .....	725
31.1.3	SFD .....	725
31.1.4	Long PHR .....	725
31.1.5	Short PHR.....	726
31.2	Modulation and coding .....	727
31.2.1	General.....	727

31.2.2	Reference modulator diagram.....	728
31.2.3	Differential encoding .....	728
31.2.4	Bit-to-symbol mapping.....	729
31.2.5	Modulation quality.....	729
31.2.6	Frequency deviation tolerance.....	729
31.2.7	Zero crossing tolerance.....	730
31.2.8	FEC .....	730
31.2.9	Code-symbol interleaving.....	730
31.2.10	Data whitening for RS-GFSK.....	730
31.3	Rate switch RS-GFSK .....	731
31.4	RF requirements.....	731
31.4.1	RF tolerance .....	731
31.4.2	Channel switch time.....	731
31.4.3	Receiver sensitivity.....	731
31.4.4	Receiver interference rejection .....	732
31.4.5	TX-to-RX turnaround time .....	732
31.4.6	RX-to-TX turnaround time .....	732
31.4.7	Receiver maximum input level of desired signal.....	732
31.4.8	Receiver ED.....	732
31.4.9	LQI.....	732
31.4.10	CCA .....	732
Annex A (informative) Bibliography .....		733
Annex B (normative) CCM* mode of operation.....		735
Annex C (informative) Test vectors for cryptographic building blocks.....		741
Annex D (informative) Protocol implementation conformance statement (PICS) proforma.....		753
Annex E (normative) Time-slot relaying based link extension (TRLE) .....		772
Annex F (informative) Geographic regional frequency band details .....		797