

ISO/IEC 21122-2:2024-08 (E)

Information technology - JPEG XS low-latency lightweight image coding system - Part 2 : Profiles and buffer models

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	4
5	Symbols	4
6	Conventions	7
6.1	Conformance language	7
6.2	Operators	7
6.2.1	Arithmetic operators	7
6.2.2	Logical operators	7
6.2.3	Relational operators	7
6.2.4	Other operators	7
6.2.5	Precedence order of operators	8
6.2.6	Mathematical functions	8
7	Buffer model	8
7.1	General system block diagram	8
7.2	Influencing variables on the required buffer sizes	9
7.3	Role of the buffer model	10
8	Interpretation of Bayer data	10
9	Conformance	11
Annex A (normative) Profiles, levels, sublevels and frame buffer bandwidth levels		12
Annex B (normative) Packet-based JPEG XS decoder model		35
Annex C (normative) Packet-based constant bit rate buffer model		41
Annex D (informative) Encoder model, latency bounds and codestream conformance properties for the packet-based constant bit rate buffer model		47
Annex E (informative) JPEG XS latency analysis		52
Bibliography		61