

# ISO/IEC/IEEE 8802-1Q:2024-08 (E)

## Telecommunications and exchange between information technology systems - Requirements for local and metropolitan area networks - Part 1Q: Bridges and bridged networks

---

### Contents

Page

- 1. Overview..... 74
  - 1.1 Scope..... 74
  - 1.2 Purpose..... 74
  - 1.3 Introduction..... 75
- 2. Normative references..... 83
- 3. Definitions ..... 87
- 4. Abbreviations..... 109
- 5. Conformance..... 115
  - 5.1 Requirements terminology..... 115
  - 5.2 Conformant components and equipment..... 115
  - 5.3 Protocol Implementation Conformance Statement (PICS)..... 116
  - 5.4 VLAN Bridge component requirements..... 116
    - 5.4.1 VLAN Bridge component options ..... 117
    - 5.4.2 Multiple VLAN Registration Protocol (MVRP) requirements ..... 123
    - 5.4.3 VLAN Bridge requirements for congestion notification ..... 123
    - 5.4.4 Multiple Stream Registration Protocol (MSRP) requirements ..... 124
    - 5.4.5 Shortest Path Bridging (SPB) operation (optional) ..... 124
    - 5.4.6 Path Control and Reservation (PCR) (optional) ..... 125
  - 5.5 C-VLAN component conformance..... 126
    - 5.5.1 C-VLAN component options ..... 126
    - 5.5.2 TE-MSTID (optional) ..... 126
  - 5.6 S-VLAN component conformance ..... 127
    - 5.6.1 S-VLAN component options ..... 127
    - 5.6.2 S-VLAN component requirements for Provider Backbone Bridge Traffic Engineering (PBB-TE) ..... 127
    - 5.6.3 S-VLAN component requirements for PBB-TE IPS ..... 128
    - 5.6.4 S-VLAN component requirements for ECMP with flow filtering ..... 128
  - 5.7 I-component conformance ..... 128
    - 5.7.1 I-component options ..... 128
  - 5.8 B-component conformance..... 129
    - 5.8.1 B-component options ..... 129
    - 5.8.2 B-component requirements for PBB-TE ..... 129
    - 5.8.3 B-component requirements for PBB-TE IPS ..... 130
    - 5.8.4 B-component requirements for ECMP with flow filtering ..... 130
  - 5.9 C-VLAN Bridge conformance..... 130
    - 5.9.1 C-VLAN Bridge options ..... 130
  - 5.10 Provider Bridge conformance..... 130
    - 5.10.1 S-VLAN Bridge conformance ..... 131
    - 5.10.2 Provider Edge Bridge conformance ..... 131
  - 5.11 System requirements for Priority-based Flow Control (PFC) ..... 131
  - 5.12 Backbone Edge Bridge (BEB) conformance ..... 131
    - 5.12.1 BEB requirements for PBB-TE ..... 132
  - 5.13 MAC Bridge component requirements..... 132
    - 5.13.1 MAC Bridge component options ..... 132
  - 5.14 MAC Bridge conformance..... 133
    - 5.14.1 MAC Bridge options ..... 133

|        |  |     |
|--------|--|-----|
| 5.15   | TPMR component conformance.....  | 134 |
| 5.15.1 | TPMR component options .....   | 134 |
| 5.16   | TPMR conformance.....  | 134 |
| 5.16.1 | TPMR options .....   | 135 |
| 5.17   | T-component conformance.....   | 135 |
| 5.17.1 | T-component options .....  | 135 |
| 5.18   | End station requirements for MMRP, MVRP, and MSRP.....                           | 135 |
| 5.18.1 | MMRP requirements and options .....  | 135 |
| 5.18.2 | MVRP requirements and options .....  | 136 |
| 5.18.3 | MSRP requirements and options .....  | 136 |
| 5.19   | VLAN-aware end station requirements for CFM.....                                 | 137 |
| 5.20   | End station requirements—FQTSS .....   | 137 |
| 5.21   | End station requirements for congestion notification .....                       | 138 |
| 5.22   | MAC-specific bridging methods .....  | 138 |
| 5.23   | EVB Bridge requirements.....   | 139 |
| 5.24   | EVB station requirements.....  | 139 |
| 5.24.1 | Edge relay (ER) requirements .....   | 140 |
| 5.25   | End station requirements—enhancements for scheduled traffic .....                | 141 |
| 5.26   | End station requirements—enhancements for frame preemption.....                  | 142 |
| 5.27   | End station requirements—PSFP.....   | 142 |
| 5.28   | End station requirements—Cyclic queuing and forwarding.....                      | 142 |
| 5.29   | TSN CNC station requirements .....   | 142 |
| 5.30   | VDP-NVO3 requirements.....   | 143 |
| 5.30.1 | VDP-NVO3 nNVE requirements .....   | 143 |
| 5.30.2 | VDP-NVO3 tNVE requirements .....   | 143 |
| 5.31   | End station requirements—ATS.....  | 143 |
| 6.     | Support of the MAC Service .....   | 144 |
| 6.1    | Basic architectural concepts and terms.....                                      | 145 |
| 6.2    | Provision of the MAC Service.....  | 145 |
| 6.2.1  | Point-to-point, multipoint-to-multipoint, and rooted-multipoint connectivity ... | 146 |
| 6.3    | Support of the MAC Service .....   | 146 |
| 6.4    | Preservation of the MAC Service .....  | 147 |
| 6.5    | Quality of service (QoS) maintenance.....  | 147 |
| 6.5.1  | Service availability .....   | 147 |
| 6.5.2  | Frame loss .....   | 148 |
| 6.5.3  | Frame misordering .....  | 148 |
| 6.5.4  | Frame duplication .....  | 149 |
| 6.5.5  | Transit delay .....  | 150 |
| 6.5.6  | Frame lifetime .....   | 150 |
| 6.5.7  | Undetected frame error rate .....  | 151 |
| 6.5.8  | Maximum Service Data Unit Size .....   | 151 |
| 6.5.9  | Priority .....   | 151 |
| 6.5.10 | Throughput .....   | 152 |
| 6.6    | Internal Sublayer Service (ISS) .....  | 153 |
| 6.7    | Support of the ISS by specific MAC procedures.....                               | 153 |
| 6.7.1  | Support of the ISS by IEEE Std 802.3 (Ethernet) .....                            | 153 |
| 6.7.2  | Frame preemption .....   | 153 |
| 6.8    | Enhanced Internal Sublayer Service (EISS).....                                   | 154 |
| 6.8.1  | Service primitives .....   | 154 |
| 6.8.2  | Status parameters .....  | 155 |
| 6.8.3  | Point-to-point parameters .....  | 155 |
| 6.8.4  | Control primitives and parameters .....  | 155 |

|        |  |     |
|--------|--|-----|
| 6.9    | Support of the EISS .....                                | 156 |
| 6.9.1  | Data indications .....                                   | 157 |
| 6.9.2  | Data requests .....                                      | 158 |
| 6.9.3  | Priority Code Point encoding .....                       | 158 |
| 6.9.4  | Regenerating priority .....                              | 160 |
| 6.10   | Support of the ISS/EISS by PIPs .....                    | 161 |
| 6.10.1 | Data indications .....                                   | 163 |
| 6.10.2 | Data requests .....                                      | 164 |
| 6.10.3 | Priority Code Point encoding .....                       | 164 |
| 6.11   | Support of the EISS by CBPs .....                        | 165 |
| 6.11.1 | Data indications .....                                   | 166 |
| 6.11.2 | Data requests .....                                      | 167 |
| 6.11.3 | Priority Code Point decoding .....                       | 168 |
| 6.11.4 | Regenerating priority .....                              | 168 |
| 6.12   | Protocol VLAN classification.....                        | 168 |
| 6.12.1 | Protocol Templates .....                                 | 170 |
| 6.12.2 | Protocol Group Identifiers .....                         | 170 |
| 6.12.3 | Protocol Group Database .....                            | 170 |
| 6.13   | Support of the ISS for attachment to a PBN.....          | 171 |
| 6.13.1 | Data requests .....                                      | 172 |
| 6.13.2 | Data indications .....                                   | 172 |
| 6.14   | Support of the ISS within a system.....                  | 173 |
| 6.15   | Support of the ISS by additional technologies.....       | 173 |
| 6.16   | Filtering services in Bridged Networks .....             | 173 |
| 6.16.1 | Purpose(s) of filtering service provision .....          | 174 |
| 6.16.2 | Goals of filtering service provision .....               | 174 |
| 6.16.3 | Users of filtering services .....                        | 174 |
| 6.16.4 | Basis of service .....                                   | 174 |
| 6.16.5 | Categories of service .....                              | 175 |
| 6.16.6 | Service configuration .....                              | 175 |
| 6.16.7 | Service definition for Extended Filtering Services ..... | 175 |
| 6.17   | EISS Multiplex Entity.....                               | 177 |
| 6.18   | Backbone Service Instance Multiplex Entity.....          | 178 |
| 6.18.1 | Demultiplexing direction .....                           | 179 |
| 6.18.2 | Multiplexing direction .....                             | 180 |
| 6.18.3 | Priority Code Point encoding .....                       | 180 |
| 6.18.4 | Status parameters .....                                  | 180 |
| 6.19   | TESI Multiplex Entity .....                              | 181 |
| 6.20   | Support of the ISS with signaled priority .....          | 182 |
| 6.20.1 | Data indications .....                                   | 182 |
| 6.20.2 | Data requests .....                                      | 183 |
| 6.21   | Infrastructure Segment Multiplex Entity .....            | 183 |
| 6.22   | PDU and protocol discrimination and media.....           | 184 |
| 7.     | Principles of Virtual Bridged Network operation.....     | 185 |
| 7.1    | Network overview.....                                    | 185 |
| 7.2    | Use of VLANs .....                                       | 186 |
| 7.3    | Active topology.....                                     | 186 |
| 7.4    | VLAN topology .....                                      | 187 |
| 7.5    | Locating end stations .....                              | 188 |
| 7.6    | Ingress, forwarding, and egress rules.....               | 189 |

|        |   |     |
|--------|---|-----|
| 8.     | Principles of Bridge operation .....              | 190 |
| 8.1    | Bridge operation .....                            | 190 |
| 8.1.1  | Relay .....                                       | 190 |
| 8.1.2  | Filtering and relaying information .....          | 191 |
| 8.1.3  | Duplicate frame prevention .....                  | 191 |
| 8.1.4  | Traffic segregation .....                         | 191 |
| 8.1.5  | Traffic reduction .....                           | 192 |
| 8.1.6  | Traffic expediting .....                          | 192 |
| 8.1.7  | Conversion of frame formats .....                 | 192 |
| 8.2    | Bridge architecture.....                          | 193 |
| 8.3    | Model of operation.....                           | 195 |
| 8.4    | Active topologies, learning, and forwarding ..... | 199 |
| 8.5    | Bridge Port Transmit and Receive.....             | 200 |
| 8.5.1  | Bridge Port connectivity .....                    | 200 |
| 8.5.2  | TPMR Port connectivity .....                      | 201 |
| 8.5.3  | Support of Higher Layer Entities .....            | 202 |
| 8.6    | The Forwarding Process .....                      | 202 |
| 8.6.1  | Active topology enforcement .....                 | 203 |
| 8.6.2  | Ingress filtering .....                           | 205 |
| 8.6.3  | Frame filtering .....                             | 205 |
| 8.6.4  | Egress filtering .....                            | 208 |
| 8.6.5  | Flow classification and metering .....            | 208 |
| 8.6.6  | Queuing frames .....                              | 217 |
| 8.6.7  | Queue management .....                            | 218 |
| 8.6.8  | Transmission selection .....                      | 219 |
| 8.6.9  | Scheduled traffic state machines .....            | 225 |
| 8.6.10 | Stream gate control state machines .....          | 232 |
| 8.6.11 | ATS Scheduler state machines .....                | 234 |
| 8.7    | The Learning Process.....                         | 238 |
| 8.7.1  | Default filtering utility criteria .....          | 238 |
| 8.7.2  | Enhanced filtering utility criteria .....         | 238 |
| 8.7.3  | Ageing of Dynamic Filtering Entries .....         | 239 |
| 8.8    | The Filtering Database (FDB) .....                | 239 |
| 8.8.1  | Static Filtering Entries .....                    | 242 |
| 8.8.2  | Static VLAN Registration Entries .....            | 243 |
| 8.8.3  | Dynamic Filtering Entries .....                   | 244 |
| 8.8.4  | MAC Address Registration Entries .....            | 245 |
| 8.8.5  | Dynamic VLAN Registration Entries .....           | 245 |
| 8.8.6  | Default Group filtering behavior .....            | 246 |
| 8.8.7  | Dynamic Reservation Entries .....                 | 247 |
| 8.8.8  | Allocation of VIDs to FIDs .....                  | 247 |
| 8.8.9  | Querying the FDB .....                            | 248 |
| 8.8.10 | Determination of the member set for a VID .....   | 252 |
| 8.8.11 | Permanent Database .....                          | 252 |
| 8.8.12 | Connection_Identifier .....                       | 252 |
| 8.9    | MST, SPB, and ESP configuration information.....  | 253 |
| 8.9.1  | MST Configuration Table .....                     | 254 |
| 8.9.2  | MST configuration identification .....            | 254 |
| 8.9.3  | FID to MSTI Allocation Table .....                | 254 |
| 8.9.4  | SPT Configuration Identification .....            | 254 |
| 8.10   | Spanning Tree Protocol Entity.....                | 255 |
| 8.11   | MRP entities .....                                | 255 |
| 8.12   | Bridge Management Entity .....                    | 256 |

|         |  |     |
|---------|--|-----|
| 8.13    | Addressing .....   | 256 |
| 8.13.1  | End stations .....   | 256 |
| 8.13.2  | Bridge Ports .....   | 256 |
| 8.13.3  | Use of LLC by Spanning Tree Protocol Entities .....                                      | 257 |
| 8.13.4  | Reserved MAC addresses .....   | 257 |
| 8.13.5  | Group MAC addresses for spanning tree entity .....                                       | 257 |
| 8.13.6  | Group MAC addresses for MRP Applications .....   | 259 |
| 8.13.7  | Bridge Management Entities .....   | 260 |
| 8.13.8  | Unique identification of a Bridge .....  | 260 |
| 8.13.9  | Points of attachment and connectivity for Higher Layer Entities .....                    | 260 |
| 8.13.10 | VLAN attachment and connectivity for Higher Layer Entities .....                         | 264 |
| 8.13.11 | CFM entities .....   | 265 |
| 9.      | Tagged frame format .....  | 267 |
| 9.1     | Purpose of tagging .....   | 267 |
| 9.2     | Representation and encoding of tag fields .....  | 267 |
| 9.3     | Tag format.....  | 268 |
| 9.4     | TPID formats .....   | 268 |
| 9.5     | Tag Protocol identification .....  | 268 |
| 9.6     | VLAN Tag Control Information (TCI).....  | 269 |
| 9.7     | Backbone Service Instance Tag Control Information (I-TAG TCI).....                       | 270 |
| 10.     | Multiple Registration Protocol (MRP) and Multiple MAC Registration Protocol (MMRP) ..... | 272 |
| 10.1    | MRP overview .....   | 272 |
| 10.2    | MRP architecture .....   | 275 |
| 10.3    | MRP Attribute Propagation (MAP).....   | 276 |
| 10.3.1  | MAP Context .....  | 277 |
| 10.4    | Requirements to be met by MRP.....   | 278 |
| 10.5    | Requirements for interoperability between MRP Participants .....                         | 278 |
| 10.6    | Protocol operation.....  | 280 |
| 10.7    | Protocol specification .....   | 284 |
| 10.7.1  | Notational conventions and abbreviations .....   | 285 |
| 10.7.2  | Registrar Administrative Controls .....  | 286 |
| 10.7.3  | Applicant Administrative Controls .....  | 287 |
| 10.7.4  | Protocol timers .....  | 287 |
| 10.7.5  | Protocol event definitions .....   | 288 |
| 10.7.6  | Protocol Action definitions .....  | 290 |
| 10.7.7  | Applicant state machine .....  | 292 |
| 10.7.8  | Registrar state machine .....  | 292 |
| 10.7.9  | LeaveAll state machine .....   | 292 |
| 10.7.10 | PeriodicTransmission state machine .....   | 295 |
| 10.7.11 | Timer values .....   | 295 |
| 10.7.12 | Operational reporting and statistics .....   | 296 |
| 10.7.13 | Interoperability considerations .....  | 296 |
| 10.7.14 | External control .....   | 297 |
| 10.8    | Structure and encoding of Multiple Registration Protocol Data Units (MRPDUs) .....       | 297 |
| 10.8.1  | Structure .....  | 297 |
| 10.8.2  | Encoding of MRPDUs parameters .....  | 299 |
| 10.8.3  | Packing and parsing MRPDUs .....   | 302 |
| 10.9    | Multiple MAC Registration Protocol (MMRP)—Purpose.....                                   | 304 |

|         |   |     |
|---------|---|-----|
| 10.10   | MMRP Model of operation.....  | 305 |
| 10.10.1 | Propagation of Group Membership information .....                   | 306 |
| 10.10.2 | Propagation of Group service requirement information .....          | 307 |
| 10.10.3 | Source pruning .....  | 307 |
| 10.10.4 | Use of Group service requirement registration by end stations ..... | 307 |
| 10.11   | Default Group filtering behavior and MMRP propagation .....         | 307 |
| 10.12   | Definition of the MMRP application .....                            | 309 |
| 10.12.1 | Definition of MRP elements .....                                    | 309 |
| 10.12.2 | Provision and support of Extended Filtering Services .....          | 311 |
| 10.12.3 | Use of “new” declaration capability .....                           | 313 |
| 10.12.4 | Attribute value support requirements .....                          | 313 |
| 10.12.5 | Registrar Administrative Controls .....                             | 313 |
| 11.     | VLAN topology management.....                                       | 314 |
| 11.1    | Static and dynamic VLAN configuration .....                         | 314 |
| 11.2    | Multiple VLAN Registration Protocol (MVRP) .....                    | 315 |
| 11.2.1  | MVRP overview .....   | 315 |
| 11.2.2  | VLAN registration service definition .....                          | 317 |
| 11.2.3  | Definition of the MVRP application .....                            | 318 |
| 11.2.4  | VID translation table .....   | 321 |
| 11.2.5  | Use of “new” declaration capability .....                           | 321 |
| 11.2.6  | New-Only Participant and Registrar Administrative Controls .....    | 321 |
| 11.2.7  | Attribute value support requirements .....                          | 321 |
| 12.     | Bridge management .....   | 322 |
| 12.1    | Management functions.....   | 322 |
| 12.1.1  | Configuration Management .....                                      | 322 |
| 12.1.2  | Fault Management .....  | 323 |
| 12.1.3  | Performance Management .....  | 323 |
| 12.1.4  | Security Management .....   | 323 |
| 12.1.5  | Accounting Management .....   | 323 |
| 12.2    | VLAN Bridge objects .....   | 323 |
| 12.3    | Data types .....  | 324 |
| 12.4    | Bridge Management Entity .....                                      | 325 |
| 12.4.1  | Bridge Configuration .....  | 325 |
| 12.4.2  | Port configuration .....  | 328 |
| 12.5    | MAC entities.....   | 330 |
| 12.5.1  | ISS Port Number table managed object (optional) .....               | 330 |
| 12.6    | Forwarding process.....   | 331 |
| 12.6.1  | The Port Counters .....   | 331 |
| 12.6.2  | Priority handling .....   | 332 |
| 12.6.3  | Traffic Class Table .....   | 339 |
| 12.7    | Filtering Database (FDB).....                                       | 340 |
| 12.7.1  | The Filtering Database object .....                                 | 340 |
| 12.7.2  | A Static Filtering Entry object .....                               | 341 |
| 12.7.3  | A Dynamic Filtering Entry object .....                              | 341 |
| 12.7.4  | A MAC Address Registration Entry object .....                       | 342 |
| 12.7.5  | A VLAN Registration Entry object .....                              | 342 |
| 12.7.6  | Permanent Database object .....                                     | 342 |
| 12.7.7  | General FDB operations .....  | 343 |
| 12.8    | Bridge Protocol Entity .....  | 345 |
| 12.8.1  | The Protocol Entity .....   | 345 |
| 12.8.2  | Bridge Port .....   | 348 |

|         |  |     |
|---------|--|-----|
| 12.9    | MRP Entities.....  | 352 |
| 12.9.1  | The MRP Timer object .....                                 | 352 |
| 12.9.2  | The MRP Attribute Type object .....                        | 353 |
| 12.9.3  | Periodic state machine objects .....                       | 354 |
| 12.10   | Bridge VLAN managed objects.....                           | 354 |
| 12.10.1 | Bridge VLAN Configuration managed object .....             | 355 |
| 12.10.2 | VLAN Configuration managed object .....                    | 360 |
| 12.10.3 | The VID to FID allocation managed object .....             | 361 |
| 12.11   | MMRP entities.....   | 363 |
| 12.11.1 | MMRP Configuration managed object .....                    | 363 |
| 12.12   | MST configuration entities .....                           | 365 |
| 12.12.1 | The MSTI List .....  | 365 |
| 12.12.2 | The FID to MSTID Allocation Table .....                    | 366 |
| 12.12.3 | The MST Configuration Table .....                          | 367 |
| 12.13   | Provider Bridge management .....                           | 369 |
| 12.13.1 | Provider Bridge Port Type managed object .....             | 370 |
| 12.13.2 | Customer Edge Port Configuration managed object .....      | 371 |
| 12.13.3 | Remote Customer Access managed object .....                | 374 |
| 12.14   | CFM entities .....   | 376 |
| 12.14.1 | Maintenance Domain list managed object .....               | 376 |
| 12.14.2 | CFM Stack managed object .....                             | 378 |
| 12.14.3 | Default MD Level managed object .....                      | 379 |
| 12.14.4 | Configuration Error List managed object .....              | 380 |
| 12.14.5 | Maintenance Domain managed object .....                    | 381 |
| 12.14.6 | Maintenance Association managed object .....               | 383 |
| 12.14.7 | Maintenance association Endpoint managed object .....      | 386 |
| 12.15   | Backbone Core Bridge (BCB) management.....                 | 393 |
| 12.16   | Backbone Edge Bridge (BEB) management .....                | 393 |
| 12.16.1 | BEB configuration managed object .....                     | 395 |
| 12.16.2 | BEB/PB/VLAN Bridge Port configuration managed object ..... | 399 |
| 12.16.3 | VIP configuration managed object .....                     | 399 |
| 12.16.4 | PIP configuration managed object .....                     | 400 |
| 12.16.5 | CBP Configuration managed object .....                     | 407 |
| 12.17   | DDCFM entities.....  | 410 |
| 12.17.1 | DDCFM Stack managed object .....                           | 410 |
| 12.17.2 | Reflection Responder managed object .....                  | 410 |
| 12.17.3 | RFM Receiver managed object .....                          | 414 |
| 12.17.4 | Decapsulator Responder managed object .....                | 415 |
| 12.17.5 | SFM Originator managed object .....                        | 417 |
| 12.18   | PBB-TE Protection Switching managed objects .....          | 420 |
| 12.18.1 | TE protection group list managed object .....              | 420 |
| 12.18.2 | TE protection group managed object .....                   | 421 |
| 12.19   | TPMR managed objects.....                                  | 423 |
| 12.19.1 | TPMR management entity .....                               | 424 |
| 12.19.2 | MAC and PHY entities .....                                 | 426 |
| 12.19.3 | Forwarding Process .....                                   | 426 |
| 12.19.4 | MAC Status Propagation Entity (MSPE) .....                 | 431 |
| 12.20   | Management entities for FQTSS .....                        | 433 |
| 12.20.1 | The Bandwidth Availability Parameter Table .....           | 433 |
| 12.20.2 | The Transmission Selection Algorithm Table .....           | 434 |
| 12.20.3 | The Priority Regeneration Override Table .....             | 434 |
| 12.20.4 | SR Class to Priority Mapping Table .....                   | 434 |

|          |  |     |
|----------|--|-----|
| 12.21    | Congestion Notification managed objects .....          | 435 |
| 12.21.1  | CN component managed object .....                      | 435 |
| 12.21.2  | CN component priority managed object .....             | 435 |
| 12.21.3  | CN Port priority managed object .....                  | 437 |
| 12.21.4  | Congestion Point managed object .....                  | 438 |
| 12.21.5  | Reaction Point port priority managed object .....      | 438 |
| 12.21.6  | Reaction Point group managed object .....              | 439 |
| 12.22    | Stream Reservation Protocol (SRP) entities .....       | 439 |
| 12.22.1  | SRP Bridge Base Table .....                            | 440 |
| 12.22.2  | SRP Bridge Port Table .....                            | 440 |
| 12.22.3  | SRP Latency Parameter Table .....                      | 441 |
| 12.22.4  | SRP Stream Table .....                                 | 441 |
| 12.22.5  | SRP Reservations Table .....                           | 441 |
| 12.22.6  | SRP Stream Preload Table .....                         | 442 |
| 12.22.7  | SRP Reservations Preload Table .....                   | 442 |
| 12.23    | Priority-based Flow Control objects .....              | 444 |
| 12.24    | 1:1 PBB-TE IPS managed objects .....                   | 444 |
| 12.24.1  | IPG list managed object .....                          | 444 |
| 12.24.2  | IPG managed object .....                               | 446 |
| 12.25    | Shortest Path Bridging managed objects .....           | 448 |
| 12.25.1  | The SPB System managed object .....                    | 449 |
| 12.25.2  | The SPB MTID Static managed object .....               | 451 |
| 12.25.3  | The SPB Topology Instance Dynamic managed object ..... | 453 |
| 12.25.4  | The SPB ECT Static Entry managed object .....          | 453 |
| 12.25.5  | The SPB ECT Dynamic Entry managed object .....         | 455 |
| 12.25.6  | The SPB Adjacency Static Entry managed object .....    | 456 |
| 12.25.7  | The SPB Adjacency Dynamic Entry managed object .....   | 457 |
| 12.25.8  | The SPBM BSI Static Entry managed object .....         | 457 |
| 12.25.9  | The SPB Topology Node Table managed object .....       | 459 |
| 12.25.10 | The SPB Topology ECT Table managed object .....        | 460 |
| 12.25.11 | The SPB Topology Edge Table managed object .....       | 460 |
| 12.25.12 | The SPBM Topology Service Table managed object .....   | 461 |
| 12.25.13 | The SPBV Topology Service Table managed object .....   | 462 |
| 12.25.14 | The ECMP ECT Static Entry managed object .....         | 463 |
| 12.26    | Edge Virtual Bridging (EVB) management.....            | 464 |
| 12.26.1  | EVB system base table .....                            | 467 |
| 12.26.2  | SBP table entry .....                                  | 469 |
| 12.26.3  | VSI table entry .....                                  | 470 |
| 12.26.4  | S-channel configuration and management .....           | 471 |
| 12.26.5  | ER management .....                                    | 473 |
| 12.27    | Edge Control Protocol (ECP) management.....            | 474 |
| 12.27.1  | ECP table entry .....                                  | 474 |
| 12.28    | Path Control and Reservation (PCR) management.....     | 475 |
| 12.28.1  | The PCR ECT Static Entry managed object .....          | 476 |
| 12.28.2  | The PCR Topology ECT Table managed object .....        | 478 |
| 12.29    | Managed objects for scheduled traffic.....             | 479 |
| 12.29.1  | The Gate Parameter Table .....                         | 479 |
| 12.29.2  | Timing points for scheduled traffic .....              | 481 |
| 12.30    | Managed objects for frame preemption.....              | 482 |
| 12.30.1  | Frame Preemption Parameter table .....                 | 482 |

|         |  |     |
|---------|--|-----|
| 12.31   | Managed objects for per-stream classification and metering ..... | 484 |
| 12.31.1 | The Stream Parameter Table .....                                 | 484 |
| 12.31.2 | The Stream Filter Instance Table .....                           | 485 |
| 12.31.3 | The Stream Gate Instance Table .....                             | 487 |
| 12.31.4 | The Flow Meter Instance Table .....                              | 490 |
| 12.31.5 | The Scheduler Instance Table .....                               | 490 |
| 12.31.6 | The Scheduler Group Instance Table .....                         | 491 |
| 12.31.7 | The Scheduler Port Parameter Table .....                         | 492 |
| 12.31.8 | The Scheduler Timing Characteristics Table .....                 | 492 |
| 12.32   | Stream reservation remote management.....                        | 494 |
| 12.32.1 | Bridge Delay .....   | 494 |
| 12.32.2 | Propagation Delay .....  | 496 |
| 12.32.3 | Static Trees .....   | 496 |
| 12.32.4 | MRP External Control .....                                       | 497 |
| 13.     | Spanning tree protocols .....                                    | 501 |
| 13.1    | Protocol design requirements.....                                | 502 |
| 13.2    | Protocol support requirements .....                              | 503 |
| 13.2.1  | MSTP support requirements .....                                  | 503 |
| 13.2.2  | SPB support requirements .....                                   | 503 |
| 13.3    | Protocol design goals .....                                      | 504 |
| 13.4    | RSTP overview .....  | 504 |
| 13.4.1  | Computation of the active topology .....                         | 505 |
| 13.4.2  | Example topologies .....   | 506 |
| 13.5    | MSTP overview .....  | 509 |
| 13.5.1  | Example topologies .....   | 510 |
| 13.5.2  | Relationship of MSTP to RSTP .....                               | 513 |
| 13.5.3  | Modeling an MST or SPT Region as a single Bridge .....           | 513 |
| 13.6    | SPB overview .....   | 514 |
| 13.7    | Compatibility and interoperability.....                          | 515 |
| 13.7.1  | Designated Port selection .....                                  | 515 |
| 13.7.2  | Force Protocol Version .....                                     | 515 |
| 13.8    | MST Configuration Identifier (MCID).....                         | 516 |
| 13.9    | Spanning tree priority vectors.....                              | 517 |
| 13.10   | CIST Priority Vector calculations.....                           | 519 |
| 13.11   | MST Priority Vector calculations .....                           | 521 |
| 13.12   | Port Role assignments.....                                       | 523 |
| 13.13   | Stable connectivity.....   | 524 |
| 13.14   | Communicating spanning tree information .....                    | 525 |
| 13.15   | Changing spanning tree information.....                          | 526 |
| 13.16   | Changing Port States with RSTP or MSTP .....                     | 527 |
| 13.16.1 | Subtree connectivity and priority vectors .....                  | 528 |
| 13.16.2 | Root Port transition to Forwarding .....                         | 528 |
| 13.16.3 | Designated Port transition to Forwarding .....                   | 528 |
| 13.16.4 | Master Port transition to Forwarding .....                       | 530 |
| 13.17   | Changing Port States with SPB .....                              | 532 |
| 13.17.1 | Agreement Digest .....   | 534 |
| 13.18   | Managing spanning tree topologies .....                          | 535 |
| 13.19   | Updating learned station location information .....              | 536 |
| 13.20   | Managing reconfiguration.....                                    | 538 |
| 13.21   | Partial and disputed connectivity.....                           | 539 |
| 13.22   | In-service upgrades .....  | 539 |
| 13.23   | Fragile Bridges.....   | 541 |

|          |  |     |
|----------|--|-----|
| 13.24    | Spanning tree protocol state machines..... | 541 |
| 13.25    | State machine timers .....                 | 543 |
| 13.25.1  | edgeDelayWhile .....                       | 544 |
| 13.25.2  | fdWhile .....                              | 544 |
| 13.25.3  | helloWhen .....                            | 544 |
| 13.25.4  | mdelayWhile .....                          | 544 |
| 13.25.5  | rbWhile .....                              | 544 |
| 13.25.6  | rcvdInfoWhile .....                        | 544 |
| 13.25.7  | rrWhile .....                              | 545 |
| 13.25.8  | tcDetected .....                           | 545 |
| 13.25.9  | tcWhile .....                              | 545 |
| 13.25.10 | pseudoInfoHelloWhen .....                  | 545 |
| 13.26    | Per Bridge variables.....                  | 545 |
| 13.26.1  | agreementDigest .....                      | 546 |
| 13.26.2  | BridgeIdentifier .....                     | 546 |
| 13.26.3  | BridgePriority .....                       | 546 |
| 13.26.4  | BridgeTimes .....                          | 546 |
| 13.26.5  | ForceProtocolVersion .....                 | 547 |
| 13.26.6  | MigrateTime .....                          | 547 |
| 13.26.7  | MstConfigId .....                          | 547 |
| 13.26.8  | AuxMstConfigId .....                       | 547 |
| 13.26.9  | rootPortId .....                           | 547 |
| 13.26.10 | rootPriority .....                         | 547 |
| 13.26.11 | rootTimes .....                            | 547 |
| 13.26.12 | TxHoldCount .....                          | 547 |

|          |                            |     |
|----------|----------------------------|-----|
| 13.27    | Per port variables .....   | 547 |
| 13.27.1  | AdminEdge .....            | 550 |
| 13.27.2  | ageingTime .....           | 550 |
| 13.27.3  | agree .....                | 550 |
| 13.27.4  | agreed .....               | 550 |
| 13.27.5  | agreedAbove .....          | 550 |
| 13.27.6  | agreedDigest .....         | 550 |
| 13.27.7  | agreedDigestValid .....    | 550 |
| 13.27.8  | agreeDigest .....          | 550 |
| 13.27.9  | agreeDigestValid .....     | 550 |
| 13.27.10 | agreedMisorder .....       | 551 |
| 13.27.11 | agreedN .....              | 551 |
| 13.27.12 | agreedND .....             | 551 |
| 13.27.13 | agreedPriority .....       | 551 |
| 13.27.14 | agreedTopology .....       | 551 |
| 13.27.15 | agreementOutstanding ..... | 551 |
| 13.27.16 | agreeN .....               | 551 |
| 13.27.17 | agreeND .....              | 551 |
| 13.27.18 | AutoEdge .....             | 551 |
| 13.27.19 | AutoIsolate .....          | 552 |
| 13.27.20 | designatedPriority .....   | 552 |
| 13.27.21 | designatedTimes .....      | 552 |
| 13.27.22 | disputed .....             | 552 |
| 13.27.23 | enableBPDUrx .....         | 552 |
| 13.27.24 | enableBPDUtx .....         | 552 |
| 13.27.25 | ExternalPortPathCost ..... | 552 |
| 13.27.26 | isL2gp .....               | 552 |
| 13.27.27 | isolate .....              | 553 |
| 13.27.28 | fdbFlush .....             | 553 |
| 13.27.29 | forward .....              | 553 |
| 13.27.30 | forwarding .....           | 553 |
| 13.27.31 | infoInternal .....         | 553 |
| 13.27.32 | infols .....               | 553 |
| 13.27.33 | InternalPortPathCost ..... | 553 |
| 13.27.34 | learn .....                | 554 |
| 13.27.35 | learning .....             | 554 |
| 13.27.36 | master .....               | 554 |
| 13.27.37 | mastered .....             | 554 |
| 13.27.38 | mcheck .....               | 554 |
| 13.27.39 | msgPriority .....          | 554 |
| 13.27.40 | msgTimes .....             | 554 |
| 13.27.41 | neighbourPriority .....    | 555 |
| 13.27.42 | newInfo .....              | 555 |
| 13.27.43 | newInfoMsti .....          | 555 |
| 13.27.44 | operEdge .....             | 555 |
| 13.27.45 | portEnabled .....          | 555 |
| 13.27.46 | portId .....               | 555 |
| 13.27.47 | portPriority .....         | 555 |
| 13.27.48 | portTimes .....            | 556 |
| 13.27.49 | proposed .....             | 556 |
| 13.27.50 | proposing .....            | 556 |
| 13.27.51 | pseudoRootId .....         | 556 |
| 13.27.52 | revdBPDU .....             | 556 |
| 13.27.53 | revdInfo .....             | 556 |

|          |   |     |
|----------|---|-----|
| 13.27.54 | rcvdInternal                            | 556 |
| 13.27.55 | rcvdMsg                                 | 556 |
| 13.27.56 | rcvdRSTP                                | 556 |
| 13.27.57 | rcvdSTP                                 | 556 |
| 13.27.58 | rcvdTc                                  | 556 |
| 13.27.59 | rcvdTcAck                               | 556 |
| 13.27.60 | rcvdTcn                                 | 557 |
| 13.27.61 | reRoot                                  | 557 |
| 13.27.62 | reselect                                | 557 |
| 13.27.63 | restrictedDomainRole                    | 557 |
| 13.27.64 | restrictedRole                          | 557 |
| 13.27.65 | restrictedTcn                           | 557 |
| 13.27.66 | role                                    | 557 |
| 13.27.67 | selected                                | 557 |
| 13.27.68 | selectedRole                            | 557 |
| 13.27.69 | sendRSTP                                | 558 |
| 13.27.70 | sync                                    | 558 |
| 13.27.71 | synced                                  | 558 |
| 13.27.72 | tcAck                                   | 558 |
| 13.27.73 | tcProp                                  | 558 |
| 13.27.74 | tick                                    | 558 |
| 13.27.75 | txCount                                 | 558 |
| 13.27.76 | updtInfo                                | 558 |
| 13.28    | State machine conditions and parameters | 558 |
| 13.28.1  | allSptAgree                             | 559 |
| 13.28.2  | allSynced                               | 559 |
| 13.28.3  | allTransmitReady                        | 559 |
| 13.28.4  | BestAgreementPriority                   | 559 |
| 13.28.5  | cist                                    | 559 |
| 13.28.6  | cistRootPort                            | 559 |
| 13.28.7  | cistDesignatedPort                      | 560 |
| 13.28.8  | EdgeDelay                               | 560 |
| 13.28.9  | forwardDelay                            | 560 |
| 13.28.10 | FwdDelay                                | 560 |
| 13.28.11 | HelloTime                               | 560 |
| 13.28.12 | MaxAge                                  | 560 |
| 13.28.13 | msti                                    | 560 |
| 13.28.14 | mstiDesignatedOrTCpropagatingRootPort   | 560 |
| 13.28.15 | mstiMasterPort                          | 560 |
| 13.28.16 | operPointToPoint                        | 560 |
| 13.28.17 | rcvdAnyMsg                              | 560 |
| 13.28.18 | rcvdCistMsg                             | 560 |
| 13.28.19 | rcvdMstiMsg                             | 561 |
| 13.28.20 | reRooted                                | 561 |
| 13.28.21 | rstpVersion                             | 561 |
| 13.28.22 | spt                                     | 561 |
| 13.28.23 | stpVersion                              | 561 |
| 13.28.24 | updtCistInfo                            | 561 |
| 13.28.25 | updtMstiInfo                            | 561 |

|          |   |     |
|----------|---|-----|
| 13.29    | State machine procedures .....                              | 561 |
| 13.29.1  | betterorsameInfo(newInfoIs) .....                           | 562 |
| 13.29.2  | clearAllRcvdMsgs() .....                                    | 562 |
| 13.29.3  | clearReselectTree() .....                                   | 562 |
| 13.29.4  | disableForwarding() .....                                   | 563 |
| 13.29.5  | disableLearning() .....                                     | 563 |
| 13.29.6  | enableForwarding() .....                                    | 563 |
| 13.29.7  | enableLearning() .....                                      | 563 |
| 13.29.8  | fromSameRegion() .....                                      | 563 |
| 13.29.9  | newTcDetected() .....                                       | 563 |
| 13.29.10 | newTcWhile() .....  | 563 |
| 13.29.11 | pseudoRcvMsgs() .....                                       | 564 |
| 13.29.12 | rcvInfo() .....   | 564 |
| 13.29.13 | rcvMsgs() .....   | 565 |
| 13.29.14 | rcvAgreements() .....                                       | 565 |
| 13.29.15 | recordAgreement() .....                                     | 565 |
| 13.29.16 | recordDispute() .....                                       | 566 |
| 13.29.17 | recordMastered() .....                                      | 566 |
| 13.29.18 | recordPriority() .....                                      | 566 |
| 13.29.19 | recordProposal() .....                                      | 566 |
| 13.29.20 | recordTimes() .....   | 566 |
| 13.29.21 | setReRootTree() .....                                       | 567 |
| 13.29.22 | setSelectedTree() .....                                     | 567 |
| 13.29.23 | setSyncTree() .....   | 567 |
| 13.29.24 | setTcFlags() .....  | 567 |
| 13.29.25 | setTcPropTree() .....                                       | 567 |
| 13.29.26 | syncMaster() .....  | 567 |
| 13.29.27 | txConfig() .....  | 567 |
| 13.29.28 | txRstp() .....  | 568 |
| 13.29.29 | txTcn() .....   | 568 |
| 13.29.30 | updtAgreement() .....                                       | 568 |
| 13.29.31 | updtBPDUVersion() .....                                     | 569 |
| 13.29.32 | updtDigest() .....  | 569 |
| 13.29.33 | updtRcvdInfoWhile() .....                                   | 570 |
| 13.29.34 | updtRolesTree() .....                                       | 571 |
| 13.29.35 | uptRolesDisabledTree() .....                                | 572 |
| 13.30    | The Port Timers state machine .....                         | 572 |
| 13.31    | Port Receive state machine .....                            | 573 |
| 13.32    | Port Protocol Migration state machine .....                 | 574 |
| 13.33    | Bridge Detection state machine .....                        | 574 |
| 13.34    | Port Transmit state machine .....                           | 575 |
| 13.35    | Port Information state machine .....                        | 576 |
| 13.36    | Port Role Selection state machine .....                     | 577 |
| 13.37    | Port Role Transitions state machine .....                   | 577 |
| 13.38    | Port State Transition state machine .....                   | 582 |
|          | 13.38.1 Port State transitions for the CIST and MSTIs ..... | 583 |
|          | 13.38.2 Port State transitions for SPTs .....               | 583 |
| 13.39    | Topology Change state machine .....                         | 584 |
| 13.40    | Layer 2 Gateway Port Receive state machine .....            | 585 |

|         |  |     |
|---------|--|-----|
| 13.41   | CEP spanning tree operation.....   | 585 |
| 13.41.1 | PEP operPointToPointMAC and operEdge .....                               | 585 |
| 13.41.2 | updtRolesTree() .....  | 586 |
| 13.41.3 | setReRootTree(), setSyncTree(), setTcPropTree() .....                    | 586 |
| 13.41.4 | allSynced, reRooted .....  | 586 |
| 13.41.5 | Configuration parameters .....   | 586 |
| 13.42   | Virtual Instance Port (VIP) spanning tree operation .....                | 587 |
| 14.     | Encoding of Bridge Protocol Data Units (BPDUs) .....                     | 588 |
| 14.1    | BPDU Structure .....   | 588 |
| 14.1.1  | Transmission and representation of octets .....                          | 588 |
| 14.1.2  | Common BPDU fields .....   | 588 |
| 14.2    | Encoding of parameter types .....  | 590 |
| 14.2.1  | Encoding of Protocol Identifiers .....                                   | 590 |
| 14.2.2  | Encoding of Protocol Version Identifiers .....                           | 590 |
| 14.2.3  | Encoding of BPDU types .....   | 590 |
| 14.2.4  | Encoding of flags .....  | 590 |
| 14.2.5  | Encoding of Bridge Identifiers .....                                     | 590 |
| 14.2.6  | Encoding of External Root Path Cost and Internal Root Path Cost .....    | 591 |
| 14.2.7  | Encoding of Port Identifiers .....                                       | 591 |
| 14.2.8  | Encoding of Timer Values .....   | 591 |
| 14.2.9  | Encoding of Port Role values .....                                       | 591 |
| 14.2.10 | Encoding of Length Values .....  | 592 |
| 14.2.11 | Encoding of Hop Counts .....   | 592 |
| 14.3    | Transmission of BPDUs .....  | 592 |
| 14.4    | Encoding and decoding of STP Configuration, RST, MST, and SPT BPDUs..... | 592 |
| 14.4.1  | MSTI Configuration Messages .....  | 594 |
| 14.5    | Validation of received BPDUs .....                                       | 595 |
| 14.6    | Validation and interoperability .....                                    | 596 |
| 15.     | Support of the MAC Service by PBNs .....                                 | 597 |
| 15.1    | Service transparency .....   | 597 |
| 15.2    | Customer service interfaces .....  | 598 |
| 15.3    | Port-based service interface .....                                       | 598 |
| 15.4    | C-tagged service interface .....   | 599 |
| 15.5    | S-tagged service interface.....  | 600 |
| 15.6    | Remote customer service interfaces (RCSIs) .....                         | 601 |
| 15.7    | Service instance segregation.....  | 604 |
| 15.8    | Service instance selection and identification .....                      | 604 |
| 15.9    | Service priority selection .....   | 605 |
| 15.10   | Service access protection .....  | 605 |
| 16.     | Principles of Provider Bridged Network (PBN) operation .....             | 606 |
| 16.1    | PBN overview.....  | 606 |
| 16.2    | Provider Bridged Network (PBN) .....                                     | 607 |
| 16.3    | Service instance connectivity.....                                       | 610 |
| 16.4    | Service provider learning of customer end station addresses.....         | 611 |
| 16.5    | Detection of connectivity loops through attached networks.....           | 611 |
| 16.6    | Network management .....   | 612 |
| 17.     | Management Information Base (MIB) .....                                  | 613 |
| 17.1    | Internet Standard Management Framework .....                             | 613 |

|         |   |     |
|---------|---|-----|
| 17.2    | Structure of the MIB .....  | 613 |
| 17.2.1  | Structure of the IEEE8021-TC-MIB .....  | 615 |
| 17.2.2  | Structure of the IEEE8021-BRIDGE-MIB .....                                    | 616 |
| 17.2.3  | Structure of the IEEE8021-SPANNING-TREE MIB .....                             | 620 |
| 17.2.4  | Structure of the IEEE8021-Q-BRIDGE-MIB .....                                  | 623 |
| 17.2.5  | Structure of the IEEE8021-PB-MIB .....  | 628 |
| 17.2.6  | Structure of the IEEE8021-MSTP-MIB .....                                      | 630 |
| 17.2.7  | Structure of the IEEE8021-CFM-MIB .....                                       | 633 |
| 17.2.8  | Structure of the IEEE8021-PBB-MIB .....                                       | 639 |
| 17.2.9  | Structure of the IEEE8021-DDCFM-MIBs .....                                    | 642 |
| 17.2.10 | Structure of the IEEE8021-PBBTE-MIB .....                                     | 644 |
| 17.2.11 | Structure of the TPMR MIB .....   | 647 |
| 17.2.12 | Structure of the IEEE8021-FQTSS-MIB .....                                     | 649 |
| 17.2.13 | Structure of the IEEE8021-CN-MIB .....  | 650 |
| 17.2.14 | Structure of the IEEE8021-SRP-MIB .....                                       | 652 |
| 17.2.15 | Structure of the IEEE8021-MVRPX-MIB .....                                     | 654 |
| 17.2.16 | Structure of the IEEE8021-MIRP-MIB .....                                      | 654 |
| 17.2.17 | Structure of the IEEE8021-PFC-MIB .....                                       | 655 |
| 17.2.18 | Structure of the IEEE8021-TEIPS-MIB .....                                     | 655 |
| 17.2.19 | Structure of the IEEE8021-SPB-MIB .....                                       | 657 |
| 17.2.20 | Structure of the IEEE8021-EVB-MIB .....                                       | 662 |
| 17.2.21 | Structure of the IEEE8021-ECMP-MIB .....                                      | 666 |
| 17.2.22 | Structure of the IEEE8021-ST-MIB .....  | 667 |
| 17.2.23 | Structure of the IEEE8021-Preemption-MIB .....                                | 668 |
| 17.2.24 | Structure of the IEEE8021-PSFP-MIB .....                                      | 668 |
| 17.2.25 | Structure of the IEEE8021-TSN-REMOTE-MANAGEMENT-MIB .....                     | 671 |
| 17.3    | MIB module relationships .....  | 673 |
| 17.3.1  | Relationship of the IEEE8021-TC-MIB to other MIB modules .....                | 673 |
| 17.3.2  | Relationship of the IEEE8021-BRIDGE-MIB to other MIB modules .....            | 673 |
| 17.3.3  | Relationship of the IEEE8021-RSTP MIB to other MIB modules .....              | 676 |
| 17.3.4  | Relationship of the IEEE8021-Q-BRIDGE-MIB to other MIB modules .....          | 676 |
| 17.3.5  | Relationship of the IEEE8021-PB-BRIDGE MIB to other MIB modules .....         | 678 |
| 17.3.6  | Relationship of the IEEE8021-MSTP-MIB to other MIB modules .....              | 678 |
| 17.3.7  | Relationship of the IEEE8021-CFM-MIB to other MIB modules .....               | 678 |
| 17.3.8  | Relationship of the IEEE8021-PBB-MIB to other MIB modules .....               | 679 |
| 17.3.9  | Relationship of the IEEE8021-DDCFM to other MIB modules .....                 | 680 |
| 17.3.10 | Relationship of the IEEE8021-PBBTE-MIB to other MIB modules .....             | 680 |
| 17.3.11 | Relationship of the IEEE8021-TPMR MIB to other MIB modules .....              | 681 |
| 17.3.12 | Relationship of the IEEE8021-FQTSS-MIB to other MIB modules .....             | 681 |
| 17.3.13 | Relationship of the IEEE8021-CN-MIB to other MIB modules .....                | 681 |
| 17.3.14 | Relationship of the IEEE8021-SRP-MIB to other MIB modules .....               | 682 |
| 17.3.15 | Relationship of the IEEE8021-MVRPX-MIB to other MIB modules .....             | 682 |
| 17.3.16 | Relationship of the IEEE8021-MIRP-MIB to other MIB modules .....              | 682 |
| 17.3.17 | Relationship of the IEEE8021-PFC-MIB to other MIB modules .....               | 682 |
| 17.3.18 | Relationship of the IEEE8021-TEIPS-MIB to other MIB modules .....             | 683 |
| 17.3.19 | Relationship of the IEEE8021-SPB-MIB to other MIB modules .....               | 683 |
| 17.3.20 | Relationship of the IEEE8021-EVB-MIB to other MIB modules .....               | 683 |
| 17.3.21 | Relationship of the IEEE8021-ECMP-MIB to other MIB modules .....              | 683 |
| 17.3.22 | Relationship of the IEEE8021-ST-MIB to other MIB modules .....                | 683 |
| 17.3.23 | Relationship of the IEEE8021-Preemption-MIB to other MIB modules .....        | 684 |
| 17.3.24 | Relationship of IEEE8021-PSFP-MIB to other MIB modules .....                  | 684 |
| 17.3.25 | Relationship of IEEE8021-TSN-REMOTE-MANAGEMENT-MIB to other MIB modules ..... | 684 |

|         |  |     |
|---------|--|-----|
| 17.4    | Security considerations .....  | 684 |
| 17.4.1  | Security considerations of the IEEE8021-TC-MIB .....                     | 684 |
| 17.4.2  | Security considerations of the IEEE8021-BRIDGE-MIB .....                 | 685 |
| 17.4.3  | Security considerations of the IEEE8021-SPANNING-TREE MIB .....          | 686 |
| 17.4.4  | Security considerations of the IEEE8021-Q-BRIDGE-MIB .....               | 686 |
| 17.4.5  | Security considerations of the IEEE8021-PB-MIB .....                     | 687 |
| 17.4.6  | Security considerations of the IEEE8021-MSTP-MIB .....                   | 687 |
| 17.4.7  | Security considerations of the IEEE8021-CFM-MIB .....                    | 688 |
| 17.4.8  | Security considerations of the IEEE8021-PBB-MIB .....                    | 690 |
| 17.4.9  | Security considerations of the IEEE8021-DDCFM-MIB .....                  | 691 |
| 17.4.10 | Security considerations of the IEEE8021-PBBTE-MIB .....                  | 691 |
| 17.4.11 | Security considerations of the IEEE8021-TPMR-MIB .....                   | 692 |
| 17.4.12 | Security considerations of the IEEE8021-FQTSS-MIB .....                  | 692 |
| 17.4.13 | Security considerations of the IEEE8021-CN-MIB .....                     | 693 |
| 17.4.14 | Security considerations of the IEEE8021-SRP-MIB .....                    | 695 |
| 17.4.15 | Security considerations of the IEEE8021-MVRPX-MIB .....                  | 695 |
| 17.4.16 | Security considerations of the IEEE8021-MIRP-MIB .....                   | 696 |
| 17.4.17 | Security considerations of the IEEE8021-PFC-MIB .....                    | 696 |
| 17.4.18 | Security considerations of the IEEE8021-TEIPS-MIB .....                  | 696 |
| 17.4.19 | Security considerations of the IEEE8021-SPB-MIB .....                    | 697 |
| 17.4.20 | Security considerations of the IEEE8021-EVB-MIB .....                    | 697 |
| 17.4.21 | Security considerations of the IEEE8021-ECMP-MIB .....                   | 699 |
| 17.4.22 | Security considerations of the IEEE8021-ST-MIB .....                     | 699 |
| 17.4.23 | Security considerations of the IEEE8021-Preemption-MIB .....             | 700 |
| 17.4.24 | Security considerations of the IEEE8021-PSFP-MIB .....                   | 700 |
| 17.4.25 | Security considerations of the IEEE8021-TSN-REMOTE-MANAGEMENT-MIB<br>702 |     |
| 17.5    | Dynamic component and Port creation.....                                 | 703 |
| 17.5.1  | Overview of the dynamically created Bridge entities .....                | 703 |
| 17.5.2  | Component creation .....   | 704 |
| 17.5.3  | Port creation .....  | 705 |
| 17.6    | MIB operations for service interface configuration.....                  | 715 |
| 17.6.1  | Provisioning PBN service interfaces .....                                | 715 |
| 17.6.2  | Provisioning Backbone Bridged Network service interfaces .....           | 718 |

|         |  |      |
|---------|--|------|
| 17.7    | MIB modules .....  | 724  |
| 17.7.1  | Definitions for the IEEE8021-TC-MIB module .....                   | 724  |
| 17.7.2  | Definitions for the IEEE8021-BRIDGE-MIB module .....               | 733  |
| 17.7.3  | Definitions for the IEEE8021-SPANNING-TREE-MIB module .....        | 766  |
| 17.7.4  | Definitions for the IEEE8021-Q-BRIDGE-MIB module .....             | 781  |
| 17.7.5  | Definitions for the IEEE8021-PB-MIB module .....                   | 819  |
| 17.7.6  | Definitions for the IEEE8021-MSTP-MIB module .....                 | 834  |
| 17.7.7  | Definitions for the CFM MIB modules .....                          | 858  |
| 17.7.8  | Definitions for the IEEE8021-PBB-MIB module .....                  | 926  |
| 17.7.9  | Definitions for the IEEE8021-DDCFM-MIB module .....                | 945  |
| 17.7.10 | Definitions for the IEEE8021-PBBTE-MIB module .....                | 960  |
| 17.7.11 | Definitions for the IEEE8021-TPMR-MIB module .....                 | 974  |
| 17.7.12 | Definitions for the IEEE8021-FQTSS-MIB module .....                | 986  |
| 17.7.13 | Definitions for the IEEE8021-CN-MIB module .....                   | 998  |
| 17.7.14 | Definitions for the IEEE8021-SRP-MIB module .....                  | 1028 |
| 17.7.15 | Definitions for the IEEE8021-MVRPX-MIB module .....                | 1046 |
| 17.7.16 | Definitions for the IEEE8021-MIRP-MIB module .....                 | 1050 |
| 17.7.17 | Definitions for the IEEE8021-PFC-MIB module .....                  | 1055 |
| 17.7.18 | Definitions for the IEEE8021-TEIPS-V2-MIB module .....             | 1058 |
| 17.7.19 | Definitions for the IEEE8021-SPB-MIB module .....                  | 1070 |
| 17.7.20 | Definitions for the IEEE8021-EVB-MIB module .....                  | 1106 |
| 17.7.21 | Definitions for the IEEE8021-ECMP-MIB module .....                 | 1130 |
| 17.7.22 | Definitions for the IEEE8021-ST-MIB module .....                   | 1137 |
| 17.7.23 | Definitions for the IEEE8021-Preemption-MIB module .....           | 1148 |
| 17.7.24 | Definitions for the IEEE8021-PSFP-MIB module .....                 | 1153 |
| 17.7.25 | Definitions for the IEEE8021-TSN-REMOTE-MANAGEMENT-MIB module .... | 1173 |
| 18.     | Principles of Connectivity Fault Management operation .....        | 1182 |
| 18.1    | Maintenance Domains and DoSAPs.....                                | 1183 |
| 18.2    | Service instances and MAs .....                                    | 1185 |
| 18.3    | Maintenance Domain Levels .....                                    | 1186 |
| 19.     | CFM entity operation.....  | 1190 |
| 19.1    | Maintenance Points (MPs).....                                      | 1190 |

|         |   |      |
|---------|---|------|
| 19.2    | MA Endpoints (MEPs) .....                     | 1190 |
| 19.2.1  | MEP identification .....                      | 1190 |
| 19.2.2  | MEP functions .....                           | 1192 |
| 19.2.3  | MEP architecture .....                        | 1192 |
| 19.2.4  | MP Type Demultiplexer .....                   | 1194 |
| 19.2.5  | MP Multiplexer .....                          | 1194 |
| 19.2.6  | MP Level Demultiplexer .....                  | 1194 |
| 19.2.7  | MP OpCode Demultiplexer .....                 | 1194 |
| 19.2.8  | MEP Continuity Check Receiver .....           | 1194 |
| 19.2.9  | MEP Continuity Check Initiator .....          | 1195 |
| 19.2.10 | MP Loopback Responder .....                   | 1195 |
| 19.2.11 | MEP Loopback Initiator .....                  | 1196 |
| 19.2.12 | MEP Linktrace Initiator .....                 | 1196 |
| 19.2.13 | MEP LTI SAP .....                             | 1196 |
| 19.2.14 | MEP Linktrace SAP .....                       | 1196 |
| 19.2.15 | MEP CCM Database .....                        | 1196 |
| 19.2.16 | MEP Fault Notification Generator .....        | 1196 |
| 19.2.17 | MEP Decapsulator Responder (DR) .....         | 1196 |
| 19.2.18 | MEP RFM Receiver .....                        | 1197 |
| 19.3    | MIP Half Function .....                       | 1197 |
| 19.3.1  | MHF identification .....                      | 1197 |
| 19.3.2  | MHF functions .....                           | 1197 |
| 19.3.3  | MHF architecture .....                        | 1198 |
| 19.3.4  | MHF Level Demultiplexer .....                 | 1198 |
| 19.3.5  | MHF Type Demultiplexer .....                  | 1199 |
| 19.3.6  | MHF OpCode Demultiplexer .....                | 1199 |
| 19.3.7  | MHF Multiplexer .....                         | 1199 |
| 19.3.8  | MHF Loopback Responder .....                  | 1199 |
| 19.3.9  | MHF Continuity Check Receiver .....           | 1199 |
| 19.3.10 | MIP CCM Database .....                        | 1199 |
| 19.3.11 | MHF Linktrace SAP .....                       | 1199 |
| 19.3.12 | MHF DR .....                                  | 1199 |
| 19.3.13 | MHF RFM Receiver .....                        | 1199 |
| 19.4    | MP addressing.....                            | 1200 |
| 19.5    | Linktrace Output Multiplexer (LOM).....       | 1200 |
| 19.6    | Linktrace Responder .....                     | 1201 |
| 20.     | CFM protocols .....                           | 1203 |
| 20.1    | Continuity Check protocol.....                | 1204 |
| 20.1.1  | MAC status reporting in the CCM .....         | 1206 |
| 20.1.2  | Defects and Fault Alarms .....                | 1206 |
| 20.1.3  | CCM reception .....                           | 1206 |
| 20.2    | Loopback protocol .....                       | 1207 |
| 20.2.1  | LBM transmission .....                        | 1207 |
| 20.2.2  | LBM reception and LBR transmission .....      | 1208 |
| 20.2.3  | LBR reception .....                           | 1209 |
| 20.3    | Linktrace protocol.....                       | 1209 |
| 20.3.1  | LTM origination .....                         | 1210 |
| 20.3.2  | LTM reception, forwarding, and replying ..... | 1211 |
| 20.3.3  | LTR reception .....                           | 1212 |
| 20.4    | CFM state machines.....                       | 1213 |

|         |  |      |
|---------|--|------|
| 20.5    | CFM state machine timers .....                     | 1213 |
| 20.5.1  | LTFwhile .....                                     | 1213 |
| 20.5.2  | CCIwhile .....                                     | 1213 |
| 20.5.3  | errorCCMwhile .....                                | 1214 |
| 20.5.4  | xconCCMwhile .....                                 | 1215 |
| 20.5.5  | LBIwhile .....                                     | 1215 |
| 20.5.6  | FNGwhile .....                                     | 1215 |
| 20.5.7  | mmCCMwhile .....                                   | 1215 |
| 20.5.8  | mmLocwhile .....                                   | 1215 |
| 20.5.9  | mmFNGwhile .....                                   | 1215 |
| 20.5.10 | rMEPwhile .....                                    | 1215 |
| 20.6    | CFM procedures .....                               | 1215 |
| 20.6.1  | CCMtime() .....                                    | 1215 |
| 20.7    | Maintenance Domain variable .....                  | 1216 |
| 20.7.1  | mdLevel .....                                      | 1216 |
| 20.8    | MA variables.....                                  | 1216 |
| 20.8.1  | CCMinterval .....                                  | 1216 |
| 20.9    | MEP variables.....                                 | 1216 |
| 20.9.1  | MEPactive .....                                    | 1217 |
| 20.9.2  | enableRmepDefect .....                             | 1217 |
| 20.9.3  | MAdefectIndication .....                           | 1217 |
| 20.9.4  | allRMEPsDead .....                                 | 1218 |
| 20.9.5  | lowestAlarmPri .....                               | 1218 |
| 20.9.6  | presentRDI .....                                   | 1218 |
| 20.9.7  | MEPprimaryVID .....                                | 1218 |
| 20.9.8  | presentTraffic .....                               | 1218 |
| 20.9.9  | presentmmLoc .....                                 | 1218 |
| 20.9.10 | ISpresentTraffic .....                             | 1218 |
| 20.9.11 | ISpresentmmLoc .....                               | 1218 |
| 20.9.12 | EpMEP .....  | 1219 |
| 20.10   | MEP Continuity Check Initiator variables.....      | 1219 |
| 20.10.1 | CCIenabled .....                                   | 1219 |
| 20.10.2 | CCIsentCCMs .....                                  | 1219 |
| 20.10.3 | MACstatusChanged .....                             | 1219 |
| 20.10.4 | Npaths .....                                       | 1219 |
| 20.10.5 | flowHash[ ] .....                                  | 1219 |
| 20.10.6 | pathN .....  | 1219 |
| 20.10.7 | CCMent .....                                       | 1220 |
| 20.11   | MEP Continuity Check Initiator procedures .....    | 1220 |
| 20.11.1 | xmitCCM() .....                                    | 1220 |
| 20.12   | MEP Continuity Check Initiator state machine ..... | 1221 |
| 20.13   | MHF Continuity Check Receiver variables.....       | 1221 |
| 20.13.1 | MHFrecvdCCM .....                                  | 1221 |
| 20.13.2 | MHFCCMPDU .....                                    | 1221 |
| 20.14   | MHF Continuity Check Receiver procedures.....      | 1222 |
| 20.14.1 | MHFprocessCCM() .....                              | 1222 |
| 20.15   | MHF Continuity Check Receiver state machine .....  | 1222 |

|          |  |      |
|----------|--|------|
| 20.16    | MEP Continuity Check Receiver variables .....    | 1222 |
| 20.16.1  | CCMreceivedEqual .....                           | 1223 |
| 20.16.2  | CCMequalPDU .....                                | 1223 |
| 20.16.3  | CCMreceivedLow .....                             | 1223 |
| 20.16.4  | CCMlowPDU .....                                  | 1223 |
| 20.16.5  | recvdMacAddress .....                            | 1223 |
| 20.16.6  | recvdRDI .....                                   | 1223 |
| 20.16.7  | recvdInterval .....                              | 1223 |
| 20.16.8  | recvdPortState .....                             | 1223 |
| 20.16.9  | recvdInterfaceStatus .....                       | 1223 |
| 20.16.10 | recvdSenderId .....                              | 1224 |
| 20.16.11 | recvdFrame .....                                 | 1224 |
| 20.16.12 | CCMsequenceErrors .....                          | 1224 |
| 20.16.13 | rcvdTrafficBit .....                             | 1224 |
| 20.17    | MEP Continuity Check Receiver procedures .....   | 1224 |
| 20.17.1  | MEPprocessEqualCCM() .....                       | 1224 |
| 20.17.2  | MEPprocessLowCCM() .....                         | 1225 |
| 20.18    | MEP Continuity Check Receiver state machine..... | 1225 |
| 20.19    | Remote MEP variables .....                       | 1225 |
| 20.19.1  | rMEPCCMdefect .....                              | 1226 |
| 20.19.2  | rMEPlastRDI and rMEPlastRDI[i] .....             | 1226 |
| 20.19.3  | rMEPlastPortState .....                          | 1226 |
| 20.19.4  | rMEPlastInterfaceStatus .....                    | 1226 |
| 20.19.5  | rMEPlastSenderId .....                           | 1227 |
| 20.19.6  | rCCMreceived .....                               | 1227 |
| 20.19.7  | rMEPmacAddress .....                             | 1227 |
| 20.19.8  | rMEPportStatusDefect .....                       | 1227 |
| 20.19.9  | rMEPinterfaceStatusDefect .....                  | 1227 |
| 20.19.10 | lastPathN .....                                  | 1227 |
| 20.20    | Remote MEP state machine.....                    | 1227 |
| 20.21    | Remote MEP Error variables.....                  | 1227 |
| 20.21.1  | errorCCMreceived .....                           | 1228 |
| 20.21.2  | errorCCMlastFailure .....                        | 1228 |
| 20.21.3  | errorCCMdefect .....                             | 1229 |
| 20.22    | Remote MEP Error state machine .....             | 1229 |
| 20.23    | MEP Cross Connect variables .....                | 1229 |
| 20.23.1  | xconCCMreceived .....                            | 1229 |
| 20.23.2  | xconCCMlastFailure .....                         | 1229 |
| 20.23.3  | xconCCMdefect .....                              | 1230 |
| 20.24    | MEP Cross Connect state machine.....             | 1230 |
| 20.25    | MEP Mismatch variables.....                      | 1230 |
| 20.25.1  | mmCCMreceived .....                              | 1230 |
| 20.25.2  | mmCCMdefect .....                                | 1231 |
| 20.25.3  | mmCCMTime .....                                  | 1231 |
| 20.25.4  | disableLocdefect .....                           | 1231 |
| 20.25.5  | mmLocdefect .....                                | 1231 |
| 20.26    | MEP Mismatch state machines.....                 | 1231 |
| 20.27    | MP Loopback Responder variables .....            | 1231 |
| 20.27.1  | LBMreceived .....                                | 1231 |
| 20.27.2  | LBMpDU .....                                     | 1232 |
| 20.28    | MP Loopback Responder procedures .....           | 1233 |
| 20.28.1  | ProcessLBM() .....                               | 1233 |
| 20.28.2  | xmitLBR() .....                                  | 1233 |
| 20.29    | MP Loopback Responder state machine.....         | 1234 |

|         |  |      |
|---------|--|------|
| 20.30   | MEP Loopback Initiator variables .....                       | 1234 |
| 20.30.1 | LBMstosend .....   | 1235 |
| 20.30.2 | nextLBMtransID .....   | 1235 |
| 20.30.3 | expectedLBRtransID .....                                     | 1235 |
| 20.30.4 | LBIactive .....  | 1235 |
| 20.30.5 | xmitReady .....  | 1235 |
| 20.30.6 | LBRreceived .....  | 1235 |
| 20.30.7 | LBRPDU .....   | 1235 |
| 20.31   | MEP Loopback Initiator transmit procedures.....              | 1235 |
| 20.31.1 | xmitLBM() .....  | 1236 |
| 20.32   | MEP Loopback Initiator transmit state machine .....          | 1236 |
| 20.33   | MEP Loopback Initiator receive procedures .....              | 1236 |
| 20.33.1 | ProcessLBR() .....   | 1237 |
| 20.34   | MEP Loopback Initiator receive state machine.....            | 1238 |
| 20.35   | MEP Fault Notification Generator variables .....             | 1238 |
| 20.35.1 | fngPriority .....  | 1238 |
| 20.35.2 | fngDefect .....  | 1238 |
| 20.35.3 | fngAlarmTime .....   | 1238 |
| 20.35.4 | fngResetTime .....   | 1239 |
| 20.35.5 | someRMEPCCMdefect .....                                      | 1239 |
| 20.35.6 | someMACstatusDefect .....                                    | 1239 |
| 20.35.7 | someRDId defect .....  | 1239 |
| 20.35.8 | highestDefectPri .....                                       | 1239 |
| 20.35.9 | highestDefect .....  | 1239 |
| 20.36   | MEP Fault Notification Generator procedures .....            | 1239 |
| 20.36.1 | xmitFaultAlarm() .....                                       | 1240 |
| 20.37   | MEP Fault Notification Generator state machine.....          | 1240 |
| 20.38   | MEP Mismatch Fault Notification Generator variables .....    | 1240 |
| 20.38.1 | mfngAllowed .....  | 1241 |
| 20.38.2 | mmdefectIndication .....                                     | 1241 |
| 20.38.3 | mfngAlarmTime .....  | 1241 |
| 20.38.4 | mfngResetTime .....  | 1241 |
| 20.39   | MEP Mismatch Fault Notification Generator procedures .....   | 1241 |
| 20.39.1 | xmitFaultAlarm() .....                                       | 1241 |
| 20.40   | MEP Mismatch Fault Notification Generator state machine..... | 1241 |
| 20.41   | MEP Linktrace Initiator variables.....                       | 1241 |
| 20.41.1 | nextLTMtransID .....   | 1242 |
| 20.41.2 | ltmReplyList .....   | 1242 |
| 20.42   | MEP Linktrace Initiator procedures .....                     | 1244 |
| 20.42.1 | xmitLTM() .....  | 1244 |
| 20.43   | MEP Linktrace Initiator receive variables .....              | 1245 |
| 20.43.1 | LTRreceived .....  | 1245 |
| 20.43.2 | LTRPDU .....   | 1245 |
| 20.44   | MEP Linktrace Initiator receive procedures.....              | 1245 |
| 20.44.1 | ProcessLTR() .....   | 1246 |
| 20.45   | MEP Linktrace Initiator receive state machine.....           | 1246 |
| 20.46   | Linktrace Responder variables.....                           | 1246 |
| 20.46.1 | nPendingLTRs .....   | 1246 |
| 20.46.2 | LTMreceived .....  | 1247 |
| 20.46.3 | LTM PDU .....  | 1247 |

|         |   |      |
|---------|---|------|
| 20.47   | LTM Receiver procedures .....                     | 1247 |
| 20.47.1 | ProcessLTM() .....                                | 1247 |
| 20.47.2 | clearPendingLTRs() .....                          | 1251 |
| 20.47.3 | ForwardLTM() .....                                | 1251 |
| 20.47.4 | enqueLTR() .....                                  | 1252 |
| 20.48   | LTM Receiver state machine .....                  | 1254 |
| 20.49   | LTR Transmitter procedure .....                   | 1254 |
| 20.49.1 | xmitOldestLTR() .....                             | 1254 |
| 20.50   | LTR Transmitter state machine .....               | 1254 |
| 20.51   | CFM PDU validation and versioning .....           | 1254 |
| 20.51.1 | Goals of CFM PDU versioning .....                 | 1255 |
| 20.51.2 | PDU transmission .....                            | 1255 |
| 20.51.3 | PDU validation .....                              | 1256 |
| 20.51.4 | Validation pass .....                             | 1256 |
| 20.51.5 | Execution pass .....                              | 1257 |
| 20.51.6 | Future extensions .....                           | 1258 |
| 20.52   | PDU identification .....                          | 1258 |
| 20.53   | Use of transaction IDs and sequence numbers ..... | 1258 |
| 21.     | Encoding of CFM PDUs .....                        | 1260 |
| 21.1    | Structure, representation, and encoding .....     | 1260 |
| 21.2    | CFM encapsulation .....                           | 1260 |
| 21.3    | CFM request and indication parameters .....       | 1261 |
| 21.3.1  | destination_address parameter .....               | 1261 |
| 21.3.2  | source_address parameter .....                    | 1261 |
| 21.4    | Common CFM Header .....                           | 1261 |
| 21.4.1  | MD Level .....                                    | 1261 |
| 21.4.2  | Version .....                                     | 1261 |
| 21.4.3  | OpCode .....                                      | 1262 |
| 21.4.4  | Flags .....                                       | 1262 |
| 21.4.5  | First TLV Offset .....                            | 1263 |
| 21.5    | TLV format .....                                  | 1263 |
| 21.5.1  | General format for CFM TLVs .....                 | 1263 |
| 21.5.2  | Organization-Specific TLV .....                   | 1263 |
| 21.5.3  | Sender ID TLV .....                               | 1265 |
| 21.5.4  | Port Status TLV .....                             | 1266 |
| 21.5.5  | Interface Status TLV .....                        | 1267 |
| 21.5.6  | Data TLV .....                                    | 1268 |
| 21.5.7  | End TLV .....                                     | 1268 |
| 21.6    | CCM format .....                                  | 1268 |
| 21.6.1  | Flags .....                                       | 1269 |
| 21.6.2  | First TLV Offset .....                            | 1270 |
| 21.6.3  | Sequence Number .....                             | 1270 |
| 21.6.4  | Maintenance association Endpoint Identifier ..... | 1270 |
| 21.6.5  | Maintenance Association Identifier .....          | 1270 |
| 21.6.6  | Defined by ITU-T G.8013/Y.1731 .....              | 1273 |
| 21.6.7  | Optional CCM TLVs .....                           | 1273 |
| 21.7    | LBM and LBR formats .....                         | 1273 |
| 21.7.1  | Flags .....                                       | 1274 |
| 21.7.2  | First TLV Offset .....                            | 1274 |
| 21.7.3  | Loopback Transaction Identifier .....             | 1274 |
| 21.7.4  | Additional LBM/LBR TLVs .....                     | 1274 |
| 21.7.5  | PBB-TE MIP TLV .....                              | 1274 |

|        |  |      |
|--------|--|------|
| 21.8   | LTM format .....   | 1275 |
| 21.8.1 | Flags .....  | 1276 |
| 21.8.2 | First TLV Offset .....   | 1276 |
| 21.8.3 | LTM Transaction Identifier .....   | 1276 |
| 21.8.4 | LTM TTL .....  | 1276 |
| 21.8.5 | Original MAC Address .....   | 1276 |
| 21.8.6 | Target MAC Address .....   | 1276 |
| 21.8.7 | Additional LTM TLVs .....  | 1277 |
| 21.8.8 | LTM Egress Identifier TLV .....  | 1277 |
| 21.9   | LTR format .....   | 1277 |
| 21.9.1 | Flags .....  | 1277 |
| 21.9.2 | First TLV Offset .....   | 1278 |
| 21.9.3 | LTR Transaction Identifier .....   | 1278 |
| 21.9.4 | Reply TTL .....  | 1278 |
| 21.9.5 | Relay Action .....   | 1279 |
| 21.9.6 | Additional LTR TLVs .....  | 1279 |
| 21.9.7 | LTR Egress Identifier TLV .....  | 1279 |
| 21.9.8 | Reply Ingress TLV .....  | 1280 |
| 21.9.9 | Reply Egress TLV .....   | 1281 |
| 22.    | CFM in systems .....   | 1283 |
| 22.1   | CFM shims in Bridges .....   | 1283 |
| 22.1.1 | Preliminary positioning of MPs .....   | 1283 |
| 22.1.2 | CFM and the Forwarding Process .....   | 1284 |
| 22.1.3 | Up/Down separation of MPs .....  | 1286 |
| 22.1.4 | Service instances over multiple Bridges .....  | 1288 |
| 22.1.5 | Multiple VID service instances .....   | 1290 |
| 22.1.6 | Untagged CFM PDUs .....  | 1290 |
| 22.1.7 | MPs and non-VLAN-aware Bridges .....   | 1290 |
| 22.1.8 | MPs and other standards .....  | 1291 |
| 22.1.9 | CFM and IEEE 802.3 OAM .....   | 1293 |
| 22.2   | Maintenance Entity creation .....  | 1293 |
| 22.2.1 | Creating Maintenance Domains and MAs .....   | 1294 |
| 22.2.2 | Creating MEPs .....  | 1294 |
| 22.2.3 | Creating MIPs .....  | 1296 |
| 22.2.4 | CFM configuration errors .....   | 1297 |
| 22.3   | MPs, Ports, and MD Level assignment.....   | 1298 |
| 22.4   | Stations and CFM .....   | 1298 |
| 22.5   | Scalability of CFM.....  | 1299 |
| 22.6   | CFM in Provider Bridges.....   | 1300 |
| 22.6.1 | MPs and C-VLAN components .....  | 1300 |
| 22.6.2 | Maintenance C-VLAN on a Port-based service interface .....                           | 1300 |
| 22.6.3 | Maintenance C-VLAN on a C-tagged service interface .....                             | 1302 |
| 22.6.4 | MPs and Port-mapping S-VLAN components .....   | 1302 |
| 22.7   | Management Port MEPs and CFM in the enterprise environment.....                      | 1304 |
| 22.8   | Implementing CFM on Bridges that implement earlier revisions of IEEE Std 802.1Q .... | 1306 |
| 23.    | MAC status propagation .....   | 1307 |
| 23.1   | Model of operation.....  | 1309 |
| 23.1.1 | MAC Status Shim (MSS) .....  | 1310 |
| 23.1.2 | Relationship of CFM to the MSS .....   | 1310 |
| 23.2   | MAC Status Protocol (MSP) overview .....   | 1310 |
| 23.3   | MSP state machines .....   | 1315 |

|         |  |      |
|---------|--|------|
| 23.4    | State machine timers .....                                       | 1316 |
| 23.4.1  | linkNotifyWhen .....   | 1316 |
| 23.4.2  | linkNotifyWhile .....  | 1316 |
| 23.4.3  | macNotifyWhile .....   | 1316 |
| 23.4.4  | macRecoverWhile .....  | 1316 |
| 23.5    | MSP performance parameters.....                                  | 1316 |
| 23.5.1  | LinkNotify .....   | 1317 |
| 23.5.2  | LinkNotifyWait .....   | 1317 |
| 23.5.3  | LinkNotifyRetry .....  | 1317 |
| 23.5.4  | MACNotify .....  | 1317 |
| 23.5.5  | MACNotifyTime .....  | 1317 |
| 23.5.6  | MACRecoverTime .....   | 1317 |
| 23.6    | State machine variables .....                                    | 1317 |
| 23.6.1  | BEGIN .....  | 1317 |
| 23.6.2  | addConfirmed .....   | 1317 |
| 23.6.3  | disableMAC .....   | 1317 |
| 23.6.4  | disabledMAC .....  | 1317 |
| 23.6.5  | disableMSS .....   | 1317 |
| 23.6.6  | lossConfirmed .....  | 1317 |
| 23.6.7  | macOperational .....   | 1318 |
| 23.6.8  | mssOperational .....   | 1318 |
| 23.6.9  | prop .....   | 1318 |
| 23.6.10 | rxAck .....  | 1318 |
| 23.6.11 | rxAdd .....  | 1318 |
| 23.6.12 | rxAddConfirm .....   | 1318 |
| 23.6.13 | rxLoss .....   | 1318 |
| 23.6.14 | rxLossConfirm .....  | 1318 |
| 23.6.15 | txAck .....  | 1318 |
| 23.6.16 | txAdd .....  | 1318 |
| 23.6.17 | txAddConfirm .....   | 1318 |
| 23.6.18 | txLoss .....   | 1318 |
| 23.6.19 | txLossConfirm .....  | 1318 |
| 23.7    | State machine procedures .....                                   | 1319 |
| 23.8    | Status Transition state machine (STM) .....                      | 1319 |
| 23.9    | Status Notification state machine (SNM) .....                    | 1319 |
| 23.10   | Receive Process .....  | 1319 |
| 23.11   | Transmit Process.....  | 1319 |
| 23.12   | Management of MSP .....  | 1320 |
| 23.13   | MSPDU transmission, addressing, and protocol identification..... | 1321 |
| 23.13.1 | Destination MAC Address .....                                    | 1321 |
| 23.13.2 | Source MAC Address .....   | 1321 |
| 23.13.3 | Priority .....   | 1321 |
| 23.13.4 | EtherType use and encoding .....                                 | 1321 |
| 23.14   | Representation and encoding of octets .....                      | 1322 |
| 23.15   | MSPDU structure.....   | 1322 |
| 23.15.1 | Protocol Version .....   | 1322 |
| 23.15.2 | Packet Type .....  | 1322 |
| 23.16   | Validation of received MSPDUs .....                              | 1323 |
| 23.17   | Other MSP participants.....                                      | 1323 |
| 24.     | Bridge performance .....   | 1324 |
| 24.1    | Guaranteed Port Filtering Rate .....                             | 1324 |
| 24.2    | Guaranteed Bridge Relaying Rate .....                            | 1324 |

|         |  |      |
|---------|--|------|
| 24.3    | RSTP performance requirements.....                                     | 1324 |
| 25.     | Support of the MAC Service by PBBNs .....                              | 1326 |
| 25.1    | Service transparency .....   | 1328 |
| 25.2    | Customer service interface.....  | 1328 |
| 25.3    | Port-based service interface .....                                     | 1329 |
| 25.4    | S-tagged service interface.....  | 1330 |
| 25.5    | I-tagged service interface.....  | 1332 |
| 25.6    | Service instance segregation.....                                      | 1334 |
| 25.7    | Service instance selection and identification.....                     | 1334 |
| 25.8    | Service priority and drop eligibility selection.....                   | 1334 |
| 25.9    | Service access protection.....   | 1335 |
| 25.9.1  | Class II redundant LANs access protection .....                        | 1337 |
| 25.9.2  | Class III simple redundant LANs and nodes access protection .....      | 1337 |
| 25.10   | Support of the MAC Service by a PBB-TE Region .....                    | 1338 |
| 25.10.1 | Provisioning TESIS .....   | 1339 |
| 25.10.2 | ESP forwarding behavior .....  | 1341 |
| 25.11   | Transparent service interface.....                                     | 1342 |
| 26.     | Principles of Provider Backbone Bridged Network (PBBN) operation ..... | 1344 |
| 26.1    | PBBN overview .....  | 1344 |
| 26.2    | PBBN example .....   | 1345 |
| 26.3    | B-VLAN connectivity.....   | 1347 |
| 26.4    | Backbone addressing .....  | 1347 |
| 26.4.1  | Learning individual backbone addresses at a PIP .....                  | 1348 |
| 26.4.2  | Translating backbone destination addresses at a CBP .....              | 1349 |
| 26.4.3  | Backbone addressing considerations for CFM MPs .....                   | 1349 |
| 26.5    | Detection of connectivity loops through attached networks.....         | 1350 |
| 26.6    | Scaling of PBBs.....   | 1350 |
| 26.6.1  | Hierarchical PBBNs .....   | 1350 |
| 26.6.2  | Peer PBBNs .....   | 1351 |
| 26.7    | Network management .....   | 1351 |
| 26.8    | CFM in PBBs.....   | 1351 |
| 26.8.1  | CFM over Port-based and S-tagged service interfaces .....              | 1356 |
| 26.8.2  | CFM over I-tagged Service Interfaces .....                             | 1357 |
| 26.8.3  | CFM over hierarchal E-NNI .....  | 1357 |
| 26.8.4  | CFM over peer E-NNI .....  | 1358 |
| 26.9    | CFM in a PBB-TE Region.....  | 1358 |
| 26.9.1  | Addressing PBB-TE MEPs .....   | 1359 |
| 26.9.2  | TESI identification .....  | 1359 |
| 26.9.3  | PBB-TE MEP placement in a Bridge Port .....                            | 1359 |
| 26.9.4  | PBB-TE MIP placement in a Bridge Port .....                            | 1360 |
| 26.9.5  | TESI Maintenance Domains .....   | 1360 |
| 26.9.6  | PBB-TE enhancements of the CFM protocols .....                         | 1360 |
| 26.9.7  | Addressing Infrastructure Segment MEPs .....                           | 1362 |
| 26.9.8  | Infrastructure Segment identification .....                            | 1363 |
| 26.9.9  | Infrastructure Segment MEP placement in a Bridge Port .....            | 1363 |
| 26.9.10 | Infrastructure Segment Maintenance Domains .....                       | 1365 |
| 26.9.11 | IPS extensions to Continuity Check operation .....                     | 1365 |
| 26.10   | Protection switching for point-to-point TESIS.....                     | 1365 |
| 26.10.1 | Introduction .....   | 1365 |
| 26.10.2 | 1:1 point-to-point TESI protection switching .....                     | 1366 |
| 26.10.3 | Protection Switching state machines .....                              | 1369 |

|         |   |      |
|---------|---|------|
| 26.11   | IPS in PBB-TE Region .....                                | 1375 |
| 26.11.1 | Infrastructure Segment monitoring .....                   | 1376 |
| 26.11.2 | 1:1 IPS .....   | 1376 |
| 26.11.3 | IPS Control entity .....                                  | 1379 |
| 26.11.4 | 1:1 IPS state machines .....                              | 1380 |
| 26.11.5 | M:1 IPS .....   | 1381 |
| 26.12   | Mismatch defect.....                                      | 1386 |
| 26.13   | Signaling VLAN registrations among I-components .....     | 1387 |
| 27.     | Shortest Path Bridging (SPB) .....                        | 1388 |
| 27.1    | Protocol design requirements.....                         | 1390 |
| 27.2    | Protocol support.....                                     | 1391 |
| 27.3    | Protocol design goals .....                               | 1392 |
| 27.4    | ISIS-SPB VLAN configuration .....                         | 1392 |
| 27.4.1  | SPT Region and ISIS-SPB adjacency determination .....     | 1393 |
| 27.5    | ISIS-SPB information .....                                | 1395 |
| 27.6    | Calculating CIST connectivity.....                        | 1396 |
| 27.7    | Connectivity between regions in the same domain .....     | 1397 |
| 27.8    | Calculating SPT connectivity .....                        | 1397 |
| 27.8.1  | ISIS-SPB overload .....                                   | 1398 |
| 27.9    | Loop prevention.....                                      | 1398 |
| 27.10   | SPVID and SPSourceID allocation.....                      | 1398 |
| 27.11   | Allocation of VIDs to FIDs .....                          | 1400 |
| 27.12   | SPBV SPVID translation .....                              | 1401 |
| 27.13   | VLAN topology management.....                             | 1401 |
| 27.14   | Individual addresses and SPBM .....                       | 1402 |
| 27.14.1 | Loop mitigation .....                                     | 1403 |
| 27.14.2 | Loop prevention .....                                     | 1403 |
| 27.15   | SPBM group addressing .....                               | 1403 |
| 27.16   | Backbone service instance topology management .....       | 1405 |
| 27.17   | Equal cost shortest paths, ECTs, and load spreading ..... | 1406 |
| 27.18   | Connectivity Fault Management for SPBM .....              | 1406 |
| 27.18.1 | SPBM MA types .....                                       | 1406 |
| 27.18.2 | SPBM MEP placement in a Bridge Port .....                 | 1407 |
| 27.18.3 | SPBM MIP placement in a Bridge Port .....                 | 1408 |
| 27.18.4 | SPBM modifications of the CFM protocols .....             | 1408 |
| 27.19   | Using SPBV and SPBM modes .....                           | 1409 |
| 27.19.1 | Shortest Path Bridging—VID .....                          | 1409 |
| 27.19.2 | Shortest Path Bridging—MAC .....                          | 1410 |
| 27.20   | Security considerations .....                             | 1412 |
| 28.     | ISIS-SPB Link State Protocol.....                         | 1413 |
| 28.1    | ISIS-SPB control plane MAC.....                           | 1413 |
| 28.2    | Formation and maintenance of ISIS-SPB adjacencies .....   | 1414 |
| 28.3    | Loop prevention.....                                      | 1415 |
| 28.4    | The Agreement Digest.....                                 | 1415 |
| 28.4.1  | Agreement Digest Format Identifier .....                  | 1415 |
| 28.4.2  | Agreement Digest Format Capabilities .....                | 1416 |
| 28.4.3  | Agreement Digest Convention Identifier .....              | 1416 |
| 28.4.4  | Agreement Digest Convention Capabilities .....            | 1416 |
| 28.4.5  | Agreement Digest Edge Count .....                         | 1417 |
| 28.4.6  | The Computed Topology Digest .....                        | 1417 |
| 28.5    | Symmetric shortest path tie breaking.....                 | 1418 |

|          |   |      |
|----------|---|------|
| 28.6     | Symmetric ECT framework.....  | 1419 |
| 28.7     | Symmetric ECT .....   | 1420 |
| 28.8     | Symmetric ECT Algorithm details .....                                 | 1421 |
| 28.9     | ECT Migration.....  | 1422 |
| 28.9.1   | Use of a new ECT Algorithm in SPBV .....                              | 1422 |
| 28.9.2   | Use of a new ECT Algorithm in SPBM .....                              | 1423 |
| 28.10    | MAC address registration .....  | 1424 |
| 28.11    | Circuit IDs and Port Identifiers.....                                 | 1424 |
| 28.12    | ISIS-SPB TLVs.....  | 1424 |
| 28.12.1  | MT-Capability TLV .....   | 1425 |
| 28.12.2  | SPB MCID sub-TLV .....  | 1425 |
| 28.12.3  | SPB Digest sub-TLV .....  | 1426 |
| 28.12.4  | SPB Base VLAN-Identifiers sub-TLV .....                               | 1427 |
| 28.12.5  | SPB Instance sub-TLV .....  | 1428 |
| 28.12.6  | SPB Instance Opaque ECT Algorithm sub-TLV .....                       | 1429 |
| 28.12.7  | SPB Link Metric sub-TLV .....   | 1431 |
| 28.12.8  | SPB Adjacency Opaque ECT Algorithm sub-TLV .....                      | 1431 |
| 28.12.9  | SPBV MAC address sub-TLV .....  | 1432 |
| 28.12.10 | SPBM Service Identifier and Unicast Address (ISID-ADDR) sub-TLV ..... | 1433 |
| 29.      | DDCFM operations and protocols.....                                   | 1436 |
| 29.1     | Principles of DDCFM operation.....                                    | 1436 |
| 29.1.1   | Data-driven and data-dependent faults (DDFs) .....                    | 1436 |
| 29.1.2   | Basic principle to diagnose and isolate DDFs .....                    | 1436 |
| 29.2     | DDCFM Entity operation .....  | 1439 |
| 29.2.1   | DDCFM implementation .....  | 1439 |
| 29.2.2   | FPT RR .....  | 1440 |
| 29.2.3   | RR-related parameters .....   | 1441 |
| 29.2.4   | Reflection Target and RFM Receiver .....                              | 1442 |
| 29.2.5   | RPT-related parameters .....  | 1442 |
| 29.2.6   | Decapsulator Responder (DR) .....                                     | 1443 |
| 29.2.7   | SFM Originator .....  | 1444 |
| 29.3     | DDCFM protocols .....   | 1444 |
| 29.3.1   | RR variables .....  | 1444 |
| 29.3.2   | RR Filter procedures .....  | 1446 |
| 29.3.3   | RR Encapsulation procedures .....                                     | 1447 |
| 29.3.4   | RR Transmit procedure .....   | 1448 |
| 29.3.5   | RR-related state machines .....                                       | 1449 |
| 29.3.6   | RFM Receiver variables .....  | 1450 |
| 29.3.7   | RFM Receiver procedure .....  | 1451 |
| 29.3.8   | DR variables .....  | 1452 |
| 29.3.9   | DR procedures .....   | 1452 |
| 29.3.10  | Decapsulator Responder state machine .....                            | 1454 |
| 29.4     | Encoding of DDCFM PDUs.....   | 1454 |
| 29.4.1   | RFM and SFM Header .....  | 1454 |
| 29.4.2   | RFM format .....  | 1454 |
| 29.4.3   | SFM format .....  | 1455 |
| 30.      | Principles of congestion notification .....                           | 1457 |
| 30.1     | Congestion notification design requirements .....                     | 1457 |

|        |  |      |
|--------|--|------|
| 30.2   | Quantized Congestion Notification protocol (QCN) ..... | 1459 |
| 30.2.1 | The CP algorithm .....                                 | 1460 |
| 30.2.2 | Basic RP algorithm .....                               | 1461 |
| 30.2.3 | RP algorithm with timer .....                          | 1462 |
| 30.3   | Congestion Controlled Flow (CCF).....                  | 1463 |
| 30.4   | Congestion Notification Priority Value (CNPV).....     | 1464 |
| 30.5   | Congestion Notification tag (CN-TAG) .....             | 1464 |
| 30.6   | Congestion Notification Domain (CND).....              | 1464 |
| 30.7   | Multicast data.....                                    | 1465 |
| 30.8   | Congestion notification and additional tags.....       | 1465 |
| 31.    | Congestion notification entity operation.....          | 1467 |
| 31.1   | Congestion-aware Bridge Forwarding Process.....        | 1467 |
| 31.1.1 | Congestion Point (CP) .....                            | 1468 |
| 31.1.2 | CP ingress multiplexer .....                           | 1468 |
| 31.2   | Congestion-aware end station functions .....           | 1468 |
| 31.2.1 | Output flow segregation .....                          | 1470 |
| 31.2.2 | Per-CNPV station function .....                        | 1470 |
| 31.2.3 | Flow Select Database .....                             | 1472 |
| 31.2.4 | Flow multiplexer .....                                 | 1472 |
| 31.2.5 | CNM demultiplexer .....                                | 1472 |
| 31.2.6 | Input flow segregation .....                           | 1473 |
| 31.2.7 | End station input queue .....                          | 1473 |
| 31.2.8 | Reception selection .....                              | 1473 |
| 32.    | Congestion notification protocol .....                 | 1474 |
| 32.1   | CND operations .....                                   | 1474 |
| 32.1.1 | CND defense .....                                      | 1474 |
| 32.1.2 | Automatic CND recognition .....                        | 1476 |
| 32.1.3 | Variables controlling CND defense .....                | 1476 |
| 32.2   | CN component variables.....                            | 1477 |
| 32.2.1 | cngMasterEnable .....                                  | 1478 |
| 32.2.2 | cngCnmTransmitPriority .....                           | 1478 |
| 32.2.3 | cngDiscardedFrames .....                               | 1478 |
| 32.2.4 | cngErroredPortList .....                               | 1478 |
| 32.3   | Congestion notification per-CNPV variables .....       | 1478 |
| 32.3.1 | cncpDefModeChoice .....                                | 1478 |
| 32.3.2 | cncpAlternatePriority .....                            | 1479 |
| 32.3.3 | cncpAutoAltPri .....                                   | 1479 |
| 32.3.4 | cncpAdminDefenseMode .....                             | 1479 |
| 32.3.5 | cncpCreation .....                                     | 1479 |
| 32.3.6 | cncpLdpInstanceChoice .....                            | 1479 |
| 32.3.7 | cncpLdpInstanceSelector .....                          | 1479 |

|         |   |      |
|---------|---|------|
| 32.4    | CND defense per-Port per-CNPV variables ..... | 1480 |
| 32.4.1  | cnpdDefModeChoice .....                       | 1480 |
| 32.4.2  | cnpdAdminDefenseMode .....                    | 1480 |
| 32.4.3  | cnpdAutoDefenseMode .....                     | 1481 |
| 32.4.4  | cnpdLldpInstanceChoice .....                  | 1481 |
| 32.4.5  | cnpdLldpInstanceSelector .....                | 1481 |
| 32.4.6  | cnpdAlternatePriority .....                   | 1481 |
| 32.4.7  | cnpdXmitCnpvCapable .....                     | 1481 |
| 32.4.8  | cnpdXmitReady .....                           | 1481 |
| 32.4.9  | cncpDoesEdge .....                            | 1482 |
| 32.4.10 | cnpdAcceptsCnTag .....                        | 1482 |
| 32.4.11 | cnpdRcvdCnpv .....                            | 1482 |
| 32.4.12 | cnpdRcvdReady .....                           | 1482 |
| 32.4.13 | cnpdIsAdminDefMode .....                      | 1482 |
| 32.4.14 | cnpdDefenseMode .....                         | 1482 |
| 32.5    | CND defense procedures .....                  | 1483 |
| 32.5.1  | DisableCnpvRemapping() .....                  | 1483 |
| 32.5.2  | TurnOnCnDefenses() .....                      | 1483 |
| 32.5.3  | TurnOffCnDefenses() .....                     | 1483 |
| 32.6    | CND defense state machine .....               | 1483 |
| 32.7    | Congestion notification protocol .....        | 1484 |
| 32.8    | CP variables .....                            | 1485 |
| 32.8.1  | cpMacAddress .....                            | 1486 |
| 32.8.2  | cpId .....                                    | 1486 |
| 32.8.3  | cpQSp .....                                   | 1486 |
| 32.8.4  | cpQLen .....                                  | 1486 |
| 32.8.5  | cpQLenOld .....                               | 1486 |
| 32.8.6  | cpW .....                                     | 1486 |
| 32.8.7  | cpQOffset .....                               | 1486 |
| 32.8.8  | cpQDelta .....                                | 1486 |
| 32.8.9  | cpFb .....                                    | 1486 |
| 32.8.10 | cpEnqueued .....                              | 1487 |
| 32.8.11 | cpSampleBase .....                            | 1487 |
| 32.8.12 | cpDiscardedFrames .....                       | 1487 |
| 32.8.13 | cpTransmittedFrames .....                     | 1487 |
| 32.8.14 | cpTransmittedCnms .....                       | 1487 |
| 32.8.15 | cpMinHeaderOctets .....                       | 1487 |
| 32.9    | CP procedures .....                           | 1487 |
| 32.9.1  | Random .....                                  | 1487 |
| 32.9.2  | NewCpSampleBase() .....                       | 1487 |
| 32.9.3  | EM_UNITDATA.request (parameters) .....        | 1488 |
| 32.9.4  | GenerateCnmPdu() .....                        | 1488 |
| 32.10   | RP per-Port per-CNPV variables .....          | 1489 |
| 32.10.1 | rpppMaxRps .....                              | 1489 |
| 32.10.2 | rpppCreatedRps .....                          | 1489 |
| 32.10.3 | rpppRpCentiseconds .....                      | 1490 |

|          |   |      |
|----------|---|------|
| 32.11    | RP group variables.....   | 1490 |
| 32.11.1  | rpgEnable .....   | 1490 |
| 32.11.2  | rpgTimeReset .....  | 1490 |
| 32.11.3  | rpgByteReset .....  | 1490 |
| 32.11.4  | rpgThreshold .....  | 1491 |
| 32.11.5  | rpgMaxRate .....  | 1491 |
| 32.11.6  | rpgAiRate .....   | 1491 |
| 32.11.7  | rpgHaiRate .....  | 1491 |
| 32.11.8  | rpgGd .....   | 1491 |
| 32.11.9  | rpgMinDecFac .....  | 1491 |
| 32.11.10 | rpgMinRate .....  | 1491 |
| 32.12    | RP timer.....   | 1491 |
| 32.12.1  | RpWhile .....   | 1491 |
| 32.13    | RP variables.....   | 1492 |
| 32.13.1  | rpEnabled .....   | 1492 |
| 32.13.2  | rpByteCount .....   | 1492 |
| 32.13.3  | rpByteStage .....   | 1492 |
| 32.13.4  | rpTimeStage .....   | 1492 |
| 32.13.5  | rpTargetRate .....  | 1492 |
| 32.13.6  | rpCurrentRate .....   | 1492 |
| 32.13.7  | rpFreeze .....  | 1492 |
| 32.13.8  | rpLimiterRate .....   | 1493 |
| 32.13.9  | rpFb .....  | 1493 |
| 32.14    | RP procedures.....  | 1493 |
| 32.14.1  | ResetCnm .....  | 1493 |
| 32.14.2  | TestRpTerminate .....   | 1493 |
| 32.14.3  | TransmitDataFrame .....   | 1493 |
| 32.14.4  | ReceiveCnm .....  | 1494 |
| 32.14.5  | ProcessCnm .....  | 1494 |
| 32.14.6  | AdjustRates .....   | 1494 |
| 32.15    | RP rate control state machine.....  | 1495 |
| 32.16    | Congestion notification and encapsulation interworking function.....        | 1497 |
| 33.      | Encoding of congestion notification PDUs.....                               | 1499 |
| 33.1     | Structure, representation, and encoding.....                                | 1499 |
| 33.2     | CN-TAG format.....  | 1499 |
| 33.2.1   | Flow Identifier .....   | 1500 |
| 33.3     | Congestion Notification Message (CNM).....                                  | 1500 |
| 33.4     | Congestion Notification Message PDU format.....                             | 1500 |
| 33.4.1   | Version .....   | 1500 |
| 33.4.2   | ReservedV .....   | 1500 |
| 33.4.3   | Quantized Feedback .....  | 1501 |
| 33.4.4   | Congestion Point Identifier .....   | 1501 |
| 33.4.5   | cnmQOffset .....  | 1501 |
| 33.4.6   | cnmQDelta .....   | 1501 |
| 33.4.7   | Encapsulated priority .....   | 1502 |
| 33.4.8   | Encapsulated destination MAC address .....                                  | 1502 |
| 33.4.9   | Encapsulated MSDU length .....  | 1502 |
| 33.4.10  | Encapsulated MSDU .....   | 1502 |
| 33.4.11  | CNM Validation .....  | 1502 |
| 34.      | Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS)..... | 1503 |
| 34.1     | Overview.....   | 1503 |

|        |  |      |
|--------|--|------|
| 34.2   | Detection of SRP domains .....   | 1503 |
| 34.3   | The bandwidth availability parameters .....                            | 1504 |
| 34.3.1 | deltaBandwidth when lockClassBandwidth is false .....                  | 1504 |
| 34.3.2 | deltaBandwidth when lockClassBandwidth is true .....                   | 1505 |
| 34.3.3 | Bandwidth availability parameter management .....                      | 1505 |
| 34.4   | Deriving actual bandwidth requirements from the size of the MSDU ..... | 1506 |
| 34.5   | Default SR class configuration .....                                   | 1507 |
| 34.6   | Transmission selection.....  | 1508 |
| 34.6.1 | Credit-based shaper .....  | 1509 |
| 34.6.2 | Strict priority .....  | 1510 |
| 34.6.3 | Scheduled traffic .....  | 1511 |
| 35.    | Stream Reservation Protocol (SRP).....                                 | 1512 |
| 35.1   | Multiple Stream Registration Protocol (MSRP).....                      | 1513 |
| 35.1.1 | MSRP and Shared Media .....  | 1514 |
| 35.1.2 | Behavior of end stations .....   | 1515 |
| 35.1.3 | Behavior of Bridges .....  | 1517 |
| 35.1.4 | SRP domains and status parameters .....                                | 1517 |
| 35.2   | Definition of the MSRP application .....                               | 1518 |
| 35.2.1 | Definition of internal state variables .....                           | 1518 |
| 35.2.2 | Definition of MRP elements .....                                       | 1520 |
| 35.2.3 | Provision and support of Stream registration service .....             | 1544 |
| 35.2.4 | MSRP Attribute Propagation .....                                       | 1549 |
| 35.2.5 | Operational reporting and statistics .....                             | 1558 |
| 35.2.6 | Encoding .....   | 1558 |
| 35.2.7 | Attribute value support requirements .....                             | 1559 |
| 36.    | Priority-based Flow Control (PFC).....                                 | 1560 |
| 36.1   | PFC operation .....  | 1560 |
| 36.1.1 | Overview .....   | 1560 |
| 36.1.2 | PFC primitives .....   | 1561 |
| 36.1.3 | Detailed specification of PFC operation .....                          | 1562 |
| 36.2   | PFC-aware system queue functions.....                                  | 1563 |
| 36.2.1 | PFC Initiator .....  | 1563 |
| 36.2.2 | PFC Receiver .....   | 1563 |
| 37.    | Enhanced Transmission Selection (ETS) .....                            | 1566 |
| 37.1   | Overview.....  | 1566 |
| 37.1.1 | Relationship to other transmission selection algorithms .....          | 1566 |
| 37.2   | ETS configuration parameters .....                                     | 1566 |
| 37.3   | ETS algorithm.....   | 1566 |
| 37.4   | Legacy configuration .....   | 1567 |
| 38.    | Data Center Bridging eXchange protocol (DCBX).....                     | 1568 |
| 38.1   | Overview.....  | 1568 |
| 38.2   | Goals .....  | 1568 |
| 38.3   | Types of DCBX attributes .....   | 1568 |
| 38.3.1 | Informational attributes .....   | 1568 |
| 38.4   | DCBX and LLDP.....   | 1568 |
| 38.4.1 | Asymmetric attribute passing .....                                     | 1569 |
| 38.4.2 | Symmetric attribute passing .....                                      | 1570 |

|         |  |      |
|---------|--|------|
| 39.     | Multiple I-SID Registration Protocol (MIRP) .....                  | 1572 |
| 39.1    | MIRP overview .....  | 1572 |
| 39.1.1  | Behavior of I-components .....                                     | 1574 |
| 39.1.2  | Behavior of B-components .....                                     | 1574 |
| 39.2    | Definition of the MIRP application .....                           | 1574 |
| 39.2.1  | Definition of MRP elements .....                                   | 1574 |
| 39.2.2  | Alternate MIRP model for B-components .....                        | 1577 |
| 39.2.3  | Use of “new” declaration capability .....                          | 1579 |
| 39.2.4  | Attribute value support requirements .....                         | 1579 |
| 39.2.5  | MRP Message filtering .....  | 1579 |
| 40.     | Edge Virtual Bridging (EVB) .....                                  | 1580 |
| 40.1    | EVB architecture without S-channels .....                          | 1581 |
| 40.2    | EVB architecture with S-channels .....                             | 1582 |
| 40.3    | Asymmetric EVB architecture without S-channels .....               | 1584 |
| 40.4    | EVB status parameters .....  | 1586 |
| 40.4.1  | EVBMode = Not supported .....                                      | 1586 |
| 40.4.2  | EVBMode = EVB Bridge .....   | 1586 |
| 40.4.3  | EVBMode = EVB station .....  | 1586 |
| 40.4.4  | EVBMode = NVO3 Mode .....  | 1587 |
| 40.5    | EVB Status Parameter for NVO3 Mode Support .....                   | 1587 |
| 40.5.1  | NVERole = nNVE .....   | 1587 |
| 40.5.2  | NVERole = tNVE .....   | 1587 |
| 41.     | VSI Discovery and Configuration Protocol (VDP) .....               | 1588 |
| 41.1    | VSI manager ID TLV definition .....                                | 1588 |
| 41.1.1  | TLV type .....   | 1589 |
| 41.1.2  | TLV information string length .....                                | 1589 |
| 41.1.3  | VSI Manager ID .....   | 1589 |
| 41.2    | VDP association TLV definitions .....                              | 1589 |
| 41.2.1  | TLV type .....   | 1590 |
| 41.2.2  | TLV information string length .....                                | 1590 |
| 41.2.3  | Status .....   | 1590 |
| 41.2.4  | VSI Type ID (VTID) .....   | 1591 |
| 41.2.5  | VSI Type Version .....   | 1591 |
| 41.2.6  | VSIID format .....   | 1591 |
| 41.2.7  | VSIID .....  | 1592 |
| 41.2.8  | Filter Info format .....   | 1592 |
| 41.2.9  | Filter Info field .....  | 1593 |
| 41.2.10 | VDP TLV type and status semantics .....                            | 1597 |
| 41.3    | Organizationally defined TLV definitions .....                     | 1598 |
| 41.3.1  | TLV type .....   | 1598 |
| 41.3.2  | TLV information string length .....                                | 1598 |
| 41.3.3  | Organizationally unique identifier (OUI) or Company ID (CID) ..... | 1598 |
| 41.3.4  | Organizationally defined information .....                         | 1599 |
| 41.4    | Validation rules for VDP TLVs .....                                | 1599 |

|         |   |      |
|---------|---|------|
| 41.5    | VDP state machines .....  | 1599 |
| 41.5.1  | State machine conventions .....   | 1599 |
| 41.5.2  | Bridge VDP state machine .....  | 1600 |
| 41.5.3  | Station VDP state machine .....   | 1601 |
| 41.5.4  | VDP state machine timers .....  | 1602 |
| 41.5.5  | VDP state machine variables and parameters .....  | 1602 |
| 41.5.6  | Command-Response TLV field references in state machines .....                                     | 1604 |
| 41.5.7  | VDP state machine procedures .....  | 1605 |
| 42.     | S-Channel Discovery and Configuration Protocol (CDCP) .....                                       | 1607 |
| 42.1    | CDCP discovery and configuration .....  | 1607 |
| 42.2    | CDCP state machine overview .....   | 1607 |
| 42.3    | CDCP configuration state machine.....   | 1608 |
| 42.4    | CDCP configuration variables .....  | 1609 |
| 42.4.1  | AdminChnCap .....   | 1609 |
| 42.4.2  | AdminRole .....   | 1610 |
| 42.4.3  | AdminSVIDWants .....  | 1610 |
| 42.4.4  | LastLocalSVIDPool .....   | 1610 |
| 42.4.5  | LastRemoteSVIDList .....  | 1610 |
| 42.4.6  | LastSVIDWants .....   | 1610 |
| 42.4.7  | LocalSVIDPool .....   | 1610 |
| 42.4.8  | OperChnCap .....  | 1610 |
| 42.4.9  | OperRole .....  | 1610 |
| 42.4.10 | OperSVIDList .....  | 1611 |
| 42.4.11 | RemoteChnCap .....  | 1611 |
| 42.4.12 | RemoteRole .....  | 1611 |
| 42.4.13 | RemoteSVIDList .....  | 1611 |
| 42.4.14 | schState .....  | 1611 |
| 42.5    | CDCP configuration procedures.....  | 1611 |
| 42.5.1  | SetSVIDRequest (OperRole, AdminSVIDWants, OperSVIDList) .....                                     | 1611 |
| 42.5.2  | RxSVIDConfig (OperSVIDList, LastRemoteSVIDList) .....   | 1612 |
| 42.5.3  | TxSVIDConfig (OperChnCap, RemoteChnCap, LastLocalSVIDPool,<br>RemoteSVIDList, OperSVIDList) ..... | 1612 |
| 43.     | Edge Control Protocol (ECP) .....   | 1613 |
| 43.1    | ECP operation .....   | 1613 |
| 43.2    | Edge Control Sublayer Service (ECSS).....   | 1614 |
| 43.3    | ECP state machines.....   | 1614 |
| 43.3.1  | State machine conventions .....   | 1614 |
| 43.3.2  | Overview .....  | 1614 |
| 43.3.3  | Edge Control Protocol Data Unit (ECPDU) .....   | 1615 |
| 43.3.4  | ECP transmit state machine .....  | 1616 |
| 43.3.5  | ECP receive state machine .....   | 1617 |
| 43.3.6  | ECP state machine timers .....  | 1617 |
| 43.3.7  | ECP state machine variables and parameters .....  | 1618 |
| 43.3.8  | ECP state machine procedures .....  | 1619 |
| 44.     | Equal Cost Multiple Paths (ECMP).....   | 1620 |
| 44.1    | SPBM ECMP .....   | 1620 |
| 44.1.1  | ECMP Operation .....  | 1620 |
| 44.1.2  | ECMP ECT Algorithm .....  | 1621 |
| 44.1.3  | Loop prevention for ECMP .....  | 1623 |

|         |   |      |
|---------|---|------|
| 44.2    | Support for Flow Filtering .....                          | 1623 |
| 44.2.1  | Flow filtering tag (F-TAG) .....                          | 1624 |
| 44.2.2  | F-TAG processing .....                                    | 1625 |
| 44.2.3  | Forwarding process extension for flow filtering .....     | 1626 |
| 44.2.4  | TTL Loop mitigation .....                                 | 1627 |
| 44.2.5  | CFM for ECMP with flow filtering .....                    | 1627 |
| 44.2.6  | Operation with selective support for flow filtering ..... | 1629 |
| 45.     | Path Control and Reservation (PCR) .....                  | 1630 |
| 45.1    | Explicit trees .....                                      | 1630 |
| 45.1.1  | Tree structures .....                                     | 1634 |
| 45.1.2  | Explicit ECT Algorithms .....                             | 1635 |
| 45.1.3  | ISIS-PCR VLAN configuration .....                         | 1637 |
| 45.1.4  | Use of VIDs for strict explicit trees .....               | 1641 |
| 45.1.5  | MAC addresses and ISIS-PCR .....                          | 1642 |
| 45.1.6  | Filtering Database entries for explicit trees .....       | 1642 |
| 45.1.7  | ISIS-PCR support .....                                    | 1643 |
| 45.1.8  | Attributes for path computation .....                     | 1643 |
| 45.1.9  | Topology sub-TLV .....                                    | 1645 |
| 45.1.10 | Hop sub-TLV .....   | 1648 |
| 45.1.11 | Administrative Group sub-TLV .....                        | 1652 |
| 45.1.12 | Bandwidth Constraint sub-TLV .....                        | 1652 |
| 45.2    | Reservation .....   | 1653 |
| 45.2.1  | Bandwidth Assignment sub-TLV .....                        | 1653 |
| 45.2.2  | Timestamp sub-TLV .....                                   | 1654 |
| 45.2.3  | Precedence ordering .....                                 | 1655 |
| 45.3    | Redundancy .....  | 1655 |
| 45.3.1  | Loop-free alternates for unicast data flows .....         | 1655 |
| 45.3.2  | Static redundant trees .....                              | 1656 |
| 45.3.3  | Maximally Redundant Trees (MRTs) .....                    | 1657 |
| 45.3.4  | MRTs with centralized GADAG computation .....             | 1659 |
| 46.     | Time-Sensitive Networking (TSN) configuration .....       | 1664 |
| 46.1    | Overview of TSN configuration .....                       | 1664 |
| 46.1.1  | User/Network Interface (UNI) .....                        | 1664 |
| 46.1.2  | Modeling of user/network configuration information .....  | 1664 |
| 46.1.3  | TSN configuration models .....                            | 1664 |
| 46.1.4  | Stream transformation .....                               | 1669 |
| 46.2    | User/network configuration information .....              | 1671 |
| 46.2.1  | Data types .....  | 1671 |
| 46.2.2  | Protocol integration .....                                | 1672 |
| 46.2.3  | Talker .....  | 1673 |
| 46.2.4  | Listener .....  | 1685 |
| 46.2.5  | Status .....  | 1686 |
| 46.3    | YANG for TSN user/network configuration .....             | 1692 |
| 47.     | Asynchronous Traffic Shaping (ATS) in end stations .....  | 1693 |
| 47.1    | Talker transmission behavior .....                        | 1693 |
| 47.1.1  | ATS traffic class model in Talkers .....                  | 1693 |
| 47.1.2  | Simplified ProcessFrame(frame) procedure .....            | 1693 |
| 47.1.3  | System clock functions and processing delays .....        | 1693 |
| 47.2    | Scheduler parameter consistency .....                     | 1694 |

|         |  |      |
|---------|--|------|
| 48.     | YANG Data Models .....   | 1695 |
| 48.1    | YANG Framework .....   | 1696 |
| 48.1.1  | Interface Management (IETF RFC 8343) Model .....                           | 1697 |
| 48.2    | IEEE 802.1Q YANG models.....   | 1698 |
| 48.2.1  | VLAN Bridge components model .....   | 1698 |
| 48.2.2  | Two-Port MAC Relay (TPMR) model .....                                      | 1701 |
| 48.2.3  | Customer VLAN Bridge model .....   | 1702 |
| 48.2.4  | Provider Bridge model .....  | 1703 |
| 48.2.5  | CFM Model .....  | 1706 |
| 48.2.6  | Stream filters and stream gates model .....                                | 1710 |
| 48.2.7  | Asynchronous Traffic Shaping (ATS) model .....                             | 1711 |
| 48.3    | Structure of the YANG models .....   | 1712 |
| 48.3.1  | VLAN Bridge components model .....   | 1713 |
| 48.3.2  | Two-Port MAC Relay model .....   | 1713 |
| 48.3.3  | Customer VLAN Bridge model .....   | 1713 |
| 48.3.4  | Provider Bridge model .....  | 1713 |
| 48.3.5  | CFM model .....  | 1714 |
| 48.3.6  | Stream filters and stream gates model .....                                | 1714 |
| 48.3.7  | Asynchronous Traffic Shaping (ATS) model .....                             | 1714 |
| 48.4    | Security considerations .....  | 1716 |
| 48.4.1  | Security considerations of the VLAN Bridge components model .....          | 1716 |
| 48.4.2  | Security considerations of the Two-Port MAC Relay model .....              | 1717 |
| 48.4.3  | Security considerations of the Customer VLAN Bridge model .....            | 1717 |
| 48.4.4  | Security considerations of the Provider Bridge model .....                 | 1717 |
| 48.4.5  | Security considerations of the CFM model .....                             | 1718 |
| 48.4.6  | Security considerations of the Stream filters and stream gates model ..... | 1718 |
| 48.4.7  | Security considerations of the Asynchronous Traffic Shaping model .....    | 1718 |
| 48.5    | YANG schema tree definitions.....  | 1719 |
| 48.5.1  | Schema for the ieee802-types YANG module .....                             | 1719 |
| 48.5.2  | Schema for the ieee802-dot1q-types YANG module .....                       | 1719 |
| 48.5.3  | Schema for the ieee802-dot1q-tsn-types YANG module .....                   | 1719 |
| 48.5.4  | Schema for the ieee802-dot1q-bridge YANG module .....                      | 1719 |
| 48.5.5  | Schema for the ieee802-dot1q-tpmr YANG module .....                        | 1723 |
| 48.5.6  | Schema for the ieee802-dot1q-pb YANG module .....                          | 1723 |
| 48.5.7  | Schema for the ieee802-dot1q-cfm-types YANG module .....                   | 1723 |
| 48.5.8  | Schema for the ieee802-dot1q-cfm YANG module .....                         | 1724 |
| 48.5.9  | Schema for the ieee802-dot1q-cfm-bridge YANG module .....                  | 1726 |
| 48.5.10 | Schema for the ieee802-dot1q-cfm-alarm YANG module .....                   | 1727 |
| 48.5.11 | Schema for the ieee802-dot1q-stream-filters-gates YANG module .....        | 1727 |
| 48.5.12 | Schema for the ieee802-dot1q-ats YANG module .....                         | 1728 |
| 48.6    | YANG modules .....   | 1729 |
| 48.6.1  | The ieee802-types YANG module .....  | 1729 |
| 48.6.2  | The ieee802-dot1q-types YANG module .....                                  | 1734 |
| 48.6.3  | The ieee802-dot1q-tsn-types YANG module .....                              | 1748 |
| 48.6.4  | The ieee802-dot1q-bridge YANG module .....                                 | 1767 |
| 48.6.5  | The ieee802-dot1q-tpmr YANG module .....                                   | 1792 |
| 48.6.6  | The ieee802-dot1q-pb YANG module .....                                     | 1797 |
| 48.6.7  | The ieee802-dot1q-cfm-types YANG module .....                              | 1800 |
| 48.6.8  | The ieee802-dot1q-cfm YANG module .....                                    | 1811 |
| 48.6.9  | The ieee802-dot1q-cfm-bridge YANG module .....                             | 1830 |
| 48.6.10 | The ieee802-dot1q-cfm-alarm YANG module .....                              | 1838 |
| 48.6.11 | The ieee802-dot1q-stream-filters-gates YANG module .....                   | 1840 |
| 48.6.12 | The ieee802-dot1q-ats YANG module .....                                    | 1846 |

|  |      |
|--|------|
| Annex A (normative) PICS proforma—Bridge implementations .....                   | 1851 |
| A.1 Introduction.....  | 1851 |
| A.2 Abbreviations and special symbols.....                                       | 1851 |
| A.2.1 Status symbols .....   | 1851 |
| A.2.2 General abbreviations .....  | 1851 |
| A.3 Instructions for completing the PICS proforma.....                           | 1852 |
| A.3.1 General structure of the PICS proforma .....                               | 1852 |
| A.3.2 Additional information .....   | 1852 |
| A.3.3 Exception information .....  | 1852 |
| A.3.4 Conditional status .....   | 1853 |
| A.4 PICS proforma for IEEE Std 802.1Q—Bridge implementations .....               | 1854 |
| A.4.1 Implementation identification .....  | 1854 |
| A.4.2 Protocol summary, IEEE Std 802.1Q .....                                    | 1854 |
| A.5 Major capabilities .....   | 1855 |
| A.6 Media access control methods .....   | 1860 |
| A.7 Relay and filtering of frames .....  | 1861 |
| A.8 Basic Filtering Services .....   | 1862 |
| A.9 Addressing .....   | 1863 |
| A.10 Rapid Spanning Tree Protocol (RSTP).....                                    | 1865 |
| A.12 Implementation parameters.....  | 1867 |
| A.11 BPDU encoding .....   | 1867 |
| A.13 Performance .....   | 1868 |
| A.14 Bridge management .....   | 1869 |
| A.15 Remote management.....  | 1879 |
| A.16 Expedited traffic classes .....   | 1880 |
| A.17 Extended Filtering Services .....   | 1880 |
| A.18 Multiple Spanning Tree Protocol (MSTP).....                                 | 1881 |
| A.19 VLAN support .....  | 1883 |
| A.20 Multiple MAC Registration Protocol (MMRP).....                              | 1886 |
| A.21 Multiple VLAN Registration Protocol (MVRP) .....                            | 1887 |
| A.22 Multiple Registration Protocol (MRP) .....                                  | 1888 |
| A.23 Connectivity Fault Management (CFM).....                                    | 1889 |
| A.24 Management Information Base (MIB) .....                                     | 1894 |
| A.25 Protection Switching (PS).....  | 1897 |
| A.26 Data-driven and data-dependent connectivity fault management (DDCFM).....   | 1897 |
| A.27 Two-Port MAC Relay (TPMR) .....   | 1897 |
| A.28 MAC Status Protocol (MSP) .....   | 1898 |
| A.29 Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS)..... | 1899 |
| A.30 Congestion notification.....  | 1899 |
| A.31 Stream Reservation Protocol (SRP).....                                      | 1900 |
| A.32 Multiple I-SID Registration Protocol (MIRP) .....                           | 1904 |
| A.34 Enhanced Transmission Selection (ETS) .....                                 | 1905 |
| A.33 Priority-based Flow Control (PFC).....                                      | 1905 |
| A.35 Data Center Bridging eXchange protocol (DCBX).....                          | 1906 |
| A.36 Infrastructure Protection Switching (IPS).....                              | 1906 |
| A.38 EVB Bridge.....   | 1907 |
| A.37 Shortest Path Bridging (SPB) .....  | 1907 |
| A.39 EVB station.....  | 1908 |
| A.40 Edge relay (ER) .....   | 1909 |
| A.42 VDP, CDCP, and ECP .....  | 1911 |
| A.41 VEB and VEPA ER components.....   | 1911 |
| A.43 Path Control and Reservation .....  | 1912 |
| A.44 Scheduled traffic .....   | 1913 |

|  |   |      |
|--|---|------|
| A.45   | Frame preemption .....  | 1913 |
| A.46   | Per-Stream Filtering and Policing.....                                      | 1914 |
| A.47   | YANG .....  | 1915 |
| A.48   | Stream reservation remote management (SRRM).....                            | 1916 |
| A.49   | TSN Centralized Network Configuration (CNC) station .....                   | 1917 |
| A.50   | VDP for NVO3 nNVE Devices .....   | 1918 |
| A.51   | VDP for NVO3 tNVE Devices .....   | 1919 |
| A.52   | Asynchronous Traffic Shaping .....  | 1920 |
| Annex B (normative) PICS proforma—End station implementations .....  |   | 1921 |
| B.1  | Introduction.....   | 1921 |
| B.2  | Abbreviations and special symbols.....                                      | 1921 |
| B.2.1  | Status symbols .....  | 1921 |
| B.2.2  | General abbreviations .....   | 1921 |
| B.3  | Instructions for completing the PICS proforma.....                          | 1922 |
| B.3.1  | General structure of the PICS proforma .....                                | 1922 |
| B.3.2  | Additional information .....  | 1922 |
| B.3.3  | Exception information .....   | 1922 |
| B.3.4  | Conditional status .....  | 1923 |
| B.4  | PICS proforma for IEEE Std 802.1Q—End station implementations .....         | 1924 |
| B.4.1  | Implementation identification .....   | 1924 |
| B.4.2  | Protocol summary, IEEE Std 802.1Q .....                                     | 1924 |
| B.5  | Major capabilities .....  | 1925 |
| B.6  | Multiple MAC Registration Protocol (MMRP).....                              | 1926 |
| B.8  | Multiple Registration Protocol (MRP) .....                                  | 1927 |
| B.7  | Multiple VLAN Registration Protocol (MVRP) .....                            | 1927 |
| B.9  | Forwarding and Queuing Enhancements for time-sensitive streams (FQTSS)..... | 1928 |
| B.10   | Stream Reservation Protocol (SRP).....                                      | 1929 |
| B.11   | Congestion notification.....  | 1932 |
| B.13   | Enhanced Transmission Selection (ETS) .....                                 | 1934 |
| B.14   | Data Center Bridging eXchange protocol (DCBX).....                          | 1934 |
| B.12   | Priority-based Flow Control (PFC).....                                      | 1934 |
| B.16   | Frame Preemption.....   | 1935 |
| B.17   | Per-Stream Filtering and Policing.....                                      | 1935 |
| B.15   | Scheduled traffic .....   | 1935 |
| B.18   | Asynchronous Traffic Shaping .....  | 1936 |
| Annex C (normative) Designated MSRP Node (DMN) Implementations ..... |   | 1937 |
| C.1  | DMNs on CSNs .....  | 1937 |
| C.1.1  | CSN characteristics .....   | 1937 |
| C.1.2  | DMN handling on CSN .....   | 1938 |
| C.1.3  | MSRPDU handling on a CSN .....  | 1939 |
| C.1.4  | CSN bandwidth fluctuations .....  | 1940 |
| C.2  | DMN on MoCA .....   | 1940 |
| C.2.1  | DMN Selection on MoCA Network .....   | 1940 |
| C.2.2  | MoCA network bandwidth management .....                                     | 1944 |
| C.3  | DMNs on IEEE 802.11 media .....   | 1945 |
| C.3.1  | MSRP handling .....   | 1946 |
| C.3.2  | BSS DMN selection .....   | 1949 |
| C.3.3  | BSS network bandwidth management .....                                      | 1950 |

# ISO/IEC/IEEE 8802-1Q:2024(en)

|   |      |
|---|------|
| Annex D (normative) IEEE 802.1 Organizationally Specific TLVs.....              | 1953 |
| D.1 Requirements of the IEEE 802.1 Organizationally Specific TLV sets.....      | 1953 |
| D.2 Organizationally Specific TLV definitions.....                              | 1954 |
| D.2.1 Port VLAN ID TLV .....  | 1954 |
| D.2.2 Port And Protocol VLAN ID TLV .....                                       | 1954 |
| D.2.3 VLAN Name TLV .....   | 1955 |
| D.2.4 Protocol Identity TLV .....   | 1956 |
| D.2.5 VID Usage Digest TLV .....  | 1957 |
| D.2.6 Management VID TLV .....  | 1957 |
| D.2.7 Congestion Notification TLV .....   | 1958 |
| D.2.8 ETS Configuration TLV .....   | 1959 |
| D.2.9 ETS Recommendation TLV .....  | 1961 |
| D.2.10 Priority-based Flow Control Configuration TLV .....                      | 1962 |
| D.2.11 Application Priority TLV .....   | 1963 |
| D.2.12 EVB TLV .....  | 1964 |
| D.2.13 CDCP TLV .....   | 1969 |
| D.2.14 Application VLAN TLV .....   | 1971 |
| D.3 IEEE 802.1 Organizationally Specific TLV management.....                    | 1972 |
| D.3.1 IEEE 802.1 Organizationally Specific TLV selection management .....       | 1972 |
| D.3.2 IEEE 802.1 managed objects—TLV variables .....                            | 1973 |
| D.4 PICS proforma for IEEE 802.1 Organizationally Specific TLV extensions ..... | 1974 |
| D.4.1 Implementation identification .....                                       | 1974 |
| D.4.2 Protocol summary, IEEE Std 802.1Q .....                                   | 1974 |
| D.4.3 Major capabilities and options .....                                      | 1975 |
| D.5 IEEE 802.1/LLDP extension MIB.....  | 1977 |
| D.5.1 Internet Standard Management Framework .....                              | 1977 |
| D.5.2 Structure of the IEEE 802.1/LLDP extension MIB .....                      | 1977 |
| D.5.3 Relationship to other MIBs .....  | 1984 |
| D.5.4 Security considerations for IEEE 802.1 LLDP extension MIB module .....    | 1985 |
| D.5.5 IEEE 802.1 LLDP extension MIB module—version 2 .....                      | 1987 |
| D.5.6 EVB extensions to the IEEE 802.1 LLDP extension MIB module .....          | 2047 |
| Annex E (normative) Notational conventions used in state diagrams.....          | 2054 |
| Annex F (informative) Shared and Independent VLAN Learning (SVL and IVL) .....  | 2056 |
| F.1 Requirements for Shared and Independent Learning .....                      | 2056 |
| F.1.1 Connecting independent VLANs .....  | 2057 |
| F.1.2 Duplicate MAC addresses .....   | 2058 |
| F.1.3 Asymmetric VLANs and Rooted-Multipoint connectivity .....                 | 2059 |
| F.1.4 Shared learning and Shortest Path Bridging VID (SPBV) mode .....          | 2062 |
| F.1.5 Generic constraints on SVL and IVL use .....                              | 2064 |
| Annex G (informative) MAC method-dependent aspects of VLAN support.....         | 2065 |
| G.1 Example tagged IEEE 802.3 EtherType-encoded frame format .....              | 2065 |
| G.2 Padding and frame size considerations .....                                 | 2065 |
| G.2.1 Treatment of PAD fields in IEEE 802.3 frames .....                        | 2065 |
| G.2.2 Maximum PDU size .....  | 2066 |
| G.2.3 Minimum PDU size .....  | 2066 |
| G.3 Tag insertion and removal for LLC media .....                               | 2067 |

# ISO/IEC/IEEE 8802-1Q:2024(en)

|         |  |      |
|---------|--|------|
| G.4     | IEEE 802.11 and PMPN media .....   | 2068 |
| G.4.1   | IEEE 802.11 Portal convergence .....   | 2068 |
| G.4.2   | Point-to-Multipoint Network convergence: multiple connections .....  | 2068 |
| G.4.3   | Point-to-Multipoint Network convergence: single connection .....   | 2068 |
| Annex H | (informative) Interoperability considerations.....   | 2069 |
| H.1     | Requirements for interoperability .....  | 2069 |
| H.1.1   | Static filtering requirements .....  | 2069 |
| H.1.2   | Configuration requirements for VLAN-tagging .....  | 2069 |
| H.2     | Homogeneous VLAN-aware networks.....   | 2070 |
| H.2.1   | Consistency of static VLAN filtering .....   | 2070 |
| H.2.2   | Consistent view of the “untagged VLAN(s)” on a given LAN .....   | 2071 |
| H.3     | Heterogeneous networks: Intermixing MAC Bridges (M) and VLAN Bridges (V) .....   | 2072 |
| H.3.1   | Example: Adding a VLAN Bridge to provide filtering to a MAC Bridged Network<br>2072  |      |
| H.3.2   | Example: Adding a MAC Bridge to a (previously) Homogeneous VLAN Bridged<br>Network .....   | 2073 |
| H.4     | Intermixing Port-based classification and Port-and-Protocol-based classification or future<br>enhancements in VLAN Bridges ..... | 2073 |
| H.4.1   | Example: Intermixing Protocol-based ingress rules .....  | 2074 |
| H.4.2   | Differing views of untagged traffic on a given LAN .....   | 2074 |
| Annex I | (informative) Priority and drop precedence.....  | 2075 |
| I.1     | Traffic types.....   | 2075 |
| I.2     | Managing latency and throughput .....  | 2076 |
| I.3     | Traffic type to traffic class mapping.....   | 2076 |
| I.4     | Traffic types and priority values.....   | 2078 |
| I.5     | Supporting the credit-based shaper algorithm .....   | 2079 |
| I.6     | Supporting drop precedence .....   | 2080 |
| I.7     | Priority Code Point allocation.....  | 2080 |
| I.8     | Interoperability.....  | 2081 |
| Annex J | (informative) CFM protocol design and use.....   | 2083 |
| J.1     | Origin of CFM .....  | 2083 |
| J.2     | Deployment of CFM .....  | 2083 |
| J.3     | MD Level allocation alternative .....  | 2084 |
| J.4     | Relationship of IEEE Std 802.1Q CFM to other standards .....   | 2084 |
| J.5     | Interpreting Linktrace results.....  | 2085 |
| J.6     | MP addressing: Individual and Shared MP addresses .....  | 2086 |
| J.6.1   | Individual MP address model .....  | 2087 |
| J.6.2   | Shared MP address model and the CFM Port .....   | 2087 |
| Annex K | (informative) TPMR use cases.....  | 2090 |
| K.1     | Use case 1—TPMR as User to Network Interface (UNI) demarcation device .....  | 2090 |
| K.2     | Use case 2—TPMRs with aggregated links .....   | 2091 |
| K.3     | Use case 3—Multiple TPMRs .....  | 2091 |
| K.4     | Special cases .....  | 2092 |
| Annex L | (informative) Operation of the credit-based shaper algorithm .....   | 2095 |
| L.1     | Overview of credit-based shaper operation .....  | 2095 |
| L.2     | “Class measurement intervals” in Bridges.....  | 2100 |

# ISO/IEC/IEEE 8802-1Q:2024(en)

|         |  |      |
|---------|--|------|
| L.3     | Determining worst-case latency contribution and buffering requirements ..... | 2101 |
| L.3.1   | Interference delay .....   | 2102 |
| L.3.2   | Maximum interference delay and maximum buffer requirement .....              | 2110 |
| L.4     | Operation of credit-based shaper in Coordinated Shared Network (CSN).....    | 2111 |
| Annex M | (normative) Support for PFC in link layers without MAC Control .....         | 2112 |
| M.1     | Overview.....  | 2112 |
| M.2     | PFC PDU format.....  | 2112 |
| Annex N | (informative) Buffer requirements for PFC .....                              | 2113 |
| N.1     | Overview.....  | 2113 |
| N.2     | Delay model.....   | 2113 |
| N.3     | Interface Delay.....   | 2116 |
| N.4     | Cable Delay.....   | 2116 |
| N.5     | Higher Layer Delay .....   | 2116 |
| N.6     | Computation example .....  | 2117 |
| Annex O | (informative) Preserving the integrity of FCS fields in MAC Bridges .....    | 2118 |
| O.1     | Background.....  | 2118 |
| O.2     | Basic mathematical ideas behind CRC and FCS .....                            | 2119 |
| O.3     | Detection Lossless Circuit approach.....                                     | 2120 |
| O.4     | Algorithmic modification of an FCS .....                                     | 2121 |
| O.4.1   | Data changed, length unchanged .....   | 2121 |
| O.4.2   | Length changed, original data unchanged .....                                | 2122 |
| O.4.3   | Preservation of detectability .....  | 2123 |
| O.5     | Conclusions.....   | 2124 |
| Annex P | (informative) Frame duplication and misordering.....                         | 2125 |
| P.1     | Background.....  | 2125 |
| P.2     | Frame duplication .....  | 2125 |
| P.3     | Frame misordering.....   | 2126 |
| P.4     | Other considerations .....   | 2127 |
| Annex Q | (informative) Traffic scheduling.....  | 2128 |
| Q.1     | Motivation.....  | 2128 |
| Q.2     | Using gate operations to create protected windows.....                       | 2129 |
| Q.3     | Availability of PTP .....  | 2130 |
| Q.4     | Scheduled traffic and end stations .....                                     | 2130 |
| Q.5     | CycleTimeExtension variables .....   | 2130 |
| Annex R | (informative) Preemption and IEEE 802.1AE MAC Security .....                 | 2131 |
| Annex S | (informative) Preemption and scheduled traffic .....                         | 2133 |
| S.1     | Scheduling used in isolation .....   | 2133 |
| S.2     | Preemption used in isolation.....  | 2133 |
| S.3     | Scheduling and preemption used in combination, no HOLD/RELEASE .....         | 2134 |
| S.4     | Scheduling and preemption used in combination with HOLD/RELEASE .....        | 2134 |
| S.5     | Bandwidth allocation and express traffic.....                                | 2134 |

|   |      |
|---|------|
| Annex T (informative) Cyclic queuing and forwarding .....                         | 2136 |
| T.1 Overview of CQF.....  | 2136 |
| T.2 An approach to CQF implementation.....  | 2137 |
| T.3 Use of Per-Stream Filtering and Policing for CQF.....                         | 2138 |
| T.3.1 Stream filter configuration .....   | 2138 |
| T.3.2 Stream gate configuration .....   | 2138 |
| T.4 Use of traffic scheduling for CQF .....                                       | 2139 |
| T.5 Timing considerations.....  | 2140 |
| T.5.1 Choice of T .....   | 2140 |
| T.5.2 Cycle interleaving .....  | 2141 |
| T.5.3 Cycle alignment between adjacent Ports .....                                | 2143 |
| Annex U (informative) TSN configuration examples .....                            | 2144 |
| U.1 Examples for time-aware talker.....   | 2144 |
| U.1.1 Using enhancements for scheduled traffic .....                              | 2145 |
| U.1.2 Using strict priority .....   | 2146 |
| U.1.3 Using per-stream scheduling .....   | 2147 |
| U.2 Example of workflow for fully centralized models.....                         | 2148 |
| Annex V (informative) Asynchronous Traffic Shaping delay analysis framework ..... | 2152 |
| V.1 General assumptions .....   | 2152 |
| V.2 End-to-end delay modeling approach.....                                       | 2152 |
| V.3 Buffering delays.....   | 2153 |
| V.4 Media-dependent delays .....  | 2155 |
| V.5 Bridge—Internal arrival time recognition delays .....                         | 2155 |
| V.6 Bridge—Internal processing delays.....  | 2155 |
| V.7 Bridge—Internal clock offset variations.....                                  | 2156 |
| V.8 Inter-device clock rate deviations .....                                      | 2156 |
| V.9 Combined delay bounds.....  | 2157 |
| Annex W (informative) Bibliography.....   | 2158 |

**Figures**

|             |  |     |
|-------------|--|-----|
| Figure 6-1  | Internal organization of the MAC sublayer .....                              | 144 |
| Figure 6-2  | Provider Instance Ports (PIPs) .....   | 162 |
| Figure 6-3  | B-Component CBP .....  | 165 |
| Figure 6-4  | Example of operation of Port-and-Protocol-based classification .....         | 168 |
| Figure 6-5  | Service access priority selection .....                                      | 171 |
| Figure 6-6  | Two back-to-back EISS Multiplex Entities .....                               | 177 |
| Figure 6-7  | Two back-to-back Backbone Service Instance Multiplex Entities .....          | 178 |
| Figure 6-8  | Backbone Service Instance Multiplex Entities with example CFM shims .....    | 178 |
| Figure 6-9  | Two back-to-back Up and Down TESI Multiplex Entities .....                   | 181 |
| Figure 6-10 | Supporting the ISS with signaled priority .....                              | 182 |
| Figure 6-11 | Two back-to-back Up and Down Infrastructure Segment Multiplex Entities ..... | 183 |
| Figure 7-1  | VLAN Bridging overview .....   | 185 |
| Figure 8-1  | A Bridged Network .....  | 191 |
| Figure 8-2  | VLAN Bridge architecture .....   | 193 |
| Figure 8-3  | MAC Bridge architecture .....  | 194 |
| Figure 8-4  | Relaying MAC frames .....  | 196 |
| Figure 8-5  | Observation of network traffic .....   | 196 |
| Figure 8-6  | Operation of Spanning Tree Protocol Entity .....                             | 197 |
| Figure 8-7  | Operation of MRP .....   | 197 |
| Figure 8-8  | Management Port transmission and reception .....                             | 198 |
| Figure 8-9  | Infrastructure Segment MEP placement in a PNP .....                          | 198 |
| Figure 8-10 | Bridge Port Transmit and Receive .....                                       | 201 |
| Figure 8-11 | TPMR Port Transmit and Receive .....   | 201 |
| Figure 8-12 | Forwarding process functions .....   | 203 |
| Figure 8-13 | Flow classification and metering .....                                       | 208 |
| Figure 8-14 | Per-stream classification for PSFP .....                                     | 210 |
| Figure 8-15 | Per-stream classification and metering for ATS .....                         | 212 |
| Figure 8-16 | Transmission selection with gates .....                                      | 222 |
| Figure 8-17 | Frame timing at gate-close events .....                                      | 224 |
| Figure 8-18 | Scheduled traffic state machines—overview and relationships .....            | 226 |
| Figure 8-19 | Cycle Timer state machine .....  | 226 |
| Figure 8-20 | List Execute state machine .....   | 227 |
| Figure 8-21 | List Config state machine .....  | 228 |
| Figure 8-22 | Logical points of attachment of the Higher Layer and Relay Entities .....    | 261 |
| Figure 8-23 | Effect of control information on the forwarding path .....                   | 261 |
| Figure 8-24 | Per-Port points of attachment .....  | 262 |
| Figure 8-25 | Single point of attachment—relay permitted .....                             | 262 |
| Figure 8-26 | Single point of attachment—relay not permitted .....                         | 262 |
| Figure 8-27 | Effect of Port State .....   | 263 |
| Figure 8-28 | Controlled and Uncontrolled Port connectivity .....                          | 264 |
| Figure 8-29 | Ingress/egress control information in the forwarding path .....              | 264 |
| Figure 9-1  | VLAN TCI format .....  | 269 |
| Figure 9-2  | I-TAG TCI format .....   | 270 |
| Figure 10-1 | Example—Attribute value propagation from one station .....                   | 273 |
| Figure 10-2 | Example—Attribute value propagation from two stations .....                  | 273 |
| Figure 10-3 | Example—Registrations as pointers to the sources of declarations .....       | 274 |
| Figure 10-4 | MRP architecture .....   | 276 |
| Figure 10-5 | Format of the major components of an MRPDU .....                             | 299 |
| Figure 10-6 | Operation of MMRP for a single VLAN Context .....                            | 305 |
| Figure 10-7 | Example Directed Graph .....   | 306 |
| Figure 10-8 | Example of MMRP propagation in a VLAN Context .....                          | 308 |
| Figure 11-1 | Operation of MVRP .....  | 316 |

|              |   |     |
|--------------|---|-----|
| Figure 12-1  | Relationships among CFM managed objects.....                            | 377 |
| Figure 12-2  | Relationship among BEB managed objects.....                             | 394 |
| Figure 12-3  | SPB managed objects (MOs).....  | 449 |
| Figure 12-4  | Relationships among EVB Bridge managed objects .....                    | 465 |
| Figure 12-5  | Relationship among EVB station managed objects.....                     | 465 |
| Figure 12-6  | Timing points for scheduled traffic .....                               | 482 |
| Figure 12-7  | Timing points for PSFP .....  | 489 |
| Figure 13-1  | Diagrammatic conventions for spanning tree topologies .....             | 506 |
| Figure 13-2  | Physical topology and active topology .....                             | 507 |
| Figure 13-3  | Port Roles and Port States.....   | 507 |
| Figure 13-4  | A Backup Port.....  | 508 |
| Figure 13-5  | “Ring Backbone” example.....  | 508 |
| Figure 13-6  | An MST Bridge network .....   | 510 |
| Figure 13-7  | CIST Priority Vectors, Port Roles, and MST Regions .....                | 511 |
| Figure 13-8  | MSTI Active Topology in Region 2 .....                                  | 512 |
| Figure 13-9  | CIST and MSTI active topologies in Region 1 of the example network..... | 525 |
| Figure 13-10 | Agreements and Proposals.....   | 529 |
| Figure 13-11 | CIST and MSTI Active Topologies in Region 2 of Figure 13-6.....         | 530 |
| Figure 13-12 | Enhanced Agreements .....   | 531 |
| Figure 13-13 | Spanning tree protocol state machines—overview and relationships .....  | 542 |
| Figure 13-14 | MSTP overview notation.....   | 543 |
| Figure 13-15 | Port Timers state machine.....  | 573 |
| Figure 13-16 | Port Receive state machine .....  | 573 |
| Figure 13-17 | Port Protocol Migration state machine .....                             | 574 |
| Figure 13-18 | Bridge Detection state machine .....                                    | 574 |
| Figure 13-19 | Port Transmit state machine .....                                       | 575 |
| Figure 13-20 | Port Information state machine.....                                     | 576 |
| Figure 13-21 | Port Role Selection state machine .....                                 | 577 |
| Figure 13-22 | Disabled Port role transitions.....                                     | 578 |
| Figure 13-23 | Port Role Transitions state machine—MasterPort.....                     | 579 |
| Figure 13-24 | Port Role Transitions state machine—RootPort.....                       | 580 |
| Figure 13-25 | Port Role Transitions state machine—DesignatedPort.....                 | 581 |
| Figure 13-26 | Port Role Transitions state machine—AlternatePort and BackupPort .....  | 582 |
| Figure 13-27 | Port State Transition state machine .....                               | 582 |
| Figure 13-28 | Topology Change state machine.....                                      | 584 |
| Figure 13-29 | L2 Gateway Port Receive state machine .....                             | 585 |
| Figure 14-1  | RST, MST, SPT, and STP Configuration BPDU format.....                   | 589 |
| Figure 14-2  | STP TCN BPDU format .....   | 589 |
| Figure 14-3  | MSTI Configuration Message parameters and format .....                  | 594 |
| Figure 15-1  | Internal organization of the MAC sublayer in a PBN .....                | 597 |
| Figure 15-2  | Port-based service interface to a PBN .....                             | 598 |
| Figure 15-3  | Port-based service interface to a PBN .....                             | 599 |
| Figure 15-4  | C-tagged service interface to a PBN .....                               | 599 |
| Figure 15-5  | C-tagged service interface to a PBN.....                                | 599 |
| Figure 15-6  | Customer Edge Ports (CEPs).....   | 600 |
| Figure 15-7  | S-tagged service interface to a PBN .....                               | 600 |
| Figure 15-8  | S-tagged interface to a PBN.....  | 601 |
| Figure 15-9  | RCSIs to a PBN .....  | 601 |
| Figure 15-10 | Remote Customer Access Ports (RCAPs) .....                              | 602 |
| Figure 15-11 | C-tagged RCSI to a PBN .....  | 603 |
| Figure 15-12 | Port-based RCSI to a PBN.....   | 603 |
| Figure 15-13 | Provider Network Port (PNP) interface .....                             | 604 |
| Figure 16-1  | PBN with interface examples .....                                       | 607 |
| Figure 16-2  | Examples of remote customer service access via a second PBN .....       | 609 |

|              |   |      |
|--------------|---|------|
| Figure 16-3  | Access service separation and “Hairpin Switching”           | 610  |
| Figure 16-3  | Access service separation and “Hairpin Switching”           | 610  |
| Figure 17-1  | C-VLAN component internal LAN managed system                | 675  |
| Figure 17-2  | I/B-component internal LAN managed system                   | 680  |
| Figure 18-1  | One Maintenance Domain: operator’s view                     | 1184 |
| Figure 18-2  | One service instance: operator’s view                       | 1185 |
| Figure 18-3  | One service instance: customer’s view                       | 1185 |
| Figure 18-4  | MEP and MIP Symbols   | 1186 |
| Figure 18-5  | MAs: one service instance in a provider network             | 1187 |
| Figure 18-6  | MAs: Expansion of Figure 18-5                               | 1188 |
| Figure 18-7  | MEPs, MIPs, and MD Levels                                   | 1189 |
| Figure 19-1  | CFM Protocol shims  | 1190 |
| Figure 19-2  | MA Endpoint (MEP)   | 1193 |
| Figure 19-3  | MIP Half Function (MHF)                                     | 1198 |
| Figure 19-4  | LOM shim  | 1200 |
| Figure 19-5  | LOM architecture  | 1201 |
| Figure 20-1  | MEP state machines—overview and relationships               | 1214 |
| Figure 20-2  | MEP Continuity Check Initiator state machine                | 1221 |
| Figure 20-3  | MHF Continuity Check Receiver state machine                 | 1222 |
| Figure 20-4  | MEP Continuity Check Receiver state machine                 | 1226 |
| Figure 20-5  | Remote MEP state machine                                    | 1228 |
| Figure 20-6  | Remote MEP Error state machine                              | 1229 |
| Figure 20-7  | MEP Cross Connect state machine                             | 1230 |
| Figure 20-8  | MEP Traffic Field Mismatch state machine                    | 1232 |
| Figure 20-9  | MEP Local Mismatch state machine                            | 1232 |
| Figure 20-10 | MP Loopback Responder state machine                         | 1234 |
| Figure 20-11 | MEP Loopback Initiator transmit state machine               | 1237 |
| Figure 20-12 | MEP Loopback Initiator receive state machine                | 1238 |
| Figure 20-13 | MEP Fault Notification Generator state machine              | 1240 |
| Figure 20-14 | MEP Mismatch Fault Notification Generator state machine     | 1242 |
| Figure 20-15 | MEP Linktrace Initiator receive state machine               | 1246 |
| Figure 20-16 | Linktrace Responder, MEPs, MHFs, and LOMs                   | 1248 |
| Figure 20-17 | LTM Receiver state machine                                  | 1254 |
| Figure 20-18 | LTR Transmitter state machine                               | 1255 |
| Figure 22-1  | MEPs and MIPs distinguished by VID (incomplete picture)     | 1284 |
| Figure 22-2  | Alternate view of Forwarding process                        | 1285 |
| Figure 22-3  | Combining per-VLAN MPs into two shims                       | 1286 |
| Figure 22-4  | More complete picture of MP placement in a Bridge Port      | 1287 |
| Figure 22-5  | Service instance spanning two Bridges protected by Up MPs   | 1289 |
| Figure 22-6  | Service instance spanning two Bridges protected by Down MPs | 1289 |
| Figure 22-7  | MP placement in a non-VLAN-aware Bridge Port                | 1291 |
| Figure 22-8  | MP placement relative to other standards                    | 1292 |
| Figure 22-9  | Creating MEPs and MIPs                                      | 1295 |
| Figure 22-10 | CFM in a Provider Edge Bridge C-tagged service interface    | 1301 |
| Figure 22-11 | CFM in a Provider Edge Bridge C-tagged RCSI                 | 1303 |
| Figure 22-12 | Up MEPs in a Management Port                                | 1304 |
| Figure 22-13 | CFM in the enterprise environment                           | 1305 |
| Figure 22-14 | CFM on a Bridge that implements IEEE Std 802.1Q-2005        | 1306 |
| Figure 23-1  | TPMR connecting two Bridge Ports                            | 1307 |
| Figure 23-2  | TPMR chain connecting Bridge Ports                          | 1307 |
| Figure 23-3  | MSSs and the MSPE   | 1309 |
| Figure 23-4  | Adding connectivity   | 1311 |
| Figure 23-5  | Losing connectivity   | 1312 |
| Figure 23-6  | TPMR recovery   | 1313 |

|              |  |      |
|--------------|--|------|
| Figure 23-7  | Notification from one end of the link to the other .....                 | 1314 |
| Figure 23-8  | Immediate MAC status notification at the end of a link .....             | 1314 |
| Figure 23-9  | MSPE state machine overview .....  | 1315 |
| Figure 23-10 | Status Transition state machine (STM) .....                              | 1319 |
| Figure 23-11 | Status Notification state machine (SNM) .....                            | 1320 |
| Figure 23-12 | MSPDU structure.....   | 1322 |
| Figure 25-1  | Internal organization of the MAC sublayer in a PBBN.....                 | 1326 |
| Figure 25-2  | PBB terminology .....  | 1327 |
| Figure 25-3  | Customer service interface types .....                                   | 1328 |
| Figure 25-4  | Port-based service interface .....                                       | 1329 |
| Figure 25-5  | Port-based interface equipment .....                                     | 1330 |
| Figure 25-6  | Encapsulated service frames at ISS .....                                 | 1331 |
| Figure 25-7  | S-tagged service interface.....  | 1331 |
| Figure 25-8  | S-tagged service interface equipment .....                               | 1332 |
| Figure 25-9  | I-tagged service interface.....  | 1333 |
| Figure 25-10 | I-tagged service interface equipment.....                                | 1333 |
| Figure 25-11 | S-tagged and Port-based service interface access classifications .....   | 1335 |
| Figure 25-12 | I-tagged service interface access protection classifications.....        | 1336 |
| Figure 25-1  | Internal organization of the MAC sublayer in a PBB-TE Region.....        | 1339 |
| Figure 25-14 | PBB-TE Region .....  | 1341 |
| Figure 25-15 | Transparent service interface .....                                      | 1342 |
| Figure 25-16 | Transparent service interface equipment .....                            | 1343 |
| Figure 26-1  | PBBN example .....   | 1345 |
| Figure 26-2  | CFM shim model .....   | 1352 |
| Figure 26-3  | CFM example applied to a Port-based and S-tagged service interface ..... | 1353 |
| Figure 26-4  | CFM example applied to an I-tagged Service Interface .....               | 1354 |
| Figure 26-5  | CFM example applied to a hierarchal E-NNI, CBP-PIP Demarc.....           | 1355 |
| Figure 26-6  | CFM example applied to a peer E-NNI, CBP-PIP .....                       | 1356 |
| Figure 26-7  | Independent ESPs using the same ESP-DAs and ESP-VIDs .....               | 1359 |
| Figure 26-8  | PBB-TE MEP placement in a CBP.....                                       | 1360 |
| Figure 26-9  | Independent Infrastructure Segments distinguished by SMP-SA.....         | 1363 |
| Figure 26-10 | Infrastructure Segment MEP placement in a PNP.....                       | 1364 |
| Figure 26-11 | Protection switching architecture.....                                   | 1365 |
| Figure 26-12 | PBB-TE point-to-point protection switching.....                          | 1367 |
| Figure 26-13 | Mapping data traffic to the protection entity .....                      | 1368 |
| Figure 26-14 | Relationships of the Protection switching state machines—overview .....  | 1369 |
| Figure 26-15 | Hold-off state machine.....  | 1373 |
| Figure 26-16 | Clear Manual Switch state machine.....                                   | 1373 |
| Figure 26-17 | Service Mapping state machine .....                                      | 1374 |
| Figure 26-18 | Segment terminology and properties .....                                 | 1375 |
| Figure 26-19 | Infrastructure Segment monitoring.....                                   | 1376 |
| Figure 26-20 | Working Segment and Protection Segment.....                              | 1377 |
| Figure 26-21 | Nested IPGs .....  | 1378 |
| Figure 26-22 | IPS Control entity .....   | 1380 |
| Figure 26-23 | M:1 IPS .....  | 1381 |
| Figure 26-24 | M:1 IPS state machines.....  | 1382 |
| Figure 26-25 | M:1 Hold-off state machine .....   | 1385 |
| Figure 26-26 | Protection Segment Selection state machine .....                         | 1386 |
| Figure 27-1  | Configuring VLAN support in an SPT Region (example) .....                | 1393 |
| Figure 27-2  | SPBM group MAC address—general format .....                              | 1404 |
| Figure 27-3  | SPBM group MAC addresses—source rooted SPT .....                         | 1404 |
| Figure 27-4  | SPBM group MAC addresses—shared tree.....                                | 1405 |
| Figure 27-5  | SPBM MEP placement in a CBP.....   | 1407 |
| Figure 27-6  | SPBV campus network example.....   | 1410 |

|              |  |      |
|--------------|--|------|
| Figure 27-7  | SPT Bridge Network using SPBM example.....                             | 1411 |
| Figure 28-1  | Agreement Digest field format .....                                    | 1416 |
| Figure 28-2  | MT-Capability TLV.....   | 1425 |
| Figure 28-3  | SPB MCID sub-TLV .....   | 1425 |
| Figure 28-4  | SPB Digest sub-TLV .....   | 1426 |
| Figure 28-5  | SPB Base VLAN-Identifiers sub-TLV .....                                | 1427 |
| Figure 28-6  | SPB Instance sub-TLV .....   | 1428 |
| Figure 28-7  | SPB Instance Opaque ECT-ALGORITHM sub-TLV .....                        | 1430 |
| Figure 28-8  | ECMP ECT-ALGORITHM sub-TLV .....                                       | 1430 |
| Figure 28-9  | SPB Link Metric sub-TLV .....  | 1431 |
| Figure 28-10 | SPB Adjacency Opaque ECT-ALGORITHM sub-TLV .....                       | 1432 |
| Figure 28-11 | SPBV MAC Address sub-TLV.....  | 1432 |
| Figure 28-12 | SPBM Service Identifier and Unicast Address sub-TLV .....              | 1434 |
| Figure 29-1  | Forward path test (FPT).....   | 1437 |
| Figure 29-2  | Return path test (RPT) .....   | 1438 |
| Figure 29-3  | Combination of FPT and RPT .....                                       | 1439 |
| Figure 29-4  | Detailed functions of RR .....   | 1440 |
| Figure 29-5  | RFM Receiver on a non-MP.....  | 1443 |
| Figure 29-6  | Return Path DR.....  | 1444 |
| Figure 29-7  | RR Filter state machine.....   | 1449 |
| Figure 29-8  | RR Encapsulation state machine.....                                    | 1450 |
| Figure 29-9  | RR Transmit state machine.....   | 1450 |
| Figure 29-10 | RFM Receiver state machine.....  | 1451 |
| Figure 29-11 | Decapsulator Responder state machine .....                             | 1454 |
| Figure 30-1  | Congestion detection in QCN CP .....                                   | 1460 |
| Figure 30-2  | Sampling (reflection) probability in QCN CP as a function of  Fb ..... | 1460 |
| Figure 30-3  | QCN RP operation .....   | 1461 |
| Figure 30-4  | Byte Counter and Timer interaction with Rate Limiter.....              | 1463 |
| Figure 30-5  | CP–RP peering in VLAN Bridged Network.....                             | 1465 |
| Figure 30-6  | CP–RP peering in PBBN .....  | 1466 |
| Figure 31-1  | CPs and congestion-aware queues in a Bridge .....                      | 1467 |
| Figure 31-2  | Congestion-aware queue functions in an end station.....                | 1469 |
| Figure 31-3  | Per-CNPV station function .....  | 1471 |
| Figure 32-1  | CND defense state machine.....   | 1484 |
| Figure 32-2  | RP rate control state machine .....                                    | 1496 |
| Figure 32-3  | CP–RP peering in any hierarchical Bridged Network .....                | 1497 |
| Figure 34-1  | Queuing model for a Talker station .....                               | 1509 |
| Figure 35-1  | Operation of MSRP .....  | 1514 |
| Figure 35-2  | Format of the components of the reservation FirstValue fields.....     | 1525 |
| Figure 35-3  | Format of the components of the Domain FirstValue .....                | 1530 |
| Figure 35-4  | Value of StreamID TLV .....  | 1535 |
| Figure 35-5  | Value of StreamRank TLV .....  | 1535 |
| Figure 35-6  | Value of InterfaceID TLV .....   | 1535 |
| Figure 35-7  | Value of IEEE802-MacAddresses TLV .....                                | 1536 |
| Figure 35-8  | Value of IEEE802-VlanTag TLV.....                                      | 1536 |
| Figure 35-9  | Value of IPv4-tuple TLV .....  | 1537 |
| Figure 35-10 | Value of IPv6-tuple TLV .....  | 1537 |
| Figure 35-11 | Value of TrafficSpecification TLV.....                                 | 1540 |
| Figure 35-12 | Value of TSpecTimeAware TLV .....                                      | 1540 |
| Figure 35-13 | Value of UserToNetworkRequirements TLV.....                            | 1541 |
| Figure 35-14 | Value of InterfaceCapabilities TLV .....                               | 1542 |
| Figure 35-15 | Value of StatusInfo TLV .....  | 1542 |
| Figure 35-16 | Value of AccumulatedLatency TLV.....                                   | 1543 |
| Figure 35-17 | Value of TimeAwareOffset TLV.....                                      | 1544 |

|              |  |      |
|--------------|--|------|
| Figure 36-1  | PFC peering .....  | 1560 |
| Figure 36-2  | PFC Receiver state diagram for priority n .....                              | 1562 |
| Figure 36-3  | PFC-aware system queue functions .....                                       | 1564 |
| Figure 36-4  | PFC-aware system queue functions with Link Aggregation .....                 | 1565 |
| Figure 38-1  | DCBX Asymmetric state machine .....  | 1570 |
| Figure 38-2  | Symmetric state machine .....  | 1571 |
| Figure 39-1  | Operation of MIRP in an I-component .....                                    | 1573 |
| Figure 39-2  | Operation of MIRP in a B-component .....                                     | 1573 |
| Figure 39-3  | Alternate model for MIRP in a B-component .....                              | 1578 |
| Figure 40-1  | EVB architecture overview .....  | 1580 |
| Figure 40-2  | EVB architecture without S-channels .....                                    | 1582 |
| Figure 40-3  | EVB architecture with S-channel .....  | 1582 |
| Figure 40-4  | EVB components and internal LANs with S-channels .....                       | 1583 |
| Figure 40-5  | EVB architecture without S-channels, with EVB Bridge S-VLAN component .....  | 1585 |
| Figure 40-6  | EVB architecture without S-channels, with EVB station S-VLAN component ..... | 1585 |
| Figure 41-1  | VSI manager ID TLV .....   | 1588 |
| Figure 41-2  | VDP association TLV .....  | 1589 |
| Figure 41-3  | VID Filter Info format .....   | 1594 |
| Figure 41-4  | MAC/VID filter format .....  | 1594 |
| Figure 41-5  | GroupID/VID filter format .....  | 1595 |
| Figure 41-6  | GroupID/MAC/VID filter format .....  | 1595 |
| Figure 41-7  | GroupID/VID/IPv4 filter format .....   | 1595 |
| Figure 41-8  | GroupID/MAC/VID/IPv4 filter format .....                                     | 1596 |
| Figure 41-9  | GroupID/VID/IPv6 filter format .....   | 1596 |
| Figure 41-10 | GroupID/MAC/VID/IPv6 filter format .....                                     | 1597 |
| Figure 41-11 | Organizationally defined TLV .....   | 1598 |
| Figure 41-12 | Bridge VDP state machine .....   | 1600 |
| Figure 41-13 | Station VDP state machine .....  | 1601 |
| Figure 42-1  | CDCP state machine—Station role .....  | 1608 |
| Figure 42-2  | CDCP state machine—Bridge role .....   | 1609 |
| Figure 43-1  | Example ECP exchange .....   | 1613 |
| Figure 43-2  | ECPDU structure .....  | 1615 |
| Figure 43-3  | ECP transmit state machine .....   | 1616 |
| Figure 43-4  | ECP receive state machine .....  | 1617 |
| Figure 44-1  | Flow Filtering TCI format .....  | 1624 |
| Figure 44-2  | SPBM VID MEP and ECMP path MEP placement in a CBP .....                      | 1628 |
| Figure 45-1  | An SPT Region controlled by a single PCE .....                               | 1631 |
| Figure 45-2  | An SPT Region controlled by multiple PCEs .....                              | 1632 |
| Figure 45-3  | The use of the SPB Instance sub-TLV for MRT .....                            | 1640 |
| Figure 45-4  | Shared Risk Link Group (SRLG) TLV .....                                      | 1644 |
| Figure 45-5  | Topology sub-TLV .....   | 1645 |
| Figure 45-6  | A strict tree and its descriptor Topology sub-TLV .....                      | 1646 |
| Figure 45-7  | Topology sub-TLV of a loose tree .....                                       | 1647 |
| Figure 45-8  | Hop sub-TLV .....  | 1649 |
| Figure 45-9  | Administrative Group sub-TLV .....   | 1652 |
| Figure 45-10 | Bandwidth Constraint sub-TLV .....   | 1652 |
| Figure 45-11 | Bandwidth Assignment sub-TLV .....   | 1653 |
| Figure 45-12 | Timestamp sub-TLV .....  | 1654 |
| Figure 45-13 | A GADAG and its descriptor Topology sub-TLV .....                            | 1660 |
| Figure 45-14 | MRT-Blue and MRT-Red for MRT Root 55 .....                                   | 1661 |
| Figure 45-15 | A GADAG for a topology with multiple blocks .....                            | 1662 |
| Figure 46-1  | Fully distributed model .....  | 1665 |
| Figure 46-2  | Centralized network/distributed user model .....                             | 1666 |
| Figure 46-3  | Fully centralized model .....  | 1668 |

|              |   |      |
|--------------|---|------|
| Figure 46-4  | Example of Stream transformation in Talker end station .....                          | 1669 |
| Figure 46-5  | Example of IEEE 802.1CB functions in Talker end station .....                         | 1670 |
| Figure 46-6  | Example of IEEE 802.1CB functions in Listener end station .....                       | 1670 |
| Figure 48-1  | General YANG hierarchy .....  | 1696 |
| Figure 48-2  | YANG root hierarchy with IEEE 802.1Q YANG modules.....                                | 1696 |
| Figure 48-3  | Interface YANG model.....   | 1697 |
| Figure 48-4  | VLAN Bridge components model (MAC Relay Entities).....                                | 1699 |
| Figure 48-5  | Bridge Port model.....  | 1700 |
| Figure 48-6  | TPMR model (MAC Relay Entity).....  | 1701 |
| Figure 48-7  | TPMR port model .....   | 1702 |
| Figure 48-8  | Provider Bridge model.....  | 1703 |
| Figure 48-9  | Provider Edge Bridge C-VLAN Interface model .....                                     | 1704 |
| Figure 48-10 | Provider Edge Bridge S-VLAN interface model .....                                     | 1705 |
| Figure 48-11 | Bridge to CFM YANG model .....  | 1707 |
| Figure 48-12 | CFM CFM MEP model relationships model relationships .....                             | 1708 |
| Figure 48-13 | CFM MEP model.....  | 1709 |
| Figure 48-14 | CFM operations structure .....  | 1709 |
| Figure 48-15 | Stream filters and stream gates model MEP model.....                                  | 1710 |
| Figure 48-16 | Asynchronous Traffic Shaping model .....  | 1711 |
| Figure C-1   | CSN backbone .....  | 1937 |
| Figure C-2   | Bridge’s CSN model for bandwidth reservation.....                                     | 1938 |
| Figure C-3   | Talker MSRPDU flow .....  | 1939 |
| Figure C-4   | Listener MSRPDU flow.....   | 1939 |
| Figure C-5   | IEEE DMN Device Attribute IE.....   | 1941 |
| Figure C-6   | DMN Confirmation Transaction.....   | 1943 |
| Figure C-7   | Bandwidth reservation—bridge model for IEEE 802.11 BSS<br>(STA downstream Port) ..... | 1945 |
| Figure C-8   | Bandwidth reservation—bridge model for IEEE 802.11 BSS<br>(STA upstream Port).....    | 1946 |
| Figure C-9   | Bandwidth reservation—bridge model for IEEE 802.11 BSS<br>(direct link setup) .....   | 1946 |
| Figure C-10  | MSRP/IEEE 802.11 query flows .....  | 1947 |
| Figure C-11  | MSRP/802.11 Talker STA to Listener STA reservation flows .....                        | 1947 |
| Figure C-12  | MSRP/802.11 “Bridged” Listener to Talker STA reservation flows .....                  | 1948 |
| Figure C-13  | MSRP/802.11 Listener STA to “Bridged” Talker reservation flows .....                  | 1948 |
| Figure D-1   | Port VLAN ID TLV format .....   | 1954 |
| Figure D-2   | Port And Protocol VLAN ID TLV format.....   | 1954 |
| Figure D-3   | VLAN Name TLV format .....  | 1955 |
| Figure D-4   | Protocol Identity TLV format.....   | 1956 |
| Figure D-5   | VID Usage Digest TLV format .....   | 1957 |
| Figure D-6   | Management VID TLV format.....  | 1957 |
| Figure D-7   | Congestion Notification TLV format .....  | 1958 |
| Figure D-8   | ETS Configuration TLV format .....  | 1959 |
| Figure D-9   | ETS Recommendation TLV format.....  | 1961 |
| Figure D-10  | Priority-based Flow Control Configuration TLV format .....                            | 1962 |
| Figure D-11  | Application Priority TLV format.....  | 1963 |
| Figure D-12  | EVB TLV format .....  | 1965 |
| Figure D-13  | CDCP TLV structure .....  | 1969 |
| Figure D-14  | Application VLAN TLV format.....  | 1971 |
| Figure F-1   | Connecting independent VLANs—1 .....  | 2057 |
| Figure F-2   | Connecting independent VLANs—2.....   | 2058 |
| Figure F-3   | Duplicate MAC addresses .....   | 2058 |
| Figure F-4   | Asymmetric VID use: “multi-netted server” .....                                       | 2059 |
| Figure F-5   | Asymmetric VLAN use: “Rooted-Multipoint”.....   | 2061 |

|             |   |      |
|-------------|---|------|
| Figure F-6  | Rooted-Multipoint with tagged interfaces .....  | 2062 |
| Figure F-7  | SPBV VLAN Shared Learning and VID Translation.....                                      | 2063 |
| Figure G-1  | Example of IEEE 802.3 MAC frame format .....  | 2065 |
| Figure G-2  | Methods for Bridge access to IEEE 802.11 and PMPN media: example.....                   | 2068 |
| Figure H-1  | Static filtering inconsistency.....   | 2071 |
| Figure H-2  | Interoperability with MAC Bridges: example 1 .....                                      | 2072 |
| Figure H-3  | Interoperability with MAC Bridges: example 2 .....                                      | 2073 |
| Figure H-4  | Interoperability between Port-based and<br>Port-and-Protocol-based classification ..... | 2074 |
| Figure J-1  | Up MPs in a CFM Port .....  | 2088 |
| Figure K-1  | TPMR as UNI demarcation device .....  | 2090 |
| Figure K-2  | TPMRs with aggregated links.....  | 2091 |
| Figure K-3  | Multiple TPMRs .....  | 2091 |
| Figure K-4  | Recovery at the end of a chain.....   | 2092 |
| Figure K-5  | Near simultaneous recoveries .....  | 2093 |
| Figure K-6  | Near simultaneous failure and recovery .....  | 2093 |
| Figure K-7  | Loss with quick recovery .....  | 2094 |
| Figure L-1  | Credit-based shaper operation—no conflicting traffic .....                              | 2097 |
| Figure L-2  | Credit-based shaper operation—conflicting traffic .....                                 | 2098 |
| Figure L-3  | Credit-based shaper operation—burst traffic.....  | 2099 |
| Figure L-4  | Interference and latency .....  | 2103 |
| Figure L-5  | Burst behavior and credit.....  | 2103 |
| Figure L-6  | Fan-in scenario.....  | 2107 |
| Figure L-7  | Permanent delay scenario .....  | 2108 |
| Figure L-8  | Building up buffer occupancy—1.....   | 2109 |
| Figure L-9  | Building up buffer occupancy—2.....   | 2109 |
| Figure L-10 | Building up buffer occupancy—3.....   | 2109 |
| Figure L-11 | Building up buffer occupancy—4.....   | 2110 |
| Figure M-1  | PFC PDU format.....   | 2112 |
| Figure N-1  | PFC delays .....  | 2113 |
| Figure N-2  | Delay model.....  | 2114 |
| Figure N-3  | Worst-case delay .....  | 2115 |
| Figure O-1  | Converting a CRC to an FCS.....   | 2120 |
| Figure O-2  | Detection Lossless Circuit .....  | 2120 |
| Figure O-3  | Field change adjustment .....   | 2122 |
| Figure O-4  | Field insertion adjustment.....   | 2123 |
| Figure P-1  | Frame duplication scenario .....  | 2126 |
| Figure P-2  | Frame misordering scenario.....   | 2127 |
| Figure Q-1  | Establishing a guard band.....  | 2129 |
| Figure Q-2  | Using gate operations.....  | 2130 |
| Figure T-1  | Example Stream Filter and Stream Gate configuration for CQF.....                        | 2139 |
| Figure T-2  | Traffic scheduling example for CQF .....  | 2140 |
| Figure T-3  | Example Stream Filter and Stream Gate configuration with two values of T .....          | 2141 |
| Figure T-4  | Traffic scheduling example with two values of T .....                                   | 2141 |
| Figure T-5  | Interleaving example—factor of 2 .....  | 2142 |
| Figure U-1  | Example of enhancements for scheduled traffic.....                                      | 2146 |
| Figure V-1  | Path of frames along a single hop with index k with two Bridges .....                   | 2153 |

**Tables**

|             |   |     |
|-------------|---|-----|
| Table 6-1   | Bridge transit delay .....  | 151 |
| Table 6-2   | Priority Code Point encoding.....   | 159 |
| Table 6-3   | Priority Code Point decoding.....   | 159 |
| Table 6-4   | Priority regeneration .....   | 160 |
| Table 6-5   | Default SRP domain boundary port priority regeneration override values .....  | 161 |
| Table 6-6   | Service Access Priority .....   | 172 |
| Table 6-7   | Encapsulated Addresses EtherType.....   | 179 |
| Table 8-1   | C-VLAN and MAC Bridge component Reserved addresses.....   | 206 |
| Table 8-2   | S-VLAN component Reserved addresses.....  | 207 |
| Table 8-3   | TPMR component Reserved addresses.....  | 207 |
| Table 8-4   | Stream gate control operations .....  | 214 |
| Table 8-5   | Recommended priority to traffic class mappings .....  | 217 |
| Table 8-6   | Transmission selection algorithm identifiers .....  | 220 |
| Table 8-7   | Gate operations .....   | 223 |
| Table 8-8   | Scheduled Traffic and Stream Gate procedures/variables.....   | 232 |
| Table 8-9   | Ageing time parameter value.....  | 239 |
| Table 8-10  | Combining Static and Dynamic Filtering Entries for an individual MAC address .....  | 249 |
| Table 8-11  | Combining Static Filtering Entry and MAC Address Registration Entry for<br>“All Group Addresses” and “All Unregistered Group Addresses” ..... | 250 |
| Table 8-12  | Forwarding or Filtering for specific group MAC addresses .....  | 250 |
| Table 8-13  | Forwarding or Filtering with Dynamic Reservation Entries .....  | 251 |
| Table 8-14  | Determination of whether a Port is in a VID’s member set.....   | 252 |
| Table 8-15  | Standard LLC address assignment.....  | 257 |
| Table 8-17  | ISIS-SPB Recommended Address Usage.....   | 259 |
| Table 8-16  | ISIS-SPB reserved addresses .....   | 259 |
| Table 8-18  | CCM group destination MAC addresses .....   | 266 |
| Table 8-19  | LTM group destination MAC addresses.....  | 266 |
| Table 9-2   | Reserved VID values .....   | 269 |
| Table 9-1   | IEEE 802.1Q™ EtherType allocations.....   | 269 |
| Table 9-3   | Reserved I-SID values .....   | 271 |
| Table 10-1  | MRP application addresses .....   | 279 |
| Table 10-2  | MRP EtherType values .....  | 279 |
| Table 10-3  | Applicant state table.....  | 293 |
| Table 10-4  | Registrar state table.....  | 294 |
| Table 10-5  | LeaveAll state table .....  | 294 |
| Table 10-6  | PeriodicTransmission state table .....  | 295 |
| Table 10-7  | MRP timer parameter default values .....  | 295 |
| Table 12-1  | Component table entry managed object.....   | 327 |
| Table 12-2  | Port table entry.....   | 329 |
| Table 12-3  | ISS Port Number table entry .....   | 330 |
| Table 12-4  | Bandwidth Availability Parameter Table row elements .....   | 433 |
| Table 12-5  | Transmission Selection Algorithm Table row elements.....  | 434 |
| Table 12-6  | Priority Regeneration Override Table row elements .....   | 434 |
| Table 12-7  | SR Class to Priority Mapping Table row elements.....  | 435 |
| Table 12-9  | CN component priority managed object row elements .....   | 436 |
| Table 12-8  | CN component managed object row elements .....  | 436 |
| Table 12-10 | CN Port priority managed object row elements.....   | 437 |
| Table 12-11 | Congestion Point managed object row elements .....  | 438 |
| Table 12-13 | Reaction Point group managed object row elements.....   | 439 |
| Table 12-12 | Reaction Point port priority managed object row elements.....   | 439 |
| Table 12-14 | SRP Bridge Base Table row elements .....  | 440 |
| Table 12-15 | SRP Bridge Port Table row elements .....  | 440 |

|             |   |     |
|-------------|---|-----|
| Table 12-16 | SRP Latency Parameter Table row elements.....                 | 441 |
| Table 12-17 | SRP Stream Table row elements .....                           | 441 |
| Table 12-19 | SRP Stream Preload Table row elements .....                   | 442 |
| Table 12-18 | SRP Reservations Table row elements .....                     | 442 |
| Table 12-20 | SRP Reservations Preload Table row elements.....              | 443 |
| Table 12-21 | Priority-based Flow Control objects.....                      | 444 |
| Table 12-22 | EVB system base table .....                                   | 468 |
| Table 12-24 | SBP table entry .....   | 469 |
| Table 12-23 | EVB system parameter defaults.....                            | 469 |
| Table 12-25 | VSI table entry .....   | 470 |
| Table 12-27 | UAP table entry parameters.....                               | 471 |
| Table 12-26 | VSI MAC/VLAN table entry.....                                 | 471 |
| Table 12-28 | UAP table entry .....   | 472 |
| Table 12-29 | S-channel interface table entry .....                         | 473 |
| Table 12-31 | ECP table entry .....   | 474 |
| Table 12-30 | URP table entry.....  | 474 |
| Table 12-32 | The Gate Parameter Table .....                                | 479 |
| Table 12-33 | Frame Preemption Parameter table.....                         | 482 |
| Table 12-34 | The Stream Parameter Table.....                               | 484 |
| Table 12-35 | Stream Filter Instance Table .....                            | 486 |
| Table 12-36 | The Stream Gate Instance Table.....                           | 487 |
| Table 12-37 | The Flow Meter Instance Table .....                           | 490 |
| Table 12-39 | The Scheduler Group Instance Table.....                       | 491 |
| Table 12-38 | The Scheduler Instance Table.....                             | 491 |
| Table 12-40 | The Scheduler Port Parameter Table .....                      | 492 |
| Table 12-41 | The Timing Characteristics Table.....                         | 493 |
| Table 12-38 | Bridge Delay attributes .....                                 | 494 |
| Table 12-39 | Propagation Delay attributes.....                             | 496 |
| Table 12-40 | Static Trees attributes.....                                  | 496 |
| Table 12-41 | MRP External Control attributes .....                         | 498 |
| Table 13-1  | Configuration Digest Signature Key.....                       | 516 |
| Table 13-2  | Sample Configuration Digest Signature Keys .....              | 517 |
| Table 13-3  | Bridge and Port Priority values.....                          | 535 |
| Table 13-4  | Port Path Cost values .....                                   | 536 |
| Table 13-5  | Timer and related parameter values.....                       | 544 |
| Table 17-1  | IEEE 802.1Q MIB modules.....                                  | 614 |
| Table 17-2  | IEEE8021-TC-MIB structure .....                               | 615 |
| Table 17-3  | IEEE8021-BRIDGE-MIB structure.....                            | 616 |
| Table 17-4  | IEEE 802.1D objects not in the IEEE8021-BRIDGE-MIB.....       | 620 |
| Table 17-5  | IEEE8021-SPANNING-TREE MIB structure .....                    | 621 |
| Table 17-6  | Clause 12 objects not in the IEEE8021-SPANNING-TREE MIB ..... | 622 |
| Table 17-7  | IEEE8021-Q-BRIDGE MIB structure.....                          | 623 |
| Table 17-8  | Clause 12 management not in IEEE8021-Q-BRIDGE-MIB .....       | 628 |
| Table 17-9  | IEEE8021-PB-MIB structure.....                                | 628 |
| Table 17-10 | IEEE8021-MSTP-MIB structure .....                             | 630 |
| Table 17-11 | IEEE8021-CFM-MIB structure .....                              | 633 |
| Table 17-12 | IEEE8021-CFM-V2-MIB structure.....                            | 637 |
| Table 17-13 | IEEE8021-PBB-MIB structure .....                              | 639 |
| Table 17-14 | IEEE8021-DDCFM-MIB structure .....                            | 642 |
| Table 17-15 | IEEE8021-PBBTE-MIB structure .....                            | 644 |
| Table 17-16 | Example of ieee8021PbbTeTeSiEspTable .....                    | 646 |
| Table 17-17 | IEEE8021-TPMR-MIB structure.....                              | 647 |
| Table 17-18 | IEEE8021-FQTSS-MIB structure.....                             | 649 |
| Table 17-19 | IEEE8021-CN-MIB structure .....                               | 650 |

|             |  |      |
|-------------|--|------|
| Table 17-20 | IEEE8021-SRP-MIB structure .....   | 652  |
| Table 17-21 | IEEE8021-MVRPX-MIB structure .....   | 654  |
| Table 17-22 | IEEE8021-MIRP-MIB structure.....   | 654  |
| Table 17-23 | PFC-MIB structure .....  | 655  |
| Table 17-24 | IEEE8021-TEIPS MIB structure .....   | 655  |
| Table 17-25 | IEEE8021-SPB-MIB structure .....   | 657  |
| Table 17-26 | IEEE8021-EVB-MIB structure.....  | 662  |
| Table 17-27 | IEEE8021-ECMP-MIB structure.....   | 666  |
| Table 17-28 | IEEE8021-ST-MIB structure .....  | 667  |
| Table 17-29 | IEEE8021-Preemption-MIB structure .....  | 668  |
| Table 17-30 | IEEE8021-PSFP-MIB structure.....   | 668  |
| Table 17-31 | IEEE8021-TSN-REMOTE-MANAGEMENT-MIB structure .....   | 671  |
| Table 17-31 | PBB-TE required MIB compliances.....   | 681  |
| Table 17-32 | Sensitive managed objects: tables and notifications .....                                    | 689  |
| Table 17-33 | Sensitive managed objects: variables in dot1agCfmMdTable.....                                | 690  |
| Table 17-34 | Sensitive managed objects (of DDCFM): tables and notifications.....                          | 691  |
| Table 17-35 | Sensitive managed objects (of DDCFM) for read .....  | 691  |
| Table 17-36 | Sensitive managed objects (of EVB): tables and notifications.....                            | 698  |
| Table 17-37 | Sensitive managed objects (of EVB) for read .....  | 699  |
| Table 17-38 | Provider Bridge service interface parameters .....   | 715  |
| Table 17-39 | PBB service interface parameters .....   | 719  |
| Table 19-1  | Actions taken by MP OpCode Demultiplexers.....   | 1195 |
| Table 19-2  | SAP use for LTMs and LTRs .....  | 1202 |
| Table 20-1  | Fault Alarm defects and priorities .....   | 1207 |
| Table 20-2  | Deriving enableRmepDefect and Port Status TLV in a Bridge.....                               | 1217 |
| Table 21-1  | CFM PDU Encapsulation EtherType .....  | 1260 |
| Table 21-3  | OpCode Field range assignments .....   | 1262 |
| Table 21-2  | Common CFM Header format .....   | 1262 |
| Table 21-4  | TLV format.....  | 1263 |
| Table 21-5  | Type Field values .....  | 1264 |
| Table 21-6  | Organization-Specific TLV format.....  | 1264 |
| Table 21-7  | Sender ID TLV format.....  | 1265 |
| Table 21-8  | Port Status TLV format.....  | 1266 |
| Table 21-10 | Interface Status TLV format .....  | 1267 |
| Table 21-11 | Interface Status TLV values .....  | 1267 |
| Table 21-9  | Port Status TLV values .....   | 1267 |
| Table 21-12 | Data TLV format .....  | 1268 |
| Table 21-13 | End TLV format.....  | 1268 |
| Table 21-14 | CCM format.....  | 1269 |
| Table 21-15 | CCM Interval field encoding.....   | 1270 |
| Table 21-16 | CCM Maintenance Association Identifier field format:<br>Maintenance Domain present .....     | 1271 |
| Table 21-17 | CCM Maintenance Association Identifier field format:<br>Maintenance Domain not present ..... | 1271 |
| Table 21-19 | Short MA Name Format .....   | 1272 |
| Table 21-18 | Maintenance Domain Name Format.....  | 1272 |
| Table 21-20 | LBM and LBR formats .....  | 1273 |
| Table 21-21 | PBB-TE MIP TLV format .....  | 1274 |
| Table 21-22 | LTM format .....   | 1275 |
| Table 21-23 | LTM Flags field.....   | 1276 |
| Table 21-24 | LTM Egress Identifier TLV format.....  | 1277 |
| Table 21-25 | LTR format .....   | 1278 |
| Table 21-26 | LTR Flags field.....   | 1278 |
| Table 21-27 | Relay Action field values.....   | 1279 |

|             |  |      |
|-------------|--|------|
| Table 21-28 | LTR Egress Identifier TLV format .....   | 1279 |
| Table 21-29 | Reply Ingress TLV format .....   | 1280 |
| Table 21-30 | Ingress Action field values .....  | 1281 |
| Table 21-31 | Reply Egress TLV format .....  | 1282 |
| Table 21-32 | Egress Action field values .....   | 1282 |
| Table 22-1  | MEP creation .....   | 1295 |
| Table 22-2  | MIP creation .....   | 1296 |
| Table 22-3  | Bandwidth required for CCMs for 1 MA .....                                     | 1299 |
| Table 22-4  | Bandwidth required for CCMs for 1000 MAs .....                                 | 1300 |
| Table 23-1  | Time sequence diagram symbols .....  | 1311 |
| Table 23-2  | MSP performance parameters .....   | 1316 |
| Table 23-3  | MSP EtherType assignment .....   | 1321 |
| Table 23-4  | MSP Packet Types .....   | 1322 |
| Table 24-1  | Transmission and reception delays .....  | 1325 |
| Table 26-1  | Backbone Service Instance Group address OUI .....                              | 1348 |
| Table 26-2  | Protection Requests Hierarchy .....  | 1370 |
| Table 27-1  | Allocation of VIDs to FIDs and FIDs to MSTIDs in an SPT Region (example) ..... | 1393 |
| Table 28-1  | Bridge Priority Masking .....  | 1421 |
| Table 29-1  | RFM format .....   | 1455 |
| Table 29-2  | SFM format .....   | 1456 |
| Table 32-1  | LLDP instance selection managed object overrides .....                         | 1477 |
| Table 32-2  | CND defense mode selection managed object overrides .....                      | 1477 |
| Table 32-3  | Determining cnpdIsAdminDefMode and cnpdDefenseMode .....                       | 1483 |
| Table 32-4  | Correspondence of QCN and CCF message fields .....                             | 1485 |
| Table 32-5  | NewCpSampleBase() return value as a function of cpFb .....                     | 1488 |
| Table 33-2  | CNM Encapsulation .....  | 1500 |
| Table 33-1  | CN-TAG Encapsulation .....   | 1500 |
| Table 33-3  | Congestion Notification Message PDU .....                                      | 1501 |
| Table 34-1  | Default priority to traffic class mappings for SR classes A and B .....        | 1507 |
| Table 34-2  | Default priority to traffic class mappings for SR class B only .....           | 1508 |
| Table 35-1  | AttributeType Values .....   | 1522 |
| Table 35-2  | AttributeLength Values .....   | 1522 |
| Table 35-3  | FourPackedEvent Values .....   | 1523 |
| Table 35-4  | MSRP FirstValue NumberOfValues example .....                                   | 1524 |
| Table 35-5  | TSpec components examples .....  | 1527 |
| Table 35-6  | SR class ID .....  | 1530 |
| Table 35-7  | TLV types .....  | 1533 |
| Table 35-8  | Summary of Talker primitives .....   | 1546 |
| Table 35-9  | Summary of Listener primitives .....   | 1546 |
| Table 35-10 | Talker attribute propagation per port .....                                    | 1550 |
| Table 35-11 | Translation of Talker attributes .....   | 1551 |
| Table 35-12 | Incoming Listener attribute propagation per port .....                         | 1554 |
| Table 35-15 | Listener Declaration Type Summation .....                                      | 1555 |
| Table 35-13 | Updating Dynamic Reservation Entries .....                                     | 1555 |
| Table 35-14 | Updating operIdleSlope(N) .....  | 1555 |
| Table 35-16 | Translation of Listener attributes .....                                       | 1556 |
| Table 41-1  | VDP TLV types .....  | 1589 |
| Table 41-2  | Flag values in VDP requests .....  | 1590 |
| Table 41-3  | Error types in VDP responses .....   | 1591 |
| Table 41-4  | Flag values in VDP responses .....   | 1591 |
| Table 41-6  | Filter Info format values .....  | 1592 |
| Table 41-5  | VSIID format values .....  | 1592 |
| Table 43-1  | ECP subtypes .....   | 1615 |
| Table 44-1  | ECMP ECT-ALGORITHM values .....  | 1623 |

|             |   |      |
|-------------|---|------|
| Table 44-2  | F-TAG EtherType.....  | 1624 |
| Table 45-1  | ECT-ALGORITHM values for explicit trees .....                               | 1635 |
| Table 45-2  | Bridge Priority Masking for the LT and LTS ECT Algorithms .....             | 1636 |
| Table 45-3  | Hop sub-TLV flags .....   | 1650 |
| Table 46-1  | StreamID elements.....  | 1674 |
| Table 46-2  | StreamRank elements .....   | 1674 |
| Table 46-3  | InterfaceID elements.....   | 1675 |
| Table 46-4  | IEEE802-MacAddresses elements.....  | 1677 |
| Table 46-5  | IEEE802-VlanTag elements .....  | 1677 |
| Table 46-6  | IPv4-tuple elements .....   | 1678 |
| Table 46-7  | IPv6-tuple elements .....   | 1679 |
| Table 46-8  | TrafficSpecification elements.....  | 1680 |
| Table 46-9  | TSpecTimeAware elements.....  | 1680 |
| Table 46-10 | UserToNetworkRequirements elements.....                                     | 1682 |
| Table 46-11 | InterfaceCapabilities elements.....   | 1684 |
| Table 46-12 | StatusInfo elements.....  | 1687 |
| Table 46-13 | TalkerStatus enumeration .....  | 1687 |
| Table 46-14 | ListenerStatus enumeration.....   | 1688 |
| Table 46-15 | TSN Failure Codes.....  | 1689 |
| Table 46-16 | AccumulatedLatency elements .....   | 1690 |
| Table 48-1  | Summary of the YANG modules.....  | 1712 |
| Table 48-2  | VLAN Bridge component model YANG modules.....                               | 1713 |
| Table 48-3  | Two-Port MAC Relay (TPMR) model YANG modules .....                          | 1713 |
| Table 48-4  | Customer VLAN Bridge model YANG modules.....                                | 1713 |
| Table 48-6  | CFM model YANG modules.....   | 1714 |
| Table 48-7  | Stream filters and stream gates model YANG modules .....                    | 1714 |
| Table 48-5  | Provider Bridge model YANG modules.....                                     | 1714 |
| Table 48-8  | ATS model YANG modules.....   | 1715 |
| Table C-1   | SRP to MoCA PQoS Transaction mapping.....                                   | 1944 |
| Table C-2   | SRP TSpec to MoCA TSPEC mapping.....  | 1944 |
| Table C-3   | SRP StreamID to MoCA PQoS Flow transaction mapping .....                    | 1945 |
| Table C-4   | SRP to MLME QoS Services mapping.....                                       | 1950 |
| Table C-5   | EDCA-AC for AV Streams .....  | 1951 |
| Table C-6   | HCCA for AV Streams .....   | 1952 |
| Table D-1   | IEEE 802.1 Organizationally Specific TLVs .....                             | 1953 |
| Table D-2   | Port and protocol capability/status.....                                    | 1955 |
| Table D-3   | Priority assignment table .....   | 1959 |
| Table D-4   | Traffic class bandwidth assignment table.....                               | 1960 |
| Table D-5   | TSA Assignment Table.....   | 1960 |
| Table D-6   | PFC Enable bit vector.....  | 1963 |
| Table D-7   | Application Priority Table Entry format.....                                | 1964 |
| Table D-8   | Sel field values.....   | 1964 |
| Table D-9   | RRSAT flag values and meanings .....  | 1967 |
| Table D-10  | EVB Mode values.....  | 1968 |
| Table D-11  | NVE Role values .....   | 1969 |
| Table D-12  | Application VLAN Table Entry format.....                                    | 1971 |
| Table D-13  | Sel field values.....   | 1972 |
| Table D-14  | IEEE 802.1 extension MIB object group conformance requirements .....        | 1977 |
| Table D-15  | IEEE 802.1/LLDP extension MIB object cross reference .....                  | 1978 |
| Table E-1   | State machine symbols.....  | 2055 |
| Table I-1   | Traffic type to traffic class mapping.....                                  | 2077 |
| Table I-2   | Traffic type acronyms .....   | 2078 |
| Table I-3   | Defining traffic types.....   | 2078 |
| Table I-4   | Defining traffic types—Credit-based shaper support of SR class B only ..... | 2079 |

# ISO/IEC/IEEE 8802-1Q:2024(en)

|           |  |      |
|-----------|--|------|
| Table I-5 | Defining traffic types—Credit-based shaper support of SR classes A and B ..... | 2080 |
| Table I-6 | Priority Code Point encoding.....  | 2082 |
| Table I-7 | Priority Code Point decoding.....  | 2082 |
| Table J-1 | Provider MD Level allocation .....   | 2084 |
| Table J-2 | IEEE / ITU-T terminology differences.....                                      | 2084 |
| Table N-1 | IEEE 802.3 Interface Delays .....  | 2116 |