

ISO/IEC 30181:2024-12 (E)

Internet of Things (IoT) - Functional architecture for resource identifier interoperability

Contents	Page
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions.....	7
4 Abbreviated terms.....	9
5 IoT resource name system.....	10
5.1 Requirements for the interoperability of the resource ID in an IoT platform.....	10
5.1.1 General.....	10
5.1.2 Uniqueness.....	10
5.1.3 Equality.....	11
5.1.4 Persistency.....	11
5.1.5 Scalability.....	11
5.1.6 Security.....	11
5.2 IoT RNS architecture.....	11
5.2.1 Assumption.....	11
5.2.2 Architecture.....	12
5.2.3 Metamodel.....	14
5.2.4 Sequence and algorithms.....	15
Annex A (informative) Resource identifier format of various IoT platforms.....	18
A.1 Overview.....	18
A.2 oneM2M.....	18
A.3 GS1 OIiot.....	20
A.4 IBM Watson IoT.....	21
A.5 OCF IoTivity.....	22
A.6 FIWARE.....	22
A.7 Identification Link.....	23
Annex B (informative) Resource interoperability scenario and implementation examples between heterogeneous IoT platforms in a smart city.....	24
B.1 Overview.....	24
B.2 Resource registration and deletion.....	25
B.3 Discovery service and path conversion.....	26
B.4 Resource request.....	29
Bibliography.....	30
Figure 1 – The IoT metamodel.....	10
Figure 2 – Overview of system structure and components.....	13
Figure 3 – The IoT RNS architecture.....	14
Figure 4 – The metamodel of IoT RNS.....	15
Figure 5 – Resource registration and deletion of IoT RNS.....	16
Figure 6 – Discovery service and path conversion in the local IoT RNS.....	16

Figure A.1 – International OID tree	19
Figure A.2 – oneM2M standard object identifiers.....	19
Figure A.3 – oneM2M resource structure	20
Figure A.4 – GS1 ID key value	21
Figure A.5 – FIWARE IoT device management architecture based on IoT agents	22
Figure A.6 – Example of Identification Link with QR-Code in Identification Link frame.....	23
Figure A.7 – Example of RFID emblem with Identification Link frame	23
Figure B.1 – IoT RNS interoperability scenario in a smart city	24
Figure B.2 – Scenario-based sequence diagram that converts the resource path among heterogeneous IoT platforms	25
Figure B.3 – Resource registration example of IoT RNS	26
Figure B.4 – Resource deletion example of IoT RNS.....	26
Figure B.5 – Discovery service example of IoT RNS	27
Figure B.6 – Path conversion example in the local IoT RNS: phases 1 and 2	27
Figure B.7 – Path conversion example in the local IoT RNS: phases 3 and 4	27
Figure B.8 – Results of path conversion in each local IoT RNS	28
Figure B.9 – Resource request example of IoT RNS	29
Table A.1 – Comparison of five IoT platforms' resource ID formats	18
Table A.2 – GS1 identification key type.....	20
Table A.3 – Type of Watson IoT client ID	21
Table A.4 – Request identifier parameter	21
Table B.1 – Mapping table example of IoT RNS	28