

# ISO/IEC 30181:2024-12 (E)

## Internet of Things (IoT) - Functional architecture for resource identifier interoperability

---

<b>Contents</b>	<b>Page</b>
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	7
4 Abbreviated terms .....	9
5 IoT resource name system.....	10
5.1 Requirements for the interoperability of the resource ID in an IoT platform .....	10
5.1.1 General .....	10
5.1.2 Uniqueness .....	10
5.1.3 Equality .....	11
5.1.4 Persistency.....	11
5.1.5 Scalability.....	11
5.1.6 Security .....	11
5.2 IoT RNS architecture .....	11
5.2.1 Assumption.....	11
5.2.2 Architecture .....	12
5.2.3 Metamodel.....	14
5.2.4 Sequence and algorithms .....	15
Annex A (informative) Resource identifier format of various IoT platforms.....	18
A.1 Overview.....	18
A.2 oneM2M.....	18
A.3 GS1 OIiot.....	20
A.4 IBM Watson IoT .....	21
A.5 OCF IoTivity.....	22
A.6 FIWARE.....	22
A.7 Identification Link.....	23
Annex B (informative) Resource interoperability scenario and implementation examples between heterogeneous IoT platforms in a smart city.....	24
B.1 Overview.....	24
B.2 Resource registration and deletion.....	25
B.3 Discovery service and path conversion .....	26
B.4 Resource request.....	29
Bibliography.....	30
Figure 1 – The IoT metamodel .....	10
Figure 2 – Overview of system structure and components.....	13
Figure 3 – The IoT RNS architecture.....	14
Figure 4 – The metamodel of IoT RNS .....	15
Figure 5 – Resource registration and deletion of IoT RNS.....	16
Figure 6 – Discovery service and path conversion in the local IoT RNS .....	16

Figure A.1 – International OID tree .....	19
Figure A.2 – oneM2M standard object identifiers.....	19
Figure A.3 – oneM2M resource structure .....	20
Figure A.4 – GS1 ID key value .....	21
Figure A.5 – FIWARE IoT device management architecture based on IoT agents .....	22
Figure A.6 – Example of Identification Link with QR-Code in Identification Link frame.....	23
Figure A.7 – Example of RFID emblem with Identification Link frame .....	23
Figure B.1 – IoT RNS interoperability scenario in a smart city .....	24
Figure B.2 – Scenario-based sequence diagram that converts the resource path among heterogeneous IoT platforms .....	25
Figure B.3 – Resource registration example of IoT RNS .....	26
Figure B.4 – Resource deletion example of IoT RNS.....	26
Figure B.5 – Discovery service example of IoT RNS .....	27
Figure B.6 – Path conversion example in the local IoT RNS: phases 1 and 2 .....	27
Figure B.7 – Path conversion example in the local IoT RNS: phases 3 and 4 .....	27
Figure B.8 – Results of path conversion in each local IoT RNS .....	28
Figure B.9 – Resource request example of IoT RNS .....	29
Table A.1 – Comparison of five IoT platforms' resource ID formats .....	18
Table A.2 – GS1 identification key type.....	20
Table A.3 – Type of Watson IoT client ID .....	21
Table A.4 – Request identifier parameter .....	21
Table B.1 – Mapping table example of IoT RNS .....	28