ISO/IEC 18809:2000-12 (E)

Information technology - 8 mm wide magnetic tape cartridge for information interchange - Helical scan recording AIT-1 with MIC format

Contents

Page

Section 1 - General 1

1 Scope 1

2 Conformance 1
2.1 Magnetic tape cartridge 1
2.2 Generating drive 1
2.3 Receiving drive 1

3 Normative references 2

4 Terms and definitions 2
4.1 Absolute Frame Number (AFN) 2
4.2 a.c. erase 2
4.3 Access 2
4.4 algorithm 2
4.5 Area ID 2
4.6 Automatic Track Finding (ATF) 2
4.7 Average Signal Amplitude 2
4.8 azimuth 2
4.9 back surface 2
4.10 byte 2
4.11 cartridge 2
4.12 Channel bit 2
4.13 Codeword 2
4.14 Early Warning Point (EWP) 2
4.15 End of Data (EOD) 2
4.16 Entity 2
4.17 Error Correcting Code (ECC) 2
4.18 flux transition position 2
4.19 flux transition spacing 2
4.20 Frame 3
4.21 Housekeeping Frame 3
4.22 Logical Beginning of Tape (LBOT) 3
4.23 magnetic tape 3
4.24 Master Standard Amplitude Calibration Tape 3
4.25 Master Standard Reference Tape 3
4.26 Memory In Cartridge (MIC) 3
4.27 Partition Boundary 3
4.28 Physical Beginning of Tape (PBOT) 3
4.29 Physical End of Tape (PEOT) 3
4.30 physical recording density 3
4.31 pre-recording condition 3
4.32 processing 3
4.33 processed data 3
4.34 Processed Record 3
4.35 record 3
4.36 Reference Field 3
4.37 Secondary Standard Amplitude Calibration Tape 3
4.38 Secondary Standard Reference Tape 3
4.39 Separator Mark 3

4.40 Standard Reference Amplitude (SRA) 3
4.41 Tape Reference Edge 4
4.42 Typical Field 4
4.43 Standard Reference Current 4
4.44 Test Recording Current 4
4.45 track 4
4.46 unprocessed data 4
4.47 Unprocessed Record 4

5 Conventions and Notations 4
5.1 Representation of numbers 4
5.2 Names 4

6 Acronyms 4

7 Environment and safety 4
7.1 Test environment 4
7.2 Operating environment 5
7.3 Storage environment 5
7.4 Transportation 5
7.5 Safety 5
7.6 Flammability 5

Section 2 - Requirements for the case 6

8 Dimensional and mechanical characteristics of the case 6
8.1 General 6
8.2 Overall dimension (figures 5 and 6) 6
8.3 Holding areas 7
8.4 Cartridge insertion 7
8.5 Window (figure 1) 8
8.6 Loading grips (figures 5 and 7) 8
8.7 Label areas (figures 6 and 8) 8
8.8 Datum areas and Datum holes 8
8.9 Support areas (figure 9) 9
8.10 Recognition holes (figures 10, 11 and 12) 10
8.11 Write-inhibit hole (figure 11) 10
8.12 Pre-positioning surfaces (figures 4 and 10) 11
8.13 Cartridge lid (figures 6, 13 and 15) 11
8.14 Cartridge reel lock (figures 10 and 16) 12
8.15 Reel access holes (figure 10) 13
8.16 Interface between the reels and the drive spindles 13
8.17 Light path (figures 10, 12, 20 and 21) 14
8.18 Position of the tape in the case (figure 21) 15
8.19 Tape path zone 15
8.20 Tape access cavity (figure 10) 16
8.21 Tape access cavity clearance (figure 24) 16
8.22 Requirements for the MIC (figures 25 and 26) 16
8.23 Recognition recesses (figures 8 and 10) 17

Section 3 - Requirements for the unrecorded tape 38

9 Mechanical, physical and dimensional characteristics of the tape 38
9.1 Materials 38
9.2 Tape length 38
9.2.1 Length of the magnetic tape 38
9.2.2 Length of the leader and trailer tapes 38
9.2.3 Length of the splicing tapes 38
9.3 Tape width 38
9.3.1 Width of the magnetic, leader and trailer tapes 38
9.3.2 Width and position of the splicing tape 38
9.4 Discontinuities 39

9.5 Tape thickness 39
9.5.1 Thickness of the magnetic tape 39
9.5.2 Thickness of the leader and trailer tapes 39
9.5.3 Thickness of the splicing tape 39
9.6 Longitudinal curvature 39
9.7 Cupping 39
9.8 Coating adhesion 39
9.9 Layer-to-layer adhesion 40
9.10 Tensile strength 40
9.10.1 Breaking strength 40
9.10.2 Yield strength 40
9.11 Residual elongation 40
9.12 Electrical resistance of the recording surface 40
9.13 Tape winding 41
9.14 Light transmittance of the tape 41

10 Magnetic recording characteristics 41
10.1 Typical Field 42
10.2 Signal Amplitude 42
10.3 Resolution 42
10.4 Overwrite 42
10.5 Ease of erasure 42
10.6 Tape quality 42
10.6.1 Missing pulses 42
10.6.2 Missing pulse zone 43
10.7 Signal-to-Noise Ratio (SNR) characteristic 43

Section 4 - Requirements for an interchanged tape 43

11 Format 43
11.1 General 43
11.2 Basic Groups 43
11.2.1 Entity 44
11.2.2 Group Information Table 45
11.2.3 Block Access Table (BAT) 47
11.3 Sub-Groups 50
11.3.1 G1 Sub-Group 50
11.3.2 G2 Sub-Group - Randomizing 51
11.3.3 G3 Sub-Group 52
11.4 Data Block 53
11.4.1 ID information 54
11.4.2 Recording of the ID Information in the Data Block Headers 56

12 Method of recording 62
12.1 Physical recording density 62
12.2 Long-term average bit cell length 62
12.3 Short-term average bit cell length 62
12.4 Rate of change 62
12.5 Bit shift 63
12.6 Read signal amplitude 63
12.7 Maximum recorded levels 63

13 Track geometry 63
13.1 Track configuration 63
13.2 Average track pitch 63
13.3 Variations of the track pitch 64
13.4 Track width 64
13.5 Track angle 64
13.6 Track edge straightness 64
13.7 Track length 64
13.8 Azimuth angles 64

14 Recorded patterns 64
14.1 Recorded Data Block 64
14.2 Margin blocks 64

15 Format of a track 64
15.1 Track structure 64
15.2 Positioning accuracy 65
15.3 Tracking scheme 66

16 Layout of the tape 66
16.1 Device Area 67
16.2 Reference Area 67
16.3 Position Tolerance Band No. 1 68
16.4 System Area 68
16.4.1 System Preamble 68
16.4.2 System Log 68
16.4.3 System Postamble 72
16.4.4 Position Tolerance Band No. 2 72
16.4.5 Vendor Group Preamble 72
16.5 Data Area 72
16.5.1 Vendor Group 72
16.5.2 Recorded Data Group 72
16.5.3 ECC3 72
16.5.4 Multiple Recorded Instances 73
16.5.5 Repeated Frames 73
16.5.6 Appending and overwriting 74
16.6 EOD Area 75
16.7 Optional Device Area 75
16.8 Logical End Of Tape (LEOT) 76
16.9 Logical Beginning of Tape (LBOT) 76
16.10 Early Warning Point - EWP 76
16.11 Empty Partition 76
16.12 Initialization 76

17 Housekeeping Frames 77
17.1 Amble Frames 77
17.2 System Amble Frames 77

18 Content of the MIC 77

Annexes A - Measurement of light transmittance 79

B - Measurement of Signal-to-Noise Ratio 82

C - Method for determining the nominal and the maximum allowable recorded levels 83

D - Representation of 8-bit bytes by 10-bit patterns 84

E - Measurement of bit shift 96

F - Method of measuring the straightness of track edges 98

G - ECC calculation 99

H - Recommendations for transportation 102

J - Read-After-Write 103

K - Example of the content of a Basic Group No. 0 104

L - Examples of MIC chip 105