

ISO/IEC 18809:2000-12 (E)

Information technology - 8 mm wide magnetic tape cartridge for information interchange - Helical scan recording AIT-1 with MIC format

Contents		Page
Section 1 - General	1
1	Scope	1
2	Conformance	1
2.1	Magnetic tape cartridge	1
2.2	Generating drive	1
2.3	Receiving drive	1
3	Normative references	2
4	Terms and definitions	2
4.1	Absolute Frame Number (AFN)	2
4.2	a.c. erase	2
4.3	Access	2
4.4	algorithm	2
4.5	Area ID	2
4.6	Automatic Track Finding (ATF)	2
4.7	Average Signal Amplitude	2
4.8	azimuth	2
4.9	back surface	2
4.10	byte	2
4.11	cartridge	2
4.12	Channel bit	2
4.13	Codeword	2
4.14	Early Warning Point (EWP)	2
4.15	End of Data (EOD)	2
4.16	Entity	2
4.17	Error Correcting Code (ECC)	2
4.18	flux transition position	2
4.19	flux transition spacing	2
4.20	Frame	3
4.21	Housekeeping Frame	3
4.22	Logical Beginning of Tape (LBOT)	3
4.23	magnetic tape	3
4.24	Master Standard Amplitude Calibration Tape	3
4.25	Master Standard Reference Tape	3
4.26	Memory In Cartridge (MIC)	3
4.27	Partition Boundary	3
4.28	Physical Beginning of Tape (PBOT)	3
4.29	Physical End of Tape (PEOT)	3
4.30	physical recording density	3
4.31	pre-recording condition	3
4.32	processing	3
4.33	processed data	3
4.34	Processed Record	3
4.35	record	3
4.36	Reference Field	3
4.37	Secondary Standard Amplitude Calibration Tape	3
4.38	Secondary Standard Reference Tape	3
4.39	Separator Mark	3

4.40	Standard Reference Amplitude (SRA)	3
4.41	Tape Reference Edge	4
4.42	Typical Field	4
4.43	Standard Reference Current	4
4.44	Test Recording Current	4
4.45	track	4
4.46	unprocessed data	4
4.47	Unprocessed Record	4
5	Conventions and Notations	4
5.1	Representation of numbers	4
5.2	Names	4
6	Acronyms	4
7	Environment and safety	4
7.1	Test environment	4
7.2	Operating environment	5
7.3	Storage environment	5
7.4	Transportation	5
7.5	Safety	5
7.6	Flammability	5
Section 2 - Requirements for the case		6
8	Dimensional and mechanical characteristics of the case	6
8.1	General	6
8.2	Overall dimension (figures 5 and 6)	6
8.3	Holding areas	7
8.4	Cartridge insertion	7
8.5	Window (figure 1)	8
8.6	Loading grips (figures 5 and 7)	8
8.7	Label areas (figures 6 and 8)	8
8.8	Datum areas and Datum holes	8
8.9	Support areas (figure 9)	9
8.10	Recognition holes (figures 10, 11 and 12)	10
8.11	Write-inhibit hole (figure 11)	10
8.12	Pre-positioning surfaces (figures 4 and 10)	11
8.13	Cartridge lid (figures 6, 13 and 15)	11
8.14	Cartridge reel lock (figures 10 and 16)	12
8.15	Reel access holes (figure 10)	13
8.16	Interface between the reels and the drive spindles	13
8.17	Light path (figures 10, 12, 20 and 21)	14
8.18	Position of the tape in the case (figure 21)	15
8.19	Tape path zone	15
8.20	Tape access cavity (figure 10)	16
8.21	Tape access cavity clearance (figure 24)	16
8.22	Requirements for the MIC (figures 25 and 26)	16
8.23	Recognition recesses (figures 8 and 10)	17
Section 3 - Requirements for the unrecorded tape		38
9	Mechanical, physical and dimensional characteristics of the tape	38
9.1	Materials	38
9.2	Tape length	38
9.2.1	Length of the magnetic tape	38
9.2.2	Length of the leader and trailer tapes	38
9.2.3	Length of the splicing tapes	38
9.3	Tape width	38
9.3.1	Width of the magnetic, leader and trailer tapes	38
9.3.2	Width and position of the splicing tape	38
9.4	Discontinuities	39

9.5	Tape thickness	39
9.5.1	Thickness of the magnetic tape	39
9.5.2	Thickness of the leader and trailer tapes	39
9.5.3	Thickness of the splicing tape	39
9.6	Longitudinal curvature	39
9.7	Cupping	39
9.8	Coating adhesion	39
9.9	Layer-to-layer adhesion	40
9.10	Tensile strength	40
9.10.1	Breaking strength	40
9.10.2	Yield strength	40
9.11	Residual elongation	40
9.12	Electrical resistance of the recording surface	40
9.13	Tape winding	41
9.14	Light transmittance of the tape	41
10	Magnetic recording characteristics	41
10.1	Typical Field	42
10.2	Signal Amplitude	42
10.3	Resolution	42
10.4	Overwrite	42
10.5	Ease of erasure	42
10.6	Tape quality	42
10.6.1	Missing pulses	42
10.6.2	Missing pulse zone	43
10.7	Signal-to-Noise Ratio (SNR) characteristic	43
Section 4 - Requirements for an interchanged tape		43
11	Format	43
11.1	General	43
11.2	Basic Groups	43
11.2.1	Entity	44
11.2.2	Group Information Table	45
11.2.3	Block Access Table (BAT)	47
11.3	Sub-Groups	50
11.3.1	G1 Sub-Group	50
11.3.2	G2 Sub-Group - Randomizing	51
11.3.3	G3 Sub-Group	52
11.4	Data Block	53
11.4.1	ID information	54
11.4.2	Recording of the ID Information in the Data Block Headers	56
12	Method of recording	62
12.1	Physical recording density	62
12.2	Long-term average bit cell length	62
12.3	Short-term average bit cell length	62
12.4	Rate of change	62
12.5	Bit shift	63
12.6	Read signal amplitude	63
12.7	Maximum recorded levels	63
13	Track geometry	63
13.1	Track configuration	63
13.2	Average track pitch	63
13.3	Variations of the track pitch	64
13.4	Track width	64
13.5	Track angle	64
13.6	Track edge straightness	64
13.7	Track length	64
13.8	Azimuth angles	64

14	Recorded patterns	64
14.1	Recorded Data Block	64
14.2	Margin blocks	64
15	Format of a track	64
15.1	Track structure	64
15.2	Positioning accuracy	65
15.3	Tracking scheme	66
16	Layout of the tape	66
16.1	Device Area	67
16.2	Reference Area	67
16.3	Position Tolerance Band No. 1	68
16.4	System Area	68
16.4.1	System Preamble	68
16.4.2	System Log	68
16.4.3	System Postamble	72
16.4.4	Position Tolerance Band No. 2	72
16.4.5	Vendor Group Preamble	72
16.5	Data Area	72
16.5.1	Vendor Group	72
16.5.2	Recorded Data Group	72
16.5.3	ECC3	72
16.5.4	Multiple Recorded Instances	73
16.5.5	Repeated Frames	73
16.5.6	Appending and overwriting	74
16.6	EOD Area	75
16.7	Optional Device Area	75
16.8	Logical End Of Tape (LEOT)	76
16.9	Logical Beginning of Tape (LBOT)	76
16.10	Early Warning Point - EWP	76
16.11	Empty Partition	76
16.12	Initialization	76
17	Housekeeping Frames	77
17.1	Amble Frames	77
17.2	System Amble Frames	77
18	Content of the MIC	77
Annexes A - Measurement of light transmittance		79
B	- Measurement of Signal-to-Noise Ratio	82
C	- Method for determining the nominal and the maximum allowable recorded levels	83
D	- Representation of 8-bit bytes by 10-bit patterns	84
E	- Measurement of bit shift	96
F	- Method of measuring the straightness of track edges	98
G	- ECC calculation	99
H	- Recommendations for transportation	102
J	- Read-After-Write	103
K	- Example of the content of a Basic Group No. 0	104
L	- Examples of MIC chip	105