

# ISO/IEC 8802-3:2000-12 (E)

**Information technology – Telecommunications and information exchange between systems –  
Local and metropolitan area networks; Specific requirements – Part 3:  
Carrier sense multiple access with collision detection (CSMA/CD) access method and  
physical layer specifications**

## Contents

1.	Introduction .....	1
1.1	Overview .....	1
1.1.1	Basic concepts .....	1
1.1.2	Architectural perspectives .....	2
1.1.3	Layer interfaces .....	4
1.1.4	Application areas .....	4
1.2	Notation .....	4
1.2.1	State diagram conventions .....	4
1.2.2	Service specification method and notation .....	5
1.2.3	Physical Layer and media notation .....	6
1.2.4	Physical Layer message notation .....	7
1.3	Normative references .....	7
1.4	Definitions .....	11
1.5	Abbreviations .....	30
2.	Media Access Control (MAC) service specification .....	33
2.1	Scope and field of application .....	33
2.2	Overview of the service .....	33
2.2.1	General description of services provided by the layer .....	33
2.2.2	Model used for the service specification .....	33
2.2.3	Overview of interactions .....	34
2.2.4	Basic services and options .....	34
2.3	Detailed service specification .....	34
2.3.1	MA_DATA.request .....	34
2.3.2	MA_DATA.indication .....	35
2.3.3	MA_CONTROL.request .....	36
2.3.4	MA_CONTROL.indication .....	37
3.	Media access control frame structure .....	38
3.1	Overview .....	38
3.1.1	MAC frame format .....	38
3.2	Elements of the MAC frame .....	39
3.2.1	Preamble field .....	39
3.2.2	Start Frame Delimiter (SFD) field .....	39
3.2.3	Address fields .....	39
3.2.4	Destination Address field .....	40
3.2.5	Source Address field .....	40
3.2.6	Length/Type field .....	40
3.2.7	Data and PAD fields .....	40
3.2.8	Frame Check Sequence (FCS) field .....	41
3.2.9	Extension field .....	41
3.3	Order of bit transmission .....	41
3.4	Invalid MAC frame .....	41
3.5	Elements of the Tagged MAC Frame .....	42
3.5.1	Preamble field .....	43
3.5.2	Start Frame Delimiter (SFD) field .....	43
3.5.3	Address fields .....	43
3.5.4	Length/Type field .....	43

3.5.5	Tag Control Information field (informative) .....	43
3.5.6	MAC Client Length/Type field .....	43
3.5.7	Data and PAD fields .....	43
3.5.8	Frame Check Sequence (FCS) field .....	43
3.5.9	Extension field .....	43
4.	Media Access Control .....	44
4.1	Functional model of the MAC method .....	44
4.1.1	Overview .....	44
4.1.2	CSMA/CD operation .....	45
4.1.3	Relationships to the MAC client and Physical Layers .....	47
4.1.4	CSMA/CD access method functional capabilities .....	48
4.2	CSMA/CD Media Access Control (MAC) method: Precise specification .....	49
4.2.1	Introduction .....	49
4.2.2	Overview of the procedural model .....	49
4.2.3	Frame transmission model .....	56
4.2.4	Frame reception model .....	59
4.2.5	Preamble generation .....	61
4.2.6	Start frame sequence .....	61
4.2.7	Global declarations .....	61
4.2.8	Frame transmission .....	65
4.2.9	Frame reception .....	72
4.2.10	Common procedures .....	75
4.3	Interfaces to/from adjacent layers .....	76
4.3.1	Overview .....	76
4.3.2	Services provided by the MAC sublayer .....	76
4.3.3	Services required from the physical layer .....	77
4.4	Specific implementations .....	79
4.4.1	Compatibility overview .....	79
4.4.2	Allowable implementations .....	80
4.4.3	Configuration guidelines .....	82
5.	Layer Management .....	83
5.1	Introduction .....	83
5.1.1	Systems Management overview .....	83
5.1.2	Layer Management model .....	83
5.1.3	Packages .....	84
5.1.4	Conformance requirements .....	84
5.2	Management facilities .....	84
5.2.1	Introduction .....	84
5.2.2	DTE MAC Sublayer Management facilities .....	84
5.2.3	DTE Physical Sublayer Management facilities .....	94
5.2.4	DTE Management procedural model .....	95
6.	Physical Signaling (PLS) service specifications .....	100
6.1	Scope and field of application .....	100
6.2	Overview of the service .....	100
6.2.1	General description of services provided by the layer .....	100
6.2.2	Model used for the service specification .....	100
6.2.3	Overview of interactions .....	100
6.2.4	Basic services and options .....	101

6.3	Detailed service specification .....	101
6.3.1	Peer-to-peer service primitives .....	101
6.3.2	Sublayer-to-sublayer service primitives .....	102
7.	Physical Signaling (PLS) and Attachment Unit Interface (AUI) specifications.....	104
7.1	Scope.....	104
7.1.1	Definitions .....	104
7.1.2	Summary of major concepts .....	104
7.1.3	Application .....	105
7.1.4	Modes of operation .....	105
7.1.5	Allocation of function .....	105
7.2	Functional specification .....	105
7.2.1	PLS-PMA (DTE-MAU) Interface protocol .....	105
7.2.2	PLS interface to MAC and management entities .....	112
7.2.3	Frame structure .....	114
7.2.4	PLS functions.....	115
7.3	Signal characteristics .....	118
7.3.1	Signal encoding .....	118
7.3.2	Signaling rate .....	123
7.3.3	Signaling levels.....	123
7.4	Electrical characteristics .....	123
7.4.1	Driver characteristics .....	123
7.4.2	Receiver characteristics .....	126
7.4.3	AUI cable characteristics .....	128
7.5	Functional description of interchange circuits.....	130
7.5.1	General.....	130
7.5.2	Definition of interchange circuits .....	130
7.6	Mechanical characteristics.....	132
7.6.1	Definition of mechanical interface .....	132
7.6.2	Line interface connector .....	132
7.6.3	Contact assignments .....	133
8.	Medium Attachment Unit and baseband medium specifications, type 10BASE5 .....	136
8.1	Scope.....	136
8.1.1	Overview.....	136
8.1.2	Definitions .....	137
8.1.3	Application perspective: MAU and MEDIUM objectives .....	137
8.2	MAU functional specifications .....	138
8.2.1	MAU Physical Layer functions .....	138
8.2.2	MAU interface messages .....	141
8.2.3	MAU state diagrams .....	142
8.3	MAU-medium electrical characteristics .....	143
8.3.1	MAU-to-coaxial cable interface .....	143
8.3.2	MAU electrical characteristics .....	149
8.3.3	MAU-DTE electrical characteristics .....	149
8.3.4	MAU-DTE mechanical connection .....	149
8.4	Characteristics of the coaxial cable .....	150
8.4.1	Coaxial cable electrical parameters .....	150
8.4.2	Coaxial cable properties .....	151
8.4.3	Total segment dc loop resistance .....	152
8.5	Coaxial trunk cable connectors.....	153
8.5.1	Inline coaxial extension connector .....	153

8.5.2	Coaxial cable terminator .....	153
8.5.3	MAU-to-coaxial cable connection .....	153
8.6	System considerations .....	156
8.6.1	Transmission system model .....	156
8.6.2	Transmission system requirements .....	156
8.6.3	Labeling .....	157
8.7	Environmental specifications .....	157
8.7.1	General safety requirements .....	157
8.7.2	Network safety requirements .....	158
8.7.3	Electromagnetic environment .....	159
8.7.4	Temperature and humidity .....	160
8.7.5	Regulatory requirements .....	160
8.8	Protocol Implementation Conformance Statement (PICS) proforma for Clause 8, Medium Attachment Unit and baseband medium specifications, type 10BASE5 .....	161
8.8.1	Overview .....	161
8.8.2	Abbreviations and special symbols .....	161
8.8.3	Instructions for completing the PICS proforma .....	161
8.8.4	Identification .....	163
8.8.5	Global statement of conformance .....	163
8.8.6	PICS proforma tables for MAU .....	164
8.8.7	PICS proforma tables for MAU AUI characteristics .....	171
8.8.8	PICS proforma tables for 10BASE5 coaxial cable .....	174
9.	Repeater unit for 10 Mb/s baseband networks .....	176
9.1	Overview .....	176
9.2	References .....	177
9.3	Definitions .....	177
9.4	Compatibility interface .....	177
9.4.1	AUI compatibility .....	177
9.4.2	Mixing segment compatibility .....	177
9.4.3	Link segment compatibility .....	178
9.5	Basic functions .....	178
9.5.1	Repeater set network properties .....	178
9.5.2	Signal amplification .....	178
9.5.3	Signal symmetry .....	178
9.5.4	Signal retiming .....	179
9.5.5	Data handling .....	179
9.5.6	Collision handling .....	180
9.5.7	Electrical isolation .....	181
9.6	Detailed repeater functions and state diagrams .....	182
9.6.1	State diagram notation .....	182
9.6.2	Data and collision handling .....	185
9.6.3	Preamble regeneration .....	185
9.6.4	Fragment extension .....	185
9.6.5	MAU Jabber Lockup Protection .....	186
9.6.6	Auto-Partitioning/Reconnection (optional) .....	186
9.7	Electrical isolation .....	189
9.7.1	Environment A requirements .....	189
9.7.2	Environment B requirements .....	189
9.8	Reliability .....	189
9.9	Medium attachment unit and baseband medium specification for a vendor-independent FOIRL .....	190
9.9.1	Scope .....	190

9.9.2	FOMAU functional specifications .....	192
9.9.3	FOMAU electrical characteristics .....	198
9.9.4	FOMAU/Optical medium interface .....	199
9.9.5	Characteristics of the optical fiber cable link segment .....	202
9.9.6	System requirements .....	203
9.9.7	Environmental specifications.....	205
10.	Medium attachment unit and baseband medium specifications, type 10BASE2 .....	207
10.1	Scope.....	207
10.1.1	Overview.....	207
10.1.2	Definitions .....	208
10.1.3	Application perspective: MAU and medium objectives.....	208
10.2	References.....	209
10.3	MAU functional specifications .....	209
10.3.1	MAU Physical Layer functional requirements .....	210
10.3.2	MAU interface messages .....	212
10.3.3	MAU state diagrams .....	214
10.4	MAU–medium electrical characteristics .....	215
10.4.1	MAU-to-coaxial cable interface .....	215
10.4.2	MAU electrical characteristics .....	217
10.4.3	MAU–DTE electrical characteristics .....	218
10.5	Characteristics of coaxial cable system .....	218
10.5.1	Coaxial cable electrical parameters .....	218
10.5.2	Coaxial cable physical parameters.....	219
10.5.3	Total segment dc loop resistance .....	220
10.6	Coaxial trunk cable connectors .....	221
10.6.1	In-line coaxial extension connector .....	221
10.6.2	Coaxial cable terminator.....	222
10.6.3	MAU-to-coaxial cable connection.....	222
10.7	System considerations .....	222
10.7.1	Transmission system model.....	222
10.7.2	Transmission system requirements .....	224
10.8	Environmental specifications.....	225
10.8.1	Safety requirements .....	225
10.8.2	Electromagnetic environment .....	225
10.8.3	Regulatory requirements .....	225
11.	Broadband medium attachment unit and broadband medium specifications, type 10BROAD36 ..	226
11.1	Scope.....	226
11.1.1	Overview.....	226
11.1.2	Definitions .....	228
11.1.3	MAU and medium objectives .....	228
11.1.4	Compatibility considerations .....	228
11.1.5	Relationship to PLS and AUI .....	229
11.1.6	Mode of operation.....	229
11.2	MAU functional specifications .....	229
11.2.1	MAU functional requirements .....	229
11.2.2	DTE PLS to MAU and MAU to DTE PLS messages .....	232
11.2.3	MAU state diagrams .....	233
11.3	MAU characteristics .....	236
11.3.1	MAU-to-coaxial cable interface .....	236
11.3.2	MAU frequency allocations.....	241

11.3.3	AUI electrical characteristics .....	242
11.3.4	MAU transfer characteristics .....	243
11.3.5	Reliability .....	249
11.4	System considerations .....	250
11.4.1	Delay budget and network diameter .....	250
11.4.2	MAU operation with packets shorter than 512 bits .....	250
11.5	Characteristics of the coaxial cable system .....	251
11.5.1	Electrical requirements .....	251
11.5.2	Mechanical requirements .....	251
11.5.3	Delay requirements .....	251
11.6	Frequency translator requirements for the single-cable version .....	252
11.6.1	Electrical requirements .....	252
11.6.2	Mechanical requirements .....	252
11.7	Environmental specifications .....	252
11.7.1	Safety requirements .....	252
11.7.2	Electromagnetic environment .....	253
11.7.3	Temperature and humidity .....	253
12.	Physical signaling, medium attachment, and baseband medium specifications, type 1BASE5 .....	254
12.1	Introduction.....	254
12.1.1	Overview.....	254
12.1.2	Scope.....	254
12.1.3	Definitions .....	255
12.1.4	General characteristics .....	255
12.1.5	Compatibility .....	255
12.1.6	Objectives of type 1BASE5 specification .....	255
12.2	Architecture .....	255
12.2.1	Major concepts.....	255
12.2.2	Application perspective .....	257
12.2.3	Packet structure.....	257
12.3	DTE physical signaling (PLS) specification.....	258
12.3.1	Overview.....	258
12.3.2	Functional specification.....	259
12.4	Hub specification .....	266
12.4.1	Overview.....	266
12.4.2	Hub structure .....	267
12.4.3	Hub PLS functional specification .....	268
12.5	Physical medium attachment (PMA) specification .....	273
12.5.1	Overview.....	273
12.5.2	PLS-PMA interface .....	273
12.5.3	Signal characteristics .....	274
12.6	Medium Dependent Interface (MDI) specification .....	281
12.6.1	Line interface connector .....	281
12.6.2	Connector contact assignments.....	282
12.6.3	Labeling .....	282
12.7	Cable medium characteristics .....	283
12.7.1	Overview.....	283
12.7.2	Transmission parameters .....	283
12.7.3	Coupling parameters .....	284
12.7.4	Noise environment.....	285
12.8	Special link specification .....	286
12.8.1	Overview.....	286

12.8.2	Transmission characteristics .....	286
12.8.3	Permitted configurations.....	286
12.9	Timing.....	286
12.9.1	Overview.....	286
12.9.2	DTE timing .....	287
12.9.3	Medium timing .....	287
12.9.4	Special link timing.....	287
12.9.5	Hub timing .....	287
12.10	Safety .....	288
12.10.1	Isolation .....	288
12.10.2	Telephony voltages.....	289
13.	System considerations for multisegment 10 Mb/s baseband networks .....	290
13.1	Overview.....	290
13.1.1	Repeater usage .....	291
13.2	Definitions .....	291
13.3	Transmission System Model 1.....	291
13.4	Transmission System Model 2.....	296
13.4.1	Round-trip collision delay .....	296
13.4.2	Interpacket gap (IPG) shrinkage .....	297
13.5	Full duplex topology limitations.....	298
14.	Twisted-pair medium attachment unit (MAU) and baseband medium, type 10BASE-T .....	299
14.1	Scope.....	299
14.1.1	Overview.....	299
14.1.2	Definitions .....	300
14.1.3	Application perspective .....	300
14.1.4	Relationship to PLS and AUI .....	302
14.2	MAU functional specifications .....	302
14.2.1	MAU functions .....	303
14.2.2	PMA interface messages.....	307
14.2.3	MAU state diagrams .....	308
14.3	MAU electrical specifications .....	313
14.3.1	MAU-to-MDI interface characteristics.....	313
14.3.2	MAU-to-AUI specification.....	322
14.4	Characteristics of the simplex link segment .....	322
14.4.1	Overview.....	323
14.4.2	Transmission parameters .....	323
14.4.3	Coupling parameters .....	324
14.4.4	Noise environment .....	324
14.5	MDI specification .....	325
14.5.1	MDI connectors .....	325
14.5.2	Crossover function.....	325
14.6	System considerations .....	326
14.7	Environmental specifications.....	326
14.7.1	General safety .....	326
14.7.2	Network safety .....	326
14.7.3	Environment .....	328
14.8	MAU labeling .....	329
14.9	Timing summary.....	330

14.10	Protocol Implementation Conformance Statement (PICS) proforma for Clause 14, Twisted-pair medium attachment unit (MAU) and baseband medium, type 10BASE-T .....	331
14.10.1	Introduction.....	331
14.10.2	Identification of implementation .....	332
14.10.3	Identification of the protocol .....	332
14.10.4	PICS proforma for 10BASE-T .....	333
15.	Fiber optic medium and common elements of medium attachment units and star, type 10BASE-F .....	349
15.1	Scope.....	349
15.1.1	Overview.....	349
15.1.2	Definitions .....	350
15.1.3	Applications perspective: MAUs, stars, and fiber optic medium .....	350
15.2	MDI optical characteristics.....	354
15.2.1	Transmit optical parameters .....	354
15.2.2	Receive optical parameters .....	361
15.3	Characteristics of the fiber optic medium.....	362
15.3.1	Optical fiber and cable .....	362
15.3.2	Optical medium connector plug and socket.....	363
15.3.3	Fiber optic medium insertion loss.....	364
15.3.4	Electrical isolation .....	364
15.4	MAU reliability .....	365
15.5	MAU-AUI specification .....	365
15.5.1	MAU-AUI electrical characteristics .....	365
15.5.2	MAU-AUI mechanical connections.....	365
15.5.3	Power consumption .....	365
15.5.4	MAU-AUI messages .....	365
15.6	Environmental specifications.....	366
15.6.1	Safety requirements .....	366
15.6.2	Electromagnetic environment .....	367
15.6.3	Other environmental requirements .....	367
15.7	MAU labeling .....	367
15.7.1	10BASE-FP star labeling .....	367
15.8	Protocol implementation conformance statement (PICS) proforma for Clause 15, Fiber optic medium and common elements of medium attachment units and star, type 10BASE-F .....	368
15.8.1	Introduction.....	368
15.8.2	Abbreviations and special symbols .....	368
15.8.3	Instructions for completing the pics proforma.....	368
15.8.4	Identification.....	371
15.8.5	Major capabilities/options .....	372
15.8.6	PICS Proforma for the fiber optic medium.....	372
16.	Fiber optic passive star and medium attachment unit, type 10BASE-FP .....	374
16.1	Scope.....	374
16.1.1	Overview.....	374
16.2	PMA interface messages.....	375
16.2.1	PMA-to-MDI interface signal encodings .....	375
16.2.2	PMA-to-MDI OTD messages .....	375
16.2.3	MDI ORD-to-PMA messages.....	376
16.3	10BASE-FP MAU functional specifications.....	377
16.3.1	Transmit function requirements.....	377

16.3.2	Receive function requirements .....	379
16.3.3	Loopback function requirements .....	380
16.3.4	Collision presence function requirements .....	380
16.3.5	signal_quality_error Message (SQE) Test function requirements.....	381
16.3.6	Jabber function requirements .....	381
16.3.7	Link fault detection and low light function requirements .....	382
16.3.8	Interface message time references .....	383
16.3.9	MAU state diagram.....	383
16.4	Timing summary.....	391
16.5	10BASE-FP Star functional specifications.....	391
16.5.1	Star functions .....	391
16.5.2	Star optical characteristics .....	392
16.6	Protocol Implementation Conformance Statement (PICS) proforma for Clause 16, Fiber optic passive star and medium attachment unit, type 10BASE-FP .....	393
16.6.1	Introduction.....	393
16.6.2	Abbreviations and special symbols .....	393
16.6.3	Instructions for completing the PICS proforma.....	393
16.6.4	Identification.....	395
16.6.5	Major capabilities/options .....	396
16.6.6	PICS proforma for the type 10BASE-FP MAU .....	396
16.6.7	PICS proforma tables for 10BASE-FP stars.....	408
17.	Fiber optic medium attachment unit, type 10BASE-FB .....	410
17.1	Scope.....	410
17.1.1	Overview.....	410
17.1.2	Relationship to AUI .....	410
17.2	PMA interface messages.....	411
17.2.1	PMA-to-MDI interface signal encodings .....	411
17.2.2	PMA-to-MDI OTD messages .....	411
17.2.3	MDI ORD-to-PMA messages.....	412
17.2.4	Transitions between signals .....	413
17.2.5	Signaling rate .....	413
17.3	MAU functional specifications .....	413
17.3.1	Transmit function requirements.....	413
17.3.2	Receive function requirements .....	414
17.3.3	Collision function requirements .....	414
17.3.4	Loopback function requirements .....	415
17.3.5	Fault-handling function requirements.....	415
17.3.6	Jabber function requirements .....	415
17.3.7	Low light level detection function requirements .....	416
17.3.8	Synchronous qualification function requirements .....	416
17.3.9	Interface message time references .....	416
17.3.10	MAU state diagrams .....	417
17.4	Timing summary.....	421
17.5	Protocol implementation conformance statement (PICS) proforma for Clause 17, Fiber optic medium attachment unit, type 10BASE-FB .....	422
17.5.1	Introduction.....	422
17.5.2	Abbreviations and special symbols .....	422
17.5.3	Instructions for completing the PICS proforma.....	422
17.5.4	Identification.....	424
17.5.5	PICS proforma for the type 10BASE-FB MAU.....	425
17.5.6	PICS proforma for the type 10BASE-FB MAU.....	425

18.	Fiber optic medium attachment unit, type 10BASE-FL .....	436
18.1	Scope.....	436
18.1.1	Overview.....	436
18.2	PMA interface messages.....	436
18.2.1	PMA to fiber optic link segment messages .....	437
18.2.2	Fiber optic link segment to PMA messages .....	437
18.2.3	Interface message time references .....	438
18.3	MAU functional specifications .....	438
18.3.1	MAU functions .....	438
18.3.2	MAU state diagrams .....	442
18.4	Timing summary.....	449
18.5	Protocol implementation conformance statement (PICS) proforma for Clause 18, Fiber optic medium attachment unit, type 10BASE-FL .....	450
18.5.1	Introduction.....	450
18.5.2	Abbreviations and special symbols .....	450
18.5.3	Instructions for completing the PICS proforma.....	451
18.5.4	Identification .....	452
18.5.5	Major capabilities/options .....	453
18.5.6	PICS proforma tables for the type 10BASE-FL MAU .....	453
19.	Layer Management for 10 Mb/s baseband repeaters .....	465
19.1	Introduction.....	465
19.1.1	Scope.....	465
19.1.2	Relationship to objects in IEEE Std 802.1F-1993 .....	465
19.1.3	Definitions .....	465
19.1.4	Symbols and abbreviations .....	465
19.1.5	Management model .....	466
19.2	Managed objects .....	467
19.2.1	Introduction.....	467
19.2.2	Overview of managed objects .....	467
19.2.3	Repeater managed object class .....	472
19.2.4	ResourceTypeID Managed Object Class .....	475
19.2.5	Group managed object class .....	475
19.2.6	Port managed object class.....	476
20.	Layer Management for 10 Mb/s baseband medium attachment units .....	482
20.1	Introduction.....	482
20.1.1	Scope.....	482
20.1.2	Management model .....	482
20.2	Managed objects .....	482
20.2.1	Text description of managed objects .....	482
20.2.2	MAU Managed object class.....	484
21.	Introduction to 100 Mb/s baseband networks, type 100BASE-T .....	488
21.1	Overview.....	488
21.1.1	Reconciliation Sublayer (RS) and Media Independent Interface (MII) .....	489
21.1.2	Physical Layer signaling systems .....	489
21.1.3	Repeater .....	489
21.1.4	Auto-Negotiation .....	489
21.1.5	Management .....	489

21.2	References.....	489
21.3	Definitions .....	489
21.4	Abbreviations.....	489
21.5	State diagrams.....	490
21.5.1	Actions inside state blocks.....	490
21.5.2	State diagram variables .....	490
21.5.3	State transitions.....	490
21.5.4	Operators.....	490
21.6	Protocol Implementation Conformance Statement (PICS) proforma.....	491
21.6.1	Introduction.....	491
21.6.2	Abbreviations and special symbols .....	491
21.6.3	Instructions for completing the PICS proforma.....	492
21.6.4	Additional information .....	492
21.6.5	Exceptional information .....	493
21.6.6	Conditional items .....	493
21.7	Relation of 100BASE-T to other standards .....	493
21.8	MAC delay constraints (exposed MII) .....	495
22.	Reconciliation Sublayer (RS) and Media Independent Interface (MII).....	496
22.1	Overview.....	496
22.1.1	Summary of major concepts .....	497
22.1.2	Application .....	497
22.1.3	Rates of operation .....	498
22.1.4	Allocation of functions .....	498
22.1.5	Relationship of MII and GMII.....	498
22.2	Functional specifications .....	498
22.2.1	Mapping of MII signals to PLS service primitives and Station Management.....	498
22.2.2	MII signal functional specifications .....	502
22.2.3	Frame structure .....	508
22.2.4	Management functions.....	511
22.3	Signal timing characteristics .....	523
22.3.1	Signals that are synchronous to TX_CLK .....	523
22.3.2	Signals that are synchronous to RX_CLK .....	524
22.3.3	Signals that have no required clock relationship .....	524
22.3.4	MDIO timing relationship to MDC .....	524
22.4	Electrical characteristics .....	525
22.4.1	Signal levels .....	525
22.4.2	Signal paths.....	526
22.4.3	Driver characteristics .....	526
22.4.4	Receiver characteristics .....	527
22.4.5	Cable characteristics .....	528
22.4.6	Hot insertion and removal .....	529
22.5	Power supply .....	529
22.5.1	Supply voltage .....	529
22.5.2	Load current .....	530
22.5.3	Short-circuit protection .....	530
22.6	Mechanical characteristics .....	530
22.6.1	Definition of mechanical interface .....	530
22.6.2	Shielding effectiveness and transfer impedance .....	530
22.6.3	Connector pin numbering .....	531
22.6.4	Clearance dimensions .....	531
22.6.5	Contact assignments .....	532

22.7	Protocol Implementation Conformance Statement (PICS) proforma for Clause 22, Reconciliation Sublayer (RS) and Media Independent Interface (MII) .....	533
22.7.1	Introduction.....	533
22.7.2	Identification.....	533
22.7.3	PICS proforma tables for reconciliation sublayer and media independent interface .....	535
23.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 100BASE-T4.....	544
23.1	Overview.....	544
23.1.1	Scope.....	544
23.1.2	Objectives .....	544
23.1.3	Relation of 100BASE-T4 to other standards .....	544
23.1.4	Summary .....	544
23.1.5	Application of 100BASE-T4 .....	547
23.2	PCS functional specifications .....	548
23.2.1	PCS functions .....	548
23.2.2	PCS interfaces.....	553
23.2.3	Frame structure .....	553
23.2.4	PCS state diagrams .....	554
23.2.5	PCS electrical specifications.....	562
23.3	PMA service interface .....	562
23.3.1	PMA_TYPE.indicate .....	563
23.3.2	PMA_UNITDATA.request .....	563
23.3.3	PMA_UNITDATA.indicate .....	564
23.3.4	PMA_CARRIER.indicate .....	565
23.3.5	PMA_LINK.indicate .....	565
23.3.6	PMA_LINK.request.....	566
23.3.7	PMA_RXERROR.indicate .....	567
23.4	PMA functional specifications .....	567
23.4.1	PMA functions .....	567
23.4.2	PMA interface messages.....	571
23.4.3	PMA state diagrams.....	572
23.5	PMA electrical specifications .....	575
23.5.1	PMA-to-MDI interface characteristics .....	575
23.5.2	Power consumption .....	587
23.6	Link segment characteristics.....	588
23.6.1	Cabling.....	588
23.6.2	Link transmission parameters .....	588
23.6.3	Noise .....	590
23.6.4	Installation practice.....	591
23.7	MDI specification .....	592
23.7.1	MDI connectors .....	592
23.7.2	Crossover function.....	593
23.8	System considerations .....	593
23.9	Environmental specifications.....	593
23.9.1	General safety .....	593
23.9.2	Network safety .....	593
23.9.3	Environment .....	595
23.10	PHY labeling .....	595
23.11	Timing summary.....	596
23.11.1	Timing references .....	596
23.11.2	Definitions of controlled parameters .....	597

23.11.3	Table of required timing values .....	599
23.12	Protocol Implementation Conformance Statement (PICS) proforma for Clause 23, Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, type 100BASE-T4.....	606
23.12.1	Introduction.....	606
23.12.2	Identification.....	606
23.12.3	Major capabilities/options .....	607
23.12.4	PICS proforma tables for the Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 100BASE-T4 .....	607
24.	Physical Coding Sublayer (PCS) and Physical Medium Attachment (PMA) sublayer, type 100BASE-X .....	620
24.1	Overview.....	620
24.1.1	Scope.....	620
24.1.2	Objectives .....	620
24.1.3	Relationship of 100BASE-X to other standards .....	620
24.1.4	Summary of 100BASE-X sublayers .....	621
24.1.5	Inter-sublayer interfaces .....	622
24.1.6	Functional block diagram .....	622
24.1.7	State diagram conventions .....	622
24.2	Physical Coding Sublayer (PCS) .....	625
24.2.1	Service Interface (MII) .....	625
24.2.2	Functional requirements .....	625
24.2.3	State variables .....	630
24.2.4	State diagrams .....	632
24.3	Physical Medium Attachment (PMA) sublayer.....	636
24.3.1	Service interface .....	636
24.3.2	Functional requirements .....	641
24.3.3	State variables .....	642
24.3.4	Process specifications and state diagrams .....	644
24.4	Physical Medium Dependent (PMD) sublayer service interface.....	647
24.4.1	PMD service interface .....	647
24.4.2	Medium Dependent Interface (MDI) .....	650
24.5	Compatibility considerations .....	650
24.6	Delay constraints .....	651
24.6.1	PHY delay constraints (exposed MII) .....	651
24.6.2	DTE delay constraints (unexposed MII).....	652
24.6.3	Carrier de-assertion/assertion constraint (half duplex mode only).....	652
24.7	Environmental specifications.....	652
24.8	Protocol Implementation Conformance Statement (PICS) proforma for Clause 24, Physical Coding Sublayer (PCS) and Physical Medium Attachment (PMA) sublayer, type 100BASE-X .....	653
24.8.1	Introduction.....	653
24.8.2	Identification .....	653
24.8.3	PICS proforma tables for the Physical Coding Sublayer (PCS) and Physical Medium Attachment (PMA) sublayer, type 100BASE-X .....	654
25.	Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-TX.....	656
25.1	Overview.....	656
25.2	Functional specifications .....	656
25.3	General exceptions.....	656
25.4	Specific requirements and exceptions .....	657

25.4.1	Change to 7.2.3.1.1, "Line state patterns" .....	657
25.4.2	Change to 7.2.3.3, "Loss of synchronization" .....	657
25.4.3	Change to Table 8-1, "Contact assignments for unshielded twisted pair" .....	657
25.4.4	Deletion of 8.3, "Station labelling" .....	657
25.4.5	Change to 9.1.9, "Jitter" .....	658
25.4.6	Replacement of 11.2, "Crossover function" .....	658
25.4.7	Change to A.2, "DDJ test pattern for baseline wander measurements" .....	658
25.4.8	Change to annex G, "Stream cipher scrambling function".....	658
25.4.9	Change to annex I, "Common mode cable termination" .....	658
25.5	Protocol Implementation Conformance Statement (PICS) proforma for Clause 25, Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-TX .....	659
25.5.1	Introduction.....	659
25.5.2	Identification .....	659
25.5.3	Major capabilities/options .....	660
25.5.4	PICS proforma tables for the Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-TX.....	660
26.	Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-FX .....	661
26.1	Overview.....	661
26.2	Functional specifications .....	661
26.3	General exceptions.....	661
26.4	Specific requirements and exceptions .....	662
26.4.1	Medium Dependent Interface (MDI) .....	662
26.4.2	Crossover function .....	662
26.5	Protocol Implementation Conformance Statement (PICS) proforma for Clause 26, Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-FX .....	663
26.5.1	Introduction.....	663
26.5.2	Identification .....	663
26.5.3	Protocol summary .....	663
26.5.4	Major capabilities/options .....	664
26.5.5	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and baseband medium, type 100BASE-FX.....	664
27.	Repeater for 100 Mb/s baseband networks .....	665
27.1	Overview.....	665
27.1.1	Scope.....	665
27.1.2	Application perspective .....	666
27.1.3	Relationship to PHY .....	667
27.2	PMA interface messages.....	667
27.3	Repeater functional specifications .....	667
27.3.1	Repeater functions .....	668
27.3.2	Detailed repeater functions and state diagrams .....	672
27.4	Repeater electrical specifications .....	686
27.4.1	Electrical isolation .....	686
27.5	Environmental specifications.....	686
27.5.1	General safety .....	686
27.5.2	Network safety .....	686
27.5.3	Electrical isolation .....	687
27.5.4	Reliability .....	687
27.5.5	Environment .....	688
27.6	Repeater labeling .....	688

27.7	Protocol Implementation Conformance Statement (PICS) proforma for Clause 27, Repeater for 100 Mb/s baseband networks.....	689
27.7.1	Introduction.....	689
27.7.2	Identification.....	689
27.7.3	Major capabilities/options .....	690
27.7.4	PICS proforma tables for the repeater for 100 Mb/s baseband networks .....	690
28.	Physical Layer link signaling for 10 Mb/s, 100 Mb/s, and 1000 Mb/s Auto-Negotiation on twisted pair.....	698
28.1	Overview.....	698
28.1.1	Scope.....	698
28.1.2	Application perspective/objectives .....	699
28.1.3	Relationship to ISO/IEC 8802-3.....	699
28.1.4	Compatibility considerations .....	700
28.2	Functional specifications .....	701
28.2.1	Transmit function requirements.....	702
28.2.2	Receive function requirements .....	705
28.2.3	Arbitration function requirements .....	707
28.2.4	Management function requirements .....	711
28.2.5	Absence of management function .....	717
28.2.6	Technology-Dependent Interface .....	717
28.3	State diagrams and variable definitions .....	719
28.3.1	State diagram variables .....	720
28.3.2	State diagram timers .....	724
28.3.3	State diagram counters.....	726
28.3.4	State diagrams.....	727
28.4	Electrical specifications .....	730
28.5	Protocol Implementation Conformance Statement (PICS) proforma for Clause 28, Physical Layer link signaling for 10 Mb/s, 100 Mb/s, and 1000 Mb/s Auto-Negotiation on twisted pair .....	731
28.5.1	Introduction.....	731
28.5.2	Identification .....	731
28.5.3	Major capabilities/options .....	732
28.5.4	PICS proforma tables for Physical Layer link signaling for 10 Mb/s, 100 Mb/s, and 1000 Mb/s Auto-Negotiation on twisted pair .....	732
28.6	Auto-Negotiation expansion .....	744
29.	System considerations for multisegment 100BASE-T networks.....	745
29.1	Overview.....	745
29.1.1	Single collision domain multisegment networks .....	746
29.1.2	Repeater usage .....	747
29.2	Transmission System Model 1 .....	747
29.3	Transmission System Model 2 .....	747
29.3.1	Round-trip collision delay .....	749
29.4	Full duplex 100 Mb/s topology limitations .....	752
30.	10 Mb/s, 100 Mb/s, 1000 Mb/s, MAC Control, and Link Aggregation Management.....	753
30.1	Overview.....	753
30.1.1	Scope.....	754
30.1.2	Relationship to objects in IEEE 802.1F.....	754

30.1.3	Systems management overview .....	754
30.1.4	Management model .....	755
30.2	Managed objects .....	756
30.2.1	Introduction.....	756
30.2.2	Overview of managed objects .....	756
30.2.3	Containment.....	761
30.2.4	Naming .....	761
30.2.5	Capabilities .....	762
30.3	Layer management for DTEs.....	772
30.3.1	MAC entity managed object class .....	772
30.3.2	PHY devicePHY device managed object class .....	781
30.3.3	MAC control entity object class .....	783
30.3.4	PAUSE entity managed object class.....	784
30.4	Layer management for 10, 100, and 1000 Mb/s baseband repeaters.....	785
30.4.1	Repeater managed object class .....	785
30.4.2	Group managed object class .....	789
30.4.3	Repeater port managed object class.....	790
30.5	Layer management for 10, 100, and 1000 Mb/s medium attachment units (MAUs) .....	796
30.5.1	MAU managed object class .....	796
30.6	Management for link Auto-Negotiation .....	801
30.6.1	Auto-Negotiation managed object class .....	801
30.7	Management for Link Aggregation .....	804
30.7.1	Aggregator managed object class .....	804
30.7.2	Aggregation Port managed object class.....	815
30.7.3	Aggregation Port Statistics managed object class .....	822
30.7.4	Aggregation Port Debug Information managed object class .....	824
31.	MAC Control .....	829
31.1	Overview.....	829
31.2	Layer architecture .....	829
31.3	Support by interlayer interfaces.....	829
31.4	MAC Control frames .....	831
31.4.1	MAC Control frame format .....	831
31.5	Opcode-independent MAC Control sublayer operation .....	832
31.5.1	Frame parsing and data frame reception.....	832
31.5.2	Control frame reception .....	833
31.5.3	Opcode-independent MAC Control receive state diagram .....	833
31.6	Compatibility requirements .....	834
31.7	MAC Control client behavior .....	834
31.8	Protocol Implementation Conformance Statement (PICS) proforma for Clause 31, MAC Control .....	835
31.8.1	Introduction.....	835
31.8.2	Identification .....	835
31.8.3	PICS proforma for MAC Control frames .....	836
32.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 100BASE-T2.....	837
32.1	Overview.....	837
32.1.1	Relation of 100BASE-T2 to other standards .....	837
32.1.2	Operation of 100BASE-T2 .....	839
32.1.3	Application of 100BASE-T2 .....	842
32.1.4	State diagram conventions .....	842

32.2	PHY Control functional specifications and service interface .....	842
32.2.1	PHY Control function .....	842
32.2.2	PHY Control Service interface .....	843
32.2.3	State diagram variables .....	845
32.2.4	State diagram timers .....	846
32.2.5	PHY Control state diagram.....	846
32.3	PCS functional specifications .....	847
32.3.1	PCS functions .....	848
32.3.2	PCS interfaces.....	854
32.3.3	Frame structure .....	855
32.3.4	State variables .....	855
32.3.5	State diagrams.....	857
32.3.6	PCS electrical specifications.....	858
32.4	PMA functional specifications and service interface .....	861
32.4.1	PMA functional specifications .....	861
32.4.2	PMA service interface .....	865
32.5	Management functions.....	868
32.5.1	100BASE-T2 Use of Auto-Negotiation and MII Registers 8, 9, and 10 .....	868
32.5.2	Management functions.....	869
32.5.3	PHY specific registers for 100BASE-T2 .....	870
32.5.4	Changes and additions to Auto-Negotiation (Clause 28) .....	873
32.6	PMA electrical specifications .....	876
32.6.1	PMA-to-MDI interface characteristics .....	876
32.6.2	Power consumption .....	899
32.7	Link segment characteristics.....	900
32.7.1	Cabling .....	900
32.7.2	Link transmission parameters .....	900
32.7.3	Noise .....	903
32.7.4	Installation practice..	905
32.8	MDI specification .....	905
32.8.1	MDI connectors .....	905
32.8.2	Crossover function.....	905
32.9	System considerations .....	906
32.10	Environmental specifications.....	907
32.10.1	General safety .....	907
32.10.2	Network safety .....	907
32.10.3	Environment .....	908
	32.10.4 Cabling specifications.....	908
32.11	PHY labeling .....	908
32.12	Delay constraints .....	909
32.12.1	PHY delay constraints (exposed MII) .....	909
32.12.2	DTE delay constraints (unexposed MII).....	909
32.13	Protocol Implementation Conformance Statement (PICS) proforma for Clause 32, Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 100BASE-T2.....	910
32.13.1	Identification .....	910
32.13.2	Major capabilities/options .....	911
32.13.3	Compatibility considerations .....	911
32.13.4	PHY control function.....	912
32.13.5	Physical Coding Sublayer (PCS) or Physical Medium Attachment (PMA) sublayer.....	913

33.	Clause 33 is reserved for future use.....	930
34.	Introduction to 1000 Mb/s baseband network .....	931
34.1	Overview.....	931
34.1.1	Reconciliation Sublayer (RS) and Gigabit Media Independent Interface (GMII) .....	931
34.1.2	Physical Layer signaling systems .....	932
34.1.3	Repeater .....	932
34.1.4	Auto-Negotiation, type 1000BASE-X.....	932
34.1.5	Physical Layer line signaling for 10 Mb/s and 100 Mb/s Auto-Negotiation on twisted pair.....	932
34.1.6	Management .....	933
34.2	State diagrams .....	933
34.3	Protocol Implementation Conformance Statement (PICS) proforma .....	933
34.4	Relation of Gigabit Ethernet to other standards .....	933
35.	Reconciliation Sublayer (RS) and Gigabit Media Independent Interface (GMII) .....	935
35.1	Overview.....	935
35.1.1	Summary of major concepts .....	936
35.1.2	Application .....	936
35.1.3	Rate of operation.....	936
35.1.4	Allocation of functions .....	936
35.2	Functional specifications .....	936
35.2.1	Mapping of GMII signals to PLS service primitives and Station Management... .....	937
35.2.2	GMII signal functional specifications .....	940
35.2.3	GMII data stream.....	948
35.2.4	MAC delay constraints (with GMII) .....	951
35.2.5	Management functions.....	951
35.3	Signal mapping .....	951
35.4	Electrical characteristics .....	952
35.4.1	DC characteristics .....	952
35.4.2	AC characteristics .....	952
35.5	Protocol Implementation Conformance Statement (PICS) proforma for Clause 35, Reconciliation Sublayer (RS) and Gigabit Media Independent Interface (GMII) .....	957
35.5.1	Introduction.....	957
35.5.2	Identification.....	957
35.5.3	PICS proforma tables for reconciliation sublayer and Gigabit Media Independent Interface .....	958
36.	Physical Coding Sublayer (PCS) and Physical Medium Attachment (PMA) sublayer, type 1000BASE-X .....	962
36.1	Overview.....	962
36.1.1	Scope.....	962
36.1.2	Objectives .....	962
36.1.3	Relationship of 1000BASE-X to other standards .....	962
36.1.4	Summary of 1000BASE-X sublayers .....	963
36.1.5	Inter-sublayer interfaces .....	963
36.1.6	Functional block diagram .....	964
36.1.7	State diagram conventions .....	964
36.2	Physical Coding Sublayer (PCS) .....	965
36.2.1	PCS Interface (GMII) .....	965
36.2.2	Functions within the PCS .....	966

36.2.3	Use of code-groups .....	966
36.2.4	8B/10B transmission code .....	966
36.2.5	Detailed functions and state diagrams .....	979
36.3	Physical Medium Attachment (PMA) sublayer.....	992
36.3.1	Service Interface .....	992
36.3.2	Functions within the PMA .....	994
36.3.3	A physical instantiation of the PMA Service Interface .....	995
36.3.4	General electrical characteristics of the TBI .....	999
36.3.5	TBI transmit interface electrical characteristics .....	1000
36.3.6	TBI receive interface electrical characteristics.....	1000
36.3.7	Loopback mode .....	1002
36.3.8	Test functions.....	1003
36.4	Compatibility considerations .....	1003
36.5	Delay constraints .....	1003
36.5.1	MDI to GMII delay constraints .....	1003
36.5.2	DTE delay constraints (half duplex mode) .....	1003
36.5.3	Carrier de-assertion/assertion constraint (half duplex mode) .....	1004
36.6	Environmental specifications.....	1004
36.7	Protocol Implementation Conformance Statement (PICS) proforma for Clause 36, Physical Coding Sublayer (PCS) and Physical Medium Attachment (PMA) sublayer, type 1000BASE-X .....	1005
36.7.1	Introduction.....	1005
36.7.2	Identification.....	1005
36.7.3	Major Capabilities/Options.....	1006
36.7.4	PICS proforma tables for the PCS and PMA sublayer, type 1000BASE-X ..	1006
37.	Auto-Negotiation function, type 1000BASE-X.....	1009
37.1	Overview.....	1009
37.1.1	Scope.....	1009
37.1.2	Application perspective/objectives .....	1009
37.1.3	Relationship to ISO/IEC 8802-3.....	1010
37.1.4	Compatibility considerations .....	1010
37.2	Functional specifications .....	1011
37.2.1	Config_Reg encoding .....	1011
37.2.2	Transmit function requirements.....	1014
37.2.3	Receive function requirements .....	1014
37.2.4	Arbitration process requirements.....	1015
37.2.5	Management function requirements .....	1019
37.2.6	Absence of management function .....	1022
37.3	Detailed functions and state diagrams .....	1022
37.3.1	State diagram variables .....	1022
37.4	Environmental specifications.....	1027
37.5	Protocol Implementation Conformance Statement (PICS) proforma for Clause 37, Auto-Negotiation function, type 1000BASE-X .....	1029
37.5.1	Introduction.....	1029
37.5.2	Identification .....	1029
37.5.3	Major Capabilities/Options.....	1030
37.5.4	PICS proforma tables for the Auto-Negotiation function, type 1000BASE-X ..	1030
38.	Physical Medium Dependent (PMD) sublayer and baseband medium, type 1000BASE-LX (Long Wavelength Laser) and 1000BASE-SX (Short Wavelength Laser) .....	1033
38.1	Overview .....	1033

38.1.1	Physical Medium Dependent (PMD) sublayer service interface.....	1033
38.1.2	Medium Dependent Interface (MDI).....	1034
38.2	PMD functional specifications .....	1034
38.2.1	PMD block diagram.....	1035
38.2.2	PMD transmit function .....	1035
38.2.3	PMD receive function.....	1035
38.2.4	PMD signal detect function .....	1035
38.3	PMD to MDI optical specifications for 1000BASE-SX.....	1036
38.3.1	Transmitter optical specifications.....	1037
38.3.2	Receive optical specifications.....	1038
38.3.3	Worst-case 1000BASE-SX link power budget and penalties (informative) .....	1038
38.4	PMD to MDI optical specifications for 1000BASE-LX .....	1039
38.4.1	Transmitter optical specifications .....	1039
38.4.2	Receive optical specifications.....	1040
38.4.3	Worst-case 1000BASE-LX link power budget and penalties (informative) .....	1040
38.5	Jitter specifications for 1000BASE-SX and 1000BASE-LX .....	1041
38.6	Optical measurement requirements .....	1042
38.6.1	Center wavelength and spectral width measurements .....	1042
38.6.2	Optical power measurements.....	1042
38.6.3	Extinction ratio measurements .....	1042
38.6.4	Relative Intensity Noise (RIN) .....	1042
38.6.5	Transmitter optical waveform (transmit eye) .....	1042
38.6.6	Transmit rise/fall characteristics .....	1043
38.6.7	Receive sensitivity measurements .....	1043
38.6.8	Total jitter measurements .....	1044
38.6.9	Deterministic jitter measurement (informative) .....	1044
38.6.10	Coupled Power Ratio (CPR) measurements.....	1044
38.6.11	Conformance test signal at TP3 for receiver testing.....	1045
38.6.12	Measurement of the receiver 3 dB electrical upper cutoff frequency .....	1046
38.7	Environmental specifications.....	1047
38.7.1	General safety .....	1047
38.7.2	Laser safety .....	1047
38.7.3	Installation .....	1047
38.8	Environment .....	1047
38.8.1	Electromagnetic emission .....	1048
38.8.2	Temperature, humidity, and handling.....	1048
38.9	PMD labeling requirements .....	1048
38.10	Fiber optic cabling model .....	1048
38.11	Characteristics of the fiber optic cabling .....	1049
38.11.1	Optical fiber and cable .....	1049
38.11.2	Optical fiber connection .....	1050
38.11.3	Medium Dependent Interface (MDI) .....	1050
38.11.4	single-mode fiber offset-launch mode-conditioning patch cord for MMF operation of 1000BASE-LX .....	1051
38.12	Protocol Implementation Conformance Statement (PICS) proforma for Clause 38, Physical Medium Dependent (PMD) sublayer and baseband medium, type 1000BASE-LX (Long Wavelength Laser) and 1000BASE-SX (Short Wavelength Laser) .....	1053
38.12.1	Introduction.....	1053
38.12.2	Identification.....	1053
38.12.3	Major capabilities/options .....	1054
38.12.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and baseband medium, type 1000BASE-LX (Long Wavelength Laser) and 1000BASE-SX (Short Wavelength Laser) .....	1055

39.	Physical Medium Dependent (PMD) sublayer and baseband medium, type 1000BASE-CX (short-haul copper).....	1060
39.1	Overview.....	1060
39.2	Functional specifications .....	1060
39.2.1	PMD transmit function .....	1060
39.2.2	PMD receive function .....	1060
39.2.3	PMD signal detect function .....	1060
39.3	PMD to MDI electrical specifications .....	1061
39.3.1	Transmitter electrical specifications .....	1062
39.3.2	Receiver electrical specifications .....	1064
39.3.3	Jitter specifications for 1000BASE-CX.....	1065
39.4	Jumper cable assembly characteristics .....	1066
39.4.1	Compensation networks.....	1066
39.4.2	Shielding .....	1066
39.5	MDI specification .....	1066
39.5.1	MDI connectors .....	1067
39.5.2	Crossover function.....	1069
39.6	Electrical measurement requirements .....	1070
39.6.1	Transmit rise/fall time .....	1070
39.6.2	Transmit skew measurement .....	1070
39.6.3	Transmit eye (normalized and absolute).....	1070
39.6.4	Through_connection impedance.....	1070
39.6.5	Jumper cable intra-pair differential skew .....	1070
39.6.6	Receiver link signal .....	1071
39.6.7	Near-End Cross Talk (NEXT) .....	1071
39.6.8	Differential time-domain reflectometry (TDR) measurement procedure .....	1071
39.7	Environmental specifications.....	1072
39.8	Protocol Implementation Conformance Statement (PICS) proforma for Clause 39, Physical Medium Dependent (PMD) sublayer and baseband medium, type 1000BASE-CX.....	1073
39.8.1	Introduction.....	1073
39.8.2	Identification .....	1073
39.8.3	Major capabilities/options .....	1074
39.8.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and baseband medium, type 1000BASE-CX (short-haul copper).....	1074
40.	Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer and baseband medium, type 1000BASE-T.....	1078
40.1	Overview.....	1078
40.1.1	Objectives .....	1078
40.1.2	Relationship of 1000BASE-T to other standards .....	1078
40.1.3	Operation of 1000BASE-T .....	1078
40.1.4	Signaling .....	1083
40.1.5	Inter-sublayer interfaces .....	1083
40.1.6	Conventions in this clause .....	1083
40.2	1000BASE-T Service Primitives and Interfaces .....	1084
40.2.1	Technology-Dependent Interface .....	1084
40.2.2	PMA Service Interface .....	1085
40.2.3	PMA_TXMODE.indicate .....	1086
40.2.4	PMA_CONFIG.indicate .....	1087
40.2.5	PMA_UNITDATA.request .....	1087
40.2.6	PMA_UNITDATA.indicate .....	1088
40.2.7	PMA_SCRSTATUS.request .....	1089

40.2.8	PMA_RXSTATUS.indicate .....	1089
40.2.9	PMA_REMRXSTATUS.request.....	1090
40.2.10	PMA_RESET.indicate.....	1090
40.3	Physical Coding Sublayer (PCS).....	1090
40.3.1	PCS functions .....	1091
40.3.2	Stream structure .....	1106
40.3.3	State variables .....	1106
40.3.4	State diagrams.....	1111
40.4	Physical Medium Attachment (PMA) sublayer.....	1116
40.4.1	PMA functional specifications .....	1116
40.4.2	PMA functions.....	1117
40.4.3	MDI.....	1119
40.4.4	Automatic MDI/MDI-X Configuration .....	1120
40.4.5	State variables .....	1120
40.4.6	State Diagrams.....	1123
40.5	Management interface .....	1125
40.5.1	Support for Auto-Negotiation .....	1125
40.5.2	MASTER-SLAVE configuration resolution .....	1129
40.6	PMA electrical specifications .....	1131
40.6.1	PMA-to-MDI interface tests .....	1131
40.7	Link segment characteristics.....	1152
40.7.1	Cabling system characteristics.....	1152
40.7.2	Link transmission parameters .....	1152
40.7.3	Coupling parameters .....	1153
40.7.4	Delay .....	1154
40.7.5	Noise environment .....	1154
40.7.6	External coupled noise.....	1155
40.8	MDI specification .....	1155
40.8.1	MDI connectors .....	1155
40.8.2	Crossover function.....	1156
40.8.3	MDI electrical specifications .....	1157
40.9	Environmental specifications.....	1159
40.9.1	General safety .....	1159
40.9.2	Network safety.....	1159
40.9.3	Environment .....	1160
40.10	PHY labeling .....	1160
40.11	Delay constraints .....	1161
40.11.1	MDI to GMII delay constraints .....	1161
40.11.2	DTE delay constraints (half duplex only).....	1161
40.11.3	Carrier de-assertion/assertion constraint (half duplex mode) .....	1162
40.12	Protocol implementation conformance statement (PICS) proforma for Clause 40— Physical coding sublayer (PCS), physical medium attachment (PMA) sublayer and baseband medium, type 1000BASE-T .....	1162
40.12.1	Identification .....	1163
40.12.2	Major capabilities/options .....	1163
40.12.3	Clause conventions .....	1164
40.12.4	Physical Coding Sublayer (PCS) .....	1164
40.12.5	Physical Medium Attachment (PMA) .....	1168
40.12.6	Management interface .....	1170
40.12.7	PMA Electrical Specifications.....	1172
40.12.8	Characteristics of the link segment .....	1178
40.12.9	MDI requirements.....	1180
40.12.10	General safety and environmental requirements .....	1182
40.12.11	Timing requirements.....	1182

41.	Repeater for 1000 Mb/s baseband networks .....	1183
41.1	Overview.....	1183
41.1.1	Scope.....	1183
41.1.2	Application perspective .....	1184
41.1.3	Relationship to PHY .....	1184
41.2	Repeater functional specifications .....	1184
41.2.1	Repeater functions .....	1185
41.2.2	Detailed repeater functions and state diagrams .....	1189
41.3	Repeater electrical specifications .....	1197
41.3.1	Electrical isolation .....	1197
41.4	Environmental specifications.....	1197
41.4.1	General safety .....	1197
41.4.2	Network safety.....	1197
41.4.3	Electrical isolation .....	1198
41.4.4	Reliability .....	1198
41.4.5	Environment .....	1199
41.5	Repeater labeling .....	1199
41.6	Protocol Implementation Conformance Statement (PICS) proforma for Clause 41, Repeater for 1000 Mb/s baseband networks.....	1200
41.6.1	Introduction.....	1200
41.6.2	Identification .....	1200
41.6.3	Major capabilities/options .....	1201
41.6.4	PICS proforma tables for the Repeater for 1000 Mb/s baseband networks .....	1201
42.	System considerations for multisegment 1000 Mb/s networks .....	1208
42.1	Overview.....	1208
42.1.1	Single collision domain multisegment networks.....	1209
42.1.2	Repeater usage .....	1210
42.2	Transmission System Model 1.....	1210
42.3	Transmission System Model 2.....	1210
42.3.1	Round-trip collision delay .....	1211
42.4	Full duplex 1000 Mb/s topology limitations .....	1214
43.	Link Aggregation .....	1215
43.1	Overview.....	1215
43.1.1	Terminology .....	1215
43.1.2	Goals and objectives .....	1215
43.1.3	Positioning of Link Aggregation within the IEEE 802.3 architecture.....	1216
43.1.4	State diagram conventions .....	1216
43.2	Link Aggregation operation.....	1218
43.2.1	Principles of Link Aggregation .....	1218
43.2.2	Service interfaces .....	1219
43.2.3	Frame Collector .....	1220
43.2.4	Frame Distributor.....	1221
43.2.5	Marker Generator/Receiver (optional) .....	1223
43.2.6	Marker Responder .....	1223
43.2.7	Aggregator Parser/Multiplexer .....	1223
43.2.8	Aggregator .....	1224
43.2.9	Control Parser/Multiplexer .....	1225
43.2.10	Addressing .....	1227
43.3	Link Aggregation Control.....	1228

43.3.1	Characteristics of Link Aggregation Control .....	1228
43.3.2	System identification .....	1229
43.3.3	Aggregator identification .....	1229
43.3.4	Port identification .....	1230
43.3.5	Capability identification .....	1230
43.3.6	Link Aggregation Group identification .....	1231
43.3.7	Selecting a Link Aggregation Group .....	1233
43.3.8	Agreeing on a Link Aggregation Group .....	1233
43.3.9	Attaching a link to an Aggregator .....	1233
43.3.10	Signaling readiness to transfer user data .....	1234
43.3.11	Enabling Collection and Distribution .....	1234
43.3.12	Monitoring the membership of a Link Aggregation Group.....	1234
43.3.13	Detaching a link from an Aggregator .....	1234
43.3.14	Configuration and administrative control of Link Aggregation .....	1235
43.3.15	Link Aggregation Control state information .....	1235
43.4	Link Aggregation Control Protocol (LACP) .....	1236
43.4.1	LACP design elements .....	1236
43.4.2	LACPDU structure and encoding .....	1236
43.4.3	LACP state machine overview .....	1240
43.4.4	Constants.....	1242
43.4.5	Variables associated with the System.....	1242
43.4.6	Variables associated with each Aggregator .....	1243
43.4.7	Variables associated with each port.....	1244
43.4.8	Variables used for managing the operation of the state machines.....	1247
43.4.9	Functions.....	1248
43.4.10	Timers .....	1250
43.4.11	Messages.....	1250
43.4.12	Receive machine .....	1251
43.4.13	Periodic Transmission machine .....	1253
43.4.14	Selection Logic .....	1254
43.4.15	Mux machine .....	1257
43.4.16	Transmit machine .....	1260
43.4.17	Churn Detection machines .....	1261
43.5	Marker protocol .....	1262
43.5.1	Introduction.....	1262
43.5.2	Sequence of operations .....	1263
43.5.3	Marker and Marker Response PDU structure and encoding .....	1263
43.5.4	Protocol definition .....	1265
43.6	Configuration capabilities and restrictions .....	1266
43.6.1	Use of system and port priorities .....	1266
43.6.2	Dynamic allocation of operational Keys .....	1267
43.6.3	Link Aggregation on shared-medium links .....	1268
43.6.4	Selection Logic variants .....	1268
43.7	Protocol Implementation Conformance Statement (PICS) proforma for Clause 43, Aggregation of Multiple Link Segments .....	1269
43.7.1	Introduction.....	1269
43.7.2	Identification .....	1269
43.7.3	Major capabilities/options .....	1270
43.7.4	Frame Collector .....	1270
43.7.5	Frame Distributor.....	1271
43.7.6	Marker protocol .....	1271
43.7.7	Aggregator Parser/Multiplexer .....	1271
43.7.8	Control Parser/Multiplexer .....	1272
43.7.9	System identification .....	1272

43.7.10	Aggregator identification .....	1272
43.7.11	Port identification .....	1272
43.7.12	Capability identification .....	1273
43.7.13	Link Aggregation Group identification .....	1273
43.7.14	Detaching a link from an Aggregator .....	1273
43.7.15	LACPDU structure .....	1273
43.7.16	State machine variables .....	1274
43.7.17	Receive machine .....	1274
43.7.18	Periodic Transmission machine .....	1274
43.7.19	Selection Logic .....	1275
43.7.20	Mux machine .....	1275
43.7.21	Transmit machine .....	1276
43.7.22	Churn Detection machines .....	1276
43.7.23	Marker protocol .....	1277
43.7.24	Configuration capabilities and restrictions .....	1277
43.7.25	Link Aggregation on shared-medium links .....	1278
Annex A (informative) Additional reference material .....		1279
Annex B (informative) System guidelines .....		1282
Annex C (informative) State diagram, MAC sublayer .....		1305
Annex D (informative) Application context, selected medium specifications .....		1306
Annex E (informative) Receiver wavelength design considerations (FOIRL) .....		1313
Annex F (normative) Additional attributes required for systems .....		1314
Annex G (normative) Additional material required for conformance testing .....		1316
Annex H (normative) GDMO specifications for CSMA/CD managed objects .....		1317
Annex 22A (informative) MII output delay, setup, and hold time budget .....		1345
Annex 22B (informative) MII driver ac characteristics .....		1348
Annex 22C (informative) Measurement techniques for MII signal timing characteristics .....		1350
Annex 23A (normative) 6T code words .....		1352
Annex 23B (informative) Noise budget .....		1354
Annex 23C (informative) Use of cabling systems with a nominal differential characteristic impedance of 120 Ω .....		1355
Annex 27A (normative) Repeater delay consistency requirements .....		1356
Annex 28A (normative) Selector Field definitions .....		1357
Annex 28B (normative) IEEE 802.3 Selector Base Page definition .....		1358
Annex 28C (normative) Next Page Message Code Field definitions .....		1361

Annex 28D (normative) Description of extensions to Clause 28 and associated annexes .....	1364
Annex 29A (informative) DTE and repeater delay components .....	1366
Annex 29B (informative) Recommended topology documentation .....	1367
Annex 30A (normative) GDMO specification for 802.3 managed object classes .....	1368
Annex 30B (normative) GDMO and ASN.1 definitions for management .....	1431
Annex 30C (normative) SNMP MIB definitions for Link Aggregation.....	1438
Annex 31A (normative) MAC Control opcode assignments.....	1471
Annex 31B (normative) MAC Control PAUSE operation .....	1472
Annex 32A (informative) Use of cabling systems with nominal differential characteristic impedance of 120 $\Omega$ or 150 $\Omega$ .....	1482
Annex 36A (informative) Jitter test patterns .....	1483
Annex 36B (informative) 8B/10B transmission code running disparity calculation examples.....	1486
Annex 38A (informative) Fiber launch conditions .....	1488
Annex 40A (informative) Additional cabling design guidelines .....	1489
Annex 40B (informative) Description of cable clamp.....	1491
Annex 40C (informative) Add-on interface for additional Next Pages .....	1495
Annex 43A (informative) Collection and Distribution functions .....	1501
Annex 43B (normative) Requirements for support of Slow Protocols.....	1505
Annex 43C (informative) LACP standby link selection and dynamic Key management .....	1510